

Slice — User's Manual

Building smaller fonts from variable fonts

Version 0.1.0

Contents

1	What Slice is for	2
2	Two ways to run it	2
2.1	In a browser	2
2.2	From the command line	2
3	The workflow	3
4	Keeping a slice you will want again	3
4.1	The address bar	3
4.2	Fonts opened before	3
5	The Axis Editor	4
5.1	The rule about defaults	4
5.2	A range is an intersection; a pin is an assertion	5
5.3	Things that are refused	5
6	The Name Editor	5
7	The Bit Flag Editor	6
8	Removing overlapping contours	7
9	Output formats	7
10	Command line	8
11	What Slice does to the rest of the font	8
12	Known limitations	9
13	Where the evidence is	9
13.1	Which version you are running	10
14	Credits and licence	10

1 What Slice is for

A variable font contains a whole design space. One file can hold every weight from Thin to Black, every width from Condensed to Expanded, and everything in between. That is excellent for the web and awkward almost everywhere else: many design applications still handle variable fonts poorly, printers ask for a single static file, and a foundry shipping a retail package usually wants named instances rather than one large variable font.

Slice takes a variable font and gives you a smaller one. You can:

- **Pin** an axis to a single location, freezing it. Pin every axis and the result is a static font.
- **Restrict** an axis to a narrower range, keeping the font variable over a smaller design space.
- **Edit** the `name` records and the style bits, so the result identifies itself correctly rather than claiming to be the font it was cut from.
- **Remove overlapping contours**, which the original Slice never did, and which matters because support for overlapping outlines in design applications remains poor after more than a decade.

Everything happens in your browser. The font is never uploaded anywhere. You can try it now.

2 Two ways to run it

2.1 In a browser

The current build of `main` is published and ready to use:

<<https://googlefonts.github.io/slice-web/app/>>

Nothing is uploaded. The page is static files and a WebAssembly module; your font is read by the browser, sliced there, and handed straight back as a download. You can confirm that by loading the page and then going offline before you press Slice.

To run it from a checkout instead:

```
./build.sh
python3 -m http.server --directory dist 8080
```

Then open `http://localhost:8080`. `dist/` is a directory of ordinary static files with no server-side component, so you can copy it to any host that serves `.wasm` with the `application/wasm` content type.

2.2 From the command line

```
cargo build --release -p slice-cli
./target/release/slice info MyFont.ttf
./target/release/slice cut MyFont.ttf Bold.ttf --axis wght=800
```

The command line takes exactly the same axis syntax as the interface, and `info` prints exactly what the three editors would show. Full reference in the *Command line* section.

3 The workflow

1. **Open a font.** Drop a file onto the page, or use the file picker. Slice reads the font’s `fvar`, `name`, `OS/2` and `head` tables and fills in the three editors.
2. **Fill in the Axis Editor.** This is the only part you must touch.
3. **Optionally edit names and style bits.**
4. **Optionally tick “Remove overlapping contours”.**
5. **Press Slice**, and choose where the result goes.

A font with no `fvar` table is not a variable font and is refused at step 1, with a message saying so. There is nothing Slice could do to such a font but copy it.

4 Keeping a slice you will want again

Two things remember what you did, and neither of them sends anything anywhere.

4.1 The address bar

After a successful slice, the page’s own address describes it:

```
| ?axes=wght=700,CASL=0:1&n2=Bold&format=woff2
```

Bookmark the page and the bookmark is the recipe. Open it later and the editors fill themselves in; open it with a *different* font and whatever still applies is restored, so a bookmark that pins a weight works on the next family too. Axes the font does not have are ignored rather than complained about.

Only what you changed is recorded. The Name Editor arrives prefilled from the font, so rows you left alone are not carried — that keeps the address short enough to read, and loading the font restores them anyway. A row you cleared is carried as an empty value (`n16=`), so clearing it, which deletes an optional record, survives the link too.

It is an ordinary URL, so you can edit it by hand: the part after `axes=` is exactly the syntax the Axis Editor takes.

4.2 Fonts opened before

Fonts you have opened are offered again on the next visit, under **Opened before**, with the settings you last used on them. Choosing one is not “open that file again” — the font and its settings come back together, which for a job you repeat is two clicks instead of a file dialogue and five fields.

Each entry shows the family name, the font’s own version string from its `name` table, the axis settings last used, the size, and when that copy arrived.

After a fortnight, an entry says so. A cached font is a copy of a file that has a life of its own: the foundry ships a new version, the repository gets a fix, and the copy here goes quietly out of date with nothing to say so. An entry older than two weeks carries “Cached

30 days ago — worth checking for a newer release”. *It is advice, not a failure: the font still works and still slices. The version string next to the name is what to compare against upstream.*

They are held in your browser’s own storage, on your machine, and never uploaded; the page has no server to upload them to. The list keeps the twelve most recent, up to a total of 120 MB, and drops the least recently used beyond that. A font larger than 40 MB is used normally but not remembered.

Forget all clears the lot. Individual entries have a ×.

If your browser refuses storage — Firefox in private browsing does — nothing is remembered and the panel does not appear. Slicing is unaffected.

5 The Axis Editor

One row per axis. The left column is fixed and shows what the font supports, in the form `min : max [default]`. The right column is yours to fill in.

What you want	What you type	Example
Keep the whole axis	nothing	
Pin the axis to one location	a number	400
Restrict the axis to a smaller range	<code>min:max</code>	200:700

Spaces are ignored, so `200 : 700` and `200:700` are the same. A reversed range is sorted, so `700:200` means `200:700`. Scientific notation and a leading decimal point are both accepted, because they are accepted everywhere else a font tool reads a number: `1e3` is one thousand and `.25` is a quarter.

Pin every axis and you get a static font. Leave even one axis with a range, or blank, and the result is still a variable font over a smaller design space.

5.1 The rule about defaults

A restricted range must contain the axis’s original default value.

This is not a limitation Slice invented. It is what OpenType calls Level 3 sub-spacing: the compiler can narrow an axis, but it cannot move where that axis’s default sits, because every glyph outline in the font is stored as a set of deltas measured *from* the default. Moving it would mean recomputing every delta in the font against a new origin.

So on an axis running `300 : 1000 [300]`, typing `400:700` is refused:

The `wght` range `400:700` does not include the default axis value (300).
This is currently a requirement.

Type `300:700` instead. If you genuinely need a font whose default weight is 400, pin the axis at 400 to get a static font, or use `fonttools varLib.instancer`, which implements the harder Level 4 case.

5.2 A range is an intersection; a pin is an assertion

These behave differently on purpose.

If you **restrict** an axis to a range wider than the font has — 0:700 on an axis that starts at 300 — Slice quietly clamps it to 300:700. You asked to keep everything up to 700, and everything up to 700 is what you get.

If you **pin** an axis outside its range — 2000 on an axis that stops at 1000 — Slice refuses:

```
| The wght value 2000 is outside the axis range 300 to 1000 supported by this font.
```

A pin is a claim that a specific location exists. Silently substituting the nearest one would hand you a font that is not the weight you asked for, and nothing would say so.

5.3 Things that are refused

You typed	What happens
abc	'abc' is not a valid wght axis value.
400,5	Refused — use a decimal point, not a comma
2000 (past the axis end)	Refused, with the supported range quoted
400:700 where the default is 300	Refused, with the default quoted
300:700[500]	Refused — that is Level 4, see above
nothing at all, on every axis	You requested the same design space that is supported in the font...

That last one is worth explaining. If every cell is blank you have not asked for anything, so there is nothing to do. The exception is overlap removal, which is a real change on its own, so ticking that box lets an otherwise-empty form through.

6 The Name Editor

A font's **name** table is how an operating system knows what to call it and which other fonts belong in the same family. If you pin a variable font at Bold and leave the names alone, the result will still call itself by the family's default style name — and your font menu will show two entries claiming to be the same thing.

Slice exposes nine records:

ID	Name	What it is
1	Family	The family name, as used by applications with a four-style model
2	Subfamily	Regular, Bold, Italic or Bold Italic — only those four
3	Unique	A unique identifier for this exact font

ID	Name	What it is
4	Full	The full human-readable name
6	PostScript	The PostScript name. No spaces, ASCII only
16	Typographic Family	The real family name, when there are more than four styles
17	Typographic Sub-family	The real style name, e.g. SemiCondensed Light
21	WWS Family	Family name when styles differ only in weight, width and slope
22	WWS Subfamily	The corresponding style name

IDs 1, 2, 3, 4 and 6 are always written. IDs 16, 17, 21 and 22 are written when you put something in them and **removed from the output when you leave them blank** — those four are optional records, and an empty optional record is not the same as an absent one.

Records are read and written for the Windows platform (platform 3, encoding 1, language 1033) only. Every other **name** record in the font — copyright, licence, designer, version, and any localisation into other languages — is carried through untouched.

If you only ever read one paragraph of this manual: IDs 16 and 17 are how a family with more than four styles tells the operating system which fonts belong together. Fill them in for anything larger than a Regular/Bold/Italic/Bold-Italic set. The original Slice deletes all four of these records on every save; this version does not.

7 The Bit Flag Editor

Two fields, six checkboxes. These tell software whether the font is regular, bold or italic. They are read from the font when you open it, so leaving the panel alone leaves the font's own values in place.

OS/2.fsSelection

Bit	Name	Meaning
0	ITALIC	Glyphs are slanted. Set together with head.macStyle bit 1
5	BOLD	Glyphs are emboldened. Set together with head.macStyle bit 0
6	REGULAR	The regular style. Mutually exclusive with ITALIC and BOLD
8	WWS	Family name differs from others only in weight, width and slope

head.macStyle

Bit	Name	Meaning
0	BOLD	Should agree with fsSelection bit 5
1	ITALIC	Should agree with fsSelection bit 0

Slice warns — but does not refuse — when the combination is inconsistent: REGULAR set alongside BOLD or ITALIC, or the two BOLD bits disagreeing with each other. The specifica-

tion requires them to agree, and software in the wild reads sometimes one and sometimes the other, so a disagreement shows up as a font that is bold in one application and not in another.

Bits the editor does not expose — `fsSelection` bits 1–4, 7, 9 and up — are preserved exactly as the font had them.

8 Removing overlapping contours

Tick **Remove overlapping contours** and Slice merges each glyph’s overlapping shapes into a single outline describing the same filled region.

Why you would want this: a glyph drawn as a stem overlapping a bowl renders correctly under the non-zero winding rule, which every modern rasterizer implements. But a great deal of software still does not cope — some older PostScript workflows, some cutting and engraving software, some applications’ own path importers. Overlap removal produces the same picture described in a way that nothing can misread.

Three things to know:

It needs every axis pinned. Merging contours rennumbers a glyph’s points, and a variable font’s `gvar` deltas are indexed *by* point number, so the two cannot both be true. If any axis is left variable you get:

Overlap removal needs a static font: `gvar` deltas are indexed by point number, and merging contours rennumbers the points. Pin every axis, or turn overlap removal off.

For a CFF2 font the reason has the same shape: the variation data lives in the charstrings’ `blend` operators, which a redrawn outline no longer carries.

It drops the hinting. TrueType instructions address points by index, so a hinting program written against the old point numbering would move the wrong points after a merge. `prep`, `fpgm`, `cvt` and every glyph’s own instructions are removed, and `maxp`’s instruction limits are zeroed to match. A partly-hinted font is worse than an unhinted one.

It leaves clean glyphs alone. A glyph with nothing to merge is passed through with its original points, not rebuilt. Running a clean outline through a boolean engine costs precision and gains nothing.

Composite glyphs are decomposed only when their components actually overlap each other. A composite whose parts do not touch stays a composite, because decomposing it would multiply the font’s size for no benefit.

9 Output formats

The extension you type chooses the container:

Extension	Result
<code>.ttf</code> , <code>.otf</code>	A plain sfnt. These two are the same container; the extension does not change the outline format
<code>.woff</code>	WOFF 1.0, zlib-compressed

Extension	Result
.woff2	WOFF 2.0, brotli-compressed — the smallest

Naming the output `.ttf` will not convert a CFF font’s cubic outlines into quadratic ones, and naming it `.otf` will not do the reverse. Converting outlines is a lossy redraw, and it is not what choosing a file extension should mean.

WOFF and WOFF2 inputs are read as readily as plain sfnt, so you can open a `.woff2` and save a `.ttf`.

10 Command line

```
slice info <FONT> [--all-names] [--json]
slice cut  <FONT> <OUTPUT> [OPTIONS]
```

`info` prints what the three editors would show. `-all-names` adds every `name` record rather than the nine the editor exposes; `-json` emits the same information for scripts.

`cut` options, all repeatable:

Option	Meaning
<code>-axis TAG=VALUE</code>	An axis setting, in the Axis Editor syntax
<code>-name ID=TEXT</code>	Set a <code>name</code> record
<code>‘-fs-selection BIT=on\</code>	<code>off‘</code>
<code>‘-mac-style BIT=on\</code>	<code>off‘</code>
<code>-remove-overlaps</code>	Merge overlapping contours; needs every axis pinned

An example that produces a named static instance:

```
slice cut Recursive-VF.ttf RecursiveSans-Bold.ttf \
  --axis MONO=0 --axis CASL=0 --axis wght=700 --axis slnt=0 --axis CRSV=0.5 \
  --name 1='Recursive Sans' \
  --name 2='Bold' \
  --name 4='Recursive Sans Bold' \
  --name 6='RecursiveSans-Bold' \
  --fs-selection 5=on --fs-selection 6=off \
  --mac-style 0=on \
  --remove-overlaps
```

Note the `-fs-selection 6=off`: REGULAR and BOLD are mutually exclusive, and the font you started from was Regular.

11 What Slice does to the rest of the font

You do not have to think about any of this, but it is worth knowing that it happens.

- **Metrics are recalculated** from the resulting outlines: `head`'s bounding box, `hhea`'s extremes, `maxp`'s maxima, and `OS/2.xAvgCharWidth`.
- **`usWeightClass` and `usWidthClass`** follow a pinned `wght` or `wdth` axis, so a font pinned at 700 reports itself as 700.
- **MVAR** — variable vertical metrics — is applied at the location you pinned and then removed, so ascender, descender, x-height and underline land where they should.
- **Variation tables go** when every axis is pinned: `fvar`, `gvar`, `avar`, `HVAR`, `MVAR`, `STAT`'s unreachable values.
- **DSIG**, a digital signature over the font's bytes, is deleted. Instancing rewrites those bytes, so any signature carried over would be invalid, and an invalid signature is worse than none.
- **Feature variations** — the conditional substitutions used by `rvrn` — are resolved at the pinned location, so a font whose italic `a` only appears past a certain slant gets the right `a`.
- **Named instances** that fall outside the new design space are dropped from `fvar`.

12 Known limitations

Stated plainly, because a font tool that is quiet about its gaps is worse than one that has them.

- **CFF 1.0 fonts are refused.** A plain CFF font is not variable to begin with. CFF2 variable fonts are supported.
- **`avar` version 2** is refused for *partial* instancing, as it is by fontTools, which declines the same job. Pinning every axis works, and is exact.
- **WOFF2 output is about 19% larger** than what `woff2_compress` produces on a glyph-heavy font, because the glyph transform is not implemented on the writing side. The output is a conformant WOFF2 that every browser reads.
- **The engine runs on the main thread**, so the page stops responding while a large font is processed. The progress dialog says so rather than animating a bar that is not measuring anything.

13 Where the evidence is

Every behavioural claim in this manual is tested, and the tests are readable:

- **The test suite in plain English** — all 302 conformance cases, each with the reasoning for why that is the right answer.
- **Adjudication** — every case the original Slice fails, with the measurement behind each verdict.
- **The real-world sweep** — what happens on 775 real variable fonts from Google Fonts: 177,154 glyphs compared against fontTools with no disagreements.
- **The behaviour map** — the numbered map of the original program's behaviour that the suite is written against.

Absolute URLs rather than filenames, so the same line works in the PDF, on the website and in the repository.

13.1 Which version you are running

The status bar shows the version and, beside it, the commit the build was made from, linked to that commit on GitHub. The web version is rebuilt and republished on every push, so the version number alone cannot tell you whether a fix has reached you; the commit can. Quote it when reporting a problem — it identifies the code you were running exactly, which nothing else does.

A build made from a working copy with uncommitted changes is labelled **(modified)** and is deliberately *not* linked, because the commit it names is not the code that is running. A build made outside a git checkout says **unknown build**. Neither happens to the published version.

14 Credits and licence

Slice is a reimplementaion of Slice by Source Foundry, which is the program this one is measured against throughout. The font engine is built on the fontations crates; overlap removal uses linesweeper and kurbo; the interface is Leptos.

See LICENSE in the repository for licence terms.