

# Advances in Quantitative MRI: Acquisition, Estimation, and Applications

---

Gopal Nataraj

Dissertation Proposal

May 15, 2017

Dept. of Electrical Engineering and Computer Science

University of Michigan

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation
- reliably accurate signal models, precise estimation

# Quantitative MRI (QMRI)

**Goal:** rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation
- reliably accurate signal models, precise estimation

**Challenges** (beyond conventional MRI):

- complicated, nonlinear signal models
- more data required, so longer scan times

## Advances in Quantitative MRI:

- **Acquisition**

[Ch. 4]

How can we assemble fast, informative collections of scans to enable precise biomarker quantification?



## Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]  
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]  
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?

## Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]  
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]  
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]  
Using these tools, can we design a state-of-the-art biomarker?

## Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]  
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]  
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]  
Using these tools, can we design a state-of-the-art biomarker?

After reconstruction, single voxel  $y_d$  in  $d$ th image modeled as

$$y_d = s_d(\mathbf{x}; \boldsymbol{\nu}, \mathbf{p}_d) + \epsilon_d \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$  latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$  known parameters
- $\mathbf{p}_d \in \mathbb{R}^A$  acquisition parameters
- $s_d : \mathbb{R}^{L+K+A} \mapsto \mathbb{C}$   $d$ th signal model
- $\epsilon_d \in \mathbb{C}$  noise  $\sim \mathbb{CN}(0, \sigma_d^2)$

# Signal Model

A scan profile contains  $D$  voxels  $\mathbf{y} := [y_1, \dots, y_D]^T$ , modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) + \boldsymbol{\epsilon} \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$  latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$  known parameters
- $\mathbf{P} := [\mathbf{p}_1, \dots, \mathbf{p}_D]$  acquisition parameter matrix
- $\mathbf{s} : \mathbb{R}^{L+K+AD} \mapsto \mathbb{C}^D$  vector signal model
- $\boldsymbol{\epsilon} \sim \mathbb{C}\mathcal{N}(\mathbf{0}_D, \boldsymbol{\Sigma})$  noise, with  $\boldsymbol{\Sigma} := \text{diag}(\sigma_1^2, \dots, \sigma_D^2)$

A scan profile contains  $D$  voxels  $\mathbf{y} := [y_1, \dots, y_D]^T$ , modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) + \boldsymbol{\epsilon} \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$  latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$  known parameters
- $\mathbf{P} := [\mathbf{p}_1, \dots, \mathbf{p}_D]$  acquisition parameter matrix
- $\mathbf{s} : \mathbb{R}^{L+K+AD} \mapsto \mathbb{C}^D$  vector signal model
- $\boldsymbol{\epsilon} \sim \mathbb{C}\mathcal{N}(\mathbf{0}_D, \boldsymbol{\Sigma})$  noise, with  $\boldsymbol{\Sigma} := \text{diag}(\sigma_1^2, \dots, \sigma_D^2)$

**Task:** design  $\mathbf{P}$  to enable precise unbiased estimation of  $\mathbf{x}$

## Towards an Objective Function

When  $\mathbf{s}$  is analytic in  $\mathbf{x}$  (as is typical),

**Fisher information** characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

## Towards an Objective Function

When  $\mathbf{s}$  is analytic in  $\mathbf{x}$  (as is typical),

**Fisher information** characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When  $\mathbf{F}$  is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates  $\hat{\mathbf{x}}$  of  $\mathbf{x}$  satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$



## Towards an Objective Function

When  $\mathbf{s}$  is analytic in  $\mathbf{x}$  (as is typical),

**Fisher information** characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When  $\mathbf{F}$  is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates  $\hat{\mathbf{x}}$  of  $\mathbf{x}$  satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$

Maximum-likelihood (ML) estimates achieve CRB asymptotically or equivalently (for Gaussian data) at sufficiently high SNR.

## Towards an Objective Function

When  $\mathbf{s}$  is analytic in  $\mathbf{x}$  (as is typical),

**Fisher information** characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When  $\mathbf{F}$  is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates  $\hat{\mathbf{x}}$  of  $\mathbf{x}$  satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$

Maximum-likelihood (ML) estimates achieve CRB asymptotically or equivalently (for Gaussian data) at sufficiently high SNR.

**Idea:** choose  $\mathbf{P}$  such that imprecision matrix  $\mathbf{F}^{-1}$  “small”

**Idea:** choose  $\mathbf{P}$  to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where  $\mathbf{W} \in \mathbb{R}^{L \times L}$  is a pre-selected diagonal matrix of weights.

**Idea:** choose  $\mathbf{P}$  to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}\left(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T\right), \quad (4)$$

where  $\mathbf{W} \in \mathbb{R}^{L \times L}$  is a pre-selected diagonal matrix of weights.

**Challenge:**  $\mathbf{x}, \nu$  vary spatially

**Idea:** choose  $\mathbf{P}$  to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where  $\mathbf{W} \in \mathbb{R}^{L \times L}$  is a pre-selected diagonal matrix of weights.

**Challenge:**  $\mathbf{x}, \nu$  vary spatially

**Two problems considered:**

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \nu \in \mathbb{N}^t}} \Psi(\mathbf{x}; \nu, \mathbf{P}), \right\} \quad (5)$$

where  $\mathbb{X}^t \subseteq \mathbb{R}^L$  and  $\mathbb{N}^t \subseteq \mathbb{R}^K$  are “tight” ranges of interest and  $\mathbb{P}$  is defined by acquisition/timing constraints

**Idea:** choose  $\mathbf{P}$  to minimize the objective

$$\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where  $\mathbf{W} \in \mathbb{R}^{L \times L}$  is a pre-selected diagonal matrix of weights.

**Challenge:**  $\mathbf{x}, \boldsymbol{\nu}$  vary spatially

**Two problems considered:**

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \boldsymbol{\nu} \in \mathbb{N}^t}} \Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}), \right\} \quad (5)$$

- Bayesian scan design [§6.3]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} E_{\mathbf{x}, \boldsymbol{\nu}}(\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})) \right\} \quad (6)$$

# Scan Design

**Idea:** choose  $\mathbf{P}$  to minimize the objective

$$\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where  $\mathbf{W} \in \mathbb{R}^{L \times L}$  is a pre-selected diagonal matrix of weights.

**Challenge:**  $\mathbf{x}, \boldsymbol{\nu}$  vary spatially

**Two problems considered:**

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \boldsymbol{\nu} \in \mathbb{N}^t}} \Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}), \right\} \quad (5)$$

- Bayesian scan design [§6.3]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} E_{\mathbf{x}, \boldsymbol{\nu}}(\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})) \right\} \quad (6)$$

## Detailed Example Study

**Task:** design fast acquisition for precise estimation of relaxation parameters  $T_1$ ,  $T_2$  in white/gray matter (WM/GM) of brain



## Detailed Example Study

**Task:** design fast acquisition for precise estimation of relaxation parameters  $T_1$ ,  $T_2$  in white/gray matter (WM/GM) of brain

- Consider scan profiles consisting of two fast pulse sequences
  - Spoiled Gradient-Recalled Echo (SPGR) [Zur et al., 1991]
  - Dual-Echo Steady-State (DESS) [Redpath and Jones, 1988]

## Detailed Example Study

**Task:** design fast acquisition for precise estimation of relaxation parameters  $T_1, T_2$  in white/gray matter (WM/GM) of brain

- Consider scan profiles consisting of two fast pulse sequences
  - Spoiled Gradient-Recalled Echo (SPGR) [Zur et al., 1991]
  - Dual-Echo Steady-State (DESS) [Redpath and Jones, 1988]
- For each scan profile feasible under total time constraint:
  1. Let  $\mathbf{s}$  model corresponding single-component signal
    - $\mathbf{x} \leftarrow [m_0, T_1, T_2]^T$ , where  $m_0$  is a scale factor
    - $\nu \leftarrow$  flip angle variation
    - $\mathbf{P} \leftarrow$  nominal flip angles, repetition times
  2. Optimize  $\mathbf{P}$  subject to flip angle, sequence timing constraints
    - $\mathbf{W} \leftarrow \text{diag}(0, 0.1, 1)$  emphasizes  $T_1, T_2$  est roughly equally
    - $\mathbb{X}^t$  chosen to focus on WM/GM at 3T field strength
    - $\mathbb{N}^t$  chosen to allow 10% flip angle variation

## Scan Profile Comparison

| (#SPGR, #DESS) Profiles | (2, 1)       | (1, 1) | (0, 2)       |
|-------------------------|--------------|--------|--------------|
| SPGR nom. flip (deg)    | (15, 5)      | 15     | –            |
| DESS nom. flip (deg)    | 30           | 10     | (35, 10)     |
| SPGR rep. times (ms)    | (12.2, 12.2) | 13.9   | –            |
| DESS rep. times (ms)    | 17.5         | 28.0   | (24.4, 17.5) |
| Optimized Cost          | 4.0          | 4.9    | <b>3.5</b>   |

## Scan Profile Comparison

| (#SPGR, #DESS) Profiles | (2, 1)       | (1, 1) | (0, 2)       |
|-------------------------|--------------|--------|--------------|
| SPGR nom. flip (deg)    | (15, 5)      | 15     | –            |
| DESS nom. flip (deg)    | 30           | 10     | (35, 10)     |
| SPGR rep. times (ms)    | (12.2, 12.2) | 13.9   | –            |
| DESS rep. times (ms)    | 17.5         | 28.0   | (24.4, 17.5) |
| Optimized Cost          | 4.0          | 4.9    | <b>3.5</b>   |

**Main finding:** 2 DESS sequences can yield  $T_1$ ,  $T_2$  WM/GM estimates that are at least as precise as  $T_1$ ,  $T_2$  estimates from SPGR/DESS scan profiles, under this competitive time constraint.

## Numerical Simulation

- Simulated many WM-like, GM-like voxel realizations
- Studied sample statistics of  $T_1, T_2$  ML estimates  $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$

## Numerical Simulation

- Simulated many WM-like, GM-like voxel realizations
- Studied sample statistics of  $T_1, T_2$  ML estimates  $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$

| Profile                    | (2, 1)         | (1, 1)         | (0, 2)          | Truth |
|----------------------------|----------------|----------------|-----------------|-------|
| WM $\hat{T}_1^{\text{ML}}$ | $830 \pm 17$   | $830 \pm 15$   | $830 \pm 14$    | 832   |
| GM $\hat{T}_1^{\text{ML}}$ | $1330 \pm 30.$ | $1330 \pm 24$  | $1330 \pm 24$   | 1331  |
| WM $\hat{T}_2^{\text{ML}}$ | $80. \pm 1.0$  | $80. \pm 2.1$  | $79.6 \pm 0.94$ | 79.6  |
| GM $\hat{T}_2^{\text{ML}}$ | $110. \pm 1.4$ | $110. \pm 3.0$ | $110. \pm 1.6$  | 110   |

**Table 1:**  $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$  sample means  $\pm$  sample standard deviations

## Experimental Setup

Candidate  $(2, 1)$ ,  $(1, 1)$ ,  $(0, 2)$  SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used  $256 \times 256 \times 8$  3D matrix over  $24 \times 24 \times 4$ cm FOV
- Required **1m37s** scan time for each profile

## Experimental Setup

Candidate (2, 1), (1, 1), (0, 2) SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used  $256 \times 256 \times 8$  3D matrix over  $24 \times 24 \times 4\text{cm}$  FOV
- Required **1m37s** scan time for each profile

Reference scan profile

- Four inversion recovery (IR) scans for  $T_1$  estimation
- Four spin-echo (SE) scans for  $T_2$  estimation
- $256 \times 256$  matrix over  $24 \times 24 \times 0.5\text{cm}$  FOV
- Required **40m58s** scan time total



## Experimental Setup

Candidate (2, 1), (1, 1), (0, 2) SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used  $256 \times 256 \times 8$  3D matrix over  $24 \times 24 \times 4$ cm FOV
- Required **1m37s** scan time for each profile


Reference scan profile

- Four inversion recovery (IR) scans for  $T_1$  estimation
- Four spin-echo (SE) scans for  $T_2$  estimation
- $256 \times 256$  matrix over  $24 \times 24 \times 0.5$ cm FOV
- Required **40m58s** scan time total


Bloch-Siegert (BS) acquisition for separate flip angle calibration

- Acquired 2 BS-shifted SPGR scans in 1m40s total
- Used for  $T_1$ ,  $T_2$  est from both candidate and reference profiles

# Phantom Accuracy Results



(a)  $\hat{T}_1^{\text{ML}}$  Estimates



(b)  $\hat{T}_2^{\text{ML}}$  Estimates

Compared against NIST NMR measurements [Keenan et al., 2016]

## Phantom Precision Results

- Repeated each profile 10 times
- Estimated  $T_1$ ,  $T_2$  std dev of typical voxel across repetitions

## Phantom Precision Results

|   | (2, 1)         | (1, 1)         | (0, 2)         |
|---|----------------|----------------|----------------|
| V5 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 50 $\pm$ 12    | 40 $\pm$ 10.   | 39 $\pm$ 9.4   |
| V6 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 70 $\pm$ 18    | 60 $\pm$ 15    | 70 $\pm$ 16    |
| V7 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 60 $\pm$ 13    | 50 $\pm$ 13    | 50 $\pm$ 13    |
| V5 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 2.6 $\pm$ 0.63 | 6 $\pm$ 1.4    | 3.5 $\pm$ 0.84 |
| V6 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 1.9 $\pm$ 0.46 | 5 $\pm$ 1.1    | 2.3 $\pm$ 0.54 |
| V7 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 1.4 $\pm$ 0.34 | 3.4 $\pm$ 0.80 | 1.5 $\pm$ 0.35 |

**Table 2:** Pooled sample standard deviations  $\pm$  pooled standard errors of sample standard deviations (ms), from optimized SPGR/DESS profiles.

## Phantom Precision Results

|   | (2, 1)         | (1, 1)         | (0, 2)         |
|---|----------------|----------------|----------------|
| V5 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 50 $\pm$ 12    | 40 $\pm$ 10.   | 39 $\pm$ 9.4   |
| V6 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 70 $\pm$ 18    | 60 $\pm$ 15    | 70 $\pm$ 16    |
| V7 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$ | 60 $\pm$ 13    | 50 $\pm$ 13    | 50 $\pm$ 13    |
| V5 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 2.6 $\pm$ 0.63 | 6 $\pm$ 1.4    | 3.5 $\pm$ 0.84 |
| V6 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 1.9 $\pm$ 0.46 | 5 $\pm$ 1.1    | 2.3 $\pm$ 0.54 |
| V7 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$ | 1.4 $\pm$ 0.34 | 3.4 $\pm$ 0.80 | 1.5 $\pm$ 0.35 |

**Table 2:** Pooled sample standard deviations  $\pm$  pooled standard errors of sample standard deviations (ms), from optimized SPGR/DESS profiles.

Similar trends across profiles of empirical vs. theoretical std dev!

## In vivo Results




Figure 1: Colorbar ranges in ms.

## Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for  $T_1$ ,  $T_2$  estimation in brain

## Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for  $T_1$ ,  $T_2$  estimation in brain
  - Simulation and phantom results validate method as a predictor of unbiased estimation precision.



## Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for  $T_1$ ,  $T_2$  estimation in brain
  - Simulation and phantom results validate method as a predictor of unbiased estimation precision.
  - *In vivo* results reveal discrepancies (especially in  $T_2$  estimates), suggesting sensitivity to model mismatch.

## Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for  $T_1$ ,  $T_2$  estimation in brain
  - Simulation and phantom results validate method as a predictor of unbiased estimation precision.
  - *In vivo* results reveal discrepancies (especially in  $T_2$  estimates), suggesting sensitivity to model mismatch.

## How to address model mismatch?

- More complete *in vivo* signal models
- More scalable parameter estimation

## Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]  
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]  
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]  
Using these tools, can we design a state-of-the-art biomarker?

**Given:** at each voxel, image sequence  $\mathbf{y} \in \mathbb{C}^D$  modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}, \boldsymbol{\nu}) + \boldsymbol{\epsilon} \quad (7)$$

- $\mathbf{x} \in \mathbb{R}^L$  latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$  known parameters
- $\mathbf{s} : \mathbb{R}^{L+K} \mapsto \mathbb{C}^D$  vector signal model
- $\boldsymbol{\epsilon} \in \mathbb{C}^D$  noise  $\sim \mathbb{CN}(\mathbf{0}_D, \boldsymbol{\Sigma})$

**Given:** at each voxel, image sequence  $\mathbf{y} \in \mathbb{C}^D$  modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}, \boldsymbol{\nu}) + \boldsymbol{\epsilon} \quad (7)$$

- $\mathbf{x} \in \mathbb{R}^L$  latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$  known parameters
- $\mathbf{s} : \mathbb{R}^{L+K} \mapsto \mathbb{C}^D$  vector signal model
- $\boldsymbol{\epsilon} \in \mathbb{C}^D$  noise  $\sim \mathbb{CN}(\mathbf{0}_D, \boldsymbol{\Sigma})$

**Task:** construct fast estimator  $\hat{\mathbf{x}}(\mathbf{y}, \boldsymbol{\nu})$

**Task:** construct fast estimator  $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

**Challenges:**

- signal  $\mathbf{s}$  often nonlinear in  $\mathbf{x}$ : non-convex inverse problems
- signal  $\mathbf{s}$  might be difficult to write in closed form

**Task:** construct fast estimator  $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

**Challenges:**

- signal  $\mathbf{s}$  often nonlinear in  $\mathbf{x}$ : non-convex inverse problems
- signal  $\mathbf{s}$  might be difficult to write in closed form

**Conventional Approaches:**

- gradient-based local optimization
  - initialization-dependent solution
  - requires signal gradients

**Task:** construct fast estimator  $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

**Challenges:**

- signal  $\mathbf{s}$  often nonlinear in  $\mathbf{x}$ : non-convex inverse problems
- signal  $\mathbf{s}$  might be difficult to write in closed form

**Conventional Approaches:**

- gradient-based local optimization
  - initialization-dependent solution
  - requires signal gradients
- stochastic methods (e.g., simulated annealing)
  - unclear convergence analysis [Bertsimas and Tsitsiklis, 1993]
  - several unintuitive tuning parameters



**Task:** construct fast estimator  $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

**Challenges:**

- signal  $\mathbf{s}$  often nonlinear in  $\mathbf{x}$ : non-convex inverse problems
- signal  $\mathbf{s}$  might be difficult to write in closed form

**Conventional Approaches:**

- gradient-based local optimization
  - initialization-dependent solution
  - requires signal gradients
- stochastic methods (e.g., simulated annealing)
  - unclear convergence analysis [Bertsimas and Tsitsiklis, 1993]
  - several unintuitive tuning parameters
- grid search e.g., for 1-compartment relaxivity [Ch. 4]

## Grid search computational costs

|                          | $L$ | $\sim$ number dictionary atoms |
|--------------------------|-----|--------------------------------|
| 1-compartment relaxivity | 3   | $\sim 100^2$                   |

## Grid search computational costs

|                            | $L$  | $\sim$ number dictionary atoms |
|----------------------------|------|--------------------------------|
| 1-compartment relaxivity   | 3    | $\sim 100^2$                   |
| flow velocity              | 4    | $\sim 100^3$                   |
| diffusivity tensor         | 7    | $\sim 100^6$                   |
| 2-3 compartment relaxivity | 6-10 | $\sim 100^5 - 100^9$           |

## Grid search computational costs

|                            | $L$  | $\sim$ number dictionary atoms |
|----------------------------|------|--------------------------------|
| 1-compartment relaxivity   | 3    | $\sim 100^2$                   |
| flow velocity              | 4    | $\sim 100^3$                   |
| diffusivity tensor         | 7    | $\sim 100^6$                   |
| 2-3 compartment relaxivity | 6-10 | $\sim 100^5 - 100^9$           |

Can we scale computation with  $L$  more gracefully?

# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

- sample  $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$  from prior distributions
- simulate image data vectors  $\mathbf{y}_1, \dots, \mathbf{y}_N$  via signal model  $\mathbf{s}$

# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

- sample  $(\mathbf{x}_1, \boldsymbol{\nu}_1, \epsilon_1), \dots, (\mathbf{x}_N, \boldsymbol{\nu}_N, \epsilon_N)$  from prior distributions
- simulate image data vectors  $\mathbf{y}_1, \dots, \mathbf{y}_N$  via signal model  $\mathbf{s}$
- design *nonlinear* functions  $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$  for  $l \in \{1, \dots, L\}$  that map each  $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^\top, \text{Im}(\mathbf{y}_n)^\top, \boldsymbol{\nu}_n^\top]^\top \in \mathcal{Q}$  to  $x_{l,n} \in \mathbb{R}$

# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

- sample  $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$  from prior distributions
- simulate image data vectors  $\mathbf{y}_1, \dots, \mathbf{y}_N$  via signal model  $\mathbf{s}$
- design *nonlinear* functions  $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$  for  $l \in \{1, \dots, L\}$  that map each  $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$  to  $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 \right\}$$



# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

- sample  $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$  from prior distributions
- simulate image data vectors  $\mathbf{y}_1, \dots, \mathbf{y}_N$  via signal model  $\mathbf{s}$
- design *nonlinear* functions  $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$  for  $l \in \{1, \dots, L\}$  that map each  $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$  to  $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 \right\} \quad \text{ill-posed!}$$

# Machine Learning for QMRI Parameter Estimation

**Idea:** learn a *nonlinear* estimator from simulated training data

- sample  $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$  from prior distributions
- simulate image data vectors  $\mathbf{y}_1, \dots, \mathbf{y}_N$  via signal model  $\mathbf{s}$
- design *nonlinear* functions  $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$  for  $l \in \{1, \dots, L\}$  that map each  $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$  to  $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (8)$$

**Solution:** solve a *kernel ridge regression* (KRR) problem

- *restrict function space* over which we optimize
- *include function regularization*

## A Function Space over which Optimization is Tractable

**Hilbert space:** complete inner product function space

# A Function Space over which Optimization is Tractable

**Hilbert space:** complete inner product function space

## Reproducing kernel Hilbert space (RKHS)

Hilbert space  $\mathbb{H}$  over input space  $\mathcal{Q}$  with *reproducing property*

$$\langle h, k(\cdot, \mathbf{q}) \rangle_{\mathbb{H}} = h(\mathbf{q}), \quad \forall h \in \mathbb{H}, \mathbf{q} \in \mathcal{Q}$$

for some  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$  called a **reproducing kernel (RK)**

# A Function Space over which Optimization is Tractable

**Hilbert space:** complete inner product function space

## Reproducing kernel Hilbert space (RKHS)

Hilbert space  $\mathbb{H}$  over input space  $\mathcal{Q}$  with *reproducing property*

$$\langle h, k(\cdot, \mathbf{q}) \rangle_{\mathbb{H}} = h(\mathbf{q}), \quad \forall h \in \mathbb{H}, \mathbf{q} \in \mathcal{Q}$$

for some  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$  called a **reproducing kernel (RK)**

## Relevant facts

- Bijection between RKHS  $\mathbb{H}$  and RK  $k$  [Aronszajn, 1950]
- Function  $k(\cdot, \mathbf{q}) \in \mathbb{H}$  called a *feature mapping*

## Function Optimization over a RKHS

Choose: RK  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ , which induces choice of RKHS  $\mathcal{H}$

## Function Optimization over a RKHS

Choose: RK  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ , which induces choice of RKHS  $\mathcal{H}$

- *Nonlinear* kernel corresponds to *nonlinear* estimation
- We use  $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2}\|\Lambda^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$

## Function Optimization over a RKHS

**Choose:** RK  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ , which induces choice of RKHS  $\mathbb{H}$

**Solve:** for each desired latent parameter  $l \in \{1, \dots, L\}$ ,

$$\left( \hat{h}_l, \hat{b}_l \right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$



## Function Optimization over a RKHS

**Choose:** RK  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ , which induces choice of RKHS  $\mathbb{H}$

**Solve:** for each desired latent parameter  $l \in \{1, \dots, L\}$ ,

$$\left( \hat{h}_l, \hat{b}_l \right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$

- Optimal  $\hat{h}_l$  over  $\mathbb{H}$  takes form [Schölkopf et al., 2001]

$$\hat{h}_l(\cdot) \equiv \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) \quad (10)$$

## Function Optimization over a RKHS

**Choose:** RK  $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ , which induces choice of RKHS  $\mathbb{H}$

**Solve:** for each desired latent parameter  $l \in \{1, \dots, L\}$ ,

$$\left( \hat{h}_l, \hat{b}_l \right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$

- Optimal  $\hat{h}_l$  over  $\mathbb{H}$  takes form [Schölkopf et al., 2001]

$$\hat{h}_l(\cdot) \equiv \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) \quad (10)$$

- Plug (10) into (9); solve now instead for  $(\hat{a}_l, \hat{b}_l)$ ; construct:

$$\hat{x}_l(\cdot) = \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) + \hat{b}_l \quad (11)$$

## MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K} \mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$  training pt regressands

# MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$  training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$  Gram matrix

# MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K} \mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$  training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$  Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$  de-meaning operator

# MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$  training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$  Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$  de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^\top$  nonlin kernel embedding

# MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^T \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^T$  training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$  Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^T$  de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^T$  nonlin kernel embedding

Can we scale computation with  $L$  more gracefully?

- Yes, in fact (12) separable in  $l \in \{1, \dots, L\}$  by construction

# MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for  $l \in \{1, \dots, L\}$ :

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left( \frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left( \mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$  training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$  Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$  de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^\top$  nonlin kernel embedding

Can we scale computation with  $L$  more gracefully?

- Yes, in fact (12) separable in  $l \in \{1, \dots, L\}$  by construction
- However, explicitly computing  $\mathbf{K}$  may be undesirable...



## KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping”  $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$  such that  $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$  has for  $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^\top \tilde{\mathbf{Z}}. \quad (13)$$

## KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping”  $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$  such that  $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$  has for  $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \frac{1}{N} \mathbf{x}_l^T \mathbf{1}_N + \frac{1}{N} \mathbf{x}_l^T \mathbf{M} \tilde{\mathbf{Z}}^T \left( \frac{1}{N} \tilde{\mathbf{Z}} \mathbf{M} \tilde{\mathbf{Z}}^T + \rho_l \mathbf{I}_Z \right)^{-1} \left( \tilde{\mathbf{z}}(\cdot) - \frac{1}{N} \tilde{\mathbf{Z}} \mathbf{1}_N \right)$$

## KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping”  $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$  such that  $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$  has for  $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \hat{m}_{x_l} + \hat{\mathbf{c}}_{x_l \tilde{\mathbf{z}}}^T \left( \hat{\mathbf{C}}_{\tilde{\mathbf{z}} \tilde{\mathbf{z}}} + \rho_l \mathbf{I}_Z \right)^{-1} (\tilde{\mathbf{z}}(\cdot) - \hat{\mathbf{m}}_{\tilde{\mathbf{z}}}) \quad (14)$$

which is regularized (“ridge”)  $Z$ -dimensional affine regression!

## KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping”  $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$  such that  $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$  has for  $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \hat{m}_{x_l} + \hat{\mathbf{c}}_{x_l \tilde{\mathbf{z}}}^T \left( \hat{\mathbf{C}}_{\tilde{\mathbf{z}} \tilde{\mathbf{z}}} + \rho_l \mathbf{I}_Z \right)^{-1} (\tilde{\mathbf{z}}(\cdot) - \hat{\mathbf{m}}_{\tilde{\mathbf{z}}}) \quad (14)$$

which is regularized (“ridge”)  $Z$ -dimensional affine regression!

Does such a  $\tilde{\mathbf{z}}$  exist and work well in practice?

- Yes, e.g. for “shift invariant” kernels (like our Gaussian) of form  $k(\mathbf{q}, \mathbf{q}') \equiv k(\mathbf{q} - \mathbf{q}')$  [Rahimi and Recht, 2007]
- In such cases, can reduce from  $\sim N^2$  to  $\sim NZ$  computations

## Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

## Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions

# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters Bayesian perspective...

# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters Bayesian perspective...

- Assume prior  $h_l(\cdot) + b_l \sim \mathcal{GP}(0(\cdot), k(\cdot, \cdot)), l \in \{1, \dots, L\}$



# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters Bayesian perspective...
  - Assume prior  $h_l(\cdot) + b_l \sim \mathcal{GP}(0(\cdot), k(\cdot, \cdot)), l \in \{1, \dots, L\}$
  - Include latent parameter variability  $\epsilon_{x_l}$   
in observed regressand model  $x_l(\mathbf{q}) + b_l + \epsilon_{x_l}$

# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters Bayesian perspective...

- Assume prior  $h_l(\cdot) + b_l \sim \mathcal{GP}(0(\cdot), k(\cdot, \cdot)), l \in \{1, \dots, L\}$
- Include latent parameter variability  $\epsilon_{x_l}$   
in observed regressand model  $x_l(\mathbf{q}) + b_l + \epsilon_{x_l}$
- If we further assume  $\epsilon_{x_l} \sim \mathcal{N}(0, N_{\rho_l})$  then posterior mean function is KRR solution (12) [Rasmussen and Williams, 2005]
- Reasonable to set  $N_{\rho_l} \leftarrow \text{cov}(x_l) \approx \frac{1}{N} \mathbf{x}_l^T \mathbf{M} \mathbf{x}_l$

# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters  $\rho_l \leftarrow \frac{1}{N^2} \mathbf{x}_l^\top \mathbf{M} \mathbf{x}_l$ 
  - Assume prior  $h_l(\cdot) + b_l \sim \mathcal{GP}(0(\cdot), k(\cdot, \cdot)), l \in \{1, \dots, L\}$
  - Include latent parameter variability  $\epsilon_{x_l}$   
in observed regressand model  $x_l(\mathbf{q}) + b_l + \epsilon_{x_l}$
  - If we further assume  $\epsilon_{x_l} \sim \mathcal{N}(0, N\rho_l)$  then posterior mean function is KRR solution (12) [Rasmussen and Williams, 2005]
  - Reasonable to set  $N\rho_l \leftarrow \text{cov}(x_l) \approx \frac{1}{N} \mathbf{x}_l^\top \mathbf{M} \mathbf{x}_l$
- Kernel smoothing length-scale  $\Lambda \leftarrow \text{diag}\left(\sum_{n=1}^N \mathbf{q}_n\right)$

# Model Selection

*Online* model selection: train *after* observing (unlabeled) test data

- Prior on known  $\nu$  density estimation
- Noise covariance  $\Sigma$  low-signal data regions
- Regularization parameters  $\rho_l \leftarrow \frac{1}{N^2} \mathbf{x}_l^\top \mathbf{M} \mathbf{x}_l$ 
  - Assume prior  $h_l(\cdot) + b_l \sim \mathcal{GP}(0(\cdot), k(\cdot, \cdot)), l \in \{1, \dots, L\}$
  - Include latent parameter variability  $\epsilon_{x_l}$   
in observed regressand model  $x_l(\mathbf{q}) + b_l + \epsilon_{x_l}$
  - If we further assume  $\epsilon_{x_l} \sim \mathcal{N}(0, N\rho_l)$  then posterior mean function is KRR solution (12) [Rasmussen and Williams, 2005]
  - Reasonable to set  $N\rho_l \leftarrow \text{cov}(x_l) \approx \frac{1}{N} \mathbf{x}_l^\top \mathbf{M} \mathbf{x}_l$
- Kernel smoothing length-scale  $\Lambda \leftarrow \text{diag}\left(\sum_{n=1}^N \mathbf{q}_n\right)$

Some parameters still require manual selection...

- Prior on  $\mathbf{x}$  from tissue properties
- Kernel shape  $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2} \|\Lambda^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$

## Contribution

- Fast KRR method for nonlinear MRI parameter estimation

## Contribution

- Fast KRR method for nonlinear MRI parameter estimation
  - Key insight: even with complicated MR signal models, can simulate training points “for free”
  - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels

## Contribution

- Fast KRR method for nonlinear MRI parameter estimation
  - Key insight: even with complicated MR signal models, can simulate training points “for free”
  - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels

## Ongoing work

- Performance analysis: how should  $N$  scale with  $L, Q$ ?

## Contribution

- Fast KRR method for nonlinear MRI parameter estimation
  - Key insight: even with complicated MR signal models, can simulate training points “for free”
  - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels

## Ongoing work

- Performance analysis: how should  $N$  scale with  $L, Q$ ?
- Exploit partially linear structure to incorporate scale invariance



## Contribution

- Fast KRR method for nonlinear MRI parameter estimation
  - Key insight: even with complicated MR signal models, can simulate training points “for free”
  - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels

## Ongoing work


- Performance analysis: how should  $N$  scale with  $L, Q$ ?
- Exploit partially linear structure to incorporate scale invariance
- Validation on a compelling problem...

## Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]  
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]  
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]  
Using these tools, can we design a state-of-the-art biomarker?


## Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model




## Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model



## Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model



**Goal:** rapidly estimate  $f_F$  (proxy for MWF) in white matter (WM)

## Application: MWF Imaging

### Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$  flip angle variation
- $\mathbf{y} \leftarrow$  voxel values from 10 datasets

[Nataraj et al., 2017a]

## Application: MWF Imaging

### Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$  flip angle variation
- $\mathbf{y} \leftarrow$  voxel values from 10 datasets [Nataraj et al., 2017a]

### Use KRR to estimate just $f_F$

- Separable prior on  $\mathbf{x}$ :  $f_F, m_0$  uniform; others log-uniform
- $N \leftarrow 10^6$  training points
- $Z \leftarrow 10^3$  kernel approximation order

# Application: MWF Imaging

## Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$  flip angle variation
- $\mathbf{y} \leftarrow$  voxel values from 10 datasets [Nataraj et al., 2017a]

## Use KRR to estimate just $f_F$

- Separable prior on  $\mathbf{x}$ :  $f_F, m_0$  uniform; others log-uniform
- $N \leftarrow 10^6$  training points
- $Z \leftarrow 10^3$  kernel approximation order


## Compare against grid search

- unconstrained search would require  $\sim 100^5$  dictionary atoms
- we artificially constrain search here to limit computation




## MWF Imaging: Simulation Result

Fast-fraction  $f_F$  estimates, in simulation:



## MWF Imaging: Simulation Result

Fast-fraction  $f_F$  estimates, in simulation:



~4h

40s training, 2s testing

## MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction  $f_F$  estimates, from 3D Cartesian data

## MWF Imaging: Proof-of-concept In Vivo Result


Fast-fraction  $f_F$  estimates, from 3D Cartesian data

- Full-scale grid search intractable on typical desktop

## MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction  $f_F$  estimates, from 3D Cartesian data


- Full-scale grid search intractable on typical desktop
- KRR estimates in single slice took about **70s**



# MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction  $f_F$  estimates, from 3D Cartesian data

- Full-scale grid search intractable on typical desktop
- KRR estimates in single slice took about **70s**
- KRR MWF estimates in WM comparable to literature





Cramér, H. (1946).

**Mathematical methods of statistics.**

Princeton Univ. Press, Princeton.



Aronszajn, N. (1950).

**Theory of reproducing kernels.**

*Trans. Amer. Math. Soc.*, 68(3):337–404.



Bertsimas, D. and Tsitsiklis, J. (1993).

**Simulated annealing.**

*Statistical Science*, 8(1):10–15.



Keenan, K. E., Stupic, K. F., Boss, M. A., Russek, S. E., Chenevert, T. L., Prasad, P. V., Reddick, W. E., Cecil, K. M., Zheng, J., Hu, P., and Jackson, E. F. (2016).

**Multi-site, multi-vendor comparison of T1 measurement using ISMRM/NIST system phantom.**

*In Proc. Intl. Soc. Mag. Res. Med.*, page 3290.



Nataraj, G., Nielsen, J.-F., and Fessler, J. A. (2017a).

**Myelin water fraction estimation from optimized steady-state sequences using kernel ridge regression.**

*In Proc. Intl. Soc. Mag. Res. Med.*, page 5076.

To appear.



Nataraj, G., Nielsen, J.-F., and Fessler, J. A. (2017b).

**Optimizing MR scan design for model-based T1, T2 estimation from steady-state sequences.**

*IEEE Trans. Med. Imag.*, 36(2):467–77.





Rahimi, A. and Recht, B. (2007).

**Random features for large-scale kernel machines.**

In *NIPS*.



Rasmussen, C. E. and Williams, C. K. I. (2005).

**Gaussian processes for machine learning (adaptive computation and machine learning).**

MIT Press.



Redpath, T. W. and Jones, R. A. (1988).

**FADE-A new fast imaging sequence.**

*Mag. Res. Med.*, 6(2):224–34.



Schölkopf, B., Herbrich, R., and Smola, A. J. (2001).

**A generalized representer theorem.**

In *Proc. Computational Learning Theory (COLT)*, pages 416–426.

LNCS 2111.



Zur, Y., Wood, M. L., and Neuringer, L. J. (1991).

**Spoiling of transverse magnetization in steady-state sequences.**

*Mag. Res. Med.*, 21(2):251–63.