

Advances in Quantitative MRI: Acquisition, Estimation, and Applications

Gopal Nataraj

Dissertation Proposal

May 15, 2017

Dept. of Electrical Engineering and Computer Science

University of Michigan

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation
- reliably accurate signal models, precise estimation

Quantitative MRI (QMRI)

Goal: rapidly and reliably localize biomarkers from MR data

- biomarker measurable tissue property (e.g., elasticity) that characterizes a biological process (e.g., sclerosis)
- localize produce quantitative MR images
- rapidly fast acquisition, fast estimation
- reliably accurate signal models, precise estimation

Challenges (beyond conventional MRI):

- complicated, nonlinear signal models
- more data required, so longer scan times

Advances in Quantitative MRI:

- **Acquisition**

[Ch. 4]

How can we assemble fast, informative collections of scans to enable precise biomarker quantification?

Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?

Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]
Using these tools, can we design a state-of-the-art biomarker?

Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]
Using these tools, can we design a state-of-the-art biomarker?

After reconstruction, single voxel y_d in d th image modeled as

$$y_d = s_d(\mathbf{x}; \boldsymbol{\nu}, \mathbf{p}_d) + \epsilon_d \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$ latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$ known parameters
- $\mathbf{p}_d \in \mathbb{R}^A$ acquisition parameters
- $s_d : \mathbb{R}^{L+K+A} \mapsto \mathbb{C}$ d th signal model
- $\epsilon_d \in \mathbb{C}$ noise $\sim \mathbb{CN}(0, \sigma_d^2)$

Signal Model

A *scan profile* contains D voxels $\mathbf{y} := [y_1, \dots, y_D]^T$, modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) + \boldsymbol{\epsilon} \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$ latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$ known parameters
- $\mathbf{P} := [\mathbf{p}_1, \dots, \mathbf{p}_D]$ acquisition parameter matrix
- $\mathbf{s} : \mathbb{R}^{L+K+AD} \mapsto \mathbb{C}^D$ vector signal model
- $\boldsymbol{\epsilon} \sim \mathbb{C}\mathcal{N}(\mathbf{0}_D, \boldsymbol{\Sigma})$ noise, with $\boldsymbol{\Sigma} := \text{diag}(\sigma_1^2, \dots, \sigma_D^2)$

A *scan profile* contains D voxels $\mathbf{y} := [y_1, \dots, y_D]^T$, modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) + \boldsymbol{\epsilon} \quad (1)$$

- $\mathbf{x} \in \mathbb{R}^L$ latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$ known parameters
- $\mathbf{P} := [\mathbf{p}_1, \dots, \mathbf{p}_D]$ acquisition parameter matrix
- $\mathbf{s} : \mathbb{R}^{L+K+AD} \mapsto \mathbb{C}^D$ vector signal model
- $\boldsymbol{\epsilon} \sim \mathbb{C}\mathcal{N}(\mathbf{0}_D, \boldsymbol{\Sigma})$ noise, with $\boldsymbol{\Sigma} := \text{diag}(\sigma_1^2, \dots, \sigma_D^2)$

Task: design \mathbf{P} to enable precise unbiased estimation of \mathbf{x}

Towards an Objective Function

When \mathbf{s} is analytic in \mathbf{x} (as is typical),

Fisher information characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

Towards an Objective Function

When \mathbf{s} is analytic in \mathbf{x} (as is typical),

Fisher information characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When \mathbf{F} is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates $\hat{\mathbf{x}}$ of \mathbf{x} satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$

Towards an Objective Function

When \mathbf{s} is analytic in \mathbf{x} (as is typical),

Fisher information characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When \mathbf{F} is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates $\hat{\mathbf{x}}$ of \mathbf{x} satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$

Maximum-likelihood (ML) estimates achieve CRB asymptotically or equivalently (for Gaussian data) at sufficiently high SNR.

Towards an Objective Function

When \mathbf{s} is analytic in \mathbf{x} (as is typical),

Fisher information characterizes unbiased estimator precision:

$$\mathbf{F}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) := (\nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}))^H \boldsymbol{\Sigma}^{-1} \nabla_{\mathbf{x}} \mathbf{s}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (2)$$

When \mathbf{F} is invertible, Cramér-Rao Bound (CRB) [Cramér, 1946] ensures covariance of unbiased estimates $\hat{\mathbf{x}}$ of \mathbf{x} satisfy

$$\text{cov}(\hat{\mathbf{x}}; \boldsymbol{\nu}, \mathbf{P}) \succeq \mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}). \quad (3)$$

Maximum-likelihood (ML) estimates achieve CRB asymptotically or equivalently (for Gaussian data) at sufficiently high SNR.

Idea: choose \mathbf{P} such that imprecision matrix \mathbf{F}^{-1} “small”

Idea: choose \mathbf{P} to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where $\mathbf{W} \in \mathbb{R}^{L \times L}$ is a pre-selected diagonal matrix of weights.

Idea: choose \mathbf{P} to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}\left(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T\right), \quad (4)$$

where $\mathbf{W} \in \mathbb{R}^{L \times L}$ is a pre-selected diagonal matrix of weights.

Challenge: \mathbf{x}, ν vary spatially

Idea: choose \mathbf{P} to minimize the objective

$$\Psi(\mathbf{x}; \nu, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \nu, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where $\mathbf{W} \in \mathbb{R}^{L \times L}$ is a pre-selected diagonal matrix of weights.

Challenge: \mathbf{x}, ν vary spatially

Two problems considered:

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \nu \in \mathbb{N}^t}} \Psi(\mathbf{x}; \nu, \mathbf{P}), \right\} \quad (5)$$

where $\mathbb{X}^t \subseteq \mathbb{R}^L$ and $\mathbb{N}^t \subseteq \mathbb{R}^K$ are “tight” ranges of interest and \mathbb{P} is defined by acquisition/timing constraints

Idea: choose \mathbf{P} to minimize the objective

$$\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where $\mathbf{W} \in \mathbb{R}^{L \times L}$ is a pre-selected diagonal matrix of weights.

Challenge: $\mathbf{x}, \boldsymbol{\nu}$ vary spatially

Two problems considered:

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \boldsymbol{\nu} \in \mathbb{N}^t}} \Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}), \right\} \quad (5)$$

- Bayesian scan design [§6.3]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} E_{\mathbf{x}, \boldsymbol{\nu}}(\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})) \right\} \quad (6)$$

Scan Design

Idea: choose \mathbf{P} to minimize the objective

$$\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}) = \text{tr}(\mathbf{W}\mathbf{F}^{-1}(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})\mathbf{W}^T), \quad (4)$$

where $\mathbf{W} \in \mathbb{R}^{L \times L}$ is a pre-selected diagonal matrix of weights.

Challenge: $\mathbf{x}, \boldsymbol{\nu}$ vary spatially

Two problems considered:

- min-max scan design [Nataraj et al., 2017b]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} \max_{\substack{\mathbf{x} \in \mathbb{X}^t \\ \boldsymbol{\nu} \in \mathbb{N}^t}} \Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P}), \right\} \quad (5)$$

- Bayesian scan design [§6.3]

$$\check{\mathbf{P}} \in \left\{ \arg \min_{\mathbf{P} \in \mathbb{P}} E_{\mathbf{x}, \boldsymbol{\nu}}(\Psi(\mathbf{x}; \boldsymbol{\nu}, \mathbf{P})) \right\} \quad (6)$$

Detailed Example Study

Task: design fast acquisition for precise estimation of relaxation parameters T_1 , T_2 in white/gray matter (WM/GM) of brain

Detailed Example Study

Task: design fast acquisition for precise estimation of relaxation parameters T_1 , T_2 in white/gray matter (WM/GM) of brain

- Consider scan profiles consisting of two fast pulse sequences
 - Spoiled Gradient-Recalled Echo (SPGR) [Zur et al., 1991]
 - Dual-Echo Steady-State (DESS) [Redpath and Jones, 1988]

Detailed Example Study

Task: design fast acquisition for precise estimation of relaxation parameters T_1, T_2 in white/gray matter (WM/GM) of brain

- Consider scan profiles consisting of two fast pulse sequences
 - Spoiled Gradient-Recalled Echo (SPGR) [Zur et al., 1991]
 - Dual-Echo Steady-State (DESS) [Redpath and Jones, 1988]
- For each scan profile feasible under total time constraint:
 1. Let \mathbf{s} model corresponding single-component signal
 - $\mathbf{x} \leftarrow [m_0, T_1, T_2]^T$, where m_0 is a scale factor
 - $\nu \leftarrow$ flip angle variation
 - $\mathbf{P} \leftarrow$ nominal flip angles, repetition times
 2. Optimize \mathbf{P} subject to flip angle, sequence timing constraints
 - $\mathbf{W} \leftarrow \text{diag}(0, 0.1, 1)$ emphasizes T_1, T_2 est roughly equally
 - \mathbb{X}^t chosen to focus on WM/GM at 3T field strength
 - \mathbb{N}^t chosen to allow 10% flip angle variation

Scan Profile Comparison

(#SPGR, #DESS) Profiles	(2, 1)	(1, 1)	(0, 2)
SPGR nom. flip (deg)	(15, 5)	15	–
DESS nom. flip (deg)	30	10	(35, 10)
SPGR rep. times (ms)	(12.2, 12.2)	13.9	–
DESS rep. times (ms)	17.5	28.0	(24.4, 17.5)
Optimized Cost	4.0	4.9	3.5

Scan Profile Comparison

(#SPGR, #DESS) Profiles	(2, 1)	(1, 1)	(0, 2)
SPGR nom. flip (deg)	(15, 5)	15	–
DESS nom. flip (deg)	30	10	(35, 10)
SPGR rep. times (ms)	(12.2, 12.2)	13.9	–
DESS rep. times (ms)	17.5	28.0	(24.4, 17.5)
Optimized Cost	4.0	4.9	3.5

Main finding: 2 DESS sequences can yield T_1 , T_2 WM/GM estimates that are at least as precise as T_1 , T_2 estimates from SPGR/DESS scan profiles, under this competitive time constraint.

Numerical Simulation

- Simulated many WM-like, GM-like voxel realizations
- Studied sample statistics of T_1, T_2 ML estimates $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$

Numerical Simulation

- Simulated many WM-like, GM-like voxel realizations
- Studied sample statistics of T_1, T_2 ML estimates $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$

Profile	(2, 1)	(1, 1)	(0, 2)	Truth
WM \hat{T}_1^{ML}	830 ± 17	830 ± 15	830 ± 14	832
GM \hat{T}_1^{ML}	$1330 \pm 30.$	1330 ± 24	1330 ± 24	1331
WM \hat{T}_2^{ML}	$80. \pm 1.0$	$80. \pm 2.1$	79.6 ± 0.94	79.6
GM \hat{T}_2^{ML}	$110. \pm 1.4$	$110. \pm 3.0$	$110. \pm 1.6$	110

Table 1: $\hat{T}_1^{\text{ML}}, \hat{T}_2^{\text{ML}}$ sample means \pm sample standard deviations

Experimental Setup

Candidate $(2, 1)$, $(1, 1)$, $(0, 2)$ SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used $256 \times 256 \times 8$ 3D matrix over $24 \times 24 \times 4$ cm FOV
- Required **1m37s** scan time for each profile

Experimental Setup

Candidate (2, 1), (1, 1), (0, 2) SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used $256 \times 256 \times 8$ 3D matrix over $24 \times 24 \times 4$ cm FOV
- Required **1m37s** scan time for each profile

Reference scan profile

- Four inversion recovery (IR) scans for T_1 estimation
- Four spin-echo (SE) scans for T_2 estimation
- 256×256 matrix over $24 \times 24 \times 0.5$ cm FOV
- Required **40m58s** scan time total

Experimental Setup

Candidate (2, 1), (1, 1), (0, 2) SPGR/DESS scan profiles

- Prescribed optimized nominal flip angles, repetition times
- Used $256 \times 256 \times 8$ 3D matrix over $24 \times 24 \times 4$ cm FOV
- Required **1m37s** scan time for each profile


Reference scan profile

- Four inversion recovery (IR) scans for T_1 estimation
- Four spin-echo (SE) scans for T_2 estimation
- 256×256 matrix over $24 \times 24 \times 0.5$ cm FOV
- Required **40m58s** scan time total


Bloch-Siegert (BS) acquisition for separate flip angle calibration

- Acquired 2 BS-shifted SPGR scans in 1m40s total
- Used for T_1 , T_2 est from both candidate and reference profiles

Phantom Accuracy Results



(a) \hat{T}_1^{ML} Estimates



(b) \hat{T}_2^{ML} Estimates

Compared against NIST NMR measurements [Keenan et al., 2016]

Phantom Precision Results

- Repeated each profile 10 times
- Estimated T_1 , T_2 std dev of typical voxel across repetitions

Phantom Precision Results

	(2, 1)	(1, 1)	(0, 2)
V5 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	50 \pm 12	40 \pm 10.	39 \pm 9.4
V6 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	70 \pm 18	60 \pm 15	70 \pm 16
V7 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	60 \pm 13	50 \pm 13	50 \pm 13
V5 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	2.6 \pm 0.63	6 \pm 1.4	3.5 \pm 0.84
V6 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	1.9 \pm 0.46	5 \pm 1.1	2.3 \pm 0.54
V7 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	1.4 \pm 0.34	3.4 \pm 0.80	1.5 \pm 0.35

Table 2: Pooled sample standard deviations \pm pooled standard errors of sample standard deviations (ms), from optimized SPGR/DESS profiles.

Phantom Precision Results

	(2, 1)	(1, 1)	(0, 2)
V5 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	50 \pm 12	40 \pm 10.	39 \pm 9.4
V6 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	70 \pm 18	60 \pm 15	70 \pm 16
V7 $\hat{\sigma}_{\hat{T}_1^{\text{ML}}}$	60 \pm 13	50 \pm 13	50 \pm 13
V5 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	2.6 \pm 0.63	6 \pm 1.4	3.5 \pm 0.84
V6 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	1.9 \pm 0.46	5 \pm 1.1	2.3 \pm 0.54
V7 $\hat{\sigma}_{\hat{T}_2^{\text{ML}}}$	1.4 \pm 0.34	3.4 \pm 0.80	1.5 \pm 0.35

Table 2: Pooled sample standard deviations \pm pooled standard errors of sample standard deviations (ms), from optimized SPGR/DESS profiles.

Similar trends across profiles of empirical vs. theoretical std dev!

In vivo Results




Figure 1: Colorbar ranges in ms.

Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for T_1 , T_2 estimation in brain

Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for T_1 , T_2 estimation in brain
 - Simulation and phantom results validate method as a predictor of unbiased estimation precision.

Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for T_1 , T_2 estimation in brain
 - Simulation and phantom results validate method as a predictor of unbiased estimation precision.
 - *In vivo* results reveal discrepancies (especially in T_2 estimates), suggesting sensitivity to model mismatch.

Contributions

- MR scan design method for precise parameter estimation
- Fast SPGR/DESS scan profile for T_1 , T_2 estimation in brain
 - Simulation and phantom results validate method as a predictor of unbiased estimation precision.
 - *In vivo* results reveal discrepancies (especially in T_2 estimates), suggesting sensitivity to model mismatch.

How to address model mismatch?

- More complete *in vivo* signal models
- More scalable parameter estimation

Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]
Using these tools, can we design a state-of-the-art biomarker?

Quantitative MRI (QMRI) Parameter Estimation

Given: MR image sequence informative about a physical process

- flow
- diffusion
- multi-compartmental relaxation
- ...

Quantitative MRI (QMRI) Parameter Estimation

Given: MR image sequence informative about a physical process

- flow
- diffusion
- multi-compartmental relaxation
- ...

Task: estimate MR tissue properties characterizing the process

- flow velocity
- diffusivity
- compartmental relaxivity
- ...

QMRI Problem Statement

Given: at each voxel, image sequence $\mathbf{y} \in \mathbb{C}^D$ modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}, \boldsymbol{\nu}) + \boldsymbol{\epsilon} \quad (7)$$

- $\mathbf{x} \in \mathbb{R}^L$ latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$ known parameters
- $\mathbf{s} : \mathbb{R}^{L+K} \mapsto \mathbb{C}^D$ signal model
- $\boldsymbol{\epsilon} \in \mathbb{C}^D$ noise $\sim \mathbb{CN}(\mathbf{0}_D, \boldsymbol{\Sigma})$

QMRI Problem Statement

Given: at each voxel, image sequence $\mathbf{y} \in \mathbb{C}^D$ modeled as

$$\mathbf{y} = \mathbf{s}(\mathbf{x}, \boldsymbol{\nu}) + \boldsymbol{\epsilon} \quad (7)$$

- $\mathbf{x} \in \mathbb{R}^L$ latent free parameters
- $\boldsymbol{\nu} \in \mathbb{R}^K$ known parameters
- $\mathbf{s} : \mathbb{R}^{L+K} \mapsto \mathbb{C}^D$ signal model
- $\boldsymbol{\epsilon} \in \mathbb{C}^D$ noise $\sim \mathbb{CN}(\mathbf{0}_D, \boldsymbol{\Sigma})$

Task: construct fast estimator $\hat{\mathbf{x}}(\mathbf{y}, \boldsymbol{\nu})$

Task: construct fast estimator $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

Challenges:

- signal \mathbf{s} often nonlinear in \mathbf{x} : non-convex inverse problems
- signal \mathbf{s} might be difficult to write in closed form

Task: construct fast estimator $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

Challenges:

- signal \mathbf{s} often nonlinear in \mathbf{x} : non-convex inverse problems
- signal \mathbf{s} might be difficult to write in closed form

Conventional Approaches:

- gradient-based local optimization
 - initialization-dependent solution
 - requires signal gradients

Task: construct fast estimator $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

Challenges:

- signal \mathbf{s} often nonlinear in \mathbf{x} : non-convex inverse problems
- signal \mathbf{s} might be difficult to write in closed form

Conventional Approaches:

- gradient-based local optimization
 - initialization-dependent solution
 - requires signal gradients
- stochastic methods (e.g., simulated annealing)
 - unclear convergence analysis
 - several unintuitive tuning parameters

[?]

Task: construct fast estimator $\hat{\mathbf{x}}(\mathbf{y}, \nu)$

Challenges:

- signal \mathbf{s} often nonlinear in \mathbf{x} : non-convex inverse problems
- signal \mathbf{s} might be difficult to write in closed form

Conventional Approaches:

- gradient-based local optimization
 - initialization-dependent solution
 - requires signal gradients
- stochastic methods (e.g., simulated annealing)
 - unclear convergence analysis [?]
 - several unintuitive tuning parameters
- grid search e.g., for MR fingerprinting [Ma et al., 2013]

Grid search computational costs

	L	\sim number dictionary atoms
(1-compartment) relaxivity	3	$\sim 100^2$

Grid search computational costs

	L	\sim number dictionary atoms
(1-compartment) relaxivity	3	$\sim 100^2$
flow velocity	4	$\sim 100^3$
diffusivity tensor	7	$\sim 100^6$
2-3 compartment relaxivity	6-10	$\sim 100^5 - 100^9$

Grid search computational costs

	L	\sim number dictionary atoms
(1-compartment) relaxivity	3	$\sim 100^2$
flow velocity	4	$\sim 100^3$
diffusivity tensor	7	$\sim 100^6$
2-3 compartment relaxivity	6-10	$\sim 100^5 - 100^9$

Can we scale computation with L more gracefully?

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

- sample $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$ from prior distributions
- simulate image data vectors $\mathbf{y}_1, \dots, \mathbf{y}_N$ via signal model \mathbf{s}

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

- sample $(\mathbf{x}_1, \boldsymbol{\nu}_1, \epsilon_1), \dots, (\mathbf{x}_N, \boldsymbol{\nu}_N, \epsilon_N)$ from prior distributions
- simulate image data vectors $\mathbf{y}_1, \dots, \mathbf{y}_N$ via signal model \mathbf{s}
- design *nonlinear* functions $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$ for $l \in \{1, \dots, L\}$ that map each $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \boldsymbol{\nu}_n^T]^T \in \mathcal{Q}$ to $x_{l,n} \in \mathbb{R}$

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

- sample $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$ from prior distributions
- simulate image data vectors $\mathbf{y}_1, \dots, \mathbf{y}_N$ via signal model \mathbf{s}
- design *nonlinear* functions $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$ for $l \in \{1, \dots, L\}$ that map each $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$ to $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 \right\}$$

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

- sample $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$ from prior distributions
- simulate image data vectors $\mathbf{y}_1, \dots, \mathbf{y}_N$ via signal model \mathbf{s}
- design *nonlinear* functions $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$ for $l \in \{1, \dots, L\}$ that map each $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$ to $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 \right\} \quad \text{ill-posed!}$$

Machine Learning for QMRI Parameter Estimation

Idea: learn a *nonlinear* estimator from simulated training data

- sample $(\mathbf{x}_1, \nu_1, \epsilon_1), \dots, (\mathbf{x}_N, \nu_N, \epsilon_N)$ from prior distributions
- simulate image data vectors $\mathbf{y}_1, \dots, \mathbf{y}_N$ via signal model \mathbf{s}
- design *nonlinear* functions $\hat{x}_l(\cdot) := \hat{h}_l(\cdot) + \hat{b}_l$ for $l \in \{1, \dots, L\}$ that map each $\mathbf{q}_n := [\text{Re}(\mathbf{y}_n)^T, \text{Im}(\mathbf{y}_n)^T, \nu_n^T]^T \in \mathcal{Q}$ to $x_{l,n} \in \mathbb{R}$

$$(\hat{h}_l, \hat{b}_l) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (8)$$

Solution: solve a *kernel ridge regression* (KRR) problem

- **restrict function space** over which we optimize
- **include function regularization**

A Function Space over which Optimization is Tractable

Hilbert space: complete inner product function space

A Function Space over which Optimization is Tractable

Hilbert space: complete inner product function space

Reproducing kernel Hilbert space (RKHS)

Hilbert space \mathbb{H} over input space \mathcal{Q} with *reproducing property*

$$\langle h, k(\cdot, \mathbf{q}) \rangle_{\mathbb{H}} = h(\mathbf{q}), \quad \forall h \in \mathbb{H}, \mathbf{q} \in \mathcal{Q}$$

for some $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ called a **reproducing kernel (RK)**

A Function Space over which Optimization is Tractable

Hilbert space: complete inner product function space

Reproducing kernel Hilbert space (RKHS)

Hilbert space \mathbb{H} over input space \mathcal{Q} with *reproducing property*

$$\langle h, k(\cdot, \mathbf{q}) \rangle_{\mathbb{H}} = h(\mathbf{q}), \quad \forall h \in \mathbb{H}, \mathbf{q} \in \mathcal{Q}$$

for some $k : \mathcal{Q}^2 \mapsto \mathbb{R}$ called a **reproducing kernel (RK)**

Relevant facts

- Bijection between RKHS \mathbb{H} and RK k [Aronszajn, 1950]
- Function $k(\cdot, \mathbf{q}) \in \mathbb{H}$ called a *feature mapping*

Function Optimization over a RKHS

Choose: RK $k : \mathcal{Q}^2 \mapsto \mathbb{R}$, which induces choice of RKHS \mathcal{H}

Function Optimization over a RKHS

Choose: RK $k : \mathcal{Q}^2 \mapsto \mathbb{R}$, which induces choice of RKHS \mathcal{H}

- *Nonlinear* kernel corresponds to *nonlinear* estimation
- We use $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2}\|\Lambda^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$

Function Optimization over a RKHS

Choose: RK $k : \mathcal{Q}^2 \mapsto \mathbb{R}$, which induces choice of RKHS \mathbb{H}

Solve: for each desired latent parameter $l \in \{1, \dots, L\}$,

$$\left(\hat{h}_l, \hat{b}_l\right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$

Function Optimization over a RKHS

Choose: RK $k : \mathcal{Q}^2 \mapsto \mathbb{R}$, which induces choice of RKHS \mathbb{H}

Solve: for each desired latent parameter $l \in \{1, \dots, L\}$,

$$\left(\hat{h}_l, \hat{b}_l \right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$

- Optimal \hat{h}_l over \mathbb{H} takes form [Schölkopf et al., 2001]

$$\hat{h}_l(\cdot) \equiv \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) \quad (10)$$

Function Optimization over a RKHS

Choose: RK $k : \mathcal{Q}^2 \mapsto \mathbb{R}$, which induces choice of RKHS \mathbb{H}

Solve: for each desired latent parameter $l \in \{1, \dots, L\}$,

$$\left(\hat{h}_l, \hat{b}_l \right) \in \left\{ \arg \min_{\substack{h_l \in \mathbb{H} \\ b_l \in \mathbb{R}}} \frac{1}{N} \sum_{n=1}^N (h_l(\mathbf{q}_n) + b_l - x_{l,n})^2 + \rho_l \|h_l\|_{\mathbb{H}}^2 \right\} \quad (9)$$

- Optimal \hat{h}_l over \mathbb{H} takes form [Schölkopf et al., 2001]

$$\hat{h}_l(\cdot) \equiv \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) \quad (10)$$

- Plug (10) into (9); solve now instead for (\hat{a}_l, \hat{b}_l) ; construct:

$$\hat{x}_l(\cdot) = \sum_{n=1}^N \hat{a}_{l,n} k(\cdot, \mathbf{q}_n) + \hat{b}_l \quad (11)$$

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K} \mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$ training pt regressands

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K} \mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$ training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$ Gram matrix

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K} \mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$ training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$ Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$ de-meaning operator

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$ training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$ Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$ de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^\top$ nonlin kernel embedding

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^T \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^T$ training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$ Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^T$ de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^T$ nonlin kernel embedding

Can we scale computation with L more gracefully?

- Yes, in fact (12) separable in $l \in \{1, \dots, L\}$ by construction

MRI Parameter Estimation via KRR

Non-iterative closed-form solution, for $l \in \{1, \dots, L\}$:

$$\hat{x}_l(\cdot) = \mathbf{x}_l^\top \left(\frac{1}{N} \mathbf{1}_N + \mathbf{M}(\mathbf{K}\mathbf{M} + N\rho_l \mathbf{I}_N)^{-1} \left(\mathbf{k}(\cdot) - \frac{1}{N} \mathbf{K}\mathbf{1}_N \right) \right) \quad (12)$$

- $\mathbf{x}_l := [x_{l,1}, \dots, x_{l,N}]^\top$ training pt regressands
- $\mathbf{K} := \begin{bmatrix} k(\mathbf{q}_1, \mathbf{q}_1) & \cdots & k(\mathbf{q}_1, \mathbf{q}_N) \\ \vdots & \ddots & \vdots \\ k(\mathbf{q}_N, \mathbf{q}_1) & \cdots & k(\mathbf{q}_N, \mathbf{q}_N) \end{bmatrix}$ Gram matrix
- $\mathbf{M} := \mathbf{I}_N - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$ de-meaning operator
- $\mathbf{k}(\cdot) := [k(\cdot, \mathbf{q}_1), \dots, k(\cdot, \mathbf{q}_N)]^\top$ nonlin kernel embedding

Can we scale computation with L more gracefully?

- Yes, in fact (12) separable in $l \in \{1, \dots, L\}$ by construction
- However, explicitly computing \mathbf{K} may be undesirable...

KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping” $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$ such that $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$ has for $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^\top \tilde{\mathbf{Z}}. \quad (13)$$

KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping” $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$ such that $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$ has for $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \frac{1}{N} \mathbf{x}_l^T \mathbf{1}_N + \frac{1}{N} \mathbf{x}_l^T \mathbf{M} \tilde{\mathbf{Z}}^T \left(\frac{1}{N} \tilde{\mathbf{Z}} \mathbf{M} \tilde{\mathbf{Z}}^T + \rho_l \mathbf{I}_Z \right)^{-1} \left(\tilde{\mathbf{z}}(\cdot) - \frac{1}{N} \tilde{\mathbf{Z}} \mathbf{1}_N \right)$$

KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping” $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$ such that $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$ has for $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \hat{m}_{x_l} + \hat{\mathbf{c}}_{x_l \tilde{\mathbf{z}}}^T \left(\hat{\mathbf{C}}_{\tilde{\mathbf{z}} \tilde{\mathbf{z}}} + \rho_l \mathbf{I}_Z \right)^{-1} (\tilde{\mathbf{z}}(\cdot) - \hat{\mathbf{m}}_{\tilde{\mathbf{z}}}) \quad (14)$$

which is regularized (“ridge”) Z -dimensional affine regression!

KRR as High-Dimensional Affine Regression

Suppose there exists “approximate feature mapping” $\tilde{\mathbf{z}} : \mathcal{Q} \mapsto \mathbb{R}^Z$ such that $\tilde{\mathbf{Z}} := [\tilde{\mathbf{z}}(\mathbf{q}_1), \dots, \tilde{\mathbf{z}}(\mathbf{q}_N)]$ has for $\dim(\mathcal{Q}) \ll Z \ll N$

$$\mathbf{K} \approx \tilde{\mathbf{Z}}^T \tilde{\mathbf{Z}}. \quad (13)$$

Plugging (13) into KRR solution (12) and rearranging gives

$$\hat{x}_l(\cdot) \approx \hat{m}_{x_l} + \hat{\mathbf{c}}_{x_l \tilde{\mathbf{z}}}^T \left(\hat{\mathbf{C}}_{\tilde{\mathbf{z}} \tilde{\mathbf{z}}} + \rho_l \mathbf{I}_Z \right)^{-1} (\tilde{\mathbf{z}}(\cdot) - \hat{\mathbf{m}}_{\tilde{\mathbf{z}}}) \quad (14)$$


which is regularized (“ridge”) Z -dimensional affine regression!

Does such a $\tilde{\mathbf{z}}$ exist and work well in practice?

- Yes, e.g. for “shift invariant” kernels (like our Gaussian) of form $k(\mathbf{q}, \mathbf{q}') \equiv k(\mathbf{q} - \mathbf{q}')$ [Rahimi and Recht, 2007]
- In such cases, can reduce from $\sim N^2$ to $\sim NZ$ computations


Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model




Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model



Application: Myelin Water Fraction (MWF) Imaging

simple two-compartment model



Goal: rapidly estimate f_F (proxy for MWF) in white matter (WM)

Application: MWF Imaging

Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$ flip angle variation
- $\mathbf{y} \leftarrow$ voxel values from 10 datasets

[Nataraj et al., 2017a]

Application: MWF Imaging

Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$ flip angle variation
- $\mathbf{y} \leftarrow$ voxel values from 10 datasets [Nataraj et al., 2017a]

Use KRR to estimate just f_F

- Separable prior on \mathbf{x} : f_F, m_0 uniform; others log-uniform
- $N \leftarrow 10^6$ training points
- $Z \leftarrow 10^3$ kernel approximation order

Application: MWF Imaging

Problem dimensions (per voxel)

- $\mathbf{x} \leftarrow [f_F, T_{1,F}, T_{2,F}, T_{1,S}, T_{2,S}, m_0]^T$
- $\nu \leftarrow$ flip angle variation
- $\mathbf{y} \leftarrow$ voxel values from 10 datasets [Nataraj et al., 2017a]

Use KRR to estimate just f_F


- Separable prior on \mathbf{x} : f_F, m_0 uniform; others log-uniform
- $N \leftarrow 10^6$ training points
- $Z \leftarrow 10^3$ kernel approximation order

Compare against grid search

- unconstrained search would require $\sim 100^5$ dictionary atoms
- we artificially constrain search here to limit computation


MWF Imaging: Simulation Result

Fast-fraction f_F estimates, in simulation:



MWF Imaging: Simulation Result

Fast-fraction f_F estimates, in simulation:



~4h

40s training, 2s testing

MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction f_F estimates, from 3D Cartesian data

MWF Imaging: Proof-of-concept In Vivo Result


Fast-fraction f_F estimates, from 3D Cartesian data

- Full-scale grid search intractable on typical desktop

MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction f_F estimates, from 3D Cartesian data


- Full-scale grid search intractable on typical desktop
- KRR estimates in single slice took about **70s**



MWF Imaging: Proof-of-concept In Vivo Result

Fast-fraction f_F estimates, from 3D Cartesian data

- Full-scale grid search intractable on typical desktop
- KRR estimates in single slice took about **70s**
- KRR MWF estimates in WM comparable to literature



Contributions

- Fast KRR method for nonlin MRI multiparameter estimation

Contributions

- Fast KRR method for nonlin MRI multiparameter estimation
 - Key insight: even with complicated MR signal models, can simulate training points “for free”

Contributions

- Fast KRR method for nonlin MRI multiparameter estimation
 - Key insight: even with complicated MR signal models, can simulate training points “for free”
 - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels

Contributions

- Fast KRR method for nonlin MRI multiparameter estimation
 - Key insight: even with complicated MR signal models, can simulate training points “for free”
 - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels
- Proof-of-concept *in vivo* application to MWF imaging

Contributions

- Fast KRR method for nonlin MRI multiparameter estimation
 - Key insight: even with complicated MR signal models, can simulate training points “for free”
 - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels
- Proof-of-concept *in vivo* application to MWF imaging

Ongoing work

- Conceptual: model selection, performance analysis
- Experimental: validation studies

Contributions

- Fast KRR method for nonlin MRI multiparameter estimation
 - Key insight: even with complicated MR signal models, can simulate training points “for free”
 - Convert *nonlinear estimation* problem into *nonlinear regression* problem that we solve in closed-form with kernels
- Proof-of-concept *in vivo* application to MWF imaging

Ongoing work

- Conceptual: model selection, performance analysis
- Experimental: validation studies

Backup: An Overview of Model Selection

Some model parameters **require manual selection**...

- Kernel shape $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2}\|\mathbf{\Lambda}^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$

Backup: An Overview of Model Selection

Some model parameters **require manual selection...**

- Kernel shape $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2}\|\mathbf{\Lambda}^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$
- Prior on \mathbf{x} from tissue properties
- N, Z empirical methods

Backup: An Overview of Model Selection

Some model parameters **require manual selection**...

- Kernel shape $k(\mathbf{q}, \mathbf{q}') \leftarrow \exp\left(-\frac{1}{2}\|\mathbf{\Lambda}^{-1}(\mathbf{q} - \mathbf{q}')\|_2^2\right)$
- Prior on \mathbf{x} from tissue properties
- N, Z empirical methods

...but others **tuned automatically**

- Kernel smoothing length-scale $\mathbf{\Lambda} \leftarrow \text{diag}\left(\sum_{n=1}^N \mathbf{q}_n\right)$
- Regularization parameters $\rho_l \leftarrow \frac{1}{N^2} \mathbf{x}_l^T \mathbf{M} \mathbf{x}_l$
- Prior on known ν density estimation

Advances in Quantitative MRI:

- **Acquisition** [Ch. 4]
How can we assemble fast, informative collections of scans to enable precise biomarker quantification?
- **Estimation** [Ch. 5]
Given data from an informative acquisition, how can we rapidly and accurately quantify these biomarkers?
- **Application** [Ch. 6]
Using these tools, can we design a state-of-the-art biomarker?



Cramér, H. (1946).

Mathematical methods of statistics.

Princeton Univ. Press, Princeton.



Aronszajn, N. (1950).

Theory of reproducing kernels.

Trans. Amer. Math. Soc., 68(3):337–404.



Keenan, K. E., Stupic, K. F., Boss, M. A., Russek, S. E., Chenevert, T. L., Prasad, P. V., Reddick, W. E., Cecil, K. M., Zheng, J., Hu, P., and Jackson, E. F. (2016).

Multi-site, multi-vendor comparison of T1 measurement using ISMRM/NIST system phantom.

In *Proc. Intl. Soc. Mag. Res. Med.*, page 3290.



Ma, D., Gulani, V., Seiberlich, N., Liu, K., Sunshine, J. L., Duerk, J. L., and Griswold, M. A. (2013).

Magnetic resonance fingerprinting.

Nature, 495:187–93.



Nataraj, G., Nielsen, J.-F., and Fessler, J. A. (2017a).

Myelin water fraction estimation from optimized steady-state sequences using kernel ridge regression.

In *Proc. Intl. Soc. Mag. Res. Med.*, page 5076.

To appear.



Nataraj, G., Nielsen, J.-F., and Fessler, J. A. (2017b).

Optimizing MR scan design for model-based T1, T2 estimation from steady-state sequences.

IEEE Trans. Med. Imag., 36(2):467–77.



Rahimi, A. and Recht, B. (2007).
Random features for large-scale kernel machines.
In *NIPS*.



Redpath, T. W. and Jones, R. A. (1988).
FADE-A new fast imaging sequence.
Mag. Res. Med., 6(2):224–34.



Schölkopf, B., Herbrich, R., and Smola, A. J. (2001).
A generalized representer theorem.
In *Proc. Computational Learning Theory (COLT)*, pages 416–426.
LNCS 2111.



Zur, Y., Wood, M. L., and Neuringer, L. J. (1991).
Spoiling of transverse magnetization in steady-state sequences.
Mag. Res. Med., 21(2):251–63.