

Click to watch video about new features. Apologies for the old data loss, it was tough to map to user id's, as we have the same id for questions across, which was not the case before.

# takeUforward



Striver's  
SDE  
Sheet

Striver's A2Z  
DSA  
Course/Sheet

Striver's  
DSA  
Playlists

CS  
Subjects

Interview  
Prep  
Sheets

Striver's  
CP  
Sheet

August 25, 2022 ▪ Data Structure / Graph

## Rotten Oranges

**Problem Statement:** Given a grid of dimension  $N \times M$  where each cell in the grid can have values 0, 1, or 2 which has the following meaning:

0: Empty cell

1: Cells have fresh oranges

2: Cells have rotten oranges

We have to determine what is the minimum time required to rot all oranges. A rotten orange at index  $[i, j]$  can rot other fresh oranges at indexes  $[i-1, j]$ ,  $[i+1, j]$ ,  $[i, j-1]$ ,  $[i, j+1]$  (up, down, left and right) in unit time.

**Pre-req:** [Graph traversal techniques](#), [Queue STL](#)

**Examples:**

Search

Search

## Recent Posts

[Top Array Interview Questions – Structured Path with Video Solutions](#)

[Longest Subarray with sum K | \[Positives and Negatives\]](#)

[Count Subarray sum Equals K](#)

Example 1:

Input:

2	1	1
1	1	0
0	1	1

Output: 4

Explanation:

Example 2:

Output: 1

Binary Tree  
Representation in  
Java  
Binary Tree  
Representation in  
C++

Accolite Digital  
Amazon Arcesium  
arrays Bank of America  
Barclays BFS Binary  
Search Binary Search  
Tree Commvault CPP DE

Shaw DFS DSA

Self Paced

google HackerEarth Hashing  
infosys inorder Interview  
Experience Java Juspay  
Kreeti Technologies Morgan  
Stanley Newfold Digital  
Oracle post order recursion  
Samsung SDE Core Sheet

SDE Sheet  
Searching set-bits sorting

Strivers  
A2ZDSA

Course sub-array  
subarray Swiggy  
takeuforward TCS TCS

**Explanation:** There are 3 rotten oranges in this example. Rotting of oranges happens simultaneously.

CODEVITA TCS Ninja

TCS NQT

VMware XOR

To understand a better step-by-step process of simultaneous rotting consider the following illustration:

## Solution

**Disclaimer:** *Don't jump directly to the solution, try it out yourself first.*

## Intuition:

A rotten orange at index  $[i,j]$  can rot other fresh oranges at indexes  $[i-1,j]$ ,  $[i+1,j]$ ,  $[i,j-1]$ ,  $[i,j+1]$  (up, down, left and right) in unit time, i.e., in 4 directions.

The question arises of which algorithm to use.

A rotten orange can rot fresh orange neighbours that are at a distance of 1 or at the same level. It means each of them got rotten at a similar level or stage, implying we need to visit the same level at the same time. Hence, level-wise traversal is BFS traversal.

If we use DFS traversal then all neighbouring fresh oranges will be visited depth-wise. But here it is not the case to rot all the oranges, we need to find the minimum time to rot them all, which is possible only when we are in neighbouring directions at an equal pace. We want to rotten them simultaneously.

So, BFS traversal will be used to solve this problem.

## Approach:

### Initial configuration:

- **Queue:** contains a couple of starting points that will depend on the number of rotten oranges present initially.
- **Visited array:** is of the same size as the grid. The visited cell represents rotten orange.

The algorithm steps are as follows:

- For BFS traversal, we need a queue data structure and a visited array. Create a replica of the given array, i.e., create another array of the same size and call it a visited array. We can use the same matrix, but we will avoid alteration of the original data.
- The pairs of cell number and initial time, i.e.,  $\langle \langle \text{row}, \text{column} \rangle, \text{time} \rangle$  will be pushed in the queue and marked as visited (represents rotten) in the visited array. For example,  $((2,0), 0)$  represents cell (2, 0) and initial time 0.
- While BFS traversal, pop out an element from the queue and travel to all its neighbours. In a graph, we store the list of neighbours in an adjacency list but here we know the neighbours are in 4 directions.
- We go in all 4 directions and check for valid unvisited fresh orange neighbours.

To travel 4 directions we will use nested loops, you can find the implementation details in the code.

- BFS function call will make sure that it starts the BFS call from each rotten orange cell, and rotten all the valid fresh orange neighbours and puts them in the queue with an increase in time by 1 unit. Make sure to mark it as rotten in the visited array.
- Pop-out another rotten orange from the queue and repeat the same steps until the queue becomes empty.
- Add a counter variable to store the maximum time and return it. If any of the fresh was not rotten in the visited array then return -1.

Consider the following example to understand how BFS traverses the cells and rotten the oranges accordingly.



## How do set boundaries for 4 directions?

The 4 neighbours will have the following indexes:

Now, either we can apply 4 conditions or follow the following method.

From the above image, it is clear that the delta change in a row is -1, +0, +1, +0. Similarly, the delta change in column is 0, +1, +0, -1. So we can apply the same logic to find the neighbours of a particular pixel (<row, column>).

### Code:

---

#### C++ Code

```
#include<bits/stdc++.h>

using namespace std;

class Solution {
public:
    //Function to find minimum time
```

```

int orangesRotting(vector < vect
// figure out the grid size
int n = grid.size();
int m = grid[0].size();

// store {{row, column}, time}
queue < pair < pair < int, int
int vis[n][m];
int cntFresh = 0;
for (int i = 0; i < n; i++) {
    for (int j = 0; j < m; j++)
        // if cell contains rotten
        if (grid[i][j] == 2) {
            q.push({{i, j}, 0});
            // mark as visited (ro
            vis[i][j] = 2;
        }
        // if not rotten
        else {
            vis[i][j] = 0;
        }
        // count fresh oranges
        if (grid[i][j] == 1) cntFr
    }
}

int tm = 0;
// delta row and delta column
int drow[] = {-1, 0, +1, 0};
int dcol[] = {0, 1, 0, -1};
int cnt = 0;

// bfs traversal (until the qu
while (!q.empty()) {
    int r = q.front().first.firs
    int c = q.front().first.seco
    int t = q.front().second;
    tm = max(tm, t);
    q.pop();
    // exactly 4 neighbours
    for (int i = 0; i < 4; i++)
        // neighbouring row and co
        int nrow = r + drow[i];
        int ncol = c + dcol[i];
        // check for valid cell an
        // then for unvisited fres

```



```

        if (nrow >= 0 && nrow < nrow && ncol >= 0 && ncol < ncol &&
            vis[nrow][ncol] == 0 &&
            // push in queue with time
            q.push({{nrow, ncol}, tm})
            // mark as rotten
            vis[nrow][ncol] = 2;
            cnt++;
        }
    }
}

// if all oranges are not rotten
if (cnt != cntFresh) return -1;

return tm;
}
};

int main() {
    vector<vector<int>>grid{{0,1,2},{0,1,0},{0,1,0}};
    Solution obj;
    int ans = obj.orangesRotting(grid);
    cout << ans << "\n";

    return 0;
}

```

**Output:** 1

**Time Complexity:**  $O(N \times M + N \times M \times 4) \sim O(N \times M)$ , For the worst case, all of the cells will have fresh oranges, so the BFS function will be called for  $(N \times M)$  nodes and for every node, we are traversing for 4 neighbours, it will take  $O(N \times M \times 4)$  time.

**Space Complexity**  $\sim O(N \times M)$ ,  $O(N \times M)$  for copied input array and recursive stack space takes up  $N \times M$  locations at max.

## Java Code

```
import java.util.*;
class Solution {
    //Function to find minimum time re
    public int orangesRotting(int[][]
        // figure out the grid size
        int n = grid.length;
        int m = grid[0].length;
        // n x m
        Queue < Pair > q = new LinkedList
        // n x m
        int[][] vis = new int[n][m];
        int cntFresh = 0;

        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {
                // if cell contains rotten o
                if (grid[i][j] == 2) {
                    q.add(new Pair(i, j, 0));
                    // mark as visited (rotten
                    vis[i][j] = 2;
                }
                // if not rotten
                else {
                    vis[i][j] = 0;
                }

                // count fresh oranges
                if (grid[i][j] == 1) cntFres
            }
        }

        int tm = 0;
        // delta row and delta column
        int drow[] = {-1, 0, +1, 0};
        int dcol[] = {0, 1, 0, -1};
        int cnt = 0;

        // until the queue becomes empty
        while (!q.isEmpty()) {
            int r = q.peek().row;
            int c = q.peek().col;
            int t = q.peek().tm;
            tm = Math.max(tm, t);
```

```

        q.remove();
        // exactly 4 neighbours
        for (int i = 0; i < 4; i++) {
            int nrow = r + drow[i];
            int ncol = c + dcol[i];
            // check for valid coordinates
            // then for unvisited fresh
            if (nrow >= 0 && nrow < n &&
                vis[nrow][ncol] == 0 && gr
                // push in queue with time
                q.add(new Pair(nrow, ncol,
                // mark as rotten
                vis[nrow][ncol] = 2;
                cnt++;
            }
        }
    }
}

// if all oranges are not rotten
if (cnt != cntFresh) return -1;
return tm;
}

public static void main(String[] a
    int[][] grid = {{0,1,2},{0,1,2

    Solution obj = new Solution();
    int ans = obj.orangesRotting(gri
    System.out.println(ans);
}

}

class Pair {
    int row;
    int col;
    int tm;
    Pair(int _row, int _col, int _tm)
        this.row = _row;
        this.col = _col;
        this.tm = _tm;
    }
}

```

**Output: 1**

**Time Complexity:**  $O(N \times M + N \times M \times 4) \sim O(N \times M)$ , For the worst case, all of the cells will have fresh oranges, so the BFS function will be called for  $(N \times M)$  nodes and for every node, we are traversing for 4 neighbours, it will take  $O(N \times M \times 4)$  time.

**Space Complexity**  $\sim O(N \times M)$ ,  $O(N \times M)$  for copied input array and recursive stack space takes up  $N \times M$  locations at max.

Special thanks to [Vanshika Singh Gour](#) for contributing to this article on takeUforward. If you also wish to share your knowledge with the takeUforward fam, [please check out this article](#). If you want to suggest any improvement/correction in this article please mail us at [write4tuf@gmail.com](mailto:write4tuf@gmail.com)

---

[« Previous Post](#)

**Word Search II**

[Next Post »](#)

**Detect Cycle in an  
Undirected Graph  
(using BFS)**

Load Comments

---

Copyright © 2023 takeuforward | All rights reserved