

Register for 45 Day Coding Challenge by CodeStudio and win some exciting prizes

takeUforward



Striver's
SDE
Sheet

Striver's A2Z
DSA
Course/Sheet

Striver's
DSA
Playlists

CS
Subjects


Interviews
Prep
Sheets

Striver's
CP
Sheet


August 6, 2022 ▪ Graph

Connected Components in Graphs

So far we've seen different types of graphs. Graphs can be connected or can be like a binary tree (as we know all trees are graphs with some restrictions) as shown in the following figure.



But what would you call the following figure?



Subscribe

I want to receive latest posts and interview tips

Name*

Email*

Join takeUforward

Search

Search

Recent Posts

The most common answer would be these are 4 different graphs as they are not connected.

But is it possible to call them a single graph? To answer this, let us consider the question given:

Given an undirected graph with 10 nodes and 8 edges. The edges are (1,2), (1,3), (2,4), (4,3), (5,6), (5,7), (6,7), (8,9). The graph that can be formed with the given information is as follows:

Apparently, it's a graph, which is in 4 pieces, the last one being a single node. In this case, we can say, the graph has been broken down into 4 different **connected components**. So next time if you see two different parts of a graph and they are not connected, then do not say that it cannot be a single graph. In the above example, they can be 4 different

[Top Array](#)[Interview](#)[Questions –](#)[Structured Path](#)[with Video](#)[Solutions](#)[Longest Subarray](#)[with sum K |](#)[\[Positives and](#)[Negatives\]](#)[Count Subarray](#)[sum Equals K](#)[Binary Tree](#)[Representation in](#)[Java](#)[Binary Tree](#)[Representation in](#)[C++](#)[Accolite Digital](#)[Amazon](#) Arcesium[arrays](#) Bank of America[Barclays](#) BFS Binary[Search](#) Binary Search[Tree](#) Commvault CPP DE[Shaw](#) DFS **DSA**[Self Paced](#)[google](#) HackerEarth Hashing[infosys](#) inorder Interview[Experience](#) Java Juspay

graphs but according to the given question and the input, we can call them parts of a single graph.

Graph Traversal

In the upcoming topics, we'll be learning about a lot of algorithms. Now, assume a traversal algorithm. Any traversal algorithm will always use a **visited array**.

[Kreeti Technologies Morgan](#)[Stanley Newfold Digital](#)[Oracle post order recursion](#)[Samsung SDE Core Sheet](#)[SDE Sheet](#)[Searching set-bits sorting](#)[Strivers](#)[A2ZDSA](#)[Course](#) sub-array[subarray Swiggy](#)[takeuforward TCS TCS](#)[CODEVITA TCS Ninja](#)[TCS NQT](#)[VMware XOR](#)

For the same example, we will create an array of size $n+1$ starting with the zeroth index. Initialize this visited array to zero, indicating that all the nodes are unvisited. Then follow the following algorithm. If a node is not visited, then call the traversal algorithm.

Why can't we just call traversal(1)?

We cannot just call `traversal(node)` because a graph can have multiple components and traversal algorithms are designed in such a way that they will traverse the entire connected portion of the graph. For example, `traversal(1)` will traverse only the connected nodes, i.e., nodes 2, 3, and 4, but not the connected components.

Consider the following illustration to understand how a traversal algorithm will traverse the connected components.

Special thanks to [Vanshika Singh Gour](#) for contributing to this article on takeUforward. If you also wish to share your knowledge with the takeUforward fam, [please check out this article](#). If you want to suggest any improvement/correction in this article please mail us at write4tuf@gmail.com

« Previous Post

Passing 2D arrays as arguments in CPP

Next Post »

Breadth First Search (BFS): Level Order Traversal

Load Comments

Copyright © 2023 takeuforward | All rights reserved