SIMATS ENGINEERING
ASSESSMENT TOOL 1

COURSE NAME: CSA07 COURSE CODE: Computer Networks

COURSE OUTCOME COVERED

CO1: *Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)*

Assessment Tool Weightage: 40%

Annexure A

SHORT ANSWER TEST

Code of Conduct:

I Aravind M. (192126006 8) *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.*
I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

Criteria	Weightage	Q1 10marks	Q2 10marks	Q3 10marks	Q4 10marks
Understanding of Concepts	25%	2	2	2	2
Explanation	25%	2	2	2	2
Application	20%	1	1	1	1
Organization	15%	1	1	1	1
Accuracy	10%	1	1	1	1
Clarity	5%	1	1	1	1

Total Marks 30 **/40**

Signature of the Faculty

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.

2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.

4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5%** overhead to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7.An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests of

3 MB each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8.A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9.A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10.A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation

Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organizatio n	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers
Accuracy	10%	Completely accurate and covers all required points	Mostly accurate with minor omissions	Partially correct with missing points	Incorrect answers with major gaps
Clarity	5%	Clear, neat, professiona l presentatio n	Understanda ble with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand

M. Aravind
192126006 8
serial no: 41

AT - 1

30/30

1. A company needs to transfer a 150MB design file from a client computer to a remote server over a network with a bandwidth of 50Mbps. The Transport Layer divides the file into 1500-byte segments, while the Data link layer encapsulates each segment into frames by adding 40 bytes of header and trailer. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data link layer, and estimated the total transmission time (ignoring propagation delay). Explain how the transport and data link layers ensure reliable communication.

Ans: Total number of segments:

$$\text{segments} = \frac{150 \times 10^6}{1500}$$

$$= 100,000 \text{ segments}$$

Total number of frames :-

Assuming one segment is encapsulated into one frame.

Total data link layer Overhead:

$= 100000 \times 40 = 4000\,000$

$= 4mb$

Total Transmission time

Total Data link overheaded

$= 100,000 \times 40$

$= 4,000,000$ bytes.

$= N$

$= 150 + 4$

$= 154MB.$

Divide by bandwidth

$$T = \frac{154 \times 10^6 \times 8}{50 \times 10^6}$$

$= 24.68$ seconds.

Explanation: The transport layer divides data into segments and uses mechanism such as sequences numbers, acknowledgement and retransmission (in TCP) to provide reliable delivery. The data link layer encapsulated segments into frame and uses error detection corrupted frames. Link level transmission depends on the protocol used.

2. A transport layer protocol uses a sliding window size of 6 frames. Each frame carries 1024 bytes of user data. If the sender transmits 48 frames, calculate the number of transmission windows required. If one frame in every window is lost and must be transmitted, determine the total number of retransmission. Explain how flow control improves communication efficiency.

Ans: No. of transmission windows

$$\text{Windows} = \frac{48}{6} = 8 \text{ windows}$$

Total no. of transmission

One frame is lost in every windows and must be transmitted.

$$\text{Retransmission} = 8 \times 1$$

8 transmissions

Data transmitted per window

$$6 \times 1024 = 6144 \text{ bytes.}$$

Explanation: Flow control prevents a fast sender from overwhelming a slow reciever. The sliding - window mechanism allows multiple frames to be sent before.

Acknowledgement are received, before improving bandwidth utilization and reducing waiting time. Lost frames are retransmitted according to the protocol.

3.. A 12,000 byte IP packet is transmitted through a router where the Maximum Transmission unit is 1500 bytes. Assuming each fragment require is a 20 byte IP header, Calculate the total number of fragments created and the total header overhead introduced. Explain how the Network layer ensures succesful delivery of fragmentted packets to the destination.

Ans:-

Maximin data per fragment.

1500 - 20 = 1480 bites

The original payload is 12000 - 20 = 11980 bytes.

Total no. of fragments:

$$\text{fragment} = \frac{11980}{1480} = 9 \text{ fragments}$$

The Total header overhead

Overhead = 9 x 20 = 180 bytes.

Total Transmitted size.

= 11980 + 180

= 12160 bytes.

Explanation :- The network layers divided a large IP packet into smaller fragments to fit the MTU of the network. Each fragment contains its own IP header, including identification and fragmentation information. The destination uses this information to reassemble the fragments. If fragments are missing, higher-layer protection such as TCP may help recover the lost data.

4. Transport layer protocol uses a sliding window size of 5 frames. Each frames, calculate the number of retransmission. Explain how flow control improves communication efficiency.

Ans:

Number of transmission windows

$$\text{Windows} = \frac{48}{6}$$

$$= 8 \text{ windows}$$

Total number of retransmissions

one frame lost in every windows

Retransmissions = 8 × 1

8 transmission

Data carried by each window

6 × 1024 = 6144 bytes.

Explanation: Flow control regulates the rate of data transmision so that the reciever can process incoming framing without being overwhelmed. The sliding window method allows the sender to transmit several frames before waiting for acknowledgements.