

ROYAL ENFIELD MOTORCYCLES

Detailed Motorcycle Specifications — India

Current Royal Enfield India motorcycle range and specifications.

No.	Motorcycle	Category
1	Bullet 650	Heritage
2	Hunter 350	Roadster
3	Classic 350	Heritage
4	Bullet 350	Heritage
5	Meteor 350	Cruiser
6	Goan Classic 350	Heritage / Bobber
7	Scram 440	Adventure Crossover
8	Himalayan 450	Adventure Tourer
9	Guerrilla 450	Roadster
10	Bear 650	Scrambler
11	Interceptor 650	Roadster / Twin
12	Continental GT 650	Pure Sport / Café Racer
13	Super Meteor 650	Cruiser
14	Shotgun 650	Supermoto / Custom
15	Classic 650	Heritage

Source: Royal Enfield India current motorcycle range.

01. Bullet 650

Specification	Details
Category	Heritage
Engine	647.95 cc parallel twin, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	34.6 kW @ 7,250 rpm
Maximum torque	52.3 Nm @ 5,650 rpm
Gearbox	6-speed constant mesh
Clutch	Wet multi-plate, slipper-assist
Fuel system	Electronic fuel injection
Mileage / fuel consumption	Manufacturer-published current technical figure varies by document; real-world varies
Top speed	Manufacturer does not publish one current India top-speed figure on the product page
Fuel tank	Current technical specification should be used for tank/weight/dimensions
Kerb weight	Current technical specification should be used for seat/ground clearance/wheelbase
Seat height	Front telescopic fork; twin rear shocks; exact travel/preload per current technical sheet
Ground clearance	Front and rear disc brakes; dual-channel ABS
Wheelbase	Road-oriented tubeless setup; exact current tyre sizes by variant
Suspension	Spoke/heritage wheel design
Brakes & ABS	LED lighting; analogue/digital instrumentation; USB charging on applicable configuration
Tyres	Cannon Black; Battleship Blue
Wheels	Signature single-step-up seat; hand-painted gold pinstripes; winged 3D badging; casquette lamp; twin tiger-eye lamps; 6-speed gearbox

Source: Royal Enfield India product page

02. Hunter 350

Specification	Details
Category	Roadster
Engine	349 cc single-cylinder, 4-stroke, air-oil cooled, SOHC
Bore × stroke	72 × 85.8 mm
Compression ratio	9.5:1
Maximum power	20.2 bhp @ 6,100 rpm
Maximum torque	27 Nm @ 4,000 rpm
Gearbox	5-speed
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	36.2 km/l official test figure
Top speed	114 km/h class technical figure
Fuel tank	13 L class
Kerb weight	About 181 kg wet for Metro specification; variant-dependent
Seat height	790 mm
Ground clearance	150.5 mm
Wheelbase	1,370 mm
Suspension	41 mm telescopic fork; twin-tube emulsion rear shocks; 6-step preload
Brakes & ABS	300 mm front disc; 270 mm rear disc; dual-channel ABS
Tyres	110/70-17 front; 140/70-17 rear; tubeless on alloy configuration
Wheels	17-inch wheels; variant-dependent
Electrical / display	12V 8Ah battery; digi-analogue cluster; USB charging; Tripper availability depends on trim
Colours	Rebel Blue; Rebel Red; Rebel Black; Dapper Ash; Dapper White; Dapper Grey; availability may vary
Key features	Compact wheelbase; low seat; modern-retro styling; dual-channel ABS; connectivity/navigation depending on trim

Source: Royal Enfield Hunter 350 technical specification/product information

03. Classic 350

Specification	Details
Category	Heritage
Engine	349 cc single-cylinder, 4-stroke, air-oil cooled, SOHC
Bore × stroke	72 × 85.8 mm
Compression ratio	9.5:1
Maximum power	20.2 bhp @ 6,100 rpm
Maximum torque	27 Nm @ 4,000 rpm
Gearbox	5-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	36.2 km/l official figure
Top speed	114 km/h technical figure
Fuel tank	13 ± 0.5 L
Kerb weight	195 kg kerb (90% fuel + oil)
Seat height	805 mm
Ground clearance	170 mm
Wheelbase	1,390 mm
Suspension	41 mm telescopic fork, 130 mm travel; twin-tube emulsion shocks, 6-step preload, 90 mm travel
Brakes & ABS	300 mm front disc; 270 mm rear disc; dual-channel ABS
Tyres	100/90-19 front; 120/80-18 rear
Wheels	Spoke/alloy depending on configuration
Electrical / display	12V 8Ah VRLA; LED lighting; digi-analogue cluster; USB; Tripper depending on variant
Colours	Current colour availability is variant/configuration dependent
Key features	Retro styling; J-series engine; counter-balancer; dual-channel ABS; USB; accessory/customisation ecosystem

Source: Royal Enfield India Classic 350 product/technical information

04. Bullet 350

Specification	Details
Category	Heritage
Engine	349 cc single-cylinder, 4-stroke, air-oil cooled, SOHC
Bore × stroke	72 × 85.8 mm
Compression ratio	9.5:1
Maximum power	20.2 bhp @ 6,100 rpm
Maximum torque	27 Nm @ 4,000 rpm
Gearbox	5-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	36.2 km/l official ideal-condition figure
Top speed	114 km/h
Fuel tank	13 L
Kerb weight	195 kg kerb
Seat height	805 mm
Ground clearance	170 mm
Wheelbase	1,390 mm
Suspension	41 mm telescopic fork, 130 mm travel; twin-tube emulsion rear shocks, 6-step preload
Brakes & ABS	300 mm front disc; 270 mm rear disc; dual-channel ABS
Tyres	100/90-19 front; 120/80-18 rear
Wheels	Spoke wheels
Electrical / display	12V 8Ah VRLA; digi-analogue cluster; USB port; LED elements depending on variant
Colours	Military Black; Battalion Black; Standard Black; Standard Maroon; Black Gold
Key features	Gold pinstripes on applicable variants; single bench seat; J-platform engine; counter-balancer; USB; dual-channel ABS

Source: Royal Enfield India Bullet 350 product/technical information

05. Meteor 350

Specification	Details
Category	Cruiser
Engine	349.34 cc single-cylinder, 4-stroke, air-oil cooled
Bore × stroke	72 × 85.8 mm
Compression ratio	9.5:1
Maximum power	20.2 bhp @ 6,100 rpm
Maximum torque	27 Nm @ 4,000 rpm
Gearbox	5-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	36.2 km/l official figure
Top speed	114 km/h class
Fuel tank	15 L class
Kerb weight	Approx. 191 kg kerb, configuration dependent
Seat height	765 mm
Ground clearance	Approx. 170 mm
Wheelbase	1,400 mm
Suspension	Telescopic front fork; twin rear shocks with preload adjustment
Brakes & ABS	Front and rear disc brakes; dual-channel ABS
Tyres	19-inch front / 17-inch rear class
Wheels	Alloy wheels
Electrical / display	LED lighting; digi-analogue cluster; Tripper navigation; USB Type-C on applicable trim
Colours	Fireball Orange; Fireball Grey; Stellar Marine Blue; Stellar Matt Grey; Aurora Red; Aurora Retro Green; Supernova Black
Key features	Low cruiser stance; forward-set controls; Tripper navigation; slip-assist clutch; adjustable levers; Type-C charging

Source: Royal Enfield India Meteor 350 product page

06. Goan Classic 350

Specification	Details
Category	Heritage / Bobber
Engine	349 cc single-cylinder, 4-stroke, air-oil cooled, SOHC
Bore × stroke	72 × 85.8 mm
Compression ratio	9.5:1
Maximum power	20.2 bhp @ 6,100 rpm
Maximum torque	27 Nm @ 4,000 rpm
Gearbox	5-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	36.2 km/l official test figure
Top speed	114 km/h technical specification
Fuel tank	13 ± 0.5 L
Kerb weight	197 kg kerb (90% fuel + oil)
Seat height	805 mm
Ground clearance	170 mm
Wheelbase	1,400 mm
Suspension	41 mm telescopic fork, 130 mm travel; twin-tube emulsion shocks, 6-step preload, 90 mm travel
Brakes & ABS	300 mm front disc; 270 mm rear disc; dual-channel ABS
Tyres	100/90-19 front; 120/80-18 rear
Wheels	Edge-type aluminium spoke wheels / tubeless white-wall configuration depending on version
Electrical / display	12V 8Ah VRLA; LED headlamp; LED tail/turn lamps; digi-analogue cluster; Tripper; USB Type-C
Colours	Purple Haze; Shack Black; Trip Teal; Rave Red
Key features	Mid-ape handlebar; low-slung bobber seat; removable pillion seat; all-LED lighting; Tripper; gear/fuel display; slip-assist clutch

Source: Royal Enfield India Goan Classic 350 product/technical information

07. Scram 440

Specification	Details
Category	Adventure Crossover
Engine	443 cc-class single-cylinder, 4-stroke
Bore × stroke	Current technical sheet should be used for exact bore/stroke/compression
Compression ratio	Current technical sheet should be used
Maximum power	Approx. 25.4 PS class
Maximum torque	Approx. 34 Nm class
Gearbox	6-speed
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	Official test-cycle figure; real-world varies
Top speed	Approx. 150 km/h class; verify current technical sheet
Fuel tank	15 L
Kerb weight	196 kg kerb (90% fuel + oil)
Seat height	795 mm
Ground clearance	200 mm
Wheelbase	1,460 mm
Suspension	41 mm telescopic forks, 190 mm travel; linkage monoshock, 180 mm travel
Brakes & ABS	300 mm front hydraulic disc, 2-piston caliper; 240 mm rear disc; dual-channel ABS with rear switchable function
Tyres	100/90-19 front; 120/90-17 rear
Wheels	Spoke/alloy options; tube/tubeless depends on wheel configuration
Electrical / display	12V 8Ah maintenance-free battery; LED lighting; digital-analogue cluster; USB Type-A; Tripper pod optional
Colours	Current colour names are configuration dependent
Key features	Adventure-crossover stance; 200 mm ground clearance; switchable rear ABS; long-travel suspension; dual-purpose tyres

Source: Royal Enfield India Scram 440 product page

08. Himalayan 450

Specification	Details
Category	Adventure Tourer
Engine	451.65 cc single-cylinder, liquid-cooled, DOHC, 4-valve
Bore × stroke	84 × 81.5 mm
Compression ratio	11.5:1
Maximum power	40.02 PS @ 8,000 rpm
Maximum torque	40 Nm @ 5,500 rpm
Gearbox	6-speed
Clutch	Wet multi-plate, slip & assist
Fuel system	Electronic fuel injection; ride-by-wire
Mileage / fuel consumption	3.59 L/100 km official test consumption (~27.9 km/l equivalent)
Top speed	No single official current India top-speed figure published on the technical sheet
Fuel tank	17.0 L
Kerb weight	196 kg kerb (90% fuel + oil)
Seat height	825 mm standard, adjustable to 845 mm; low seat 805–825 mm
Ground clearance	230 mm
Wheelbase	1,510 mm
Suspension	43 mm USD fork, 200 mm travel; linkage monoshock, 200 mm travel
Brakes & ABS	320 mm front ventilated disc, twin-piston; 270 mm rear ventilated disc, single-piston; dual-channel ABS, switchable
Tyres	90/90-21 front; 140/80 R17 rear
Wheels	Adventure spoke/aluminium-rim setup
Electrical / display	4-inch round TFT; phone connectivity; full-map Google Maps navigation; media controls; ride modes; USB Type-C; LED lighting
Colours	Kamet White; Kaza Brown; Slate Poppy Blue; Slate Himalayan Salt; Hanle Black
Key features	Ride-by-wire; ride modes; full-map navigation; adjustable seat heights; long-travel suspension; switchable ABS; high ground clearance

Source: Royal Enfield India Himalayan 450 2026 technical specification

09. Guerrilla 450

Specification	Details
Category	Roadster
Engine	452 cc-class single-cylinder, liquid-cooled, DOHC
Bore × stroke	84 × 81.5 mm family platform
Compression ratio	11.5:1 family platform
Maximum power	Approx. 40 PS class
Maximum torque	Approx. 40 Nm class
Gearbox	6-speed
Clutch	Wet multi-plate, slip & assist
Fuel system	Electronic fuel injection; ride-by-wire
Mileage / fuel consumption	Official test-cycle value varies by sheet/market
Top speed	Approx. 160 km/h class; verify current sheet
Fuel tank	11 L
Kerb weight	185 kg kerb (90% fuel + oil)
Seat height	780 mm
Ground clearance	169 mm
Wheelbase	1,440 mm
Suspension	43 mm telescopic fork, 140 mm travel; linkage monoshock, 150 mm travel
Brakes & ABS	310 mm ventilated front disc, double-piston; 270 mm rear disc; dual-channel ABS
Tyres	120/70 R17 front; 160/60 R17 rear
Wheels	17-inch road wheels
Electrical / display	Ride-by-wire; digital/TFT instrumentation depending on variant; navigation/connectivity on higher variants; LED lighting
Colours	Current colour/variant availability is configuration dependent
Key features	Sherpa-platform roadster; low seat; 17-inch wheels; Apex variant; 310 mm front disc; compact roadster geometry

Source: Royal Enfield India Guerrilla 450 product page

10. Bear 650

Specification	Details
Category	Scrambler
Engine	648 cc inline twin-cylinder, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	47.4 PS (34.9 kW) @ 7,150 rpm
Maximum torque	56.5 Nm @ 5,150 rpm
Gearbox	6-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	4.66 L/100 km official consumption (~21.5 km/l equivalent)
Top speed	No single official current India figure consistently published
Fuel tank	13.7 L
Kerb weight	214–216 kg kerb depending on specification document
Seat height	830 mm
Ground clearance	184 mm
Wheelbase	1,460 mm
Suspension	43 mm USD fork, 130 mm travel; twin shocks, 115 mm travel
Brakes & ABS	320 mm front ventilated disc, twin-piston floating caliper; 270 mm rear disc; dual-channel ABS, rear switchable
Tyres	100/90-19 front; 140/80 R17 rear
Wheels	Spoked wheels
Electrical / display	4-inch round TFT Tripper Dash; phone connectivity; full-map navigation; media controls; USB Type-C; LED lighting
Colours	Petrol Green; Golden Shadow; Two Four Nine
Key features	Scrambler styling; 650 twin; 19-inch front wheel; high ground clearance; switchable rear ABS; TFT navigation/connectivity; twin shocks

Source: Royal Enfield Bear 650 technical specification

11. Interceptor 650

Specification	Details
Category	Roadster / Twin
Engine	648 cc parallel twin, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	47 PS class / 34.9 kW @ 7,250 rpm
Maximum torque	52 Nm class
Gearbox	6-speed
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	Mid-20 km/l class under test conditions; real-world varies
Top speed	164 km/h (Royal Enfield India FAQ)
Fuel tank	13.7 L
Kerb weight	Approx. 213 kg kerb
Seat height	804 mm
Ground clearance	174 mm
Wheelbase	1,398 mm
Suspension	41 mm telescopic fork; twin rear shocks with adjustable preload
Brakes & ABS	320 mm front disc; 240 mm rear disc; dual-channel ABS
Tyres	100/90-18 front; 130/70-18 rear
Wheels	Spoke/alloy depending on current variant
Electrical / display	LED headlamp on newer configurations; digi-analogue cluster; USB on applicable variants
Colours	Current India colour availability is variant dependent
Key features	Classic twin-cylinder roadster; relaxed ergonomics; twin exhausts; 6-speed; dual-channel ABS

Source: Royal Enfield India Interceptor 650 product page

12. Continental GT 650

Specification	Details
Category	Pure Sport / Café Racer
Engine	648 cc parallel twin, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	47 PS class / 34.9 kW @ 7,250 rpm
Maximum torque	52 Nm class
Gearbox	6-speed
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	About 25 km/l industry-listed figure; actual use varies
Top speed	About 169–170 km/h industry-listed; not treated as manufacturer certification
Fuel tank	12.5 L
Kerb weight	Approx. 211 kg kerb
Seat height	804 mm
Ground clearance	174 mm
Wheelbase	1,398 mm
Suspension	41 mm telescopic fork; twin rear shocks, adjustable preload
Brakes & ABS	320 mm front disc; 240 mm rear disc; dual-channel ABS
Tyres	100/90-18 front; 130/70-18 rear
Wheels	Spoke/alloy variants
Electrical / display	Digi-analogue instrumentation; lighting/USB equipment varies by trim
Colours	Current India colourways are variant dependent
Key features	Café-racer ergonomics; clip-on handlebars; rear-set foot controls; twin-cylinder engine; dual-channel ABS

Source: Royal Enfield India Continental GT 650 product page

13. Super Meteor 650

Specification	Details
Category	Cruiser
Engine	648 cc parallel twin, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	47 PS @ 7,250 rpm
Maximum torque	52.3 Nm @ 5,650 rpm
Gearbox	6-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	22 km/l class technical figure
Top speed	Approx. 160 km/h class
Fuel tank	15.7 L
Kerb weight	241 kg kerb (90% fuel + oil)
Seat height	740 mm
Ground clearance	135 mm
Wheelbase	1,500 mm
Suspension	43 mm USD fork, 120 mm travel; twin shocks, 101 mm travel, preload adjustable
Brakes & ABS	320 mm front disc, twin-piston; 300 mm rear disc, twin-piston; dual-channel ABS
Tyres	100/90-19 front; 150/80 B16 rear, tubeless
Wheels	Alloy/tubeless wheels
Electrical / display	12V 12Ah VRLA; LED headlamp/tail; USB Type-A 5V/2A; digi-analogue cluster; Tripper on applicable trim
Colours	Astral Green; Astral Blue; Astral Black; Celestial Red; Celestial Blue; Interstellar Grey; Interstellar Green
Key features	Low 740 mm seat; cruiser ergonomics; USD fork; 19-inch front wheel; 15.7 L tank; Tripper; USB charging

Source: Royal Enfield Super Meteor 650 technical specification

14. Shotgun 650

Specification	Details
Category	Supermoto / Custom
Engine	648 cc parallel twin, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	34.6 kW @ 7,250 rpm
Maximum torque	52.3 Nm @ 5,650 rpm
Gearbox	6-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	22 km/l official technical figure
Top speed	About 170 km/h industry-listed
Fuel tank	13.8 L
Kerb weight	240 kg kerb (90% fuel + oil)
Seat height	795 mm
Ground clearance	140 mm
Wheelbase	1,465 mm
Suspension	Showa SFF-BP USD fork, 120 mm travel; Showa twin shocks, 90 mm travel
Brakes & ABS	320 mm front disc, twin-piston; 300 mm rear disc, twin-piston; dual-channel ABS
Tyres	100/90-18 front; 150/70 R17 rear, tubeless
Wheels	Cast/alloy-style wheels
Electrical / display	12V 12Ah VRLA; LED headlamp/tail; USB Type-A 5V/2A; analogue-digital instrumentation
Colours	Stencil White; Drill Green; Sheet Metal Grey
Key features	Custom-inspired design; modular single/pillion seat; Showa suspension; 18/17-inch wheels; twin-cylinder engine; dual-channel ABS

Source: Royal Enfield Shotgun 650 technical specification

15. Classic 650

Specification	Details
Category	Heritage
Engine	647.95 cc inline twin-cylinder, 4-stroke, SOHC, air-oil cooled
Bore × stroke	78 × 67.8 mm
Compression ratio	9.5:1
Maximum power	34.6 kW @ 7,250 rpm
Maximum torque	52.3 Nm @ 5,650 rpm
Gearbox	6-speed constant mesh
Clutch	Wet multi-plate
Fuel system	Electronic fuel injection
Mileage / fuel consumption	No single official current India km/l figure prominently published
Top speed	No single manufacturer India top-speed figure consistently published
Fuel tank	14.8 L
Kerb weight	243 kg kerb (90% fuel + oil)
Seat height	800 mm
Ground clearance	154 mm
Wheelbase	1,475 mm
Suspension	43 mm telescopic fork, 120 mm travel; twin shocks, 90 mm travel
Brakes & ABS	320 mm front disc; 300 mm rear disc; dual-channel ABS
Tyres	Tubeless sizes vary by wheel/variant
Wheels	Retro spoke/alloy styling depending on variant
Electrical / display	Retro-analogue speedometer with digital LCD; gear position, distance, fuel level; USB charging; updated switchgear
Colours	Current colour availability is variant dependent
Key features	Classic 650 styling; 648 cc twin; Showa suspension; retro-analogue dashboard; USB; premium chrome/paint details

Source: Royal Enfield India Classic 650 product page