CS 7910 Computational Complexity Assignment 10

Gopal Menon

April 23, 2016

1. **(20 points)** In this exercise, we design an approximation algorithm for the dominating set problem. We have proved in class that the dominating set problem is NP-Complete. Here we consider its optimization problem.

Given an undirected graph G of n vertices, a subset S of vertices of G is a dominating set if each vertex v of G is either in S or connects to a vertex of S by an edge. The problem is to find a dominating set of G of minimum size.

Design a polynomial-time approximation algorithm for the problem with approximation ratio O(log n). In other words, if OPT is the size of the optimal dominating set and C is the size of the dominating set found by your algorithm, then it should hold that $C \leq O(log n) \cdot OPT$, which is equivalent to $C = O(OPT \cdot log n)$ by the definition of the big-O notation.

Consider the following approximate algorithm for finding a dominating set, that takes a graph G having a set of V vertices and E edges as an input parameter

Algorithm 1 Greedy Dominating Set Approximation Algorithm

```
1: procedure Greedy Dominating Set Approximation Algorithm(G)
2:
       Create remaining vertices set R = V
       Create an empty set of vertices S = \phi
3:
       while R \neq \phi do
4:
          Select vertex \nu from R such that set S_i consisting of vertex \nu
          and all vertices connected to \nu by an edge maximizes S_i \cap R
6:
7:
          R = R - S_i
          S = S \cup \nu
8:
       end while
9:
       return S
11: end procedure
```

For every element $x \in S_i \cap R$ in algorithm 1, we can associate a cost $C_x = \frac{1}{S_i \cap R}$. If we add up the cost for every element in set S_i we will get a total of 1. The size of the dominating

set found by this algorithm will be the number of vertices in set *S*. Since the dominating set will cover all vertices either by including them in *S* or by having an edge to it from a vertex in set *S*, the number of vertices *C* in the dominating set will be given by

$$C = \sum_{x \in V} C_x$$

We need to show that this algorithm will give us a dominating set of size

$$C \le O(log n) \cdot OPT$$

where *OPT* is the number of vertices in the optimal dominating set.

We will start by proving the following lemma for any subset of vertices S_k

$$\sum_{x \in S_k} C_x \le H(d_k)$$

where H is the harmonic function defined as

$$H(n) = 1 + \frac{1}{2} + \frac{1}{3} + \frac{1}{4} + \dots + \frac{1}{n} = \theta(\log n)$$
 (1)

and

$$d_k = |S_k|$$

Let

$$S_k = \{x_1, x_2, ..., x_{d_k}\}$$

be the set S_k with its elements ordered by the time they are first removed from the set of remaining vertices R. Consider an element x_i of S_k . Suppose x_i is first removed in an iteration when we remove S_i from R. $x_i \in S_i \cap R$ at the beginning of the iteration. And $x_i, x_{i+1}, ..., x_{d_k}$ have not been removed from R yet.

2. In this exercise, we consider a "dual" problem of the load balancing problem.

Suppose there are m machines and n jobs such that each job i has a processing time t_i . Consider a job assignment that assigns each job to one of these machines. For each machine j, let T_j denote the total sum of the processing time of all jobs assigned to machine j, and we call T_j the workload of machine j. We call the value $min_{1 \le j \le m} T_j$ the $minimum\ workload$ of all machines of the assignment.

The *dual load balancing problem* is to compute a job assignment that *maximizes* the minimum workload of all machines.

Remark. Recall that the load balancing problem is to find a job assignment that minimizes the maximum workload of all machines. Therefore, the two problem are "dual" to each other.

- a) **(5 points)** The dual load balancing problem defined above is an optimization problem. What is the decision version of this problem?
- b) (10 points) Prove that the decision problem is NP-Complete.
- c) **(15 points)** Let A be the sum of the processing time of all jobs, i.e., $A = \sum_{i=1}^{n} t_i$. We assume that $t_i \leq \frac{A}{2m}$ for each job i (intuitively, each t_i is not "too big"). Under this assumption, design a polynomial-time approximation algorithm for the problem with approximation ratio 2. In other words, if OPT is the minimum workload in an optimal solution and C is the minimum workload in your solution, then it holds that $C \geq \frac{1}{2} \cdot OPT$.