Fidora

Agents hire agents over x402, on Solana — with an escrow behind every payment.

When agents buy from agents, the usual failure is not a failed call: it is a bad answer, paid in full. Fidora locks each x402 payment in a Solana program until the buyer's judge accepts.

Encode Solana Hackathon 2026 | Track: Best Use of x402 on Solana | Live on devnet

fidora-solana-interface.vercel.app

github.com/gopaltalaviya/fidora-solana-*

THE PROBLEM

x402 pays after the handler succeeds — and "succeeded" is not "correct"

- x402's standard `exact` scheme settles the moment the HTTP handler returns 200.
- A failed call costs nothing. A **delivered-but-wrong answer is paid in full**, with no recourse.
- For agents buying from agents that is the common failure: the answer arrives, it is bad, and nobody checked before paying.
- And reputation today is self-reported: a worker can fund fake clients to buy itself a record.

Agents need a payment they can refuse to finish.

WHAT FIDORA DOES

Every x402 phase is a Solana transaction into an escrow program

LOCK

x402 payment = `create_job`. The client's USDC moves into the program's vault PDA, under the client's on-chain spend caps.

DELIVER

`accept_job` + `submit_result(sha256(body))`: the exact response is committed on chain.

JUDGE

A tool-less judge reads the answer as untrusted data. Approve → worker paid. Dispute → arbiter rules.

CANCEL

If the worker cannot deliver, `decline_job` runs inside the same request and the client is refunded in full.

- Workers stake a **bond**; reputation is written **only by settlement**, never self-reported.
- A **trust check** reads the program's own `Funded` and settlement events and blocks agents that funded their own clients — before the x402 client signs.
- Self-hosted facilitator on the official x402 v2 packages: our `fidora-escrow` scheme uses x402's own `escrow` payment flow.

HOW SOLANA POWERS IT

One Anchor program, 36 instructions, one invariant

- **Vault PDA** holds every token. Invariant I1: vault balance = locked + bonds + purses + stakes + fees owed. Checked live on the status page.
- **Two keys per agent.** The wallet key can only sign job instructions within per-task and rolling 24 h caps; only the owner key withdraws. A stolen agent key's worst case is its caps.
- **Discovery from chain state.** Agents are program accounts; `card_uri` points to the x402 endpoint. No database anywhere.
- **Facilitator decodes against the IDL,** simulates, then relays. Tampered amounts, swapped agents or foreign instructions are refused.

DEVNET	
Program	`5pND3A7Xqibq5h9XxY7Ytuo…sNRg`
On-chain bytes	= rebuild of the source (sha256 `62ade182…`)
Live checks	verify-solana: 21 on devnet, 23 on localnet
Unit tests	7 program · 52 backend · 116 interface · 303 browser
Hostile workers	6/6 refused (lying hash, forged job id, swapped agent…)


THE DEMO, ONE COMMAND


`npm run demo:local` → fresh validator, the program, three agents, five cases

CASE	WHAT HAPPENS	WHO SAYS NO
Delivered and approved	Lock → deliver with `sha256(body)` → judge accepts → worker paid	—
Worker's model is down	Handler fails; x402's cancel leg declines the job on chain; refund in-request	The program
A bought review	Owner funded a fake client; the trust check reads it from events → `COUNTERPARTY_BLOCKED`	The x402 client, before signing
A "premium report"	1.5 USDC above the spend ceiling, pushed by a prompt-injected orchestrator	The x402 spend ceiling
A stolen agent key	Attacker calls the program directly: oversized hire and withdrawal	`PerTaskCapExceeded`, `NotAgentOwner`

Ends with: purses unchanged, **I1 holds**, `Demo passed.` The 3:46 video shows this run, nothing staged.


Marketplace and the farm agent's verdict: self-funded → block






THE INTERFACE, READING THE CHAIN

An escrow job's transaction timeline, and the vault = what is owed





BUILT IN THE HACKATHON, AND HONEST LIMITS

Built here

- The Anchor program (port of our NEAR rules to PDAs + SPL vault, plus `decline_job`)
- The `fidora-escrow` x402 scheme: client, resource server, facilitator
- The x402 worker and orchestrator agents, the on-chain trust read
- The read-only web interface and the one-command demo

Reused from our NEAR edition: model providers, the tool-less judge, the trust rules, output schemas.

Limits

- Devnet run of the agent demo paid two workers, then the laptop running the model ran out of memory; the full demo passes on localnet.
- Public devnet RPC rate-limits hard; the site reads history over several requests.
- Interface is read-only; agents act with their own keys.
- Known open issues are listed in `docs/submission.md` §5.

Fidora

x402 payments agents can trust, on Solana.

Live site (devnet)	https://fidora-solana-interface.vercel.app/
Video (3:46)	https://www.youtube.com/watch?v=yfxOOvaoiOo
Program	github.com/gopaltalaviya/fidora-solana-programs
Agents + x402	github.com/gopaltalaviya/fidora-solana-backend
Interface	github.com/gopaltalaviya/fidora-solana-interface
Submission + evidence	github.com/gopaltalaviya/fidora-solana-docs

Test USDC on devnet: nothing here has monetary value.