



Neural Network Basics

Quiz, 10 questions



Congratulations! You passed!

Next Item



1. What does a neuron compute?

1 / 1
point



A neuron computes a linear function ($z = Wx + b$) followed by an activation function

Correct

Correct, we generally say that the output of a neuron is $a = g(Wx + b)$ where g is the activation function (sigmoid, tanh, ReLU, ...).



A neuron computes an activation function followed by a linear function ($z = Wx + b$)



A neuron computes the mean of all features before applying the output to an activation function



A neuron computes a function g that scales the input x linearly ($Wx + b$)



2. Which of these is the "Logistic Loss"?

1 / 1
point



$\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|$



$\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = -(y^{(i)} \log(\hat{y}^{(i)}) + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)}))$

Correct

Correct, this is the logistic loss you've seen in lecture!



$\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|^2$



$\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = \max(0, y^{(i)} - \hat{y}^{(i)})$



3. Suppose `img` is a (32,32,3) array, representing a 32x32 image with 3 color channels red, green and blue. How do you reshape this into a column vector?

1 / 1
point



`x = img.reshape((3,32*32))`



`x = img.reshape((32*32*3,1))`

Correct



`x = img.reshape((1,32*32,*3))`



`x = img.reshape((32*32,3))`



4. Consider the two following random arrays "a" and "b":

1 / 1
point

```
1 a = np.random.randn(2, 3) # a.shape = (2, 3)
2 b = np.random.randn(2, 1) # b.shape = (2, 1)
3 c = a + b
```

What will be the shape of "c"?

- ☐ c.shape = (2, 1)
- ☐ c.shape = (3, 2)
- ☒ c.shape = (2, 3)

Correct

Yes! This is broadcasting. b (column vector) is copied 3 times so that it can be summed to each column of a.

- ☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!



5. Consider the two following random arrays "a" and "b":

1 / 1
point

```
1 a = np.random.randn(4, 3) # a.shape = (4, 3)
2 b = np.random.randn(3, 2) # b.shape = (3, 2)
3 c = a*b
```

What will be the shape of "c"?

- ☐ c.shape = (3, 3)
- ☐ c.shape = (4,2)
- ☐ c.shape = (4, 3)
- ☒ The computation cannot happen because the sizes don't match. It's going to be "Error"!

Correct

Indeed! In numpy the "*" operator indicates element-wise multiplication. It is different from "np.dot()". If you would try "c = np.dot(a,b)" you would get c.shape = (4, 2).



6. Suppose you have n_x input features per example. Recall that $X = [x^{(1)} x^{(2)} \dots x^{(m)}]$. What is the dimension of X?

1 / 1
point

- ☐ (1, m)
- ☒ (n_x , m)

Correct

- ☐ $(m, 1)$
- ☐ (m, n_x)



7. Recall that "np.dot(a,b)" performs a matrix multiplication on a and b, whereas "a*b" performs an element-wise multiplication.

1 / 1
point

Consider the two following random arrays "a" and "b":

```
1 a = np.random.randn(12288, 150) # a.shape = (12288, 150)
2 b = np.random.randn(150, 45) # b.shape = (150, 45)
3 c = np.dot(a,b)
```

What is the shape of c?

- ☒ c.shape = (12288, 45)

Correct

Correct, remember that a np.dot(a, b) has shape (number of rows of a, number of columns of b). The sizes match because :

"number of columns of a = 150 = number of rows of b"

- ☐ c.shape = (150,150)
- ☐ c.shape = (12288, 150)
- ☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!



8. Consider the following code snippet:

1 / 1
point

```
1 # a.shape = (3,4)
2 # b.shape = (4,1)
3
4 for i in range(3):
5     for j in range(4):
6         c[i][j] = a[i][j] + b[j]
```

How do you vectorize this?

- ☐ $c = a.T + b$
- ☐ $c = a + b$
- ☒ $c = a + b.T$

Correct

- ☐ $c = a.T + b.T$



9. Consider the following code:

```
1 a = np.random.randn(3, 3)
2 b = np.random.randn(3, 1)
```

1 / 1
point

```
3 c = a*b
```

What will be c ? (If you're not sure, feel free to run this in python to find out).

- ☒ This will invoke broadcasting, so b is copied three times to become $(3,3)$, and $*$ is an element-wise product so $c.shape$ will be $(3, 3)$


Correct

- ☐ This will invoke broadcasting, so b is copied three times to become $(3, 3)$, and $*$ invokes a matrix multiplication operation of two 3×3 matrices so $c.shape$ will be $(3, 3)$
- ☐ This will multiply a 3×3 matrix a with a 3×1 vector, thus resulting in a 3×1 vector. That is, $c.shape = (3, 1)$.
- ☐ It will lead to an error since you cannot use $"*"$ to operate on these two matrices. You need to instead use $np.dot(a,b)$



10. Consider the following computation graph.

1 / 1
point



What is the output J ?

- ☐ $J = (c - 1) * (b + a)$
- ☒ $J = (a - 1) * (b + c)$

Correct

Yes. $J = u + v - w = a*b + a*c - (b + c) = a * (b + c) - (b + c) = (a - 1) * (b + c)$.

- ☐ $J = a*b + b*c + a*c$
- ☐ $J = (b - 1) * (c + a)$

