



## The basics of ConvNets

Quiz, 10 questions

1  
point

1. What do you think applying this filter to a grayscale image will do?

$$\begin{bmatrix} 0 & 1 & -1 & 0 \\ 1 & 3 & -3 & -1 \\ 1 & 3 & -3 & -1 \\ 0 & 1 & -1 & 0 \end{bmatrix}$$

- ☐ Detect horizontal edges
- ☐ Detect image contrast
- ☐ Detect 45 degree edges
- ☒ Detect vertical edges

1  
point

2. Suppose your input is a 300 by 300 color (RGB) image, and you are not using a convolutional network. If the first hidden layer has 100 neurons, each one fully connected to the input, how many parameters does this hidden layer have (including the bias parameters)?

- ☐ 9,000,001
- ☐ 9,000,100
- ☐ 27,000,001
- ☒ 27,000,100

1  
point

3. Suppose your input is a 300 by 300 color (RGB) image, and you use a convolutional layer with 100 filters that are each 5x5. How many parameters does this hidden layer have (including the bias parameters)?

- ☐ 2501
- ☐ 2600
- ☐ 7500
- ☒ 7600

1  
point

4. You have an input volume that is 63x63x16, and convolve it with 32 filters that are each 7x7, using a stride of 2 and no padding. What is the output volume?

- ☐ 16x16x16
- ☒ 29x29x32
- ☐ 16x16x32
- ☐ 29x29x16

1  
point

5. You have an input volume that is 15x15x8, and pad it using "pad=2." What is the dimension of the resulting volume (after padding)?

- ☐ 19x19x12
- ☐ 17x17x10
- ☐ 17x17x8
- ☒ 19x19x8

1  
point

6. You have an input volume that is  $63 \times 63 \times 16$ , and convolve it with 32 filters that are each  $7 \times 7$ , and stride of 1. You want to use a "same" convolution. What is the padding?

- ☐ 1
- ☐ 2
- ☒ 3
- ☐ 7

1  
point

7. You have an input volume that is  $32 \times 32 \times 16$ , and apply max pooling with a stride of 2 and a filter size of 2. What is the output volume?

- ☐  $16 \times 16 \times 8$
- ☐  $32 \times 32 \times 8$
- ☒  $16 \times 16 \times 16$
- ☐  $15 \times 15 \times 16$

1  
point

8. Because pooling layers do not have parameters, they do not affect the backpropagation (derivatives) calculation.

- ☐ True
- ☒ False

1  
point

9. In lecture we talked about "parameter sharing" as a benefit of using convolutional networks. Which of the following statements about parameter sharing in ConvNets are true? (Check all that apply.)

- ☒ It reduces the total number of parameters, thus reducing overfitting.
- ☐ It allows gradient descent to set many of the parameters to zero, thus making the connections sparse.
- ☒ It allows a feature detector to be used in multiple locations throughout the whole input image/input volume.
- ☐ It allows parameters learned for one task to be shared even for a different task (transfer learning).

1  
point

10. In lecture we talked about "sparsity of connections" as a benefit of using convolutional layers. What does this mean?

- ☐ Each layer in a convolutional network is connected only to two other layers
- ☐ Regularization causes gradient descent to set many of the parameters to zero.
- ☐ Each filter is connected to every channel in the previous layer.
- ☒ Each activation in the next layer depends on only a small number of activations from the previous layer.

☒ I, **Gopesh Khandelwal**, understand that submitting work that isn't my own may result in permanent failure of this course or deactivation of my Coursera account.

[Learn more about Coursera's Honor Code](#)

Submit Quiz

