

Python For Data Science Cheat Sheet

Importing Data

Learn Python for data science [Interactively](#) at [www.DataCamp.com](#)



Importing Data in Python

Most of the time, you'll use either NumPy or pandas to import your data:

```
>>> import numpy as np
>>> import pandas as pd
```

Help

```
>>> np.info(np.ndarray.dtype)
>>> help(pd.read_csv)
```

Text Files

Plain Text Files

```
>>> filename = 'huck_finn.txt'
>>> file = open(filename, mode='r')
>>> text = file.read()
>>> print(file.closed)
>>> file.close()
>>> print(text)
```

Open the file for reading
Read a file's contents
Check whether file is closed
Close file

Using the context manager with

```
>>> with open('huck_finn.txt', 'r') as file:
    print(file.readline())
    print(file.readline())
    print(file.readline())
```

Read a single line

Table Data: Flat Files

Importing Flat Files with numpy

Files with one data type

```
>>> filename = 'mnist.txt'
>>> data = np.loadtxt(filename,
    delimiter=',',
    skiprows=2,
    usecols=[0,2],
    dtype=str)
```

String used to separate values
Skip the first 2 lines
Read the 1st and 3rd column
The type of the resulting array

Files with mixed data types

```
>>> filename = 'titanic.csv'
>>> data = np.genfromtxt(filename,
    delimiter=',',
    names=True,
    dtype=None)
```

Look for column header

```
>>> data_array = np.recfromcsv(filename)
```

The default dtype of the np.recfromcsv() function is None.

Importing Flat Files with pandas

```
>>> filename = 'winequality-red.csv'
>>> data = pd.read_csv(filename,
    nrows=5,
    header=None,
    sep='\t',
    comment='#',
    na_values=[""])
```

Number of rows of file to read
Row number to use as col names
Delimiter to use
Character to split comments
String to recognize as NA/NaN

Excel Spreadsheets

```
>>> file = 'urbanpop.xlsx'
>>> data = pd.ExcelFile(file)
>>> df_sheet2 = data.parse('1960-1966',
    skiprows=[0],
    names=['Country',
           'AAM: War(2002)'])

>>> df_sheet1 = data.parse(0,
    parse_cols=[0],
    skiprows=[0],
    names=['Country'])
```

To access the sheet names, use the sheet_names attribute:

```
>>> data.sheet_names
```

SAS Files

```
>>> from sas7bdat import SAS7BDAT
>>> with SAS7BDAT('urbanpop.sas7bdat') as file:
    df_sas = file.to_data_frame()
```

Stata Files

```
>>> data = pd.read_stata('urbanpop.dta')
```

Relational Databases

```
>>> from sqlalchemy import create_engine
>>> engine = create_engine('sqlite://Northwind.sqlite')
```

Use the table_names() method to fetch a list of table names:

```
>>> table_names = engine.table_names()
```

Querying Relational Databases

```
>>> con = engine.connect()
>>> rs = con.execute("SELECT * FROM Orders")
>>> df = pd.DataFrame(rs.fetchall())
>>> df.columns = rs.keys()
>>> con.close()
```

Using the context manager with

```
>>> with engine.connect() as con:
    rs = con.execute("SELECT OrderID FROM Orders")
    df = pd.DataFrame(rs.fetchmany(size=5))
    df.columns = rs.keys()
```

Querying relational databases with pandas

```
>>> df = pd.read_sql_query("SELECT * FROM Orders", engine)
```

Exploring Your Data

NumPy Arrays

```
>>> data_array.dtype
>>> data_array.shape
>>> len(data_array)
```

Data type of array elements
Array dimensions
Length of array

pandas DataFrames

```
>>> df.head()
>>> df.tail()
>>> df.index
>>> df.columns
>>> df.info()
>>> data_array = data.values
```

Return first DataFrame rows
Return last DataFrame rows
Describe index
Describe DataFrame columns
Info on DataFrame
Convert a DataFrame to an NumPy array

Pickled Files

```
>>> import pickle
>>> with open('pickled_fruit.pkl', 'rb') as file:
    pickled_data = pickle.load(file)
```

HDF5 Files

```
>>> import h5py
>>> filename = 'H-H1_LOSC_4_v1-815411200-4096.hdf5'
>>> data = h5py.File(filename, 'r')
```

Matlab Files

```
>>> import scipy.io
>>> filename = 'workspace.mat'
>>> mat = scipy.io.loadmat(filename)
```

Exploring Dictionaries

Accessing Elements with Functions

```
>>> print(mat.keys())
>>> for key in data.keys():
    print(key)
```

Print dictionary keys
Print dictionary keys

```
meta
quality
strain
```

```
>>> pickled_data.values()
>>> print(mat.items())
```

Return dictionary values
Returns items in list format of (key, value) tuple pairs

Accessing Data Items with Keys

```
>>> for key in data['meta'].keys():
    print(key)
```

Explore the HDF5 structure

```
Description
DescriptionURL
Detector
Duration
GPSstart
Observatory
Type
UTCstart
```

```
>>> print(data['meta']['Description'].value)
```

Retrieve the value for a key

Navigating Your FileSystem

Magic Commands

```
!ls
%cd ..
%pwd
```

List directory contents of files and directories
Change current working directory
Return the current working directory path

os Library

```
>>> import os
>>> path = "/usr/tmp"
>>> wd = os.getcwd()
>>> os.listdir(wd)
>>> os.chdir(path)
>>> os.rename("test1.txt",
    "test2.txt")
>>> os.remove("test1.txt")
>>> os.mkdir("newdir")
```

Store the name of current directory in a string
Output contents of the directory in a list
Change current working directory
Rename a file
Delete an existing file
Create a new directory



Python For Data Science Cheat Sheet

Python Basics

Learn More Python for Data Science Interactively at www.datacamp.com



Variables and Data Types

Variable Assignment

```
>>> x=5
>>> x
5
```

Calculations With Variables

>>> x+2 7	Sum of two variables
>>> x-2 3	Subtraction of two variables
>>> x*2 10	Multiplication of two variables
>>> x**2 25	Exponentiation of a variable
>>> x%2 1	Remainder of a variable
>>> x/float(2) 2.5	Division of a variable

Types and Type Conversion

str()	'5', '3.45', 'True'	Variables to strings
int()	5, 3, 1	Variables to integers
float()	5.0, 1.0	Variables to floats
bool()	True, True, True	Variables to booleans

Asking For Help

```
>>> help(str)
```

Strings

```
>>> my_string = 'thisStringIsAwesome'
>>> my_string
'thisStringIsAwesome'
```

String Operations

```
>>> my_string * 2
'thisStringIsAwesomethisStringIsAwesome'
>>> my_string + 'Innit'
'thisStringIsAwesomeInnit'
>>> 'm' in my_string
True
```

Lists

Also see NumPy Arrays

```
>>> a = 'is'
>>> b = 'nice'
>>> my_list = ['my', 'list', a, b]
>>> my_list2 = [[4,5,6,7], [3,4,5,6]]
```

Selecting List Elements

Index starts at 0

Subset

```
>>> my_list[1]
>>> my_list[-3]
```

Select item at index 1
Select 3rd last item

Slice

```
>>> my_list[1:3]
>>> my_list[1:]
>>> my_list[:3]
>>> my_list[:]
```

Select items at index 1 and 2
Select items after index 0
Select items before index 3
Copy my_list

Subset Lists of Lists

```
>>> my_list2[1][0]
>>> my_list2[1][:2]
```

my_list[list][itemOfList]

List Operations

```
>>> my_list + my_list
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']
>>> my_list * 2
['my', 'list', 'is', 'nice', 'my', 'list', 'is', 'nice']
>>> my_list2 > 4
True
```

List Methods

>>> my_list.index(a)	Get the index of an item
>>> my_list.count(a)	Count an item
>>> my_list.append('!')	Append an item at a time
>>> my_list.remove('!')	Remove an item
>>> del(my_list[0:1])	Remove an item
>>> my_list.reverse()	Reverse the list
>>> my_list.extend('!')	Append an item
>>> my_list.pop(-1)	Remove an item
>>> my_list.insert(0, '!')	Insert an item
>>> my_list.sort()	Sort the list

String Operations

Index starts at 0

```
>>> my_string[3]
>>> my_string[4:9]
```

String Methods

>>> my_string.upper()	String to uppercase
>>> my_string.lower()	String to lowercase
>>> my_string.count('w')	Count String elements
>>> my_string.replace('e', 'i')	Replace String elements
>>> my_string.strip()	Strip whitespaces

Libraries

Import libraries

```
>>> import numpy
>>> import numpy as np
Selective import
>>> from math import pi
```

pandas Data analysis	Machine learning
NumPy Scientific computing	matplotlib 2D plotting

Install Python

ANACONDA Leading open data science platform powered by Python	spyder Free IDE that is included with Anaconda	jupyter Create and share documents with live code, visualizations, text, ...
---	--	---

Numpy Arrays

Also see Lists

```
>>> my_list = [1, 2, 3, 4]
>>> my_array = np.array(my_list)
>>> my_2darray = np.array([[1,2,3], [4,5,6]])
```

Selecting Numpy Array Elements

Index starts at 0

Subset

```
>>> my_array[1]
2
```

Select item at index 1

Slice

```
>>> my_array[0:2]
array([1, 2])
```

Select items at index 0 and 1

Subset 2D Numpy arrays

```
>>> my_2darray[:,0]
array([1, 4])
```

my_2darray[rows, columns]

Numpy Array Operations

```
>>> my_array > 3
array([False, False, False,  True], dtype=bool)
>>> my_array * 2
array([2, 4, 6, 8])
>>> my_array + np.array([5, 6, 7, 8])
array([6, 8, 10, 12])
```

Numpy Array Functions

>>> my_array.shape	Get the dimensions of the array
>>> np.append(other_array)	Append items to an array
>>> np.insert(my_array, 1, 5)	Insert items in an array
>>> np.delete(my_array, [1])	Delete items in an array
>>> np.mean(my_array)	Mean of the array
>>> np.median(my_array)	Median of the array
>>> my_array.corrcoef()	Correlation coefficient
>>> np.std(my_array)	Standard deviation



Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



NumPy

The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:



```
>>> import numpy as np
```

NumPy Arrays

1D array

```
1 2 3
```

2D array

axis 1
axis 0

```
1.5 2 3  
4 5 6
```

3D array

axis 2
axis 1
axis 0

Creating Arrays

```
>>> a = np.array([1,2,3])  
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)  
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]],  
                dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))  
>>> np.ones((2,3,4),dtype=np.int16)  
>>> d = np.arange(10,25,5)  
  
>>> np.linspace(0,2,9)  
  
>>> e = np.full((2,2),7)  
>>> f = np.eye(2)  
>>> np.random.random((2,2))  
>>> np.empty((3,2))
```

Create an array of zeros
Create an array of ones
Create an array of evenly spaced values (step value)
Create an array of evenly spaced values (number of samples)
Create a constant array
Create a 2X2 identity matrix
Create an array with random values
Create an empty array

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)  
>>> np.savez('array.npz', a, b)  
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")  
>>> np.genfromtxt("my_file.csv", delimiter=',')  
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64  
>>> np.float32  
>>> np.complex  
>>> np.bool  
>>> np.object  
>>> np.string_  
>>> np.unicode_
```

Signed 64-bit integer types
Standard double-precision floating point
Complex numbers represented by 128 floats
Boolean type storing TRUE and FALSE values
Python object type
Fixed-length string type
Fixed-length unicode type

Inspecting Your Array

```
>>> a.shape  
>>> len(a)  
>>> b.ndim  
>>> e.size  
>>> b.dtype  
>>> b.dtype.name  
>>> b.astype(int)
```

Array dimensions
Length of array
Number of array dimensions
Number of array elements
Data type of array elements
Name of data type
Convert an array to a different type

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b  
array([[ -0.5,  0. ,  0. ],  
       [ -3. , -3. , -3. ]])  
>>> np.subtract(a,b)  
>>> b + a  
array([[ 2.5,  4. ,  6. ],  
       [ 5. ,  7. ,  9. ]])  
>>> np.add(b,a)  
>>> a / b  
array([[ 0.66666667,  1. ,  1. ],  
       [ 0.25 ,  0.4 ,  0.5 ]])  
>>> np.divide(a,b)  
>>> a * b  
array([[ 1.5,  4. ,  9. ],  
       [ 4. , 10. , 18. ]])  
>>> np.multiply(a,b)  
>>> np.exp(b)  
>>> np.sqrt(b)  
>>> np.sin(a)  
>>> np.cos(b)  
>>> np.log(a)  
>>> e.dot(f)  
array([[ 7. ,  7. ],  
       [ 7. ,  7.]])
```

Subtraction
Subtraction
Addition
Addition
Division
Division
Multiplication
Multiplication
Exponentiation
Square root
Print sines of an array
Element-wise cosine
Element-wise natural logarithm
Dot product

Comparison

```
>>> a == b  
array([[False,  True,  True],  
       [False, False, False]], dtype=bool)  
>>> a < 2  
array([[True, False, False], dtype=bool)  
>>> np.array_equal(a, b)
```

Element-wise comparison
Element-wise comparison
Array-wise comparison

Aggregate Functions

```
>>> a.sum()  
>>> a.min()  
>>> b.max(axis=0)  
>>> b.cumsum(axis=1)  
>>> a.mean()  
>>> b.median()  
>>> a.corrcoef()  
>>> np.std(b)
```

Array-wise sum
Array-wise minimum value
Maximum value of an array row
Cumulative sum of the elements
Mean
Median
Correlation coefficient
Standard deviation

Copying Arrays

```
>>> h = a.view()  
>>> np.copy(a)  
>>> h = a.copy()
```

Create a view of the array with the same data
Create a copy of the array
Create a deep copy of the array

Sorting Arrays

```
>>> a.sort()  
>>> c.sort(axis=0)
```

Sort an array
Sort the elements of an array's axis

Subsetting, Slicing, Indexing

Also see Lists

Subsetting

```
>>> a[2]  
3  
>>> b[1,2]  
6.0
```

Select the element at the 2nd index
Select the element at row 1 column 2 (equivalent to b[1][2])

Slicing

```
>>> a[0:2]  
array([1, 2])  
>>> b[0:2,1]  
array([ 2.,  5.])  
>>> b[:1]  
array([[1.5, 2., 3.]])  
>>> c[1,...]  
array([[ 3.,  2.,  1.],  
       [ 4.,  5.,  6.]])
```

Select items at index 0 and 1
Select items at rows 0 and 1 in column 1
Select all items at row 0 (equivalent to b[0:1, :])
Same as [1, :, :]

Boolean Indexing

```
>>> a[a<2]  
array([1])
```

Reversed array a
Select elements from a less than 2

Fancy Indexing

```
>>> b[[1, 0, 1, 0], [0, 1, 2, 0]]  
array([ 4. ,  2. ,  6. , 1.5])  
>>> b[[1, 0, 1, 0]][:, [0,1,2,0]]  
array([[ 4. ,  5. ,  6. ,  4. ],  
       [ 1.5,  2. ,  3. , 1.5],  
       [ 4. ,  5. ,  6. ,  4. ],  
       [ 1.5,  2. ,  3. , 1.5]])
```

Select elements (1,0), (0,1), (1,2) and (0,0)
Select a subset of the matrix's rows and columns

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)  
>>> i.T
```

Permute array dimensions
Permute array dimensions

Changing Array Shape

```
>>> b.ravel()  
>>> g.reshape(3,-2)
```

Flatten the array
Reshape, but don't change data

Adding/Removing Elements

```
>>> h.resize((2,6))  
>>> np.append(h,g)  
>>> np.insert(a, 1, 5)  
>>> np.delete(a, [1])
```

Return a new array with shape (2,6)
Append items to an array
Insert items in an array
Delete items from an array

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)  
array([ 1,  2,  3, 10, 15, 20])  
>>> np.vstack((a,b))  
array([[ 1. ,  2. ,  3. ],  
       [ 1.5,  2. ,  3. ],  
       [ 4. ,  5. ,  6. ]])  
>>> np.r_[e,f]  
>>> np.hstack((e,f))  
array([[ 7.,  7.,  1.,  0.],  
       [ 7.,  7.,  0.,  1.]])  
>>> np.column_stack((a,d))  
array([[ 1, 10],  
       [ 2, 15],  
       [ 3, 20]])  
>>> np.c_[a,d]
```

Concatenate arrays
Stack arrays vertically (row-wise)
Stack arrays vertically (row-wise)
Stack arrays horizontally (column-wise)
Create stacked column-wise arrays
Create stacked column-wise arrays

Splitting Arrays

```
>>> np.hsplit(a,3)  
[array([1]),array([2]),array([3])]  
>>> np.vsplit(c,2)  
[array([[ 1.5,  2. ,  1. ],  
       [ 4. ,  5. ,  6. ]]),  
 array([[ 3.,  2.,  3.],  
       [ 4. ,  5. ,  6.]])]
```

Split the array horizontally at the 3rd index
Split the array vertically at the 2nd index

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

Pandas Basics

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



Pandas

The **Pandas** library is built on NumPy and provides easy-to-use **data structures** and **data analysis** tools for the Python programming language.



Use the following import convention:

```
>>> import pandas as pd
```

Pandas Data Structures

Series

A **one-dimensional** labeled array capable of holding any data type

a	3
b	-5
c	7
d	4

Index

```
>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])
```

DataFrame

	Country	Capital	Population
0	Belgium	Brussels	11190846
1	India	New Delhi	1303171035
2	Brazil	Brasília	207847528

A **two-dimensional** labeled data structure with columns of potentially different types

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
           'Capital': ['Brussels', 'New Delhi', 'Brasília'],
           'Population': [11190846, 1303171035, 207847528]}
```

```
>>> df = pd.DataFrame(data,
                      columns=['Country', 'Capital', 'Population'])
```

I/O

Read and Write to CSV

```
>>> pd.read_csv('file.csv', header=None, nrows=5)
>>> df.to_csv('myDataFrame.csv')
```

Read and Write to Excel

```
>>> pd.read_excel('file.xlsx')
>>> df.to_excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')

Read multiple sheets from the same file
>>> xlsx = pd.ExcelFile('file.xls')
>>> df = pd.read_excel(xlsx, 'Sheet1')
```

Asking For Help

```
>>> help(pd.Series.loc)
```

Selection

Also see NumPy Arrays

Getting

```
>>> s['b']
-5

>>> df[1:]
   Country  Capital  Population
1   India  New Delhi  1303171035
2  Brazil  Brasília  207847528
```

Get one element

Get subset of a DataFrame

Selecting, Boolean Indexing & Setting

By Position

```
>>> df.iloc[[0], [0]]
'Belgium'

>>> df.iat([0], [0])
'Belgium'
```

Select single value by row & column

By Label

```
>>> df.loc[[0], ['Country']]
'Belgium'

>>> df.at([0], ['Country'])
'Belgium'
```

Select single value by row & column labels

By Label/Position

```
>>> df.ix[2]
Country      Brazil
Capital    Brasília
Population  207847528
```

Select single row of subset of rows

```
>>> df.ix[:, 'Capital']
0      Brussels
1    New Delhi
2     Brasilia
```

Select a single column of subset of columns

```
>>> df.ix[1, 'Capital']
'New Delhi'
```

Select rows and columns

Boolean Indexing

```
>>> s[~(s > 1)]
>>> s[(s < -1) | (s > 2)]
>>> df[df['Population'] > 1200000000]
```

Series **s** where value is not >1
s where value is <-1 or >2
Use filter to adjust DataFrame

Setting

```
>>> s['a'] = 6
```

Set index **a** of Series **s** to 6

Dropping

```
>>> s.drop(['a', 'c'])
>>> df.drop('Country', axis=1)
```

Drop values from rows (axis=0)
Drop values from columns(axis=1)

Sort & Rank

```
>>> df.sort_index()
>>> df.sort_values(by='Country')
>>> df.rank()
```

Sort by labels along an axis
Sort by the values along an axis
Assign ranks to entries

Retrieving Series/DataFrame Information

Basic Information

```
>>> df.shape
>>> df.index
>>> df.columns
>>> df.info()
>>> df.count()
```

(rows,columns)
Describe index
Describe DataFrame columns
Info on DataFrame
Number of non-NA values

Summary

```
>>> df.sum()
>>> df.cumsum()
>>> df.min()/df.max()
>>> df.idxmin()/df.idxmax()
>>> df.describe()
>>> df.mean()
>>> df.median()
```

Sum of values
Cumulative sum of values
Minimum/maximum values
Minimum/Maximum index value
Summary statistics
Mean of values
Median of values

Applying Functions

```
>>> f = lambda x: x*2
>>> df.apply(f)
>>> df.applymap(f)
```

Apply function
Apply function element-wise

Data Alignment

Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
a      10.0
b      NaN
c       5.0
d       7.0
```

Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill_value=0)
a      10.0
b     -5.0
c       5.0
d       7.0

>>> s.sub(s3, fill_value=2)
>>> s.div(s3, fill_value=4)
>>> s.mul(s3, fill_value=3)
```

Read and Write to SQL Query or Database Table

```
>>> from sqlalchemy import create_engine
>>> engine = create_engine('sqlite:///memory:')
>>> pd.read_sql("SELECT * FROM my_table;", engine)
>>> pd.read_sql_table('my_table', engine)
>>> pd.read_sql_query("SELECT * FROM my_table;", engine)
```

`read_sql()` is a convenience wrapper around `read_sql_table()` and `read_sql_query()`

```
>>> df.to_sql('myDf', engine)
```

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

Pandas

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



Reshaping Data

Pivot

```
>>> df3= df2.pivot(index='Date',
                    columns='Type',
                    values='Value')
```

Spread rows into columns

	Date	Type	Value
0	2016-03-01	a	11.432
1	2016-03-02	b	13.031
2	2016-03-01	c	20.784
3	2016-03-03	a	99.906
4	2016-03-02	a	1.303
5	2016-03-03	c	20.784

Type	a	b	c
Date			
2016-03-01	11.432	NaN	20.784
2016-03-02	1.303	13.031	NaN
2016-03-03	99.906	NaN	20.784

Pivot Table

```
>>> df4 = pd.pivot_table(df2,
                        values='Value',
                        index='Date',
                        columns='Type')
```

Spread rows into columns

Stack / Unstack

```
>>> stacked = df5.stack()
>>> stacked.unstack()
```

Pivot a level of column labels
Pivot a level of index labels

	0	1
1	5	0.233482
2	4	0.184713
3	3	0.433522

Unstacked

	0	1	2
1	5	0	0.233482
2	4	0	0.184713
3	3	0	0.433522
4	1	1	0.429401

Stacked

Melt

```
>>> pd.melt(df2,
            id_vars=["Date"],
            value_vars=["Type", "Value"],
            value_name="Observations")
```

Gather columns into rows

	Date	Type	Value
0	2016-03-01	a	11.432
1	2016-03-02	b	13.031
2	2016-03-01	c	20.784
3	2016-03-03	a	99.906
4	2016-03-02	a	1.303
5	2016-03-03	c	20.784

	Date	Variable	Observations
0	2016-03-01	Type	a
1	2016-03-02	Type	b
2	2016-03-01	Type	c
3	2016-03-03	Type	a
4	2016-03-02	Type	a
5	2016-03-03	Type	c
6	2016-03-01	Value	11.432
7	2016-03-02	Value	13.031
8	2016-03-01	Value	20.784
9	2016-03-03	Value	99.906
10	2016-03-02	Value	1.303
11	2016-03-03	Value	20.784

Iteration

```
>>> df.iteritems()
>>> df.iterrows()
```

(Column-index, Series) pairs
(Row-index, Series) pairs

Advanced Indexing

Also see NumPy Arrays

Selecting

```
>>> df3.loc[:, (df3>1).any()]
>>> df3.loc[:, (df3>1).all()]
>>> df3.loc[:, df3.isnull().any()]
>>> df3.loc[:, df3.notnull().all()]
```

Select cols with any vals >1
Select cols with vals > 1
Select cols with NaN
Select cols without NaN

Indexing With isin

```
>>> df[(df.Country.isin(df2.Type))]
>>> df3.filter(items=["a", "b"])
>>> df.select(lambda x: not x%5)
```

Find same elements
Filter on values
Select specific elements

Where

```
>>> s.where(s > 0)
```

Subset the data

Query

```
>>> df6.query('second > first')
```

Query DataFrame

Setting/Resetting Index

```
>>> df.set_index('Country')
>>> df4 = df.reset_index()
>>> df = df.rename(index=str,
                  columns={"Country": "entry",
                           "Capital": "cptl",
                           "Population": "ppltn"})
```

Set the index
Reset the index
Rename DataFrame

Reindexing

```
>>> s2 = s.reindex(['a', 'c', 'd', 'e', 'b'])
```

Forward Filling

```
>>> df.reindex(range(4),
               method='ffill')
Country Capital Population
0 Belgium Brussels 11190846
1 India New Delhi 1303171035
2 Brazil Brasilia 207847528
3 Brazil Brasilia 207847528
```

Backward Filling

```
>>> s3 = s.reindex(range(5),
                  method='bfill')
0 3
1 3
2 3
3 3
4 3
```

MultiIndexing

```
>>> arrays = [np.array([1,2,3]),
              np.array([5,4,3])]
>>> df5 = pd.DataFrame(np.random.rand(3, 2), index=arrays)
>>> tuples = list(zip(*arrays))
>>> index = pd.MultiIndex.from_tuples(tuples,
                                    names=['first', 'second'])
>>> df6 = pd.DataFrame(np.random.rand(3, 2), index=index)
>>> df2.set_index(["Date", "Type"])
```

Duplicate Data

```
>>> s3.unique()
>>> df2.duplicated('Type')
>>> df2.drop_duplicates('Type', keep='last')
>>> df.index.duplicated()
```

Return unique values
Check duplicates
Drop duplicates
Check index duplicates

Grouping Data

Aggregation

```
>>> df2.groupby(by=['Date', 'Type']).mean()
>>> df4.groupby(level=0).sum()
>>> df4.groupby(level=0).agg({'a': lambda x: sum(x)/len(x),
                           'b': np.sum})
```

Transformation

```
>>> customSum = lambda x: (x+x%2)
>>> df4.groupby(level=0).transform(customSum)
```

Missing Data

```
>>> df.dropna()
>>> df3.fillna(df3.mean())
>>> df2.replace("a", "f")
```

Drop NaN values
Fill NaN values with a predetermined value
Replace values with others

Combining Data

data1		data2	
X1	X2	X1	X3
a	11.432	a	20.784
b	1.303	b	NaN
c	99.906	d	20.784

Merge

```
>>> pd.merge(data1,
             data2,
             how='left',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
c	99.906	NaN

```
>>> pd.merge(data1,
             data2,
             how='right',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
d	NaN	20.784

```
>>> pd.merge(data1,
             data2,
             how='inner',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN

```
>>> pd.merge(data1,
             data2,
             how='outer',
             on='X1')
```

X1	X2	X3
a	11.432	20.784
b	1.303	NaN
c	99.906	NaN
d	NaN	20.784

Join

```
>>> data1.join(data2, how='right')
```

Concatenate

Vertical

```
>>> s.append(s2)
```

Horizontal/Vertical

```
>>> pd.concat([s,s2],axis=1, keys=['One', 'Two'])
>>> pd.concat([data1, data2], axis=1, join='inner')
```

Dates


```
>>> df2['Date'] = pd.to_datetime(df2['Date'])
>>> df2['Date'] = pd.date_range('2000-1-1',
                              periods=6,
                              freq='M')
>>> dates = [datetime(2012,5,1), datetime(2012,5,2)]
>>> index = pd.DatetimeIndex(dates)
>>> index = pd.date_range(datetime(2012,2,1), end, freq='BM')
```

Visualization


Also see Matplotlib

```
>>> import matplotlib.pyplot as plt
```

```
>>> s.plot()
>>> plt.show()
```



```
>>> df2.plot()
>>> plt.show()
```



DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

SciPy - Linear Algebra

Learn More Python for Data Science [Interactively](https://www.datacamp.com) at www.datacamp.com



SciPy

The **SciPy** library is one of the core packages for scientific computing that provides mathematical algorithms and convenience functions built on the NumPy extension of Python.



Interacting With NumPy

Also see NumPy

```
>>> import numpy as np
>>> a = np.array([1,2,3])
>>> b = np.array([(1+5j,2j,3j), (4j,5j,6j)])
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)])
```

Index Tricks

<pre>>>> np.mgrid[0:5,0:5] >>> np.ogrid[0:2,0:2] >>> np.r_[[3,[0]*5,-1:1:10j]] >>> np.c_[b,c]</pre>	Create a dense meshgrid Create an open meshgrid Stack arrays vertically (row-wise) Create stacked column-wise arrays
---	---

Shape Manipulation

<pre>>>> np.transpose(b) >>> b.flatten() >>> np.hstack((b,c)) >>> np.vstack((a,b)) >>> np.hsplit(c,2) >>> np.vsplit(d,2)</pre>	Permute array dimensions Flatten the array Stack arrays horizontally (column-wise) Stack arrays vertically (row-wise) Split the array horizontally at the 2nd index Split the array vertically at the 2nd index
--	--

Polynomials

<pre>>>> from numpy import polyld >>> p = polyld([3,4,5])</pre>	Create a polynomial object
---	----------------------------

Vectorizing Functions

<pre>>>> def myfunc(a): if a < 0: return a*2 else: return a/2 >>> np.vectorize(myfunc)</pre>	Vectorize functions
---	---------------------

Type Handling

<pre>>>> np.real(c) >>> np.imag(c) >>> np.real_if_close(c,tol=1000) >>> np.cast['f'](np.pi)</pre>	Return the real part of the array elements Return the imaginary part of the array elements Return a real array if complex parts close to 0 Cast object to a data type
---	--

Other Useful Functions

<pre>>>> np.angle(b,deg=True) >>> g = np.linspace(0,np.pi,num=5) >>> g[3:] += np.pi >>> np.unwrap(g) >>> np.logspace(0,10,3) >>> np.select([c<4],[c*2]) >>> misc.factorial(a) >>> misc.comb(10,3,exact=True) >>> misc.central_diff_weights(3) >>> misc.derivative(myfunc,1.0)</pre>	Return the angle of the complex argument Create an array of evenly spaced values (number of samples) Unwrap Create an array of evenly spaced values (log scale) Return values from a list of arrays depending on conditions Factorial Combine N things taken at k time Weights for Np-point central derivative Find the n-th derivative of a function at a point
---	--

Linear Algebra

You'll use the `linalg` and `sparse` modules. Note that `scipy.linalg` contains and expands on `numpy.linalg`.

```
>>> from scipy import linalg, sparse
```

Creating Matrices

```
>>> A = np.matrix(np.random.random((2,2)))
>>> B = np.asmatrix(b)
>>> C = np.mat(np.random.random((10,5)))
>>> D = np.mat([[3,4], [5,6]])
```

Basic Matrix Routines

Inverse

```
>>> A.I
>>> linalg.inv(A)
>>> A.T
>>> A.H
>>> np.trace(A)
```

Inverse
Inverse
Transpose matrix
Conjugate transposition
Trace

Norm

```
>>> linalg.norm(A)
>>> linalg.norm(A,1)
>>> linalg.norm(A,np.inf)
```

Frobenius norm
L1 norm (max column sum)
L inf norm (max row sum)

Rank

```
>>> np.linalg.matrix_rank(C)
```

Matrix rank

Determinant

```
>>> linalg.det(A)
```

Determinant

Solving linear problems

```
>>> linalg.solve(A,b)
>>> E = np.mat(a).T
>>> linalg.lstsq(D,E)
```

Solver for dense matrices
Solver for dense matrices
Least-squares solution to linear matrix equation

Generalized inverse

```
>>> linalg.pinv(C)
>>> linalg.pinv2(C)
```

Compute the pseudo-inverse of a matrix (least-squares solver)
Compute the pseudo-inverse of a matrix (SVD)

Creating Sparse Matrices

<pre>>>> F = np.eye(3, k=1) >>> G = np.mat(np.identity(2)) >>> C[C > 0.5] = 0 >>> H = sparse.csr_matrix(C) >>> I = sparse.csc_matrix(D) >>> J = sparse.dok_matrix(A) >>> E.todense() >>> sparse.isspmatrix_csc(A)</pre>	Create a 2X2 identity matrix Create a 2x2 identity matrix Compressed Sparse Row matrix Compressed Sparse Column matrix Dictionary Of Keys matrix Sparse matrix to full matrix Identify sparse matrix
--	--

Sparse Matrix Routines

Inverse

```
>>> sparse.linalg.inv(I)
```

Inverse

Norm

```
>>> sparse.linalg.norm(I)
```

Norm

Solving linear problems

```
>>> sparse.linalg.spsolve(H,I)
```

Solver for sparse matrices

Sparse Matrix Functions

<pre>>>> sparse.linalg.expm(I)</pre>	Sparse matrix exponential
---	---------------------------

Asking For Help

```
>>> help(scipy.linalg.diagsvd)
>>> np.info(np.matrix)
```

Matrix Functions

Addition

```
>>> np.add(A,D)
```

Addition

Subtraction

```
>>> np.subtract(A,D)
```

Subtraction

Division

```
>>> np.divide(A,D)
```

Division

Multiplication

```
>>> np.multiply(D,A)
>>> np.dot(A,D)
>>> np.vdot(A,D)
>>> np.inner(A,D)
>>> np.outer(A,D)
>>> np.tensordot(A,D)
>>> np.kron(A,D)
```

Multiplication
Dot product
Vector dot product
Inner product
Outer product
Tensor dot product
Kronecker product

Exponential Functions

```
>>> linalg.expm(A)
>>> linalg.expm2(A)
>>> linalg.expm3(D)
```

Matrix exponential
Matrix exponential (Taylor Series)
Matrix exponential (eigenvalue decomposition)

Logarithm Function

```
>>> linalg.logm(A)
```

Matrix logarithm

Trigonometric Functions

```
>>> linalg.sinm(D)
>>> linalg.cosm(D)
>>> linalg.tanm(A)
```

Matrix sine
Matrix cosine
Matrix tangent

Hyperbolic Trigonometric Functions

```
>>> linalg.sinhm(D)
>>> linalg.coshm(D)
>>> linalg.tanhm(A)
```

Hyperbolic matrix sine
Hyperbolic matrix cosine
Hyperbolic matrix tangent

Matrix Sign Function

```
>>> np.sigm(A)
```

Matrix sign function

Matrix Square Root

```
>>> linalg.sqrtm(A)
```

Matrix square root

Arbitrary Functions

```
>>> linalg.funm(A, lambda x: x*x)
```

Evaluate matrix function

Decompositions

Eigenvalues and Eigenvectors

```
>>> la, v = linalg.eig(A)
```

Solve ordinary or generalized eigenvalue problem for square matrix
Unpack eigenvalues
First eigenvector
Second eigenvector
Unpack eigenvalues

```
>>> l1, l2 = la
>>> v[:,0]
>>> v[:,1]
>>> linalg.eigvals(A)
```

Singular Value Decomposition

```
>>> U,s,Vh = linalg.svd(B)
>>> M,N = B.shape
>>> Sig = linalg.diagsvd(s,M,N)
```

Singular Value Decomposition (SVD)
Construct sigma matrix in SVD

LU Decomposition

```
>>> P,L,U = linalg.lu(C)
```

LU Decomposition

Sparse Matrix Decompositions

<pre>>>> la, v = sparse.linalg.eigs(F,1) >>> sparse.linalg.svds(H, 2)</pre>	Eigenvalues and eigenvectors SVD
---	-------------------------------------

DataCamp

Learn Python for Data Science [Interactively](https://www.datacamp.com)



Python For Data Science Cheat Sheet

Scikit-Learn

Learn Python for data science [Interactively](#) at [www.DataCamp.com](#)



Scikit-learn

Scikit-learn is an open source Python library that implements a range of machine learning, preprocessing, cross-validation and visualization algorithms using a unified interface.



A Basic Example

```
>>> from sklearn import neighbors, datasets, preprocessing
>>> from sklearn.model_selection import train_test_split
>>> from sklearn.metrics import accuracy_score
>>> iris = datasets.load_iris()
>>> X, y = iris.data[:, :2], iris.target
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=33)
>>> scaler = preprocessing.StandardScaler().fit(X_train)
>>> X_train = scaler.transform(X_train)
>>> X_test = scaler.transform(X_test)
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
>>> knn.fit(X_train, y_train)
>>> y_pred = knn.predict(X_test)
>>> accuracy_score(y_test, y_pred)
```

Loading The Data

Also see NumPy & Pandas

Your data needs to be numeric and stored as NumPy arrays or SciPy sparse matrices. Other types that are convertible to numeric arrays, such as Pandas DataFrame, are also acceptable.

```
>>> import numpy as np
>>> X = np.random.random((10,5))
>>> y = np.array(['M', 'M', 'F', 'F', 'M', 'F', 'M', 'F', 'F', 'F'])
>>> X[X < 0.7] = 0
```

Training And Test Data

```
>>> from sklearn.model_selection import train_test_split
>>> X_train, X_test, y_train, y_test = train_test_split(X,
                                                    y,
                                                    random_state=0)
```

Preprocessing The Data

Standardization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(X_train)
>>> standardized_X = scaler.transform(X_train)
>>> standardized_X_test = scaler.transform(X_test)
```

Normalization

```
>>> from sklearn.preprocessing import Normalizer
>>> scaler = Normalizer().fit(X_train)
>>> normalized_X = scaler.transform(X_train)
>>> normalized_X_test = scaler.transform(X_test)
```

Binarization

```
>>> from sklearn.preprocessing import Binarizer
>>> binarizer = Binarizer(threshold=0.0).fit(X)
>>> binary_X = binarizer.transform(X)
```

Create Your Model

Supervised Learning Estimators

Linear Regression

```
>>> from sklearn.linear_model import LinearRegression
>>> lr = LinearRegression(normalize=True)
```

Support Vector Machines (SVM)

```
>>> from sklearn.svm import SVC
>>> svc = SVC(kernel='linear')
```

Naïve Bayes

```
>>> from sklearn.naive_bayes import GaussianNB
>>> gnb = GaussianNB()
```

KNN

```
>>> from sklearn import neighbors
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
```

Unsupervised Learning Estimators

Principal Component Analysis (PCA)

```
>>> from sklearn.decomposition import PCA
>>> pca = PCA(n_components=0.95)
```

K Means

```
>>> from sklearn.cluster import KMeans
>>> k_means = KMeans(n_clusters=3, random_state=0)
```

Model Fitting

Supervised learning

```
>>> lr.fit(X, y)
>>> knn.fit(X_train, y_train)
>>> svc.fit(X_train, y_train)
```

Fit the model to the data

Unsupervised Learning

```
>>> k_means.fit(X_train)
>>> pca_model = pca.fit_transform(X_train)
```

Fit the model to the data
Fit to data, then transform it

Prediction

Supervised Estimators

```
>>> y_pred = svc.predict(np.random.random((2,5)))
>>> y_pred = lr.predict(X_test)
>>> y_pred = knn.predict_proba(X_test)
```

Predict labels
Predict labels
Estimate probability of a label

Unsupervised Estimators

```
>>> y_pred = k_means.predict(X_test)
```

Predict labels in clustering algos

Evaluate Your Model's Performance

Classification Metrics

Accuracy Score

```
>>> knn.score(X_test, y_test)
>>> from sklearn.metrics import accuracy_score
>>> accuracy_score(y_test, y_pred)
```

Estimator score method
Metric scoring functions

Classification Report

```
>>> from sklearn.metrics import classification_report
>>> print(classification_report(y_test, y_pred))
```

Precision, recall, f1-score
and support

Confusion Matrix

```
>>> from sklearn.metrics import confusion_matrix
>>> print(confusion_matrix(y_test, y_pred))
```

Regression Metrics

Mean Absolute Error

```
>>> from sklearn.metrics import mean_absolute_error
>>> y_true = [3, -0.5, 2]
>>> mean_absolute_error(y_true, y_pred)
```

Mean Squared Error

```
>>> from sklearn.metrics import mean_squared_error
>>> mean_squared_error(y_test, y_pred)
```

R² Score

```
>>> from sklearn.metrics import r2_score
>>> r2_score(y_true, y_pred)
```

Clustering Metrics

Adjusted Rand Index

```
>>> from sklearn.metrics import adjusted_rand_score
>>> adjusted_rand_score(y_true, y_pred)
```

Homogeneity

```
>>> from sklearn.metrics import homogeneity_score
>>> homogeneity_score(y_true, y_pred)
```

V-measure

```
>>> from sklearn.metrics import v_measure_score
>>> metrics.v_measure_score(y_true, y_pred)
```

Cross-Validation

```
>>> from sklearn.cross_validation import cross_val_score
>>> print(cross_val_score(knn, X_train, y_train, cv=4))
>>> print(cross_val_score(lr, X, y, cv=2))
```

Tune Your Model

Grid Search

```
>>> from sklearn.grid_search import GridSearchCV
>>> params = {"n_neighbors": np.arange(1,5),
            "metric": ["euclidean", "cityblock"]}
>>> grid = GridSearchCV(estimator=knn,
                      param_grid=params)
>>> grid.fit(X_train, y_train)
>>> print(grid.best_score_)
>>> print(grid.best_estimator_.n_neighbors)
```

Randomized Parameter Optimization

```
>>> from sklearn.grid_search import RandomizedSearchCV
>>> params = {"n_neighbors": range(1,5),
            "weights": ["uniform", "distance"]}
>>> rsearch = RandomizedSearchCV(estimator=knn,
                               param_distributions=params,
                               cv=4,
                               n_iter=8,
                               random_state=5)
>>> rsearch.fit(X_train, y_train)
>>> print(rsearch.best_score_)
```



Python For Data Science Cheat Sheet

Matplotlib

Learn Python Interactively at [www.DataCamp.com](https://www.datacamp.com)



Matplotlib

Matplotlib is a Python 2D plotting library which produces publication-quality figures in a variety of hardcopy formats and interactive environments across platforms.



1 Prepare The Data

Also see [Lists & NumPy](#)

1D Data

```
>>> import numpy as np
>>> x = np.linspace(0, 10, 100)
>>> y = np.cos(x)
>>> z = np.sin(x)
```

2D Data or Images

```
>>> data = 2 * np.random.random((10, 10))
>>> data2 = 3 * np.random.random((10, 10))
>>> Y, X = np.mgrid[-3:3:100j, -3:3:100j]
>>> U = -1 - X**2 + Y
>>> V = 1 + X - Y**2
>>> from matplotlib.cbook import get_sample_data
>>> img = np.load(get_sample_data('axes_grid/bivariate_normal.npy'))
```

2 Create Plot

```
>>> import matplotlib.pyplot as plt
```

Figure

```
>>> fig = plt.figure()
>>> fig2 = plt.figure(figsize=plt.figaspect(2.0))
```

Axes

All plotting is done with respect to an Axes. In most cases, a subplot will fit your needs. A subplot is an axes on a grid system.

```
>>> fig.add_axes()
>>> ax1 = fig.add_subplot(221) # row-col-num
>>> ax3 = fig.add_subplot(212)
>>> fig3, axes = plt.subplots(nrows=2,ncols=2)
>>> fig4, axes2 = plt.subplots(ncols=3)
```

3 Plotting Routines

1D Data

```
>>> fig, ax = plt.subplots()
>>> lines = ax.plot(x,y)
>>> ax.scatter(x,y)
>>> axes[0,0].bar([1,2,3],[3,4,5])
>>> axes[1,0].barh([0.5,1,2.5],[0,1,2])
>>> axes[1,1].axhline(0.45)
>>> axes[0,1].axvline(0.65)
>>> ax.fill(x,y,color='blue')
>>> ax.fill_between(x,y,color='yellow')
```

Draw points with lines or markers connecting them
Draw unconnected points, scaled or colored
Plot vertical rectangles (constant width)
Plot horizontal rectangles (constant height)
Draw a horizontal line across axes
Draw a vertical line across axes
Draw filled polygons
Fill between y-values and 0

2D Data or Images

```
>>> fig, ax = plt.subplots()
>>> im = ax.imshow(img,
                  cmap='gist_earth',
                  interpolation='nearest',
                  vmin=-2,
                  vmax=2)
```

Colormapped or RGB arrays

Vector Fields

```
>>> axes[0,1].arrow(0,0,0.5,0.5)
>>> axes[1,1].quiver(y,z)
>>> axes[0,1].streamplot(X,Y,U,V)
```

Add an arrow to the axes
Plot a 2D field of arrows
Plot a 2D field of arrows

Data Distributions

```
>>> ax1.hist(y)
>>> ax3.boxplot(y)
>>> ax3.violinplot(z)
```


Plot a histogram
Make a box and whisker plot
Make a violin plot

```
>>> axes2[0].pcolor(data2)
>>> axes2[0].pcolormesh(data)
>>> CS = plt.contour(Y,X,U)
>>> axes2[2].contourf(data1)
>>> axes2[2] = ax.clabel(CS)
```

Pseudocolor plot of 2D array
Pseudocolor plot of 2D array
Plot contours
Plot filled contours
Label a contour plot

Plot Anatomy & Workflow

Plot Anatomy



Workflow

The basic steps to creating plots with matplotlib are:

- 1 Prepare data
- 2 Create plot
- 3 Plot
- 4 Customize plot
- 5 Save plot
- 6 Show plot

```
>>> import matplotlib.pyplot as plt
>>> x = [1,2,3,4]
>>> y = [10,20,25,30]
>>> fig = plt.figure()
>>> ax = fig.add_subplot(111)
>>> ax.plot(x, y, color='lightblue', linewidth=3)
>>> ax.scatter([2,4,6],
              [5,15,25],
              color='darkgreen',
              marker='^')
>>> ax.set_xlim(1, 6.5)
>>> plt.savefig('foo.png')
>>> plt.show()
```

4 Customize Plot

Colors, Color Bars & Color Maps

```
>>> plt.plot(x, x, x, x**2, x, x**3)
>>> ax.plot(x, y, alpha = 0.4)
>>> ax.plot(x, y, c='k')
>>> fig.colorbar(im, orientation='horizontal')
>>> im = ax.imshow(img,
                  cmap='seismic')
```

Markers

```
>>> fig, ax = plt.subplots()
>>> ax.scatter(x,y,marker=".")
>>> ax.plot(x,y,marker="o")
```

Linestyles

```
>>> plt.plot(x,y,linewidth=4.0)
>>> plt.plot(x,y,ls='solid')
>>> plt.plot(x,y,ls='--')
>>> plt.plot(x,y,'--',x**2,y**2,'-.')
>>> plt.setp(lines,color='r',linewidth=4.0)
```

Text & Annotations

```
>>> ax.text(1,
          -2.1,
          'Example Graph',
          style='italic')
>>> ax.annotate("Sine",
               xy=(8, 0),
               xycoords='data',
               xytext=(10.5, 0),
               textcoords='data',
               arrowprops=dict(arrowstyle="->",
                             connectionstyle="arc3"),)
```

Mathtext

```
>>> plt.title(r'$\sigma_i=15$', fontsize=20)
```

Limits, Legends & Layouts

Limits & Autoscaling

```
>>> ax.margins(x=0.0,y=0.1)
>>> ax.axis('equal')
>>> ax.set(xlim=[0,10.5],ylim=[-1.5,1.5])
>>> ax.set_xlim(0,10.5)
```

Legends

```
>>> ax.set(title='An Example Axes',
          ylabel='Y-Axis',
          xlabel='X-Axis')
>>> ax.legend(loc='best')
```

Ticks

```
>>> ax.xaxis.set(ticks=range(1,5),
               ticklabels=[3,100,-12,"foo"])
>>> ax.tick_params(axis='y',
                  direction='inout',
                  length=10)
```

Subplot Spacing

```
>>> fig3.subplots_adjust(wspace=0.5,
                        hspace=0.3,
                        left=0.125,
                        right=0.9,
                        top=0.9,
                        bottom=0.1)
```

```
>>> fig.tight_layout()
```

Axis Spines

```
>>> ax1.spines['top'].set_visible(False)
>>> ax1.spines['bottom'].set_position(('outward',10))
```

Add padding to a plot
Set the aspect ratio of the plot to 1
Set limits for x-and y-axis
Set limits for x-axis

Set a title and x-and y-axis labels

No overlapping plot elements

Manually set x-ticks

Make y-ticks longer and go in and out

Adjust the spacing between subplots

Fit subplot(s) in to the figure area

Make the top axis line for a plot invisible
Move the bottom axis line outward

5 Save Plot

Save figures

```
>>> plt.savefig('foo.png')
```

Save transparent figures

```
>>> plt.savefig('foo.png', transparent=True)
```

6 Show Plot

```
>>> plt.show()
```

Close & Clear

```
>>> plt.cla()
>>> plt.clf()
>>> plt.close()
```

Clear an axis
Clear the entire figure
Close a window



Bokeh

Learn Bokeh **Interactively** at [www.DataCamp.com](https://www.datacamp.com),
taught by Bryan Van de Ven, core contributor




Plotting With Bokeh

The Python interactive visualization library **Bokeh** enables high-performance visual presentation of large datasets in modern web browsers.



Bokeh's mid-level general purpose `bokeh.plotting` interface is centered around two main components: data and glyphs.



The basic steps to creating plots with the `bokeh.plotting` interface are:

1. Prepare some data:
2. Create a new plot
3. Add renderers for your data, with visual customizations
4. Specify where to generate the output
5. Show or save the results

```
>>> from bokeh.plotting import figure
>>> from bokeh.io import output_file, show
>>> x = [1, 2, 3, 4, 5]
>>> y = [6, 7, 2, 4, 5]
>>> p = figure(title="simple line example",
>>>             x_axis_label='x',
>>>             y_axis_label='y')
>>> p.line(x, y, legend="Temp.", line_width=2)
>>> output_file("lines.html")
>>> show(p)
```

1 Data

Also see [Lists, NumPy & Pandas](#)

Under the hood, your data is converted to Column Data Sources. You can also do this manually:

```
>>> import numpy as np
>>> import pandas as pd
>>> df = pd.DataFrame(np.array([[33.9, 4, 65, 'US'],
>>>                             [32.4, 4, 66, 'Asia'],
>>>                             [21.4, 4, 109, 'Europe']]
>>>                  columns=['mpg', 'cyl', 'hp', 'origin'],
>>>                  index=['Toyota', 'Fiat', 'Volvo'])
>>> from bokeh.models import ColumnDataSource
>>> cds_df = ColumnDataSource(df)
```

2 Plotting

```
>>> from bokeh.plotting import figure
>>> p1 = figure(plot_width=300, tools='pan, box_zoom')
>>> p2 = figure(plot_width=300, plot_height=300,
>>>             x_range=(0, 8), y_range=(0, 8))
>>> p3 = figure()
```

Glyphs



Scatter Markers

```
>>> p1.circle(np.array([1, 2, 3]), np.array([3, 2, 1]),
>>>           fill_color='white')
>>> p2.square(np.array([1.5, 3.5, 5.5]), [1, 4, 3],
>>>           color='blue', size=1)
```




Line Glyphs

```
>>> p1.line([1, 2, 3, 4], [3, 4, 5, 6], line_width=2)
>>> p2.multi_line(pd.DataFrame([[1, 2, 3], [5, 6, 7]]),
>>>               pd.DataFrame([[3, 4, 5], [3, 2, 1]]),
>>>               color="blue")
```

Customized Glyphs

Also see [Data](#)




Selection and Non-Selection Glyphs

```
>>> p = figure(tools='box_select')
>>> p.circle('mpg', 'cyl', source=cds_df,
>>>          selection_color='red',
>>>          nonselection_alpha=0.1)
```



Hover Glyphs

```
>>> from bokeh.models import HoverTool
>>> hover = HoverTool(tooltips=None, mode='vline')
>>> p3.add_tools(hover)
```



Colormapping

```
>>> from bokeh.models import CategoricalColorMapper
>>> color_mapper = CategoricalColorMapper(
>>>               factors=['US', 'Asia', 'Europe'],
>>>               palette=['blue', 'red', 'green'])
>>> p3.circle('mpg', 'cyl', source=cds_df,
>>>           color=dict(field='origin',
>>>                       transform=color_mapper),
>>>           legend='Origin')
```

Legend Location

Inside Plot Area

```
>>> p.legend.location = 'bottom_left'
```

Outside Plot Area

```
>>> from bokeh.models import Legend
>>> r1 = p2.asterisk(np.array([1, 2, 3]), np.array([3, 2, 1]))
>>> r2 = p2.line([1, 2, 3, 4], [3, 4, 5, 6])
>>> legend = Legend(items=[("One", [p1, r1]), ("Two", [r2])],
>>>                  location=(0, -30))
>>> p.add_layout(legend, 'right')
```

Legend Orientation

```
>>> p.legend.orientation = "horizontal"
>>> p.legend.orientation = "vertical"
```

Legend Background & Border

```
>>> p.legend.border_line_color = "navy"
>>> p.legend.background_fill_color = "white"
```

Rows & Columns Layout

Rows

```
>>> from bokeh.layouts import row
>>> layout = row(p1, p2, p3)


Columns



```
>>> from bokeh.layouts import columns
>>> layout = column(p1, p2, p3)

Nesting Rows & Columns


```
>>> layout = row(column(p1, p2), p3)
```


```


```

Grid Layout

```
>>> from bokeh.layouts import gridplot
>>> row1 = [p1, p2]
>>> row2 = [p3]
>>> layout = gridplot([[p1, p2], [p3]])
```

Tabbed Layout

```
>>> from bokeh.models.widgets import Panel, Tabs
>>> tab1 = Panel(child=p1, title="tab1")
>>> tab2 = Panel(child=p2, title="tab2")
>>> layout = Tabs(tabs=[tab1, tab2])
```

Linked Plots

Linked Axes

```
>>> p2.x_range = p1.x_range
>>> p2.y_range = p1.y_range
```

Linked Brushing

```
>>> p4 = figure(plot_width = 100,
>>>             tools='box_select, lasso_select')
>>> p4.circle('mpg', 'cyl', source=cds_df)
>>> p5 = figure(plot_width = 200,
>>>             tools='box_select, lasso_select')
>>> p5.circle('mpg', 'hp', source=cds_df)
>>> layout = row(p4, p5)
```

4 Output & Export

Notebook

```
>>> from bokeh.io import output_notebook, show
>>> output_notebook()
```

HTML

Standalone HTML

```
>>> from bokeh.embed import file_html
>>> from bokeh.resources import CDN
>>> html = file_html(p, CDN, "my_plot")
```

```
>>> from bokeh.io import output_file, show
>>> output_file('my_bar_chart.html', mode='cdn')
```

Components

```
>>> from bokeh.embed import components
>>> script, div = components(p)
```

PNG

```
>>> from bokeh.io import export_png
>>> export_png(p, filename="plot.png")
```

SVG

```
>>> from bokeh.io import export_svgs
>>> p.output_backend = "svg"
>>> export_svgs(p, filename="plot.svg")
```

5 Show or Save Your Plots

```
>>> show(p1)
>>> save(p1)
```

```
>>> show(layout)
>>> save(layout)
```



Python for Data Science Cheat Sheet spaCy

Learn more Python for data science interactively at www.datacamp.com



About spaCy

spaCy is a free, open-source library for advanced Natural Language Processing (NLP) in Python. It's designed specifically for production use and helps you build applications that process and "understand" large volumes of text. **Documentation:** spacy.io

```
$ pip install spacy
```

```
import spacy
```

Statistical models

Download statistical models

Predict part-of-speech tags, dependency labels, named entities and more. See here for available models: spacy.io/models

```
$ python -m spacy download en_core_web_sm
```

Check that your installed models are up to date

```
$ python -m spacy validate
```

Loading statistical models

```
import spacy
# Load the installed model "en_core_web_sm"
nlp = spacy.load("en_core_web_sm")
```

Documents and tokens

Processing text

Processing text with the `nlp` object returns a `Doc` object that holds all information about the tokens, their linguistic features and their relationships

```
doc = nlp("This is a text")
```

Accessing token attributes

```
doc = nlp("This is a text")
# Token texts
[token.text for token in doc]
# ['This', 'is', 'a', 'text']
```

Spans

Accessing spans

Span indices are **exclusive**. So `doc[2:4]` is a span starting at token 2, up to – but not including! – token 4.

```
doc = nlp("This is a text")
span = doc[2:4]
span.text
# 'a text'
```

Creating a span manually

```
# Import the Span object
from spacy.tokens import Span
# Create a Doc object
doc = nlp("I live in New York")
# Span for "New York" with label GPE (geopolitical)
span = Span(doc, 3, 5, label="GPE")
span.text
# 'New York'
```

Linguistic features

Attributes return label IDs. For string labels, use the attributes with an underscore. For example, `token.pos_`.

Part-of-speech tags

PREDICTED BY STATISTICAL MODEL

```
doc = nlp("This is a text.")
# Coarse-grained part-of-speech tags
[token.pos_ for token in doc]
# ['DET', 'VERB', 'DET', 'NOUN', 'PUNCT']
# Fine-grained part-of-speech tags
[token.tag_ for token in doc]
# ['DT', 'VBZ', 'DT', 'NN', '.']
```

Syntactic dependencies

PREDICTED BY STATISTICAL MODEL

```
doc = nlp("This is a text.")
# Dependency labels
[token.dep_ for token in doc]
# ['nsubj', 'ROOT', 'det', 'attr', 'punct']
# Syntactic head token (governor)
[token.head.text for token in doc]
# ['is', 'is', 'text', 'is', 'is']
```

Named entities

PREDICTED BY STATISTICAL MODEL

```
doc = nlp("Larry Page founded Google")
# Text and label of named entity span
[(ent.text, ent.label_) for ent in doc.ents]
# [('Larry Page', 'PERSON'), ('Google', 'ORG')]
```

Syntax iterators

Sentences

USUALLY NEEDS THE DEPENDENCY PARSER

```
doc = nlp("This a sentence. This is another one.")
# doc.sents is a generator that yields sentence spans
[sent.text for sent in doc.sents]
# ['This is a sentence.', 'This is another one.']
```

Base noun phrases

NEEDS THE TAGGER AND PARSER

```
doc = nlp("I have a red car")
# doc.noun_chunks is a generator that yields spans
[chunk.text for chunk in doc.noun_chunks]
# ['I', 'a red car']
```

Label explanations

```
spacy.explain("RB")
# 'adverb'
spacy.explain("GPE")
# 'Countries, cities, states'
```


Visualizing

If you're in a Jupyter notebook, use `displacy.render`. Otherwise, use `displacy.serve` to start a web server and show the visualization in your browser.

```
from spacy import displacy
```

Visualize dependencies

```
doc = nlp("This is a sentence")
displacy.render(doc, style="dep")
```



Visualize named entities

```
doc = nlp("Larry Page founded Google")
displacy.render(doc, style="ent")
```

```
Larry Page PERSON founded Google ORG
```


Word vectors and similarity

To use word vectors, you need to install the larger models ending in `md` or `lg`, for example `en_core_web_lg`.

Comparing similarity


```
doc1 = nlp("I like cats")
doc2 = nlp("I like dogs")
# Compare 2 documents
doc1.similarity(doc2)
# Compare 2 tokens
doc1[2].similarity(doc2[2])
# Compare tokens and spans
doc1[0].similarity(doc2[1:3])
```

Accessing word vectors

```
# Vector as a numpy array
doc = nlp("I like cats")
# The L2 norm of the token's vector
doc[2].vector
doc[2].vector_norm
```

Pipeline components

Functions that take a `Doc` object, modify it and return it.



Pipeline information

```
nlp = spacy.load("en_core_web_sm")
nlp.pipe_names
# ['tagger', 'parser', 'ner']
nlp.pipeline
# [(('tagger', <spacy.pipeline.Tagger>),
#   ('parser', <spacy.pipeline.DependencyParser>),
#   ('ner', <spacy.pipeline.EntityRecognizer>))]
```

Custom components

```
# Function that modifies the doc and returns it
def custom_component(doc):
    print("Do something to the doc here!")
    return doc

# Add the component first in the pipeline
nlp.add_pipe(custom_component, first=True)
```

Components can be added `first`, `last` (default), or `before` or `after` an existing component.

Extension attributes

Custom attributes that are registered on the global `Doc`, `Token` and `Span` classes and become available as `._`.

```
from spacy.tokens import Doc, Token, Span
doc = nlp("The sky over New York is blue")
```

Attribute extensions WITH DEFAULT VALUE

```
# Register custom attribute on Token class
Token.set_extension("is_color", default=False)
# Overwrite extension attribute with default value
doc[6]._.is_color = True
```

Property extensions WITH GETTER & SETTER

```
# Register custom attribute on Doc class
get_reversed = lambda doc: doc.text[::-1]
Doc.set_extension("reversed", getter=get_reversed)
# Compute value of extension attribute with getter
doc._.reversed
# 'eulb si kroY weN revo yks ehT'
```

Method extensions CALLABLE METHOD

```
# Register custom attribute on Span class
has_label = lambda span, label: span.label_ == label
Span.set_extension("has_label", method=has_label)
# Compute value of extension attribute with method
doc[3:5].has_label("GPE")
# True
```

Rule-based matching

Using the matcher

```
# Matcher is initialized with the shared vocab
from spacy.matcher import Matcher
# Each dict represents one token and its attributes
matcher = Matcher(nlp.vocab)
# Add with ID, optional callback and pattern(s)
pattern = [{"LOWER": "new"}, {"LOWER": "york"}]
matcher.add("CITIES", None, pattern)
# Match by calling the matcher on a Doc object
doc = nlp("I live in New York")
matches = matcher(doc)
# Matches are (match_id, start, end) tuples
for match_id, start, end in matches:
    # Get the matched span by slicing the Doc
    span = doc[start:end]
    print(span.text)
# 'New York'
```

Rule-based matching

Token patterns


```
# "love cats", "loving cats", "loved cats"
pattern1 = [{"LEMMA": "love"}, {"LOWER": "cats"}]
# "10 people", "twenty people"
pattern2 = [{"LIKE_NUM": True}, {"TEXT": "people"}]
# "book", "a cat", "the sea" (noun + optional article)
pattern3 = [{"POS": "DET", "OP": "?"}, {"POS": "NOUN"}]
```

Operators and quantifiers

Can be added to a token dict as the `"OP"` key.


- `!` Negate pattern and match exactly 0 times.
- `?` Make pattern optional and match 0 or 1 times.
- `+` Require pattern to match 1 or more times.
- `*` Allow pattern to match 0 or more times.

Glossary	
Tokenization	Segmenting text into words, punctuation etc.
Lemmatization	Assigning the base forms of words, for example: "was" → "be" or "rats" → "rat".
Sentence Boundary Detection	Finding and segmenting individual sentences.
Part-of-speech (POS) Tagging	Assigning word types to tokens like verb or noun.
Dependency Parsing	Assigning syntactic dependency labels, describing the relations between individual tokens, like subject or object.
Named Entity Recognition (NER)	Labeling named "real-world" objects, like persons, companies or locations.
Text Classification	Assigning categories or labels to a whole document, or parts of a document.
Statistical model	Process for making predictions based on examples.
Training	Updating a statistical model with new examples.



DataCamp

Learn Python for data science interactively at www.datacamp.com



Python For Data Science Cheat Sheet

Keras

Learn Python for data science [Interactively](#) at [www.DataCamp.com](#)



Keras

Keras is a powerful and easy-to-use deep learning library for Theano and TensorFlow that provides a high-level neural networks API to develop and evaluate deep learning models.

A Basic Example

```
>>> import numpy as np
>>> from keras.models import Sequential
>>> from keras.layers import Dense
>>> data = np.random.random((1000,100))
>>> labels = np.random.randint(2,size=(1000,1))
>>> model = Sequential()
>>> model.add(Dense(32,
                    activation='relu',
                    input_dim=100))
>>> model.add(Dense(1, activation='sigmoid'))
>>> model.compile(optimizer='rmsprop',
                loss='binary_crossentropy',
                metrics=['accuracy'])
>>> model.fit(data,labels,epochs=10,batch_size=32)
>>> predictions = model.predict(data)
```

Data

Also see NumPy, Pandas & Scikit-Learn

Your data needs to be stored as NumPy arrays or as a list of NumPy arrays. Ideally, you split the data in training and test sets, for which you can also resort to the `train_test_split` module of `sklearn.cross_validation`.

Keras Data Sets

```
>>> from keras.datasets import boston_housing,
                                mnist,
                                cifar10,
                                imdb
>>> (x_train,y_train),(x_test,y_test) = mnist.load_data()
>>> (x_train2,y_train2),(x_test2,y_test2) = boston_housing.load_data()
>>> (x_train3,y_train3),(x_test3,y_test3) = cifar10.load_data()
>>> (x_train4,y_train4),(x_test4,y_test4) = imdb.load_data(num_words=20000)
>>> num_classes = 10
```

Other

```
>>> from urllib.request import urlopen
>>> data = np.loadtxt(urlopen("http://archive.ics.uci.edu/
ml/machine-learning-databases/pima-indians-diabetes/
pima-indians-diabetes.data"),delimiter=",")
>>> X = data[:,0:8]
>>> y = data[:,8]
```

Preprocessing

Sequence Padding

```
>>> from keras.preprocessing import sequence
>>> x_train4 = sequence.pad_sequences(x_train4,maxlen=80)
>>> x_test4 = sequence.pad_sequences(x_test4,maxlen=80)
```

One-Hot Encoding

```
>>> from keras.utils import to_categorical
>>> Y_train = to_categorical(y_train, num_classes)
>>> Y_test = to_categorical(y_test, num_classes)
>>> Y_train3 = to_categorical(y_train3, num_classes)
>>> Y_test3 = to_categorical(y_test3, num_classes)
```

Model Architecture

Sequential Model

```
>>> from keras.models import Sequential
>>> model = Sequential()
>>> model2 = Sequential()
>>> model3 = Sequential()
```

Multilayer Perceptron (MLP)

Binary Classification

```
>>> from keras.layers import Dense
>>> model.add(Dense(12,
                    input_dim=8,
                    kernel_initializer='uniform',
                    activation='relu'))
>>> model.add(Dense(8,kernel_initializer='uniform',activation='relu'))
>>> model.add(Dense(1,kernel_initializer='uniform',activation='sigmoid'))
```

Multi-Class Classification

```
>>> from keras.layers import Dropout
>>> model.add(Dense(512,activation='relu',input_shape=(784,)))
>>> model.add(Dropout(0.2))
>>> model.add(Dense(512,activation='relu'))
>>> model.add(Dropout(0.2))
>>> model.add(Dense(10,activation='softmax'))
```

Regression

```
>>> model.add(Dense(64,activation='relu',input_dim=train_data.shape[1]))
>>> model.add(Dense(1))
```

Convolutional Neural Network (CNN)

```
>>> from keras.layers import Activation,Conv2D,MaxPooling2D,Flatten
>>> model2.add(Conv2D(32,(3,3),padding='same',input_shape=x_train.shape[1:]))
>>> model2.add(Activation('relu'))
>>> model2.add(Conv2D(32,(3,3)))
>>> model2.add(Activation('relu'))
>>> model2.add(MaxPooling2D(pool_size=(2,2)))
>>> model2.add(Dropout(0.25))
>>> model2.add(Conv2D(64,(3,3), padding='same'))
>>> model2.add(Activation('relu'))
>>> model2.add(Conv2D(64,(3,3)))
>>> model2.add(Activation('relu'))
>>> model2.add(MaxPooling2D(pool_size=(2,2)))
>>> model2.add(Dropout(0.25))
>>> model2.add(Flatten())
>>> model2.add(Dense(512))
>>> model2.add(Activation('relu'))
>>> model2.add(Dropout(0.5))
>>> model2.add(Dense(num_classes))
>>> model2.add(Activation('softmax'))
```

Recurrent Neural Network (RNN)

```
>>> from keras.layers import Embedding,LSTM
>>> model3.add(Embedding(20000,128))
>>> model3.add(LSTM(128,dropout=0.2,recurrent_dropout=0.2))
>>> model3.add(Dense(1,activation='sigmoid'))
```

Also see NumPy & Scikit-Learn

Train and Test Sets

```
>>> from sklearn.model_selection import train_test_split
>>> X_train5,X_test5,y_train5,y_test5 = train_test_split(X,
                                                         y,
                                                         test_size=0.33,
                                                         random_state=42)
```

Standardization/Normalization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(x_train2)
>>> standardized_X = scaler.transform(x_train2)
>>> standardized_X_test = scaler.transform(x_test2)
```

Inspect Model

```
>>> model.output_shape
>>> model.summary()
>>> model.get_config()
>>> model.get_weights()
```

Model output shape
Model summary representation
Model configuration
List all weight tensors in the model

Compile Model

MLP: Binary Classification

```
>>> model.compile(optimizer='adam',
                  loss='binary_crossentropy',
                  metrics=['accuracy'])
```

MLP: Multi-Class Classification

```
>>> model.compile(optimizer='rmsprop',
                  loss='categorical_crossentropy',
                  metrics=['accuracy'])
```

MLP: Regression

```
>>> model.compile(optimizer='rmsprop',
                  loss='mse',
                  metrics=['mae'])
```

Recurrent Neural Network

```
>>> model3.compile(loss='binary_crossentropy',
                  optimizer='adam',
                  metrics=['accuracy'])
```

Model Training

```
>>> model3.fit(x_train4,
              y_train4,
              batch_size=32,
              epochs=15,
              verbose=1,
              validation_data=(x_test4,y_test4))
```

Evaluate Your Model's Performance

```
>>> score = model3.evaluate(x_test,
                           y_test,
                           batch_size=32)
```

Prediction

```
>>> model3.predict(x_test4, batch_size=32)
>>> model3.predict_classes(x_test4,batch_size=32)
```

Save/ Reload Models

```
>>> from keras.models import load_model
>>> model3.save('model_file.h5')
>>> my_model = load_model('my_model.h5')
```

Model Fine-tuning

Optimization Parameters

```
>>> from keras.optimizers import RMSprop
>>> opt = RMSprop(lr=0.0001, decay=1e-6)
>>> model2.compile(loss='categorical_crossentropy',
                  optimizer=opt,
                  metrics=['accuracy'])
```

Early Stopping

```
>>> from keras.callbacks import EarlyStopping
>>> early_stopping_monitor = EarlyStopping(patience=2)
>>> model3.fit(x_train4,
              y_train4,
              batch_size=32,
              epochs=15,
              validation_data=(x_test4,y_test4),
              callbacks=[early_stopping_monitor])
```



Data Science Cheat Sheet for Business Leaders

Data Science Basics

Types of Data Science

- **Descriptive Analytics (Business Intelligence):** Get useful data in front of the right people in the form of dashboards, reports, and emails
 - Which customers have churned?
 - Which homes have sold in a given location, and do homes of a certain size sell more quickly?
- **Predictive Analytics (Machine Learning):** Put data science models continuously into production
 - Which customers may churn?
 - How much will a home sell for, given its location and number of rooms?
- **Prescriptive Analytics (Decision Science):** Use data to help a company make decisions
 - What should we do about the particular types of customers that are prone to churn?
 - How should we market a home to sell quickly, given its location and number of rooms?

The Standard Data Science Workflow

1 **Data Collection:** Compile data from different sources and store it for efficient access



2 **Exploration and Visualization:** Explore and visualize data through dashboards






3 **Experimentation and Prediction:** The buzziest topic in data science—machine learning!

Building a Data Science Team

Your data team members require different skills for different purposes.

Data Engineer	Data Analyst	Machine Learning Engineer	Data Scientist
Store and maintain data	Visualize and describe data	Write production-level code to predict with data	Build custom models to drive business decisions
SQL/Java/Scala/Python	SQL + BI Tools + Spreadsheets	Python/Java/R	Python/R/SQL




Data Science Team Organizational Models

Centralized/isolated	Embedded	Hybrid
The data team is the owner of data and answers requests from other teams	Data experts are dispersed across an organization and report to functional leaders	Data experts sit with functional teams and also report to the Chief Data Scientist—so data is an organizational priority
		








Exploration and Visualization

The type of dashboard you should use depends on what you'll be using it for.




Common Dashboard Elements

Type	What is it best for?	Example
Time series	Tracking a value over time	
Stacked bar chart	Tracking composition over time	
Bar chart	Categorical comparison	

Popular Dashboard Tools

Spreadsheets	BI Tools	Customized Tools
 Excel	 Power BI	 R Shiny
 Sheets	 Tableau	 d3.js
	 Looker	



When You Should Request a Dashboard

-  When you'll use it multiple times
-  When you'll need the information updated regularly
-  When the request will always be the same

Experimentation and Prediction

Machine Learning

Machine learning is an application of artificial intelligence (AI) that builds algorithms and statistical models to train data to address specific questions without explicit instructions.

	Supervised Machine Learning	Unsupervised Machine Learning
Purpose	Makes predictions from data with labels and features	Makes predictions by clustering data with no labels into categories
Example	Recommendation systems, email subject optimization, churn prediction	Image segmentation, customer segmentation
		

Special Topics in Machine Learning

- **Time Series Forecasting** is a technique for predicting events through a sequence of time and can capture seasonality or periodic events.
- **Natural Language Processing (NLP)** allows computers to process and analyze large amounts of natural language data.
 - Text as input data
 - Word counts track the important words in a text
 - Word embeddings create features that group similar words

Deep Learning / Neural Networks enables unsupervised machine learning using data that is unstructured or unlabeled.	Explainable AI is an emerging field in machine learning that applies AI such that results can be easily understood.
Highly accurate predictions	Understandable by humans
Better for "What?"	Better for "Why?"