

A quick honesty note: **a truly exhaustive list of every CSS property, every descriptor, and every at-rule variant would be far too large for one chat message.** So below I'm giving you the **complete practical CSS syntax map**—covering all major language topics and syntax families—with **HTML + CSS examples for each.** This is the most useful “complete” version for learning and interviews.

Complete CSS Syntax Guide (with HTML for every topic)

1) Basic CSS Rule Syntax

Syntax

```
selector {  
  property: value;  
  property-two: value-two;  
}
```

Example

```
<!DOCTYPE html>  
  
<html>  
  
<head>  
  
  <style>  
  
    p {  
      color: red;  
      font-size: 18px;  
    }  
  
  </style>  
  
</head>  
  
<body>  
  
  <p>Hello CSS</p>  
  
</body>  
  
</html>
```

Parts

- **Selector** → chooses HTML element(s)
- **Declaration block** → inside { }
- **Property** → color
- **Value** → red

This matches the basic rule syntax documented in CSS reference - CSS | MDN.
[\[developer...ozilla.org\]](https://developer.mozilla.org)

2) Ways to Add CSS to HTML

A) Inline CSS

```
<p style="color: blue; font-size: 20px;">Inline CSS</p>
```

B) Internal CSS

```
<!DOCTYPE html>

<html>

<head>

  <style>

    h1 {

      color: green;

    }

  </style>

</head>

<body>

  <h1>Internal CSS</h1>

</body>

</html>
```

C) External CSS

index.html

```
<!DOCTYPE html>
```

```
<html>

<head>

  <link rel="stylesheet" href="styles.css">

</head>

<body>

  <h2>External CSS</h2>

</body>

</html>
```

styles.css

```
h2 {
  color: purple;
}
```

D) @import

```
<!DOCTYPE html>

<html>

<head>

  <style>

    @import url("theme.css");

  </style>

</head>

<body>

  <p>Imported CSS</p>

</body>

</html>
```

Your internal encyclopedia explicitly lists inline, internal, external, and @import as the main inclusion patterns. [\[css_produc...yclopedia | HTML\]](#)

3) Comments

Syntax

```
/* Single-line comment /
```

```
/
```

```
Multi-line comment
```

```
*/
```

Example

```
<style>
```

```
/* Make the text large */
```

```
p {
```

```
font-size: 24px;
```

```
}
```

```
</style>
```

```
<p>Comment example</p>
```

4) Selectors

MDN describes CSS selectors as the patterns used to target elements, with syntax selector { property: value; }. [\[developer...ozilla.org\]](https://developer.mozilla.org)

4.1 Universal Selector

```
* {
```

```
box-sizing: border-box;
```

```
}
```

```
<div>Box 1</div>
```

```
<p>Paragraph</p>
```

4.2 Type / Element Selector

```
p {  
  color: brown;  
}  
  
<p>This is a paragraph.</p>  
  
<p>This is another paragraph.</p>
```

4.3 Class Selector

```
.note {  
  background: yellow;  
}  
  
<p class="note">Important note</p>
```

4.4 ID Selector

```
#main-title {  
  color: darkblue;  
}  
  
<h1 id="main-title">Welcome</h1>
```

4.5 Grouping Selector

```
h1, h2, p {  
  font-family: Arial, sans-serif;  
}  
  
<h1>Heading 1</h1>  
  
<h2>Heading 2</h2>  
  
<p>Paragraph text</p>
```

4.6 Attribute Selectors

```
input[type="text"] {
```

```
border: 2px solid green;
}
```

```
a[target="_blank"] {
  color: red;
}
```

```
<input type="text" placeholder="Your name">
```

```
https://example.comOpen</a>
```

Common forms:

```
[disabled] { opacity: 0.5; }
```

```
[href] { color: blue; }
```

```
[class~="active"] { font-weight: bold; }
```

```
[lang="en"] { color: navy; }
```

```
[data-role^="admin"] { color: crimson; }
```

```
[data-role$="user"] { color: teal; }
```

```
[data-role*="mod"] { background: gold; }
```

4.7 Descendant Selector

```
article p {
  color: darkgreen;
}
```

```
<article>
  <p>Inside article</p>
</article>
```

4.8 Child Selector

```
ul > li {
  color: blue;
```

```
}  
<ul>  
  <li>Direct child item</li>  
</ul>
```

4.9 Adjacent Sibling Selector

```
h2 + p {  
  color: orange;  
}  
<h2>Heading</h2>  
<p>This paragraph is immediately after h2.</p>
```

4.10 General Sibling Selector

```
h2 ~ p {  
  color: purple;  
}  
<h2>Heading</h2>  
<div>Something else</div>  
<p>This paragraph is a later sibling.</p>
```

Your internal reference explicitly lists descendant, child, adjacent sibling, and general sibling combinators. [\[css_produc...cyclopedia | HTML\]](#)

5) Pseudo-classes

MDN defines pseudo-classes as selectors beginning with : that target elements in a certain state, such as :hover. [\[developer...ozilla.org\]](#)

Syntax

```
selector:pseudo-class {  
  property: value;  
}
```

Common pseudo-classes with examples

:hover

```
button:hover {  
    background: black;  
    color: white;  
}  
  
<button>Hover me</button>
```

:focus

```
input:focus {  
    outline: 3px solid blue;  
}  
  
<input type="text" placeholder="Focus me">
```

:active

```
button:active {  
    transform: scale(0.95);  
}  
  
<button>Click me</button>
```

:visited and :link

```
a:link { color: blue; }  
a:visited { color: purple; }  
  
https://example.comVisit link</a>
```

:first-child

```
li:first-child {  
    font-weight: bold;  
}  
  
<ul>  
    <li>First item</li>  
    <li>Second item</li>
```



```
</ul>
```

:last-child

```
li:last-child {  
    color: red;  
}
```

```
<ul>
```

```
    <li>First</li>
```

```
    <li>Last</li>
```

```
</ul>
```

:nth-child()

```
tr:nth-child(even) {  
    background: #f2f2f2;  
}
```

```
<table>
```

```
    <tr><td>1</td></tr>
```

```
    <tr><td>2</td></tr>
```

```
    <tr><td>3</td></tr>
```

```
</table>
```

:not()

```
p:not(.special) {  
    color: gray;  
}
```

```
<p>Normal paragraph</p>
```

```
<p class="special">Special paragraph</p>
```

Form-related pseudo-classes

```
input:required { border-left: 4px solid red; }
```

```
input:valid { border-color: green; }
```

```
input:invalid { border-color: red; }
```

```
input:disabled { background: #eee; }  
input:checked + label { color: green; }  
<input type="email" required placeholder="Email">  
<br><br>  
  
<input type="checkbox" id="agree" checked>  
<label for="agree">Agree</label>  
  
<br><br>  
<input type="text" disabled value="Disabled input">
```

6) Pseudo-elements

MDN defines pseudo-elements with ::, for example p::first-line. [\[developer...ozilla.org\]](https://developer.mozilla.org)

Syntax

```
selector::pseudo-element {  
  property: value;  
}
```

Common pseudo-elements

::before

```
.note::before {  
  content: "★ ";  
  color: gold;  
}  
  
<p class="note">Important</p>
```

::after

```
.note::after {  
  content: " ✓";  
  color: green;
```

```
}
```

```
<p class="note">Completed</p>
```

::first-line

```
p::first-line {  
    font-weight: bold;  
}
```

```
<p>This paragraph has a special first line when it wraps onto multiple lines.</p>
```

::first-letter

```
p::first-letter {  
    font-size: 2em;  
    color: crimson;  
}
```

```
<p>Decorative first letter example.</p>
```

::selection

```
::selection {  
    background: black;  
    color: white;  
}
```

```
<p>Select this text with your mouse.</p>
```

7) CSS Value Types

MDN's CSS reference groups syntax into data types and functional notations as part of the core language. [\[developer...ozilla.org\]](https://developer.mozilla.org)

7.1 Keywords

```
display: block;  
position: relative;  
font-weight: bold;
```

7.2 Numbers and Integers

line-height: 1.5;

z-index: 10;

opacity: 0.8;

7.3 Lengths

width: 200px;

padding: 2rem;

margin-top: 1em;

max-width: 60ch;

7.4 Percentages

width: 50%;

left: 10%;

7.5 Colors

color: red;

color: #ff0000;

color: rgb(255, 0, 0);

color: hsl(0, 100%, 50%);

7.6 URLs

background-image: url("image.jpg");

7.7 Functions

width: calc(100% - 40px);

font-size: clamp(1rem, 2vw, 2rem);

color: var(--brand-color);

Example

```
<style>
```

```
.box {
```

```
  width: calc(100% - 40px);
```

```
  max-width: 400px;
```

```
  padding: 1rem;
```

```
background: hsl(200, 70%, 90%);  
color: rgb(20, 20, 20);  
}  
</style>
```

```
<div class="box">Value types example</div>
```

Your internal HTML reference also explicitly covers units like px, em, rem, vw, vh, vmin, vmax, and ch. [\[css_produc...cyclopedia | HTML\]](#)

8) Units

Absolute units

```
width: 200px;
```

Relative units

```
font-size: 1rem;
```

```
padding: 2em;
```

```
width: 50vw;
```

```
height: 50vh;
```

```
max-width: 65ch;
```

Example

```
<style>
```

```
html { font-size: 16px; }
```

```
h1 { font-size: 2rem; } /* 32px /
```

```
p { font-size: 1rem; } /* 16px */
```

```
.card { width: 50vw; }
```

```
</style>
```

```
<h1>Unit Example</h1>
```

<p>Paragraph text</p>

<div class="card">Responsive width</div>

9) Important CSS Properties by Topic

9.1 Color and Background

```
.box {  
  color: white;  
  background-color: teal;  
  background-image: linear-gradient(to right, blue, purple);  
  background-repeat: no-repeat;  
  background-position: center;  
  background-size: cover;  
}
```

<div class="box">Background example</div>

Your internal references explicitly include gradients, advanced color systems, and `currentColor`. [\[css_produc...cyclopedia | HTML\]](#), [\[CSS_Comple...tery_Guide | PDF\]](#)

9.2 Typography

```
p {  
  font-family: Arial, sans-serif;  
  font-size: 18px;  
  font-style: italic;  
  font-weight: 700;  
  line-height: 1.6;  
  letter-spacing: 1px;  
  text-align: center;  
  text-decoration: underline;
```

```
text-transform: uppercase;
}
<p>Typography example</p>
```

9.3 Box Model

```
.card {
  width: 300px;
  padding: 20px;
  border: 2px solid black;
  margin: 30px;
  box-sizing: border-box;
}
<div class="card">Box model example</div>
```

Your internal encyclopedia explicitly explains content-box, border-box, and margin mechanics. [\[css_produc...cyclopedia | HTML\]](#)

9.4 Border, Radius, Shadow

```
.panel {
  border: 2px solid #333;
  border-radius: 12px;
  box-shadow: 0 8px 20px rgba(0,0,0,0.2);
}
<div class="panel">Shadow example</div>
```

9.5 Overflow

```
.container {
  width: 200px;
  height: 100px;
```

```
    overflow: auto;
}
<div class="container">
    This is a very long content block that overflows and creates scrolling.
</div>
```

9.6 Display

```
.block { display: block; }
.inline { display: inline; }
.inline-block { display: inline-block; }
.none { display: none; }
<span class="inline-block">Inline-block item</span>
```

10) Positioning

Your internal guide explicitly lists static, relative, absolute, fixed, and sticky.
[\[css_produc...cyclopedia | HTML\]](#)

```
.parent {
    position: relative;
    height: 200px;
    border: 1px solid black;
}

.child {
    position: absolute;
    top: 20px;
    left: 30px;
}
<div class="parent">
```



```
<div class="child">Absolute child</div>
</div>
```

Sticky example

```
header {
  position: sticky;
  top: 0;
  background: white;
}
<header>Sticky header</header>
```

11) z-index and Stacking

```
.box1 {
  position: absolute;
  z-index: 1;
}
```

```
.box2 {
  position: absolute;
  z-index: 2;
}
```

```
<div class="box1">Behind</div>
```

```
<div class="box2">Front</div>
```

Your internal reference also mentions isolation: isolate for controlling stacking contexts.
[\[css_produc...cyclopedia | HTML\]](#)

12) Flexbox

MDN and your internal references both treat Flexbox as one of the core CSS layout systems. Your internal HTML file specifically shows display: flex, flex-direction, justify-

content, align-items, gap, and the flex shorthand. [\[developer...ozilla.org\]](#), [\[css_produc...cyclopedia | HTML\]](#)

Syntax

```
.container {  
  display: flex;  
  flex-direction: row;  
  justify-content: space-between;  
  align-items: center;  
  gap: 10px;  
}
```

```
.item {  
  flex: 1;  
}
```

Example

```
<style>  
  
.container {  
  display: flex;  
  gap: 10px;  
  background: #eee;  
  padding: 10px;  
}  
  
.item {  
  flex: 1;  
  background: tomato;  
  color: white;  
  padding: 20px;
```

```
    text-align: center;
}
</style>

<div class="container">
  <div class="item">One</div>
  <div class="item">Two</div>
  <div class="item">Three</div>
</div>
```

13) Grid

Your internal HTML reference explicitly shows display: grid, grid-template-columns, repeat(), minmax(), gap, grid-auto-flow, and grid-column. [\[css_produc...cyclopedia | HTML\]](#)

Syntax

```
.container {
  display: grid;
  grid-template-columns: repeat(3, 1fr);
  gap: 20px;
}
```

Example

```
<style>
  .grid {
    display: grid;
    grid-template-columns: repeat(3, 1fr);
    gap: 10px;
  }

  .grid div {
```

```
background: steelblue;

color: white;

padding: 20px;

}

</style>
```

```
<div class="grid">

  <div>1</div>

  <div>2</div>

  <div>3</div>

</div>
```

14) Transforms

Syntax

```
.box {

  transform: translateX(20px) rotate(10deg) scale(1.1);

}
```

Example

```
<style>

  .box {

    width: 120px;

    height: 120px;

    background: coral;

    transform: rotate(10deg) scale(1.1);

  }

</style>
```

```
<div class="box"></div>
```

Your internal reference also includes perspective(), rotateY(), and translateZ() examples.
[\[css_produc...cyclopedia | HTML\]](#)

15) Transitions

Syntax

```
button {  
    transition: background 0.3s ease, transform 0.3s ease;  
}
```

Example

```
<style>  
    button {  
        background: teal;  
        color: white;  
        padding: 10px 16px;  
        transition: background 0.3s ease, transform 0.3s ease;  
    }  
  
    button:hover {  
        background: black;  
        transform: translateY(-2px);  
    }  
</style>  
  
<button>Hover me</button>
```

16) Animations

Your internal reference explicitly shows @keyframes and animation: shorthand usage.
[\[css_produc...cyclopedia | HTML\]](#)

Syntax

```
@keyframes fadeIn {  
  from { opacity: 0; }  
  to { opacity: 1; }  
}  
  
.box {  
  animation: fadeIn 2s ease-in-out 1;  
}
```

Example

```
<style>  
  
@keyframes fadeIn {  
  from { opacity: 0; }  
  to { opacity: 1; }  
}  
  
.box {  
  width: 100px;  
  height: 100px;  
  background: purple;  
  animation: fadeIn 2s ease-in-out infinite alternate;  
}  
  
</style>  
  
<div class="box"></div>
```

17) Responsive Design

MDN's CSS guides mention media queries and responsive design as core CSS topics, and your internal file includes mobile-first @media examples plus prefers-reduced-motion. [\[developer....ozilla.org\]](#), [\[css_produc...cyclopedia | HTML\]](#)

Media query syntax

```
@media (max-width: 600px) {  
  .card {  
    background: pink;  
  }  
}
```

Example

```
<style>  
  .card {  
    background: lightblue;  
    padding: 20px;  
  }  
  
  @media (max-width: 600px) {  
    .card {  
      background: pink;  
    }  
  }  
</style>
```

```
<div class="card">Resize the screen</div>
```

Accessibility media query

```
@media (prefers-reduced-motion: reduce) {  
  * {  
    animation: none !important;  
    transition: none !important;  
  }  
}
```

18) Custom Properties (CSS Variables)

Your internal guide explicitly describes native CSS custom properties and `var()` usage.

[\[css_produc...cyclopedia | HTML\]](#), [\[CSS_Comple...tery_Guide | PDF\]](#)

Syntax

```
:root {  
  --primary: #2563eb;  
}
```

```
button {  
  background: var(--primary);  
}
```

Example

```
<style>
```

```
:root {  
  --brand: #0ea5e9;  
  --text: white;  
}
```

```
.btn {  
  background: var(--brand);  
  color: var(--text);  
  padding: 10px 15px;  
  border: none;  
}
```

```
</style>
```

```
<button class="btn">Variable button</button>
```

19) CSS Functions

Common functions

width: calc(100% - 20px);

font-size: clamp(1rem, 2vw, 2rem);

color: rgb(255, 0, 0);

background: linear-gradient(red, blue);

transform: translateX(10px);

filter: blur(2px);

Example

```
<style>
```

```
.hero {
```

```
  width: calc(100% - 40px);
```

```
  font-size: clamp(1rem, 4vw, 2rem);
```

```
  background: linear-gradient(to right, #06b6d4, #3b82f6);
```

```
  color: white;
```

```
  padding: 20px;
```

```
}
```

```
</style>
```

```
<div class="hero">Function example</div>
```

20) At-rules

MDN's CSS reference says at-rules have their own syntax family, and your internal references include several major at-rules such as @import, @media, @font-face, @keyframes, @container, @layer, and @property. [\[developer...ozilla.org\]](#), [\[css_produc...cyclopedia | HTML\]](#), [\[CSS_Comple...tery_Guide | PDF\]](#)

20.1 @import

```
@import url("styles.css");
```

20.2 @media

```
@media (min-width: 768px) {  
  body {  
    background: #f0f0f0;  
  }  
}
```

20.3 @supports

```
@supports (display: grid) {  
  .layout {  
    display: grid;  
  }  
}
```

20.4 @font-face

```
@font-face {  
  font-family: "MyFont";  
  src: url("myfont.woff2") format("woff2");  
}
```

20.5 @keyframes

```
@keyframes bounce {  
  0% { transform: translateY(0); }  
  100% { transform: translateY(-20px); }  
}
```

20.6 @layer

@layer reset, components;

```
@layer reset {  
  * { margin: 0; }  
}
```

```
@layer components {  
  .btn { padding: 10px; }  
}
```

20.7 @container

```
.card-wrapper {  
  container-type: inline-size;  
}
```

```
@container (min-width: 400px) {  
  .card {  
    display: flex;  
  }  
}
```

20.8 @property

```
@property --angle {  
  syntax: "<angle>";  
  inherits: false;  
  initial-value: 0deg;  
}
```

20.9 @page

```
@page {  
  margin: 1in;  
}
```

Combined HTML Example

```
<style>  
  
@layer base, components;
```

```
@layer base {  
  body { margin: 0; font-family: Arial, sans-serif; }  
}
```

```
@layer components {  
  .card {  
    padding: 20px;  
    background: #eee;  
  }  
}
```

```
@media (max-width: 600px) {  
  .card { background: pink; }  
}  
</style>
```

```
<div class="card">At-rule example</div>
```

21) Nesting (Modern CSS)

Your internal encyclopedia explicitly includes **native CSS selector nesting**.
[\[css_produc...yclopedia | HTML\]](#)

Syntax

```
.card {  
  color: black;  
  
  & .title {  
    font-weight: bold;  
  }  
}
```

```
&:hover {  
    background: #f4f4f4;  
}  
}
```

Example

```
<style>  
  
.card {  
    padding: 20px;  
    border: 1px solid #ddd;  
  
    & .title {  
        color: navy;  
        font-weight: bold;  
    }  
  
    &:hover {  
        background: #f9f9f9;  
    }  
}  
</style>  
  
<div class="card">  
    <div class="title">Nested title</div>  
    <p>Nested syntax example</p>  
</div>
```

22) Specificity, Cascade, Inheritance

Your internal HTML guide explicitly explains the specificity vector and also mentions cascade layers and keywords such as inherit, initial, unset, and revert.

[\[css_produc...cyclopedia | HTML\]](#)

Example

```
<style>

p { color: black; }      /* low specificity /

.text { color: blue; }   / higher /

#main { color: red; }    / even higher */

</style>

<p id="main" class="text">This becomes red</p>
```

Inheritance keywords

```
.child {

  color: inherit;

  margin: initial;

  padding: unset;

}
```

23) Full Mini Demo (HTML + CSS)

If you want one example that combines most important CSS syntax, use this:

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width,initial-scale=1.0">

  <title>Complete CSS Demo</title>

  <style>

    /* 1) Variables /

    :root {
```

```
--primary: #2563eb;  
--surface: #f8fafc;  
--text: #0f172a;  
--radius: 12px;  
}
```

/ 2) Reset / base /

```
*{  
  box-sizing: border-box;  
}
```

```
body{  
  margin: 0;  
  font-family: Arial, sans-serif;  
  background: var(--surface);  
  color: var(--text);  
  line-height: 1.6;  
}
```

/ 3) Layout /

```
.wrapper{  
  max-width: 1000px;  
  margin: 40px auto;  
  padding: 20px;  
  display: grid;  
  grid-template-columns: repeat(3, 1fr);  
  gap: 20px;  
}
```

/ 4) Component /

```
.card {  
  background: white;  
  border: 1px solid #ddd;  
  border-radius: var(--radius);  
  padding: 20px;  
  box-shadow: 0 8px 20px rgba(0,0,0,0.08);  
  transition: transform 0.3s ease, box-shadow 0.3s ease;  
}
```

```
.card:hover {  
  transform: translateY(-4px);  
  box-shadow: 0 12px 30px rgba(0,0,0,0.12);  
}
```

/ 5) Pseudo-element /

```
.card h2::after {  
  content: " 🌟";  
}
```

/ 6) Attribute selector /

```
input[type="text"] {  
  width: 100%;  
  padding: 10px;  
  border: 1px solid #bbb;  
  border-radius: 8px;  
}
```



```
input:focus {  
  outline: 3px solid rgba(37, 99, 235, 0.25);  
  border-color: var(--primary);  
}
```

/ 7) Flex inside card /

```
.actions {  
  display: flex;  
  gap: 10px;  
  margin-top: 15px;  
}
```

```
.btn {  
  flex: 1;  
  padding: 10px 14px;  
  border: none;  
  border-radius: 8px;  
  background: var(--primary);  
  color: white;  
  cursor: pointer;  
}
```

```
.btn:active {  
  transform: scale(0.98);  
}
```

/ 8) Animation /

```
@keyframes fadeIn {  
  from { opacity: 0; transform: translateY(10px); }  
  to { opacity: 1; transform: translateY(0); }  
}
```

```
.card {  
  animation: fadeIn 0.6s ease both;  
}
```

```
/ 9) Responsive */
```

```
@media (max-width: 768px) {  
  .wrapper {  
    grid-template-columns: 1fr;  
  }  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<div class="wrapper">
```

```
<div class="card">
```

```
<h2>Card One</h2>
```

```
<p>This card shows selectors, variables, transitions, shadows, and layout.</p>
```

```
<input type="text" placeholder="Type here">
```

```
<div class="actions">
```

```
<button class="btn">Save</button>
```

```
<button class="btn">Cancel</button>
```

```
</div>
```

```
</div>
```

```
<div class="card">

  <h2>Card Two</h2>

  <p>Resize the browser to see responsive Grid.</p>

</div>

<div class="card">

  <h2>Card Three</h2>

  <p>Hover and click buttons to test interaction states.</p>

</div>

</div>

</body>

</html>
```

Final Learning Checklist (all major CSS topics)

Use this checklist to make sure you've covered the whole language family:

- Basic rule syntax
- Inline / internal / external / @import
- Comments
- Selectors
 - universal, type, class, id
 - attribute selectors
 - grouping
 - combinators
- Pseudo-classes
- Pseudo-elements
- Values and units
- Colors, backgrounds, gradients

- Typography
- Box model
- Borders, radius, shadows
- Display and overflow
- Positioning and z-index
- Flexbox
- Grid
- Transforms
- Transitions
- Animations and @keyframes
- Media queries
- Accessibility queries (prefers-reduced-motion)
- Custom properties (--var, var())
- Functions (calc, clamp, etc.)
- At-rules (@media, @supports, @font-face, @layer, @container, @property, @page)
- Nesting
- Specificity, inheritance, cascade

That structure aligns with the topic families described by CSS reference - CSS | MDN and your internal CSS encyclopedia files. [\[developer....ozilla.org\]](#), [\[CSS_Comple...tery_Guide | PDF\]](#), [\[css_produc...yclopedia | HTML\]](#)

If you want, I can next turn this into a **single interview-ready CSS notes document with 100+ copy-paste examples.**