

**Table 1.1 View Only Functions in contract:**

	Name	Parameters	Description	Access
1.	allowance(owner,spender)	owner: token owner address spender: token spender address	Returns the amount that the spender is still allowed to withdraw from the owner.	public
2.	balanceOf(user)	user: user's address	to get total tokens owned by the user.	public
3.	decimals()	-	Returns decimals, which refers to how divisible a token can be.	public
4.	name()	-	name of the token	public
5.	Owner()	-	Current contract Owner	public
6.	symbol()	-	Returns the symbol by which the token contract should be known, for example "ABND". It is usually 3 or 4 characters in length.	public
7.	totalSupply()	-	Returns the number of total supplied tokens, including the total minted tokens (minus the total burned tokens).	public

Table 1.2: Key state changing functions contained in the contract

	Name	Params	Description	Access
1.	approve(spender,amount)	spender: spender's address amount: amount that the spender can address	Approve an address to spend on another's behalf	public
2.	burn(amount)	amount: amount of tokens to be burned.	Allows a user to burn their token.	public
3.	burnFrom(account,amount)	account: user's wallet address from which to burn token. amount: amount of tokens to be burnt.	Burn tokens of the address that you have a spend allowance for	public
4.	increaseAllowance(spender,addedValue)	spender: spender's address/ addedValue : amount to increase allowance by.	Increase spend allowance	public
5.	decreaseAllowance(spender,subtractedValue)	spender: spender's address subtractedValue: amount to decrease allowance by.	Decrease spend allowance	public
6.	transferOwnership(newOwner)	newOwner; new owner's address	Transfer ownership of the contract to specified address. Only the owner can call this.	onlyOwner
7.	renounceOwnership()	-	Reassigns ownership of the contract to null address. Only the owner can call this.	onlyOwner
8.	transfer(address,amount)	address: recipient's address. amount: amount of token's to transfer	To transfer tokens. <ul style="list-style-type: none"> <li>When used by owner, transfers free tokens.</li> <li>When used by a listed source, transfers frozen tokens.</li> </ul>	public
9.	transferFrom(address,to,amount)	address: address from which to spend tokens from. to: recipient's address. amount: amount of tokens to be transferred.	transfer tokens from a source user has allowance for.	Public
10.	Pause	-	For owner to pause token transactions	OnlyOwner
11.	UnPause	-	For Owner to resume token transactions	OnlyOwner