

Doomcore Orbital Constellation

Ground Operations Manual

CLASSIFICATION: INTERNAL — VILLAIN ENTERPRISES OPS USE ONLY

Welcome, Operator.

This short guide provides essential procedures for interacting with the Doomcore Orbital Constellation. While the official documentation is approximately 700 pages longer, we trimmed this edition down because — shockingly — most operators never read past page two. Consider this the minimum viable training required to avoid accidentally bricking a satellite or triggering an unscheduled re-entry event.

1. System Overview

The constellation consists of four spacecraft:

- D00M■01 — Utility and attitude control testbed
- D00M■02 — Secure-relay node ("secure" in the marketing sense)
- K00KIES■01 — Crosslink sniffer and RF monitoring payload
- K00KIES■02 — Firmware experimentation platform (use gloves)

Ground operations occur through DOOMSTATION■PRIME using authenticated uplink procedures (see: "Why Our Authentication Doesn't Actually Matter," Rev. 3).

2. Uplink Procedures

Commands are packaged in DOOMLINK protocol frames and transmitted through legitimate channels (or vaguely legitimate, depending on who is supervising your shift). Always verify:

- Correct SAT_ID
- Correct command ID
- CRC16 integrity

Incorrect frames may result in rejected commands, silent drops, or passive■aggressive telemetry.

3. Crosslink Operations

D00M■02 supports encrypted crosslink frames. Operators are advised not to rely on this feature for mission■critical security. "Marketing-grade encryption" may not meet all cryptographic standards known to mankind.

K00KIES■01 receives wideband crosslink traffic for diagnostic purposes. No, you cannot disable this.

4. Firmware Handling

Firmware is staged in binary chunks and validated by onboard mechanisms. K00KIES■02 employs a reduced verification model described internally as "close enough for orbital work." Ensure your claimed hash matches the expected format, otherwise the satellite may politely decline your upload.

5. Standard Telemetry Interpretation

Nominal telemetry includes mode state, power levels, and temperature. A sudden spike in temperature may indicate:

- Incorrect heater configuration
- Attitude misalignment
- Operator error (most common)
- Cosmic rays (least common)

6. Operator Conduct (Recommended, Not Required)

- Avoid sending malformed frames unless supervised.
- Do not attempt to "optimize" encryption routines.
- Do not feed the AI-assisted autopilot memes.
- Remember: if a satellite begins broadcasting music unprompted, inform engineering before joining in.

End of Manual

If you are still reading, congratulations — you are now the most qualified operator on shift.