


Forecast Reconciliation Made Easy: The FoReco Package

Daniele Girolimetto

Department of Statistical Sciences, University of Padova

 danigi.github.io

 [danigi](https://twitter.com/danigi)

 daniele.girolimetto@unipd.it



July 10th, 2024



useR! conference





- **Post-forecasting process** aimed to improve the quality of the base forecasts (however obtained) of a **linearly constrained** multiple time series by exploiting **cross-sectional** (e.g., spatial) and/or **temporal** constraints of the **target** forecasts

$$\begin{array}{ccc} \text{Target} & \text{Base forecasts} & \text{Reconciled forecasts} \\ \mathbf{C}\mathbf{y}_h = \mathbf{0} & \mathbf{C}\hat{\mathbf{y}}_h \neq \mathbf{0} & \rightarrow \mathbf{C}\tilde{\mathbf{y}}_h = \mathbf{0} \end{array}$$

- **Forecasting examples:** Sales, Tourism, Energy demand, Healthcare, Supply chain ...
- The R package FoReco offers a robust set of tools for implementing forecast reconciliation with a variety of approaches accounting for different constraints
- Additional resources and examples on [GitHub](#)  and on the [documentation page](#) 

Present and future of reconciliation packages


in R (R Core Team, 2024)

	hts [Ⓢ]	gtop [■]	thief [Ⓢ]	ProbReco [■]	fable [Ⓒ]	bayesRecon [Ⓒ]	FoReco [Ⓒ]
Cross-sectional	✓	✓		✓	✓	✓	✓
Temporal			✓			✓	✓
Cross-temporal							✓
Probabilistic				✓	✓	✓	✓

Ⓒ Supported

Ⓢ Not updated


■ Archived



Australian Tourism Demand

Today example: `data(vndata)`

Geographical division, g.d.



×

Purpose of travel, p.o.t.

Holiday, Visiting friends and relatives, Business, Other

■ Grouped ts (geographical divisions × purpose of travel)

	AUS	States	Zones*	Regions	Tot
g.d.	1	7	21	76	105
p.o.t.	4	28	84	304	420
Tot	5	35	105	380	525

$$n_a = 221, n_b = 304, \text{ and } n = 525$$


■ Unique time series, no redundancy (*6 Zones with only one Region are included in the Regions)

■ Temporal framework, frequencies:

- Monthly
- Bi-Monthly
- Quarterly
- Four-Monthly
- Semi-Annual
- Annual

Cross-sectional framework

Hyndman *et al.* (2011); Panagiotelis *et al.* (2021)



2-level: **bottom** and **upper**

A cross-sectional hierarchical/grouped time series is a collection of n variables for which - at each time - **aggregation relationships** hold.



multiple time series with exact linear constraints.

- Two equivalent representations (Girolimetto and Di Fonzo, 2024)

Zero-constrained

$$C_{cs}y = 0_{n_a}$$

$$C_{cs} = \begin{bmatrix} I & -A \end{bmatrix}$$

not unique

$$\begin{bmatrix} 1 & -1 & -1 \end{bmatrix}$$

$$A : a = Ab$$

Linear combination (or aggregation) matrix

$$\begin{bmatrix} 1 & 1 \end{bmatrix}$$

Structural


$$y = S_{cs}b$$

$$S_{cs} = \begin{bmatrix} A \\ I_{n_b} \end{bmatrix}$$

$$\begin{bmatrix} 1 & 1 \\ I_2 \end{bmatrix}$$

Hierarchical, grouped and linearly constrained time series

Genuine hierarchical time series




Constraints

$$T = A + B$$

$$A = AA + AB$$

$$B = BA + BB + BC$$

General linearly constrained time series



Constraints

$$X = A + B$$


$$X = C + D$$

$$A = AA + AB$$


Grouped time series: two or more genuine hierarchies sharing the same top and bottom variables

T	A	B
Z	AZ	BZ
Y	AY	BY

=



+



Constraints

$$T = A + B$$

$$A = AZ + AY$$

$$B = BZ + BY$$

$$T = Z + Y$$

$$Z = AZ + BZ$$

$$Y = AY + BY$$

Optimal combination forecast reconciliation

Wickramasuriya *et al.* (2019); Panagiotelis *et al.* (2021)

1. Forecast **all series at all levels** of aggregation → **base forecasts**
2. Make the base forecasts **coherent** using least squares → **reconciled forecasts**

Two equivalent point forecast reconciliation formulae

Structural reconciliation approach

approach = "strc"

$$\hat{\mathbf{y}} = \mathbf{S}\boldsymbol{\beta} + \boldsymbol{\varepsilon}$$

⇓

$$\tilde{\mathbf{y}} = \mathbf{S} (\mathbf{S}'\mathbf{W}^{-1}\mathbf{S})^{-1} \mathbf{S}'\mathbf{W}^{-1}\hat{\mathbf{y}} = \mathbf{S}\mathbf{G}\hat{\mathbf{y}}$$

Projection reconciliation approach

approach = "proj"

$$\hat{\mathbf{y}} = \mathbf{y} + \boldsymbol{\varepsilon}, \quad \text{s.t.} \quad \mathbf{C}\mathbf{y} = 0$$


⇓

$$\tilde{\mathbf{y}} = \left[\mathbf{I} - \mathbf{W}\mathbf{C}'(\mathbf{C}\mathbf{W}\mathbf{C}')^{-1}\mathbf{C} \right] \hat{\mathbf{y}} = \mathbf{M}\hat{\mathbf{y}}$$

- The formulation of $\mathbf{W} = \text{E}(\boldsymbol{\varepsilon}\boldsymbol{\varepsilon}')$ is conceptually **complex**; in practice, approximate forms are used, possibly using in-sample residuals

Projection vs structural approach: performance index

Cross-sectional wls reconciliation - *time* in seconds - median of 100 replications



Two main factors:

■ dimensions


cs: n_a, n_b

te: \mathcal{K} (set of temporal aggregation orders)

ct: n_a, n_b, \mathcal{K}

■ computational cost of W^{-1}

$$PI = \left| \frac{time_{strc} - time_{proj}}{\max(time_{strc}, time_{proj})} \right| 100$$



FoReco at work </>

Cross-sectional optimal forecast reconciliation

Input:


- `base` (12×525) monthly base forecasts
- `comb` A string specifying the reconciliation method (e.g., `ols`, `str`, `wls`, `shr`, `sam`)
- `res` (228×525) residuals possibly used to compute the covariance matrix
- `agg_mat` (221×304) cross-sectional aggregation matrix **A**
- `cons_mat` (221×525) zero constraints cross-sectional matrix **C**

FoReco

```
1 # Using the aggregation matrix A
2 rf_opt <- csrec(base = base, agg_mat = vnaggmat, res = res, comb = "shr")
3 str(rf_opt, give.attr = FALSE)
4 #>  num [1:12, 1:525] 49160 21622 24815 29433 23260 ...
5
6 # Using the zero constraints matrix C: vnconsmat <- cbind(diag(221), -vnaggmat)
7 csrec(base = base, cons_mat = vnconsmat, res = res, comb = "shr")
```

Temporal framework

Athanasopoulos *et al.* (2017)



Quarterly hierarchy:

quarterly, semi-annual and annual series

Temporal hierarchy → **non-overlapping aggregation** of the observations of a time series (y) at regular intervals

$$x_j^{[k]} = \sum_{t=(j-1)k+1}^{jk} y_t$$

- Unlike cross-sectional hierarchies (n **variables at the same time index** are considered), in temporal hierarchies we have **one variable observed at different frequencies**
- **Structural representation** ($\mathbf{x}_\tau = \mathbf{S}_{te} \mathbf{x}_\tau^{[1]}$) and **zero-constrained representation** ($\mathbf{C}_{te} \mathbf{x}_\tau = \mathbf{0}_{(k^* \times 1)}$) still hold, and may be alternatively used for reconciliation

FoReco at work </>

Cross-sectional optimal forecast reconciliation

Input: $\left\{ \begin{array}{ll} \text{base} & (28 \times 1) \text{ base forecasts ordered as } [x^{[12]} \ x^{[6]} \ \dots \ x^{[1]}]' \\ \text{comb} & \text{A string specifying the reconciliation method (e.g., ols, str, wls, ...)} \\ \text{res} & (228 \times 1) \text{ residuals possibly used to compute the covariance matrix} \\ \text{agg_order} & \text{max. order of temporal aggregation, } m = 12 \end{array} \right.$


FoReco

```
1 rf_opt <- terec(base = base, agg_order = m, res = res, comb = "sar1")
2 str(rf_opt, give.attr = FALSE)
3 #> Named num [1:28] 1.329 0.665 0.665 0.443 0.443 ...
```


Cross-sectional + Temporal = Cross-temporal

A cross-temporal hierarchy of three quarterly time series ($T = A + B$)

cross-sectional \rightarrow temporal




temporal \rightarrow cross-sectional




Cross-temporal framework

Di Fonzo and Girolimetto (2023a)


Annual: $j = 1$



Semi-annual: $j = 1, 2$



Quarterly: $j = 1, \dots, 4$



$$\left. \begin{matrix} \mathbf{x}_{i,\tau} = \left[x_{i,1}^{[4]} & x_{i,1}^{[2]} & x_2^{[2]} & x_{i,1}^{[1]} & \dots & x_{i,4}^{[1]} \right]' \\ \text{for } i = T, A, B \end{matrix} \right\} \Rightarrow \mathbf{X}_\tau = \begin{bmatrix} \mathbf{x}'_{T,\tau} \\ \mathbf{x}'_{A,\tau} \\ \mathbf{x}'_{B,\tau} \end{bmatrix}, \quad \mathbf{x}_\tau = \text{vec}(\mathbf{X}'_\tau)$$

- Two dimensions to capture the complete nature of a multiple time series
- Any cross-temporal matrix may be constructed from the one-dimensional counterparts
 - $\mathbf{C}_{ct} \rightarrow$ **easy** to compute as a function of \mathbf{A}_{cs} and m
 - $\mathbf{S}_{ct} \rightarrow$ **fast** to compute as $\mathbf{S}_{cs} \otimes \mathbf{S}_{te}$

FoReco at work </>

Cross-temporal optimal forecast reconciliation

Input:


`base` (525×28) base forecasts matrix
`comb` A string specifying the reconciliation method (e.g., `ols`, `wlsv`, `bdshr`, ...)
`res` (525×532) residuals possibly used to compute the covariance matrix
`agg_order` max. order of temporal aggregation, $m = 12$
`agg_mat` (221×304) cross-sectional aggregation matrix **A**
`cons_mat` (221×525) zero constraints cross-sectional matrix **C**

FoReco

```
1 rf_opt <- ctrec(base = base, agg_mat = vnaggmat, # or cons_mat = vnconsmat,  
2             agg_order = m, res = res, comb = "wlsv", approach = "strc")  
3 str(rf_opt, give.attr=FALSE)  
4 #>  num [1:525, 1:28] 314297 97383 62631 77793 19695 ...
```

FoReco at work </>

Two-step cross-temporal reconciliation, Kourentzes and Athanasopoulos (2019)




- The final **temporally and cross-sectionally coherent** reconciled forecasts are a transformation of the **step 1 forecasts** through the **step 2 reconciliation matrices**
- `tcsrec()` → *first-temporal-then-cross-sectional reconciliation*
- `cstrec()` → *first-cross-sectional-then-temporal reconciliation*

FoReco 🌿

```
1 tcsrec(base = base, res = res,  
2       cslist = list(agg_mat = vnaggmat, comb = "shr"),  
3       telist = list(agg_order = m, comb = "wlsv"))
```

FoReco at work </>

Iterative cross-temporal reconciliation, Di Fonzo and Girolimetto (2023a)



- Each iteration consists in the first two steps of the heuristic KA procedure, until a convergence criterion is met

FoReco 

```
1 iterec(base = base, res = res,  
2       type = "tcs", # → first-temporal-then-cross-sectional reconciliation  
3       # or type = "cst", → first-cross-sectional-then-temporal reconciliation  
4       cslist = list(agg_mat = vnaggmat, comb = "shr"),  
5       telist = list(agg_order = m, comb = "wlsv"))
```


Additional reconciliation approaches

Classical and LCC approaches for cross-sectional, temporal and cross-temporal frameworks

■ Classical reconciliation (Dunn *et al.*, 1976; Gross and Sohl, 1990; Athanasopoulos *et al.*, 2009)

	<i>Cross-sectional</i>	<i>Temporal</i>	<i>Cross-Temporal</i>
Top-down, * td ()	cstd ()	tetd ()	cttd ()
Bottom-up, * bu ()	csbu ()	tebu ()	ctbu ()
Middle-out, * mo ()	csmo ()	temo ()	ctmo ()




■ Level conditional coherent reconciliation (Hollyman *et al.*, 2021; Di Fonzo and Girolimetto, 2024)

	<i>Cross-sectional</i>	<i>Temporal</i>	<i>Cross-Temporal</i>
LCC, * lcc ()	cslcc ()	telcc ()	ctlcc ()

Practical challenges and other features

- **Non-negative forecast reconciliation** (Wickramasuriya *et al.*, 2020)
 - nn = "osqp": quadratic programming optimization (Stellato *et al.*, 2020)
 - nn = "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023b)
- **Probabilistic forecast reconciliation** (Panagiotelis *et al.*, 2023; Girolimetto *et al.*, 2024)
 - Non-parametric approach: *boot() + *rec()
 - Parametric approach (samples): MASS::mvrnorm() + *rec()
- Reconciliation with immutable forecasts (Zhang *et al.*, 2023) using the immutable argument
- Using a subset of temporal aggregation orders, e.g. agg_order = c(12, 6, 1)



- FoReco is a **valuable tool** for researchers and practitioners in the field of time series forecasting
- It provides **state-of-the-art classical** (bottom-up and top-down) as well as **modern** (optimal and heuristic combination) reconciliation approaches for **cross-sectional**, **temporal**, and **cross-temporal** frameworks
- Its flexible and comprehensive design makes it a **versatile solution** for a wide range of forecasting applications (Sales, Tourism, Energy demand, Healthcare, Supply chain ...)
- **Links:**
 -  github.com/daniGiro/FoReco
 -  danigiro.github.io/FoReco
 -  cran.r-project.org/package=FoReco

Awesome Forecast Reconciliation - Github repository


Resources about forecast reconciliation: [danigiro/awesome-forecast-reconciliation](https://github.com/danigiro/awesome-forecast-reconciliation)

Awesome Forecast Reconciliation

This repository serves as a curated reference for the domain of forecast reconciliation. It aims to contain an extensive collection of academic papers, articles, software tools, and educational resources. Ideal for researchers, analysts, and practitioners seeking to improve the consistency and precision of forecasting methodologies.

We wish to express our deep appreciation to the authors of the paper "[Forecast reconciliation: A review](#)" - George Athanasopoulos, Rob J Hyndman, Nikolaos Kourentzes, and Anastasios Panagiotelis - for providing their BibTeX file, which served as the cornerstone of this repository. Their paper serves as an invaluable resource with its comprehensive and insightful analysis of the forecast reconciliation field, providing a thorough overview of the existing literature and highlighting key advancements and research trends.

⚠ The list is still incomplete and unorganized. We are in the process of reorganizing the various items.



Yangzhuoran Fin Yang

Monash University



Github repository

THANK YOU!

Daniele Girolimetto

Department of Statistical Sciences, University of Padova

🌐 danigiro.github.io

🐙 github.com/daniGiro

@ daniele.girolimetto@unipd.it

useR! conference

Salzburg, Austria - July 10th, 2024



References I

- Athanasopoulos, G., Ahmed, R. A. and Hyndman, R. J. (2009) Hierarchical forecasts for Australian domestic tourism. *International Journal of Forecasting* **25**(1), 146–166
- Athanasopoulos, G., Hyndman, R. J., Kourentzes, N. and Petropoulos, F. (2017) Forecasting with temporal hierarchies. *European Journal of Operational Research* **262**(1), 60–74
- Di Fonzo, T. and Girolimetto, D. (2023a) Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives. *International Journal of Forecasting* **39**(1), 39–57
- Di Fonzo, T. and Girolimetto, D. (2023b) Spatio-temporal reconciliation of solar forecasts. *Solar Energy* **251**, 13–29
- Di Fonzo, T. and Girolimetto, D. (2024) Forecast combination-based forecast reconciliation: Insights and extensions. *International Journal of Forecasting* **40**(2), 490–514
- Dunn, D. M., Williams, W. H. and Dechaine, T. L. (1976) Aggregate versus Subaggregate Models in Local Area Forecasting. *Journal of the American Statistical Association* **71**(353), 68–71
- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R. J. (2024) Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting* **40**(3), 1134–1151
- Girolimetto, D. and Di Fonzo, T. (2024) Point and probabilistic forecast reconciliation for general linearly constrained multiple time series. *Statistical Methods & Applications* **33**, 581–607
- Gross, C. W. and Sohl, J. E. (1990) Disaggregation methods to expedite product line forecasting. *Journal of Forecasting* **9**(3), 233–254
- Hollyman, R., Petropoulos, F. and Tipping, M. E. (2021) Understanding forecast reconciliation. *European Journal of Operational Research* **294**(1), 149–160

References II

- Hyndman, R. J., Ahmed, R. A., Athanasopoulos, G. and Shang, H. L. (2011) Optimal combination forecasts for hierarchical time series. *Computational Statistics & Data Analysis* **55**(9), 2579–2589
- Kourentzes, N. and Athanasopoulos, G. (2019) Cross-temporal coherent forecasts for Australian tourism. *Annals of Tourism Research* **75**, 393–409
- Panagiotelis, A., Athanasopoulos, G., Gamakumara, P. and Hyndman, R. J. (2021) Forecast reconciliation: A geometric view with new insights on bias correction. *International Journal of Forecasting* **37**(1), 343–359
- Panagiotelis, A., Gamakumara, P., Athanasopoulos, G. and Hyndman, R. J. (2023) Probabilistic forecast reconciliation: Properties, evaluation and score optimisation. *European Journal of Operational Research* **306**(2), 693–706
- R Core Team (2024) *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria **URL:** <https://www.R-project.org/>
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020) OSQP: an operator splitting solver for quadratic programs. *Mathematical Programming Computation* **12**(4), 637–672
- Wickramasuriya, S. L., Athanasopoulos, G. and Hyndman, R. J. (2019) Optimal Forecast Reconciliation for Hierarchical and Grouped Time Series Through Trace Minimization. *Journal of the American Statistical Association* **114**(526), 804–819
- Wickramasuriya, S. L., Turlach, B. A. and Hyndman, R. J. (2020) Optimal non-negative forecast reconciliation. *Statistics and Computing* **30**(5), 1167–1182
- Zhang, B., Kang, Y., Panagiotelis, A. and Li, F. (2023) Optimal reconciliation with immutable forecasts. *European Journal of Operational Research* **308**(2), 650–660