

TECHNICAL DATA SHEET : GORKHA LINER_750

Gorkha Liner_750 is a Reinforced woven coated geomembrane, High Strength HDPE core and engineered coating blend make is ideal for use in water retention and containment applications. The durable, stress crack resistance, light weight construction of products provides outstanding performance in many different climates and environment conditions.

Gorkha Liner_750's proprietary construction using high strength core and coating blend make it deal for application such as farm pond liners, aqua culture, wastewater lagoons, landfill covers, golf course ponds, irrigation storage, potable water reservoirs as well as Hay stack covers, grain covers, Heavy duty covers and tarps.

Property	Test Method	Typical Value
Product Weight	IS 7016 - Part 1	650 GSM
Thickness	IS 7016 - Part 1	750 Micron
Breaking Strength - MD	IS 13162 - Part 5	8200 N
Breaking Strength - CD	IS 13162 - Part 5	7400 N
Elongation @ Break - MD	IS 13162	20%
Elongation @ Break - CD	IS 13162	20%
Tear Strength - MD	Method A1 of IS 7016 - Part 3	400 N
Tear Strength - CD	Method A1 of IS 7016 - Part 3	400 N
Hydrostaic Resistance	Annexure E of IS 15351	No Leakage @ 20 kg/Sq.Cm
UV Weathering - % after 2000 Hours	Annexure B of IS 15351	> 90%
Bursting Strength	IS 7016 - Part 6	135 N / Sq.cm
Puncture Resistance	Annexure D of IS 15351	725 N
Limited warranty exposed	-	7 Years
Limited warranty buried	-	12 Years

- 1) Values are typical and not limiting specifications
- 2) MD & CD refers to machine and cross direction.
- 3) Warranty buried and exposed data is general recommendation



Gorkha Liner is a product of Oscar Protective Fabrics, India



IS 15351:2015



CM/L 7200312695



First time in india geomembrane made with NitroWin™ and ZigZag™ technology

www.gorkhaliner.com
info@gorkhaliner.com