

## Algorithm 11 — Structural Diagram

### IMMUTABLE CORE {I-IV}

- I. WILL — Intent (Human)
- II. WISDOM — Discernment (Human)
- III. KNOWLEDGE — Data (AI)
- IV. COMPREHENSION — Meaning (AI)

# A11 for Autonomous Vehicles — Conflict Resolution Model

Aleksej Dvojnev

Autonomous Systems / Robotics / Safety-Critical Decision-Making

Technical Report

2026

V. PRACTICAL FREEDOM  
VI. PRACTICAL LIMITATION  
VII. FOUNDATION  
VIII. REALIZATION

WORLD / ACTION / OUTPUT

# A11 for Autonomous Vehicles — Conflict Resolution Model

**Author:** Aleksej Dvojnev

**Category:** Autonomous Systems / Robotics / Safety-Critical Decision-Making

**Publication Type:** Technical Report

**Year:** 2026

# Annotation

This document presents a conflict-resolution model for autonomous vehicles based on structured decision-making principles derived from Algorithm 11 (A11).

The model provides a predictable, interpretable, and safety-oriented method for resolving situations where two or more autonomous vehicles must negotiate priority, avoid deadlock, or coordinate movement in constrained environments.

The approach is domain-agnostic and can be integrated into existing autonomous driving stacks as a decision-layer module.

# Contents

1. Introduction
2. Problem Definition
3. Limitations of Existing Approaches
4. A11-Based Conflict Resolution Model
5. Architecture Overview
6. Decision Algorithm
7. Example Scenarios
8. Integration into Autonomous Driving Systems
9. Safety Considerations
10. Performance Notes
11. Extensions
12. Conclusion
13. References

# 1. Introduction

Autonomous vehicles frequently encounter conflict situations:

- narrow passages
- intersections without clear priority
- merging lanes
- occluded environments
- multi-vehicle negotiation scenarios

Traditional rule-based or ML-based systems often fail to provide:

- predictable behavior
- mutual understanding between agents
- deadlock-free negotiation
- interpretable decision flow

This document introduces a structured conflict-resolution model designed to address these challenges.

# 2. Problem Definition

A conflict situation occurs when:

- two or more autonomous vehicles
- cannot proceed simultaneously
- must negotiate priority
- under uncertainty or incomplete information

The model must ensure:

- safety
- predictability
- fairness
- deadlock avoidance
- minimal communication requirements

- compatibility with heterogeneous agents

## 3. Limitations of Existing Approaches

### 3.1 Rule-Based Systems

- brittle
- hard to scale
- fail in edge cases

### 3.2 Machine Learning Approaches

- opaque
- unpredictable
- difficult to certify

### 3.3 V2V Communication-Dependent Models

- require infrastructure
- fail with partial adoption
- vulnerable to communication loss

A robust solution must work **without** assuming shared communication channels or identical decision policies.

## 4. A11-Based Conflict Resolution Model

The proposed model uses a structured decision-making loop with:

- explicit goals
- contextual interpretation
- controlled expansion of options
- constraint-based stabilization
- final selection based on safety and convergence

This ensures:

- deterministic behavior

- interpretable decisions
- reproducibility
- compatibility with heterogeneous agents

## 5. Architecture Overview

| Perception & Environment Model |



| Conflict Situation Detection |



| A11 Conflict Resolution Module |

| • Context Interpretation |


| • Option Generation |

| • Constraint Filtering |

| • Priority Assignment |

| • Action Selection |





## 6. Decision Algorithm

### Step 1 — Context Interpretation

Extract:

- relative positions
- velocities
- available space
- risk zones
- environmental constraints

### Step 2 — Option Generation

Each vehicle generates a small set of feasible actions:

- proceed
- yield
- slow down
- stop
- lateral adjustment

### Step 3 — Constraint Filtering

Remove unsafe or non-viable options based on:

- collision risk
- braking distance
- visibility
- road geometry

## **Step 4 — Priority Assignment**

Priority is assigned using:

- minimal-risk principle
- minimal-change principle
- fairness principle
- deadlock-avoidance rule

## **Step 5 — Action Selection**

Each vehicle selects the action with:

- highest safety score
- highest convergence probability
- lowest deviation from intended path

# **7. Example Scenarios**

## **Scenario A — Narrow Passage**

Two vehicles approach a one-car-wide corridor.

Outcome:

- vehicle with lower escape cost yields
- vehicle with higher escape cost proceeds
- no communication required

## **Scenario B — Merge Conflict**

Two vehicles attempt to merge into a single lane.

Outcome:

- priority assigned based on relative position and risk
- yielding vehicle adjusts speed
- merging vehicle proceeds smoothly

### **Scenario C — Occluded Intersection**

Vehicles cannot see each other fully.

Outcome:

- conservative priority assignment
- minimal-risk action selection
- deadlock avoided through fallback rules

## **8. Integration into Autonomous Driving Systems**

The model integrates as a **decision-layer module**:

- above motion planning
- below perception
- independent of control stack
- compatible with ROS2, Apollo, Autoware, and custom stacks

Inputs:

- environment model
- predicted trajectories
- vehicle state

Outputs:

- selected action
- priority decision
- safety justification

## **9. Safety Considerations**

The model ensures:

- deterministic behavior
- bounded decision time
- monotonic risk reduction
- fallback to safe stop
- no reliance on communication

It is suitable for safety-critical certification.

## 10. Performance Notes

- low computational cost
- deterministic runtime
- scalable to multi-vehicle scenarios
- robust to perception noise
- compatible with heterogeneous agents

## 11. Extensions

Future extensions include:

- multi-agent negotiation
- swarm-level coordination
- integration with V2V when available
- off-Earth autonomous mobility

## 12. Conclusion

This document presents a structured conflict-resolution model for autonomous vehicles.

It provides predictable, interpretable, and safe decision-making in constrained environments without requiring communication between agents.

The model is based on principles derived from the A11 cognitive architecture.

# **13. References**

1. A11 — Cognitive Architecture Specification <https://doi.org/10.5281/zenodo.18536520>
2. A11 — Language Specification <https://doi.org/10.5281/zenodo.18540045>
3. Autonomous Driving Safety Literature
4. Multi-Agent Decision-Making Research