
pysimavrgui Documentation

Release 0.0.0

ponty

August 22, 2011

CONTENTS

1	Installation	2
1.1	General	2
1.2	Ubuntu	2
1.3	Uninstall	2
2	GUI examples	3
2.1	LCD	3
2.2	LED row	3
2.3	7 segment display	4
2.4	Text	4
3	Simulation examples	6
3.1	ledramp	6
3.2	LCD	8
3.3	seven segment display	12
4	CLI help for examples	16
4.1	Pygame GUI examples	16
4.2	Simulation examples	16
5	API	18
6	Development	20
6.1	Tools	20
6.2	Install on ubuntu	20
6.3	Tasks	21
7	Indices and tables	22
	Python Module Index	23
	Index	24

pysimavrgui

Date August 22, 2011

PDF [pysimavrgui.pdf](#)

Contents:

Simple GUI elements for [AVR](#) and [arduino](#) simulation. Programmed in [python](#), based on [pygame](#). [Simavr](#) is used for simulation.

Links:

- home: <https://github.com/ponty/pysimavrgui>
- documentation: <http://ponty.github.com/pysimavrgui>

Features:

- designed to use with [pysimavr](#) ([simavr](#) wrapper)
- [arduino](#) simulator included
- maximum speed can be real-time
- speed control
- audio backend: [PyAudio](#)
- graphic backend: [PyGame](#) ([SDL](#) wrapper)

Known problems:

- Python 3 is not supported
- tested only on linux
- real-time `sleep()` is used in [simavr](#), so speed control is far from perfect
- occasional crash by firmware reload
- poor sound quality

INSTALLATION

1.1 General

- install python
- install setuptools
- install PyGame
- install PyAudio (optional)
- install pysimavr
- install the program:

```
# as root
easy_install pysimavrgui
```

1.2 Ubuntu

```
sudo apt-get install python-setuptools
sudo apt-get install python-pygame
sudo apt-get install python-pyaudio
```

```
# pysimavr
sudo apt-get install swig
sudo apt-get install python-dev
sudo apt-get install gcc
sudo apt-get install libelf-dev
sudo easy_install pysimavr
```

```
sudo easy_install pysimavrgui
```

1.3 Uninstall

first install pip:

```
# as root
pip uninstall pysimavrgui
```

GUI EXAMPLES


These examples have no simulation, they test only GUI.

2.1 LCD

```
from entrypoint2 import entrypoint
from pysimavrgui.lcdgame import LcdGame
from pysimavrgui.maingame import MainGame
```

```
@entrypoint
def start():
    def char_func(x, y):
        return chr(ord('a')+x+y)
    lcd = LcdGame(char_func, (11, 4))
    MainGame(lcd).run_game()
```

```
$ python -m pysimavrgui.examples.gui.lcdgame_ex
```



2.2 LED row

```
from entrypoint2 import entrypoint
from pysimavrgui.ledrowgame import LedRowGame
```

```
from pysimavrgui.maingame import MainGame

@entrypoint
def start():
    def func(i):
        return (i>1,i>2)
    dev = LedRowGame(func,disp_size=4,labels=['x','y','z'])
    MainGame(dev).run_game()
```

```
$ python -m pysimavrgui.examples.gui.ledrowgame_ex
```



2.3 7 segment display

```
from entrypoint2 import entrypoint
from pysimavrgui.maingame import MainGame
from pysimavrgui.sgm7game import Sgm7Game
```

```
@entrypoint
def start():
    def func(x):
        return [
            (255,0),
            (0,0),
            (255,33),
            (7,0),
        ][x]
    dev = Sgm7Game(func,4)
    MainGame(dev).run_game()
```

```
$ python -m pysimavrgui.examples.gui.sgm7game_ex
```




2.4 Text

```
from entrypoint2 import entrypoint
from pysimavrgui.compgame import CompositeGame
from pysimavrgui.maingame import MainGame
from pysimavrgui.textgame import TextGame
```

```
@entrypoint
def start():
    def func1():
        return 'hello'
```

```
def func2():  
    return 'hi'  
dev1 = TextGame(func1)  
dev2 = TextGame(func2)  
dev=CompositeGame([dev1,dev2],align=1)  
MainGame(dev).run_game()
```

```
$ python -m pysimavrgui.examples.gui.textgame_ex
```



```
hello  
hi
```


SIMULATION EXAMPLES

These examples have simulation.

3.1 ledramp

Program:

```
from entrypoint2 import entrypoint
from path import path
from pysimavr.avr import Avr
from pysimavr.connect import connect_pins_by_rule
from pysimavrgui.examples.sim.avrsimmain import AvrSimMain
from pysimavr.firmware import Firmware
from pysimavrgui.compgame import CompositeGame
from pysimavrgui.infogame import InfoGame
from pysimavrgui.ledrowgame import LedRowGame
from pysimavr.ledrow import LedRow
from pysimavr.vcdfile import VcdFile

@entrypoint
def run_sim(vcdfile='ledramp.vcd', speed=0.1, fps=20, timeout=0.0, visible=1, image_file=''):
    firmware = Firmware(path(__file__).dirname() / 'ledramp.elf')
    avr = Avr(firmware, f_cpu=8000000, mcu='atmega48')

    vcd = VcdFile(avr, period=1000, filename=vcdfile)
    ledrow = LedRow(avr)
    connect_pins_by_rule('''
        avr.B0 ==> led.0 -> vcd
        avr.B1 ==> led.1 -> vcd
        avr.B2 ==> led.2 -> vcd
        avr.B3 ==> led.3 -> vcd
        avr.B4 ==> led.4 -> vcd
        avr.B5 ==> led.5 -> vcd
        avr.B6 ==> led.6 -> vcd
        avr.B7 ==> led.7 -> vcd
    ''',
        dict(
            avr=avr,
            led=ledrow,
        ),
        vcd=vcd,
    )
```

```

def state_func(i):
    return (ledrow.pinstate(i), ledrow.reset_dirty(i))
led_game = LedRowGame(state_func=state_func,
                      labels=['B' + str(x) for x in range(8)])

dev = CompositeGame([
    led_game,
    InfoGame(avr),
])

scrshot_by_exit = [(dev, image_file)] if image_file else None

AvrSimMain(avr, dev, vcd, speed=speed, fps=fps, visible=visible, timeout=timeout,
           scrshot_by_exit=scrshot_by_exit).run_game()

```


Starting program:

```


>>> from pysimavrgui.examples.sim.ledramp import run_sim
>>> run_sim(vcdfile='docs/ledramp.vcd', speed=0.1, timeout=0.2, fps=50, visible=0, image_file='docs/ledramp.png')
Loaded 1850 .text
Loaded 32 .data
Starting atmega48 - flashend 0fff ramend 02ff e2end 00ff
atmega48 init
avr_timer_reconfigure-2 clock turned off
avr_timer_configure-2 TOP 4096.00Hz = 1953 cycles
avr_timer_write_ocr-2 mode 2 UNSUPPORTED
avr_timer_configure-2 TOP 64.00Hz = 125000 cycles
avr_timer_configure-2 A 64.00Hz = 125000 cycles

```

GUI:



Signals:



3.2 LCD

Program:

```
from entrypoint2 import entrypoint
from path import path
from pysimavr.ac import Ac
from pysimavr.avr import Avr
from pysimavr.connect import connect_pins_by_rule
from pysimavrgui.examples.sim.avrsimmain import AvrSimMain
from pysimavr.firmware import Firmware
from pysimavrgui.compgame import CompositeGame
from pysimavrgui.infogame import InfoGame
from pysimavrgui.lcdgame import LcdGame
from pysimavrgui.ledrowgame import LedRowGame
from pysimavr.lcd import Lcd
from pysimavr.ledrow import LedRow
from pysimavr.vcdfile import VcdFile

@entrypoint
def run_sim(vcdfile='lcd.vcd', speed=0.1, fps=20, timeout=0.0, visible=1, image_file=''):
    firmware = Firmware(path(__file__).dirname() / 'lcd.elf')
    avr = Avr(firmware, f_cpu=16000000)
    lcd = Lcd(avr)
    ledrow = LedRow(avr, size=7)
    # period=1000 -> vcd error
    vcd = VcdFile(avr, period=10, filename=vcdfile)

    def state_func(i):
        return (ledrow.pinstate(i), ledrow.reset_dirty(i))
    led_game = LedRowGame(state_func=state_func,
                          labels='D4 D5 D6 D7 RS E RW'.split()
                          )

    ac = Ac(avr)
    connect_pins_by_rule('''
avr.B0 <=> lcd.D4 -> vcd
avr.B1 <=> lcd.D5 -> vcd
avr.B2 <=> lcd.D6 -> vcd
avr.B3 <=> lcd.D7 -> vcd

avr.B4 ==> lcd.RS -> vcd
avr.B5 ==> lcd.E -> vcd
avr.B6 ==> lcd.RW -> vcd
vcd <- ac.OUT -> avr.D2

lcd.D4 -> led.0
lcd.D5 -> led.1
```

```

lcd.D6 -> led.2
lcd.D7 -> led.3

lcd.RS -> led.4
lcd.E   -> led.5
lcd.RW -> led.6

    '''
    dict(
        avr=avr,
        led=ledrow,
        lcd=lcd,
        ac=ac
    ),
    vcd=vcd,
)

dev = CompositeGame([
    CompositeGame(
        [LcdGame(lambda x, y:lcd.get_char(x, y), (20, 2)),
        led_game,
        ],
        align=1),
    InfoGame(avr),
])

scrshot_by_exit = [(dev, image_file)] if image_file else None

AvrSimMain(avr, dev, vcd, speed=speed, fps=fps, visible=visible, timeout=timeout,
            scrshot_by_exit=scrshot_by_exit).run_game()

```

Starting program:

```


>>> from pysimavrgui.examples.sim.lcd import run_sim
>>> run_sim(vcdfile='docs/lcd.vcd', speed=1, timeout=0.2, fps=50, visible=0, image_file='docs/lcd.png')
Loaded 2112 .text
Loaded 14 .data
Starting atmega48 - flashend 0fff ramend 02ff e2end 00ff
atmega48 init
LCD: 37uS is 592 cycles for your AVR
LCD: 1uS is 16 cycles for your AVR
ac_input_init period 2000uS or 32000 cycles
hd44780_write_command 33
hd44780_write_command 30
hd44780_process_write command 20 write when still BUSY
hd44780_write_command 20
hd44780_write_command activating 4 bits mode
hd44780_write_command 28
hd44780_write_command 08
hd44780_write_command 01
hd44780_write_command 06
hd44780_write_command 0e
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30

```


```
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 31
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 32
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 33
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 34
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 35
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 36
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
```

```
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 37
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 38
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 39
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 31
hd44780_write_data 30
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 31
hd44780_write_data 31
hd44780_write_command 01
hd44780_write_command 84
hd44780_write_data 20
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 30
hd44780_write_data 30
hd44780_write_data 3a
hd44780_write_data 31
hd44780_write_data 32
```

GUI:



Signals:



3.3 seven segment display

Program:

```
from entrypoint2 import entrypoint
from path import path
from pysimavr.avr import Avr
from pysimavr.connect import connect_pins_by_rule
from pysimavrgui.examples.sim.avrsimmain import AvrSimMain
from pysimavr.firmware import Firmware
from pysimavrgui.compgame import CompositeGame
from pysimavrgui.infogame import InfoGame
from pysimavrgui.ledrowgame import LedRowGame
from pysimavrgui.sgm7game import Sgm7Game
from pysimavr.inverter import Inverter
from pysimavr.ledrow import LedRow
from pysimavr.sgm7 import Sgm7
from pysimavr.vcdfile import VcdFile

@entrypoint
def run_sim(vcdfile='sgm7.vcd', speed=0.001, fps=20, timeout=0.0, visible=1, image_file=''):
    firmware = Firmware(path(__file__).dirname() / 'sgm7.elf')
    firmware.f_cpu = 8000000
    firmware.mcu = "atmega168"
    avr = Avr(firmware)
    vcd = VcdFile(avr, period=1000, filename=vcdfile)

    #####
    # ledrow
    ledrow = LedRow(avr, size=12)
```

```
#####
# ledrow game
def state_func_seg(i):
    return (ledrow.pinstate(i), ledrow.reset_dirty(i))
led_game_seg = LedRowGame(state_func=state_func_seg,
                           disp_size=8,
                           labels=['B' + str(x) for x in range(8)]
                           )
def state_func_dig(i):
    return (ledrow.pinstate(i + 8), ledrow.reset_dirty(i + 8))
led_game_dig = LedRowGame(state_func=state_func_dig,
                           disp_size=4,
                           labels=['C' + str(x) for x in range(4)])
#####
# sgm7
sgm7 = Sgm7(avr, size=4)

inv = [Inverter(avr) for x in range(4)]

connect_pins_by_rule('''
    ledrow.0 <== avr.B0 ==> sgm7.A -> vcd
    ledrow.1 <== avr.B1 ==> sgm7.B -> vcd
    ledrow.2 <== avr.B2 ==> sgm7.C -> vcd
    ledrow.3 <== avr.B3 ==> sgm7.D -> vcd
    ledrow.4 <== avr.B4 ==> sgm7.E -> vcd
    ledrow.5 <== avr.B5 ==> sgm7.F -> vcd
    ledrow.6 <== avr.B6 ==> sgm7.G -> vcd
    ledrow.7 <== avr.B7 ==> sgm7.P -> vcd

    ledrow.8 <== avr.C0 ==> inv0.IN | inv0.OUT -> sgm7.D0 -> vcd
    ledrow.9 <== avr.C1 ==> inv1.IN | inv1.OUT -> sgm7.D1 -> vcd
    ledrow.10<== avr.C2 ==> inv2.IN | inv2.OUT -> sgm7.D2 -> vcd
    ledrow.11<== avr.C3 ==> inv3.IN | inv3.OUT -> sgm7.D3 -> vcd
''',
dict(
    avr=avr,
    sgm7=sgm7,
    ledrow=ledrow,
    inv0=inv[0],
    inv1=inv[1],
    inv2=inv[2],
    inv3=inv[3],
),
vcd=vcd,
)

#####
# sgm7 game
def segments_func(digit_index):
    return (sgm7.digit_segments(digit_index), sgm7.reset_dirty(digit_index))
sgm7_game = Sgm7Game(segments_func=segments_func, disp_size=4)

#####
# compose game
dev = CompositeGame([
    CompositeGame(
        [
            sgm7_game,
```



```

        led_game_seg,
        led_game_dig,
        ],
        align=1),
    InfoGame(avr),
    ])

scrshot_by_exit = [(dev, image_file)] if image_file else None

AvrSimMain(avr, dev, vcd, speed=speed, fps=fps, visible=visible, timeout=timeout,
            scrshot_by_exit=scrshot_by_exit).run_game()

```


Starting program:

```


>>> from pysimavrgui.examples.sim.sgm7 import run_sim
>>> run_sim(vcdfile='docs/sgm7.vcd', speed=1, timeout=0.1, fps=50, visible=0, image_file='docs/sgm7.png')
Loaded 680 .text
Loaded 6 .data
Starting atmega168 - flashend 3fff ramend 04ff e2end 01ff
atmega168 init
avr_timer_reconfigure-1 clock turned off
avr_timer_write_ocr-1 mode 0 UNSUPPORTED
avr_timer_reconfigure-1 clock turned off
avr_timer_configure-1 TOP 639.80Hz = 12503 cycles
avr_timer_configure-1 A 639.80Hz = 12503 cycles

```

GUI:



Signals:



CLI HELP FOR EXAMPLES

4.1 Pygame GUI examples

```
$ python -m pysimavrgui.examples.gui.lcdgame_ex --help
usage: lcdgame_ex.py [-h] [--debug]
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

```
$ python -m pysimavrgui.examples.gui.ledrowgame_ex --help
usage: ledrowgame_ex.py [-h] [--debug]
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

```
$ python -m pysimavrgui.examples.gui.sgm7game_ex --help
usage: sgm7game_ex.py [-h] [--debug]
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

```
$ python -m pysimavrgui.examples.gui.textgame_ex --help
usage: textgame_ex.py [-h] [--debug]
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

4.2 Simulation examples

```
$ python -m pysimavrgui.examples.sim.ledramp --help
usage: ledramp.py [-h] [-v VCDFILE] [-s SPEED] [-f FPS] [-t TIMEOUT]
                  [--visible VISIBLE] [-i IMAGE_FILE] [--debug]
```

optional arguments:

- h, --help show this help message and exit
- v VCDFILE, --vcdfilename VCDFILE

```
-s SPEED, --speed SPEED
-f FPS, --fps FPS
-t TIMEOUT, --timeout TIMEOUT
--visible VISIBLE
-i IMAGE_FILE, --image-file IMAGE_FILE
--debug                set logging level to DEBUG
```

```
$ python -m pysimavrgui.examples.sim.lcd --help
usage: lcd.py [-h] [-v VCDFILE] [-s SPEED] [-f FPS] [-t TIMEOUT]
              [--visible VISIBLE] [-i IMAGE_FILE] [--debug]
```

optional arguments:

```
-h, --help                show this help message and exit
-v VCDFILE, --vcdfile VCDFILE
-s SPEED, --speed SPEED
-f FPS, --fps FPS
-t TIMEOUT, --timeout TIMEOUT
--visible VISIBLE
-i IMAGE_FILE, --image-file IMAGE_FILE
--debug                set logging level to DEBUG
```

```
$ python -m pysimavrgui.examples.sim.sgm7 --help
usage: sgm7.py [-h] [-v VCDFILE] [-s SPEED] [-f FPS] [-t TIMEOUT]
               [--visible VISIBLE] [-i IMAGE_FILE] [--debug]
```

optional arguments:

```
-h, --help                show this help message and exit
-v VCDFILE, --vcdfile VCDFILE
-s SPEED, --speed SPEED
-f FPS, --fps FPS
-t TIMEOUT, --timeout TIMEOUT
--visible VISIBLE
-i IMAGE_FILE, --image-file IMAGE_FILE
--debug                set logging level to DEBUG
```

API

```
class pysimavrgui.buttongame.ButtonGame(hook=None, shortcut=None, label='', size='auto',
                                          display_shortcut=True, font_size=14)
```

```
    handleEvents(event)
```

```
    size
```

```
    surface
```

```
    update()
```

```
class pysimavrgui.compgame.CompositeGame(devs, align=0, size='auto', gap=2)
```

```
    exit()
```

```
    handleEvents(event)
```

```
    size
```

```
    surface
```

```
    update()
```

```
class pysimavrgui.infogame.InfoGame(avr)
```

```
    exit()
```

```
pysimavrgui.infogame.format_freq(f)
```

```
class pysimavrgui.lcdgame.LcdGame(char_func, disp_size=(10, 2), label='')
```

```
    load_fonts()
```

```
    size
```

```
    surface
```

```
    update()
```

```
class pysimavrgui.ledgame.LedGame(state_func, label='', size=(30, 30))
```

```
    on
```

```
    pulse
```

```
    size
```

```
state
    (on/off,pulse)

surface

update ()

class pysimavrgui.ledrowgame.LedRowGame (state_func, disp_size=None, labels=None, align=0,
                                         size='auto')

class pysimavrgui.maingame.MainGame (dev, pos=(0, 0), fps=50, size='auto', title='python-simavr',
                                       visible=True, scrshot_by_exit=None)

    cb_exit ()
    cb_loop ()
    handleEvents ()
    run_game ()
    screenshot (dev=None, img_file='screenshot.png')
    terminate ()

class pysimavrgui.sgm7game.Sgm7Game (segments_func, disp_size=4, label='')

    draw_digit (i, segments, color)

    size

    surface

    update ()

class pysimavrgui.textgame.TextGame (text_func, size=(30, 30), font_size=19)
    multi line is not supported!

    font

    size

    surface

    text

    update ()
```

DEVELOPMENT

6.1 Tools

1. `setuptools`
2. `Paver`
3. `nose`
4. `ghp-import`
5. `pyflakes`
6. `pychecker`
7. `paved fork`
8. `Sphinx`
9. `sphinxcontrib-programsscreenshot`
10. `sphinxcontrib-paverutils`
11. `autorun` from `sphinx-contrib` (there is no simple method, you have to download/unpack/setup)

6.2 Install on ubuntu

```
sudo apt-get install python-setuptools
sudo apt-get install python-paver
sudo apt-get install python-nose
sudo easy_install ghp-import
sudo apt-get install pyflakes
sudo apt-get install pychecker
sudo easy_install https://github.com/ponty/paved/zipball/master
sudo apt-get install scrot
sudo apt-get install xvfb
sudo apt-get install xserver-xephyr
sudo apt-get install python-imaging
sudo apt-get install python-sphinx
sudo easy_install sphinxcontrib-programsscreenshot
sudo easy_install sphinxcontrib-programoutput
sudo easy_install sphinxcontrib-paverutils
```

6.3 Tasks

[Paver](#) is used for task management, settings are saved in `pavement.py`. [Sphinx](#) is used to generate documentation.

print [paver](#) settings:

```
paver printoptions
```

clean generated files:

```
paver clean
```

generate documentation under *docs/_build/html*:

```
paver cog pdf html
```

upload documentation to [github](#):

```
paver ghpages
```

run unit tests:

```
paver nose
#or
nosetests --verbose
```

check python code:

```
paver pyflakes
paver pychecker
```

generate python distribution:

```
paver sdist
```

upload python distribution to [PyPI](#):

```
paver upload
```


INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

PYTHON MODULE INDEX

p

- `pysimavrgui.buttongame`, 18
- `pysimavrgui.compgame`, 18
- `pysimavrgui.infogame`, 18
- `pysimavrgui.lcdgame`, 18
- `pysimavrgui.ledgame`, 18
- `pysimavrgui.ledrowgame`, 19
- `pysimavrgui.maingame`, 19
- `pysimavrgui.sgm7game`, 19
- `pysimavrgui.textgame`, 19

INDEX

B

ButtonGame (class in pysimavrgui.buttongame), 18

C

cb_exit() (pysimavrgui.maingame.MainGame method), 19

cb_loop() (pysimavrgui.maingame.MainGame method), 19

CompositeGame (class in pysimavrgui.compgame), 18

D

draw_digit() (pysimavrgui.sgm7game.Sgm7Game method), 19

E

exit() (pysimavrgui.compgame.CompositeGame method), 18

exit() (pysimavrgui.infogame.InfoGame method), 18

F

font (pysimavrgui.textgame.TextGame attribute), 19

format_freq() (in module pysimavrgui.infogame), 18

H

handleEvents() (pysimavrgui.buttongame.ButtonGame method), 18

handleEvents() (pysimavrgui.compgame.CompositeGame method), 18

handleEvents() (pysimavrgui.maingame.MainGame method), 19

I

InfoGame (class in pysimavrgui.infogame), 18

L

LcdGame (class in pysimavrgui.lcdgame), 18

LedGame (class in pysimavrgui.ledgame), 18

LedRowGame (class in pysimavrgui.ledrowgame), 19

load_fonts() (pysimavrgui.lcdgame.LcdGame method), 18

M

MainGame (class in pysimavrgui.maingame), 19

O

on (pysimavrgui.ledgame.LedGame attribute), 18

P

pulse (pysimavrgui.ledgame.LedGame attribute), 18

pysimavrgui.buttongame (module), 18

pysimavrgui.compgame (module), 18

pysimavrgui.infogame (module), 18

pysimavrgui.lcdgame (module), 18

pysimavrgui.ledgame (module), 18

pysimavrgui.ledrowgame (module), 19

pysimavrgui.maingame (module), 19

pysimavrgui.sgm7game (module), 19

pysimavrgui.textgame (module), 19

R

run_game() (pysimavrgui.maingame.MainGame method), 19

S

screenshot() (pysimavrgui.maingame.MainGame method), 19

Sgm7Game (class in pysimavrgui.sgm7game), 19

size (pysimavrgui.buttongame.ButtonGame attribute), 18

size (pysimavrgui.compgame.CompositeGame attribute), 18

size (pysimavrgui.lcdgame.LcdGame attribute), 18

size (pysimavrgui.ledgame.LedGame attribute), 18

size (pysimavrgui.sgm7game.Sgm7Game attribute), 19

size (pysimavrgui.textgame.TextGame attribute), 19

state (pysimavrgui.ledgame.LedGame attribute), 18

surface (pysimavrgui.buttongame.ButtonGame attribute), 18

surface (pysimavrgui.compgame.CompositeGame attribute), 18

surface (pysimavrgui.lcdgame.LcdGame attribute), 18

surface (pysimavrgui.ledgame.LedGame attribute), 19

surface (pysimavrgui.sgm7game.Sgm7Game attribute),
19
surface (pysimavrgui.textgame.TextGame attribute), 19

T

terminate() (pysimavrgui.maingame.MainGame method),
19
text (pysimavrgui.textgame.TextGame attribute), 19
TextGame (class in pysimavrgui.textgame), 19

U

update() (pysimavrgui.buttongame.ButtonGame method),
18
update() (pysimavrgui.compgame.CompositeGame
method), 18
update() (pysimavrgui.lcdgame.LcdGame method), 18
update() (pysimavrgui.ledgame.LedGame method), 19
update() (pysimavrgui.sgm7game.Sgm7Game method),
19
update() (pysimavrgui.textgame.TextGame method), 19