

---

# Low Power WakeUp-Receiver

Project Electrical Engineering AS2019

---

**Authors**

Cédric Renda, Manuel Tischhauser

**Supervisor**

Prof. Dr. Heinz Mathis

**Assistant Supervisor**

Selina Malacarne

**Subject**

Wireless Communications



# **Abstract**

## **Introduction**

In company buildings, universities and other similar facilities, it is usual to attach occupancy schedules next to room entrances. These schedules are mostly printed on paper, or in more modern buildings, displayed on a screen. Using paper, it is impracticable to take short-term changes into account, since every adjustment needs to be made by printing a new schedule. Screens on the other hand need either to be connected to a power supply, which entails extensive installation work, or powered by a battery, which needs to be replaced from time to time. All these disadvantages could be avoided by using a screen which harvests its energy from the indoor light, and is updated via a wireless interface. The screen should therefore be completely wireless, which simplifies the installation.

## **Approach**

Solar cells should harvest the required energy which can be store in a super-capacitor. Because this harvesting unit cannot provide unlimited energy, the whole system with display, microcontroller and wireless interface should consume as little energy as possible. To achieve this, a e-paper display is used, which only needs energy to update the screen, but not to maintain the displayed data. By using a wake up receiver, it is now possible to disconnect the energy storage from the system, since it can be reconnected again when needed if a wake up interrupt is detected. In a nutshell, the display, microcontroller and interface can be completely disconnected from the power supply when not used. In this state, only the leakage of the super-capacitor and the wakeup receiver in listening mode consume power. This consumption is in the micro watt range.

## **Conclusion**

---

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	bla . . . . .	1
<b>2</b>	<b>Theory</b>	<b>3</b>
2.1	Microencapsulated Electrophoretic Displays . . . . .	3
2.2	wake up interrupt . . . . .	4
2.3	software grafik zeichen . . . . .	4
<b>3</b>	<b>Evaluation</b>	<b>5</b>
3.1	Energy harvesting . . . . .	5
3.2	Wireless interface . . . . .	6
<b>4</b>	<b>Development</b>	<b>7</b>
4.1	Overview . . . . .	7
4.2	Hardware . . . . .	7
4.2.1	Energy Harvesting . . . . .	7
4.3	Software . . . . .	10
<b>5</b>	<b>Results</b>	<b>13</b>
<b>6</b>	<b>Summary</b>	<b>15</b>
	<b>List of figures</b>	<b>15</b>
	<b>List of tables</b>	<b>17</b>
	<b>Sources</b>	<b>21</b>
	<b>Statement of Plagiarisms</b>	<b>21</b>
<b>A</b>	<b>Requirements</b>	<b>25</b>
A.1	Assignment . . . . .	26
A.2	Requirement Specification . . . . .	28

---

# **Chapter 1**

## **Introduction**

### **1.1 bla**

---



# Chapter 2

## Theory

### 2.1 Microencapsulated Electrophoretic Displays

There are several different technologies which are applied in e-paper displays. But since the developed prototype uses a screen, which uses a microencapsulated electrophoretic display, this section only describes this specific implementation.




Figure 2.1: filler pic




Figure 2.2: E-paper display under microscope with 250x magnification

## **2.2 wake up interrupt**

## **2.3 software grafik zeichen**

# Chapter 3

## Evaluation

This section lists the pros and cons of available Technologies. On this basis was evaluated, which hardware is suitable.

### 3.1 Energy harvesting

Technologie	Pro	Contra
BLA	- bla	- bla

## 3.2 Wireless interface


Technologie	Pro	Contra
Visual light communication	<ul style="list-style-type: none"> <li>- Radiation is proper for any environment</li> <li>- High data rate (several Gb/s)</li> <li>- Light for transmission can also be used as energy resource</li> </ul>	<ul style="list-style-type: none"> <li>- Only little products are available yet</li> <li>- Limited usability with existing lighting systems, additional ethernet cables to lightbulbs may be required</li> <li>- Direct irradiation is needed</li> </ul>
Wake-up radio	<ul style="list-style-type: none"> <li>- Range typically around 30m, but can be improved with antenna diversity and directional antennas</li> </ul>	<ul style="list-style-type: none"> <li>- bla</li> </ul>

# Chapter 4

## Development

### 4.1 Overview

Not Up To Date Graphic



### 4.2 Hardware

#### 4.2.1 Energy Harvesting

The screen should be self-sustaining, thus some sort of energy-harvesting unit is needed. It was apparent to choose light as the energy source, since the screen will be used in rooms, that are artificially illuminated most of the time. The energy obtained by solar cells is converted to a

---

suitable voltage, using a ADP5090 chip. This way, a super-capacitor, which is used as an energy storage device, is charged.

### Solar cell

As solar cell, the AM-1522 by Panasonic is used. One panel has an area of  $55.0 \text{ mm} \times 40.5 \text{ mm}$  and delivers up to  $58.7 \mu\text{A}$  when operating at an optimal voltage of  $2.1 \text{ V}$ , provided an illuminance of  $200 \text{ lux}$ . To keep a reasonable display to panel ratio, four cells were connected in parallel, which corresponds to an area of ca.  $89.1 \text{ cm}^2$  (Display area =  $283 \text{ cm}^2$ ). Therefore, the solar cells should provide a power of

$$P = U \cdot I = 4 \cdot 58.7 \mu\text{A} \cdot 2.1 \text{ V} = 485.52 \mu\text{W}, \quad (4.1)$$

given a  $200 \text{ lux}$  illuminance [2].

### Power management

The ADP5090 from Analog Devices is used on the power management. This boost regulator makes it possible to charge storage elements, such as rechargeable batteries and super capacitors with the input dc-power provided by the PV-cell. Utilized features are:

- Maximum power point tracking
- Efficiency up to 90%
- Input voltage  $V_{IN}$  from  $80 \text{ mV}$  to  $3.3 \text{ V}$
- Programmable voltage range ( $2.2 \text{ V}$  to  $5.2 \text{ V}$ ) for the storage element

To prevent the storage element from overdischarging, the ADP5090 enables the user to set a maximal Voltage with resistors:

$$V_{\text{BAT\_TERM}} = \frac{3}{2} V_{\text{REF}} \left( 1 + \frac{R_{\text{TERM1}}}{R_{\text{TERM2}}} \right). \quad (4.2)$$

The same procedure is applied to set a minimal voltage:

$$V_{\text{BAT\_SD}} = V_{\text{REF}} \left( 1 + \frac{R_{\text{SD1}}}{R_{\text{SD2}}} \right). \quad (4.3)$$

While discharging, the ADP5090 will switch off the output  $V_{\text{SYS}}$  if  $V_{\text{BAT\_SD}}$  is reached. This prevents the storage element from overdischarging. The output voltage  $V_{\text{SYS}}$ , where the load is attached, will therefore always stay in this programmed range ( $V_{\text{BAT\_SD}} \leq V_{\text{SYS}} \leq V_{\text{BAT\_TERM}}$ ) [3].

For this prototype, the evaluation board for the ADP5090 was used, where the internal reference voltage ( $V_{\text{REF}}$  in (4.2) and (4.3)) is  $1.21 \text{ V}$  [4].

---

## Super capacitor

As energy storage, a super capacitor from Taiyo Yuden (LIC1235RS3R8406) has proven to be suitable, which is a 40 F cylinder type lithium ion capacitor. The operating voltage range is between 2.2 V and 3.8 V. Discharging the capacitor lower than 2.2 V causes shorter lifetime and higher leakage current. The same unwanted behaviour occurs when charging the capacitor over 3.8 V [5].

## Combined test

To test the behaviour of the power management, supercapacitor and solar cells, a couple of measurements are executed.

To carry out these measurements, it is first necessary to adjust the minimal and maximal voltage of the ADP5090. The nrf58240 accepts supply voltages between 1.6 V up to 5.5 V [6]. The STM32 on the other side is less flexible with an input voltage range of 1.71 V to 3.6 V [7]. As stated in the section above, the super capacitors operating voltage is between 2.2 V and 3.8 V. Hence it seems reasonable, to set  $V_{BAT\_TERM} \leq 3.6$  V and  $V_{BAT\_SD} \geq 2.2$  V, to satisfy all of these three elements. In order to do this, the four resistors have to be chosen as  $R_{TERM1} = 4.3$  M $\Omega$ ,  $R_{TERM2} = 4.7$  M $\Omega$ ,  $R_{SD1} = 4.3$  M $\Omega$  and  $R_{SD2} = 5.1$  M $\Omega$ . Inserted in the equation (4.2) and (4.3) we get

$$V_{BAT\_TERM} = \frac{3}{2} 1.21 \text{ V} \left( 1 + \frac{4.3 \text{ M}\Omega}{4.7 \text{ M}\Omega} \right) \approx 3.48 \text{ V} \quad (4.4)$$

and

$$V_{BAT\_SD} = 1.21 \text{ V} \left( 1 + \frac{4.3 \text{ M}\Omega}{5.1 \text{ M}\Omega} \right) \approx 2.23 \text{ V}. \quad (4.5)$$

While testing, the input voltage from the solar cells ( $V_{IN}$ ), voltage of the supercap ( $V_{BAT}$ ) and the output voltage ( $V_{SYS}$ ) are tracked. Additionally, the illuminance ( $E_v$ ) near the PV-cells is recorded.

The purpose of the first test is to check, if the ADP5090 converts  $V_{IN}$  to a voltage  $\leq V_{BAT\_TERM}$ . The measurements were taken over a couple hours and are plotted in Figure 4.1.

No load was connected to the output, which is the reason  $V_{SYS}$  is overlapped by  $V_{BAT}$ . It can be seen, that between 17:00 and 23:00, the super capacitor was being charged and that the ADP5090 controls the voltage  $V_{BAT}$  like expected to the adjusted maximum voltage  $V_{BAT\_TERM}$ .

The second test should simulate the discharging when a load is connected, after the capacitor was fully charged. It was necessary to estimate the consumed power by the electronic components of the prototype. A rough measurement with a power analyser showed, that the microcontroller and the e-paper display together draw at its peak about 240 mA when connected to 5 V. The nrf52840 on the other hand, only consumes 6 mA with a 3 V source. Thus the expected consumed power at its peak is:

$$P_e = 5 \text{ V} \cdot 0.24 \text{ A} + 3 \text{ V} \cdot 0.006 \text{ A} = 1.218 \text{ W}. \quad (4.6)$$

A load of 10  $\Omega$  should lead to currents between 0.223 A and 0.348 A which again lead to a power consumption that should approximately match the power consumption of the finished prototype. Furthermore, the solar cells were covered to observe the discharging without interference of additionally charging behaviour. Figure 4.2 shows the result.




Figure 4.1: Charging behaviour

As soon as the load is connected (after 25 s),  $V_{SYS}$  and  $V_{BAT}$  first drop by almost 1 V and after that steadily decrease. After ca. 100 s,  $V_{BAT}$  reached the value of  $V_{BAT\_SD}$  and the ADP5090 switches the output off ( $V_{SYS}$  drops to 0) to prevent the capacitor from overdischarging. The output now stays switched off, until  $V_{IN}$  again supplies energy, and  $V_{BAT} \leq V_{BAT\_SD}$ . It can also clearly be seen, that after 160 seconds, the ADP5090 controls  $V_{IN}$  to ca. 2.1 V. Recall that this is the optimal power point of the solar cell.

## 4.3 Software






Figure 4.2: Discharging behaviour

---

# **Chapter 5**

## **Results**

---

# **Chapter 6**

## **Summary**

---

---

# List of Figures

2.1	filler pic . . . . .	3
2.2	E-paper display under microscope with 250x magnification . . . . .	4
4.1	Charging behaviour . . . . .	10
4.2	Discharging behaviour . . . . .	11

---



---

## List of Tables

---

# Sources

- [1] K. Amundson, *Electrophoretic Displays*. Springer International Publishing Switzerland, 2016.
- [2] *Amorphous Silicon Solar Cells*, Aug. 2019.
- [3] *Ultralow Power Boost Regulator with MPPT and Charge Management*, Feb. 2017.
- [4] *EVAL-ADP5090 User Guide*, 2014.
- [5] *Cylinder Type Lithium Ion Capacitors*, Aug. 2019.
- [6] *nRF52840 Objective Product Specification v0.5*, Dec. 2016.
- [7] *STM32L4R5xx STM32L4R7xx STM32L4R9xx*, Apr. 2018.

---

# Statement of Plagiarism

We declare that, apart from properly referenced quotations, this report is our own work and contains no plagiarism; it has not been submitted previously for any other assessed unit on this or other degree courses.

<b>Place</b>	<b>Date</b>
Rapperswil	December 5, 2019

## Signatures

Cedric Renda

Manuel Tischhauser

---

# **Appendix A**

## **Requirements**

---

# A.1 Assignment



## Low power wakeup receiver

Semesterarbeit für Manuel Tischhauser und Cédric Renda

Herbst 2019

### 1. Einführung

Im Gebäudemanagement ist es üblich, Belegungspläne an den Eingängen der Räume anzubringen. Oftmals sind diese in Papierformat und müssen bei einer Änderung von Hand gewechselt werden. Mit dieser Methode werden kurzfristige Belegungen nicht aufgezeigt. Dies könnte man umgehen, wenn man mit Displays arbeitet die Wireless aktualisiert werden können. Dabei stellt sich allerdings das Problem, dass man entweder Kabel für die Netzeinspeisung verlegen muss oder Batterien verwendet, die regelmässig ersetzt werden müssen. Im Idealfall entfällt die Speisung komplett.

### 2. Aufgabenstellung

Zu einem Empfängermodul soll eine bidirektionale low power Kommunikationsstrecke aufgebaut werden. Der Empfänger soll durch Energy-harvesting Massnahmen möglichst passiv betrieben werden können. Dieser enthält einen Ultra Low Power Wake-up Receiver und eine Anzeige mit dem die empfangenen Daten auf entsprechende Weise dargestellt werden. Ein System kann aus mehreren Empfängern bestehen, welche unabhängig voneinander vom Sender selektiert werden können.

### 3. Ablauf

Zu Beginn der Arbeit sind ein Projektplan und ein Pflichtenheft zu erstellen, welche in den ersten Wochen dem Betreuer abgegeben werden müssen. Ein Vorschlag des Pflichtenheftes befindet sich im Arbeitsplatzordner oder als \*.docx File auf dem Public Server ([hsr.ch/root/auw/sge/labors/Mk/pub\\_for\\_students](http://hsr.ch/root/auw/sge/labors/Mk/pub_for_students)). Planen Sie total 240 Arbeitsstunden (8 ECTS \* 30 h/ECTS) ein. Die Arbeiten sollen innerhalb der Gruppe geeignet aufgeteilt werden; die Aufteilung ist im Bericht entsprechend festzuhalten, genauso wie ein Vergleich des geplanten und des effektiv durchgeführten Projektplans. Weitere Einzelheiten werden an den wöchentlichen Besprechungen festgelegt. Die Arbeiten sollen möglichst selbstständig durchgeführt werden. Die Kriterien der Beurteilung und Notengebung sind im unten erwähnten Leitfaden zu finden.

### 4. Laborjournal

Während der Arbeit ist ein persönliches (d.h. pro Person eines), gebundenes, handschriftliches und datiertes Laborjournal zu führen. Darin werden alle Tätigkeiten betreffend Dauer und Resultate eingetragen. Ebenfalls soll darin ein Protokoll geführt werden von den wöchentlichen Treffen. Das Laborjournal wird am Ende der Arbeit abgegeben und wird mitbenotet.

### 5. Bericht

Über die Arbeit ist ein Bericht zu verfassen, dessen Textteil maximal 60 Seiten umfassen und eine Dateigrösse von 5MB nicht überschreiten soll. Im Bericht sollen alle gemachten Überlegungen, Abklärungen, Berechnungen und Untersuchungen detailliert (in Text und Bild) dokumentiert werden. Der Bericht muss gut leserlich geschrieben und übersichtlich gegliedert sein. Weitere Richtlinien, wie ein Bericht aufgebaut sein kann, und weitere nützliche Informationen findet man im Leitfaden, welcher in gedruckter Version im Arbeitsplatzordner und auf dem Public Server abgelegt ist.

Des Weiteren muss im Bericht unbedingt eine unterschriebene Nicht-Plagiatserklärung enthalten sein, ein Beispiel dieser Erklärung befindet sich auf dem Public Server.

Der Bericht ist in 1 Papier-Exemplar abzugeben, mit einer beiliegenden CD-ROM, auf der alle anfallenden Daten, wie auch der Bericht selbst (im PDF-Format) gespeichert sind.



---

## Semesterarbeit

---

Writing in English is highly encouraged.

### 6. Termine

Beginn der Arbeit:

Abgabe des Berichts:

Mündliche Präsentation:

### 7. Organisatorisches

Betreuung der Arbeit:

Betreuung des Labors:

Arbeitsplatz:

Industriepartner:

Besprechungen:

Examinator:

wöchentlich, nach Vereinbarung, an der HSR

Prof. Dr. Heinz Mathis, [hmathis@hsr.ch](mailto:hmathis@hsr.ch)

Rapperswil, [Datum]

Viel Erfolg wünscht Ihnen

Heinz Mathis,

Dozent Mobilkommunikation

---

## A.2 Requirement Specification

### Pflichtenheft

Projekt: Low power wakeup receiver

Version 0.1

Cédric Renda, Manuel Tischhauser

Name	Datum	Unterschrift
Prof. Dr. Heinz Mathis		
Selina Malacarne		
Cédric Renda		
Manuel Tischhauser		

---

27. September 2019

## Inhaltsverzeichnis

<b>1</b>	<b>Einleitung</b>	<b>3</b>
<b>2</b>	<b>Auftrag</b>	<b>3</b>
<b>3</b>	<b>Produktanforderungen</b>	<b>3</b>
3.1	Hardware . . . . .	4
3.2	Software . . . . .	4
3.3	Varianten/Optionen . . . . .	4
3.4	Dokumentation . . . . .	4
<b>4</b>	<b>Zeitplan</b>	<b>5</b>

## 1 Einleitung

Im Gebäudemanagement ist es üblich, Belegungspläne an den Eingängen der Räume anzubringen. Oftmals sind diese in Papierformat und müssen bei einer Änderung von Hand gewechselt werden. Mit dieser Methode werden kurzfristige Belegungen nicht aufgezeigt. Dies könnte man umgehen, wenn man mit Displays arbeitet, die über eine drahtlose Schnittstelle aktualisiert werden können. Dabei stellt sich allerdings das Problem, dass man entweder Kabel für die Netzeinspeisung verlegen muss, oder Batterien verwendet, die regelmässig ersetzt werden müssen. Im Idealfall entfällt die Speisung komplett.

## 2 Auftrag

Im Rahmen dieser Semesterarbeit soll eine Lösung zur oben beschriebenen Problematik ausgearbeitet werden. Der Fokus liegt auf der Erstellung eines autarken Anzeigesystems welches über eine drahtlose Schnittstelle bedient werden kann. Die folgende Punkte sollen dabei abgearbeitet werden:

- Recherche bezüglich Schnittstelle und Energy Harvesting.
- Vor- und Nachteile bestehender Technologien abwägen und geeignete Hardware wählen.
- Erstellen eines lauffähigen Prototypen.




Abbildung 2.1: Use-Case Diagramm

Der Prototyp richtet sich nach dem Use-Case Diagramm in Abbildung 2.1.

## 3 Produktanforderungen

Das Empfängermodul ist autark und kann auf einem Display Stundenpläne anzeigen. Diese werden über eine drahtlose, bidirektionale Schnittstelle gesendet. Der Sender wird mit einem Computer bedient.

Besteht das System aus mehreren Empfängern, so kann das Sendemodul diese unabhängig voneinander selektieren.

### 3.1 Hardware

#### Sender

- Schnittstelle zum Computer
- Sendemodul

#### Empfänger

- Mikrocontroller oder Vergleichbares (Prozessor, Speicher, usw.)
- E-Paper-Display
- Energy-Harvesting-Einheit
- Energiespeicher
- Empfangsmodul

### 3.2 Software

#### Sender

- Treiber für Sendemodul

#### Empfänger

- Firmware für Mikrocontroller

### 3.3 Varianten/Optionen

Ist der Prototyp funktionsfähig, soll zu einem späteren Zeitpunkt auch möglich sein, verschiedene Bildschirmgrößen zu verwenden, wobei sich auch Anzeige nicht nur auf Raumbelungspläne beschränkt. Deshalb soll das System und insbesondere die Software so flexibel wie möglich entwickelt werden.

### 3.4 Dokumentation

Die Dokumentation beinhaltet sämtliche Überlegungen, Abklärungen, Berechnungen und Untersuchungen, welche im Laufe der Semesterarbeit gemacht wurden.

# 4 Zeitplan

