

Restapp

Documentation for the restaurants app

Auth

AUTHENTICATION ENDPOINTS

POST Register

http://127.0.0.1:5000/v1/auth/register

BODY raw

```
{
  "email": "re@pasre.pas",
  "password": "repas",
  "name": "saper"
}
```

Example Request

Register

```
curl --location --request POST 'http://127.0.0.1:5000/v1/auth/register' \
--data-raw '{
  "email": "re@pasre.pas",
  "password": "repas",
  "name": "saper"
}'
```

Example Response

201 CREATED

Body Header (5)



```
{
  "status": "success",
  "res": {
    "_id": "61c0e7c44f480002572e3304",
    "email": "re@pasre.pas",
    "name": "saper"
  },
  "message": "ok"
}
```

[View More](#)

POST Login

```
http://127.0.0.1:5000/v1/auth/login
```

BODY raw

```
{
  "email": "re@pasre.pas",
  "password": "repas"
}
```

Example Request

Login

```
curl --location --request POST 'http://127.0.0.1:5000/v1/auth/login' \
--data-raw '{
  "email": "re@pasre.pas",
  "password": "repas"
}'
```

Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "res": {
    "_id": "61c0e7c44f480002572e3304",
    "email": "re@pasre.pas",
    "name": "saper",
    "tokens": {
      "access": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlbnAwMzIyMTIsIm5iZiI6MTY0MDA",
      "refresh": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlbnAwMzIyMTIsIm5iZiI6MTY0MDA",
    }
  }
}
```

View More

POST Logout

http://127.0.0.1:5000/v1/logout

HEADERS


Authorization

Bearer <jwt>

Example Request

Logout

```
curl --location --request POST 'http://127.0.0.1:5000/v1/logout' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlbnAwMzIyMTIsIm5iZiI6MTY0MDA'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "msg": "Successfully logged out."
}
```

POST Refresh token

http://127.0.0.1:5000/v1/refresh/token


Authorization

Bearer <jwt>

Example Request

Refresh token

```
curl --location --request POST 'http://127.0.0.1:5000/v1/refresh/token' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOjE2NDAwMzIyMTIsI
```




Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOjE2NDAwMzI0OTEsIm5iZiI6MTY0Ml
```



User

USER ENDPOINTS

GET All users

http://127.0.0.1:5000/v1/users

HEADERS


Authorization

Bearer <jwt>

Example Request

All users

```
curl --location --request GET 'http://127.0.0.1:5000/v1/users' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI0OTEs'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "res": [
    {
      "_id": "61c0e7c44f480002572e3304",
      "email": "re@pasre.pas",
      "name": "saper"
    }
  ]
}
```

[View More](#)

GET Get a user

HEADERS


Authorization

Bearer <jwt>

Example Request

Get a user

```
curl --location --request GET 'http://127.0.0.1:5000/v1/user/61c0e7c44f480002572e3304' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI0OTEs'
```



Example Response

200 OK

Body Header (5)



```
{
  "message": "success",
  "res": {
    "_id": "61c0e7c44f480002572e3304",
    "email": "re@pasre.pas",
    "name": "saper"
  }
}
```

PUT Update a user

http://127.0.0.1:5000/v1/user/<used_id>

HEADERS

Authorization

Bearer <jwt>

BODY raw

```
{
  "email": "",
  "name": "saper repas"
}
```

Example Request

Update a user

```
curl --location --request PUT 'http://127.0.0.1:5000/v1/user/61c0e7c44f480002572e3304' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI00TES'
--data-raw '{
  "email": "",
  "name": "saper repas"
}'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "data": {
    "_id": "61c0e7c44f480002572e3304",
    "email": "re@pasre.pas",
    "name": "saper repas"
  },
  "message": "ok"
}
```

[View More](#)

DEL Delete a user

http://127.0.0.1:5000/v1/user/<used_id>

HEADERS


Authorization

Bearer <jwt>

Example Request

Delete a user

```
curl --location --request DELETE 'http://127.0.0.1:5000/v1/user/61c0e7c44f480002572e3304' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI0OTEs'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "data": true,
  "message": "Delete Successfully"
}
```

Restaurant

RESTAURANT ENDPOINTS



GET Get all restaurant

http://127.0.0.1:5000/v1/restaurant

HEADERS


Authorization

Bearer <jwt>

Example Request

Get all restaurant

```
curl --location --request GET 'http://127.0.0.1:5000/v1/restaurant' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI0OTEs'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "res": [
    {
      "_id": "61c066ea060060c4687f6abe",
      "restaurant_name": "Plaza Bagels & Deli",
      "cuisine": "Delicatessen",
      "town": "Staten Island",
      "address": {
        "building_number": "73",
```

View More

POST Add a new restaurant

http://127.0.0.1:5000/v1/restaurant

HEADERS

Authorization

Bearer <jwt>

BODY raw

View More

Add a new restaurant

View More

200 OK

View More

PUT Update a restaurant

HEADERS

Authorization

Bearer <jwt>

BODY raw

```
{
  "restaurant_name": "",
  "cuisine": "",
  "town": "",
  "address": {
    "building_number": "",
    "street": "",
    "postcode": ""
  }
}
```

Example Request

Update a restaurant

```
curl --location --request PUT 'http://127.0.0.1:5000/v1/restaurant/61c0ed154f480002572e3337' \
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlE2NDAwMzI0OTEs' \
--data-raw '{
  "restaurant_name": "Pizza Bagels",
  "cuisine": "Italien",
  "town": "Dallas",
  "address": {
    "building_number": "73",
    "street": "Old Dorp Plaza",
    "postcode": "30972"
  }
}'
```

View More

Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "data": true,
  "message": "ok"
}
```

DEL Delete a restaurant

http://127.0.0.1:5000/v1/restaurant/<restaurant_id>

HEADERS

Authorization


Bearer <jwt>



Example Request

Delete a restaurant

```
curl --location --request DELETE 'http://127.0.0.1:5000/v1/restaurant/61c0ed154f480002572e333'
--header 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlY2NDAwMzI0OTEs'
```



Example Response

200 OK

Body Header (5)

```
{
  "status": "success",
  "data": true,
  "message": "Delete Successfully"
```