Connected. Not complicated.

Compare the latest features of Honeywell Home connected thermostats.

Network Connection	Description	Model	Program Options	Power Method	Display Size	Application — Stages	Dual fuel	Ventilation with ERV/HRV or damper	Humidifier or dehumidifier	Wired indoor/outdoor sensors	Maintenance reminders	Distribution Part Number	Price
WiFi	T10 Pro Smart with RedLINK® Sensor	THX321WFS2001W/U	7-Day Programmable / 7-Day Programmable Geofencing / Non-Programmable	C-wire	7.27 sq. in.	3H/2C Heat Pumps + 2H/2C CS	•	•	•	•	•		
WiFi	T10 Pro Smart (without sensor)	THX321WF2003W/U	7-Day Programmable / 7-Day Programmable Geofencing / Non-Programmable	C-wire	7.27 sq. in.	3H/2C Heat Pumps + 2H/2C CS	•	•	•	•	•		
WiFi	T6 Pro Smart	TH6320WF2003/U	5-1-1 Programmable / 5-2 Programmable / 7-Day Programmable Geofencing / Non-Programmable	C-wire	6.89 sq. in.	3H/2C Heat Pumps + 2H/2C CS	•	•		•	•		
WiFi	T6 Pro Smart	TH6220WF2006/U	5-1-1 Programmable / 5-2 Programmable / 7-Day Programmable Geofencing / Non-Programmable	C-wire	6.89 sq. in.	2H/1C Heat Pumps + 2H/2C CS				•	•		
WiFi	9000 Smart	TH9320WF5003/U	7-Day Programmable / Non-Programmable	C-wire	8.06 sq. in.	3H/2C Heat Pumps + 2H/2C CS					•		
WiFi	VisionPRO® 8000 Smart	TH8321WF1001/U	7-Day Programmable / Non-Programmable	C-wire	10 sq. in.	3H/2C Heat Pumps + 2H/2C CS	•	•	•	•	•		
RedLINK® Internet Gateway	Prestige® IAQ Kit	YTHX9421R5085WW/U (includes Prestige thermostat, EIM, & 2 duct sensors)	7-Day Programmable / Non-Programmable	2-wire only (R + C)	8 sq. in.	4H/2C Heat Pumps + 3H/2C CS	•	•	•	•	•		
RedLINK® Internet Gateway	Prestige® IAQ Kit	YTHX9421R5127WW/U (includes Prestige thermostat, EIM, Gateway, & 2 duct sensors)	7-Day Programmable / Non-Programmable	2-wire only (R + C)	8 sq. in.	4H/2C Heat Pumps + 3H/2C CS	•	•	•	•	•		
RedLINK® Internet Gateway	Prestige® IAQ Kit	YTHX9421R5101WW/U (includes Prestige thermostat, EIM, wireless outdoor sensor, & 2 duct sensors)	7-Day Programmable / Non-Programmable	2-wire only (R + C)	8 sq. in.	4H/2C Heat Pumps + 3H/2C CS	•	•	•	•	•		
RedLINK® Internet Gateway	Prestige® IAQ Kit	YTHX9421R7001WW/U (includes Prestige thermostat, EIM, Gateway, wireless outdoor sensor, wireless indoor sensor, & 2 duct sensors)	7-Day Programmable / Non-Programmable	2-wire only (R + C)	8 sq. in.	4H/2C Heat Pumps + 3H/2C CS	•	•	•	•	•		
RedLINK® Internet Gateway	RedLINK® VisionPRO® 8000	TH8321R1001/U	7-Day Programmable / Non-Programmable			3H/2C Heat Pumps + 2H/2C CS (With EIM sold separate can control up to 4 stage heat or 4 stage cooling)	•	•	•	•	•		
RedLINK® Internet Gateway	RedLINK® VisionPRO® 8000	TH8320R1003/U	7-Day Programmable / Non-Programmable	Battery or C-wire	10 sq. in.	3H/2C Heat Pumps + 2H/2C CS (With EIM sold separate can control up to 4 stage heat or 4 stage cooling)	•			•	•		
RedLINK® Internet Gateway	RedLINK® VisionPRO® 8000	TH8110R1008/U	7-Day Programmable / Non-Programmable	Battery or C-wire	10 sq. in.	1H/1C Heat Pumps + 1H/1C CS (With EIM sold separate can control up to 4 stage heat or 4 stage cooling)				•	•		
Z-Wave	T6 Pro Z-Wave	TH6320ZW2003/U	5-1-1 Programmable / 5-2 Programmable / 7-Day Programmable / Non-Programmable / Occupancy through App	Battery or C-wire	6.89 sq. in.	3H/2C Heat Pumps + Dual Fuel 2H/2C Conventional Systems	•			•	•		

You've got a fix for everything. So do we.

For over 120 years, our thermostats have delivered dependable solutions to HVAC contractors and distributors. From simple to smart thermostats, we're dedicated to making sure every job has its perfect match.

For more information
resideo.com/pro

Resideo Technologies, Inc.
1985 Douglas Dr. N
Golden Valley, MN 55422
1-800-468-1502
resideo.com

Honeywell Home

From simple to simply smart.

Compare our complete line of thermostats for every job.

Product Comparison Guide

Don't sweat the thermostat.

Simple non-programmable basics, fully-connected solutions and everything in between. Resideo is proud to deliver the Honeywell Home thermostats you and your customers rely on. Just like we've done for generations.

Honeywell Home

	Description	Model	Program Options	Power Method	Display Size	Application	Features and Functions			Distributor part number	Price
						Stages	Dual fuel	Wired indoor/outdoor sensors	Maintenance reminders		
Non-Connected	T6 Pro	TH6320U2008/U	5-1-1 Programmable 5-2 Programmable 7-Day Programmable Non-Programmable	Battery or C-wire	5.44 sq. in.	3H/2C Heat Pumps + 2H/2C Conventional Systems	•	•	•		
		TH6220U2000/U				2H/1C Heat Pumps + 2H/2C Conventional Systems	•	•	•		
		TH6210U2001/U				2H/1C Heat Pumps + 1H/1C Conventional Systems			•		
	T6 Hydronic (Slab sensor included)	TH6100AF2004/U	5-1-1 Programmable 5-2 Programmable 7-Day Programmable Non-Programmable	Battery or C-wire	5.44 sq. in.	1 Stage Hot Water Heat Only – No Fan		•			
	T4 Pro	TH4210U2002/U	5-1-1 Programmable 5-2 Programmable 7-Day Programmable Non-Programmable	Battery or C-wire	3.93 sq. in.	2H/1C Heat Pumps + 1H/1C Conventional Systems			•		
		TH4110U2005/U				1H/1C Heat Pumps + 1H/1C Conventional Systems			•		
	TL8100 Hydronic	TL8100A1008/U	7-Day Programmable	Battery only		1 Heat					
	T3 Pro	TH3210U2004/U	Non-Programmable	Battery or C-wire	3.32 sq. in.	2H/1C Heat Pumps + 1H/1C Conventional Systems					
		TH3110U2008/U		Battery or C-wire	3.32 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems					
	T1 Pro	TH1110D2009/U	Non-Programmable	Battery or C-wire	2.37 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems					
		TH1010D2000/U		Battery or C-wire	2.37 sq. in.	1 Heat or 1 Cool Only					

Simple. Not ordinary.

Discover the full line of Honeywell Home non-connected thermostats.

	Description	Model	Program Options	Power Method	Display Size	Stages	Distributor part number	Price
Non-Connected	FocusPRO 6000	TH6220D1028/U	5-1-1 Programmable 5-2 Programmable	Battery or C-wire	5.09 sq. in.	2H/1C Heat Pumps + 2H/2C Conventional Systems		
		TH6220D1002/U			3.75 sq. in.	2H/1C Heat Pumps + 2H/2C Conventional Systems		
		TH6110D1021/U			5.09 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems		
		TH6110D1005/U			3.75 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems		
	FocusPRO 5000	TH5220D1029/U	Non-Programmable	Battery or C-wire	5.09 sq. in.	2H/1C Heat Pumps + 2H/2C Conventional Systems		
		TH5220D1003/U			3.75 sq. in.	2H/1C Heat Pumps + 2H/2C Conventional Systems		
		TH5110D1022/U			2.98 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems		
		TH5110D1006/U			1.95 sq. in.	1H/1C Heat Pumps + 1H/1C Conventional Systems		
	PRO 3000	TH3210D1004/U	Non-Programmable	Battery or C-wire	1.32 sq. in.	2H/1C Heat Pumps Only		
		TH3110D1008/U				1H/1C Heat Pumps + 1H/1C Conventional Systems		
	PRO 2000	TH2210DH1000/U	5-2 Programmable	Battery or C-wire	1.73 sq. in.	2H/1C Heat Pumps Only		
		TH2210DV1006/U				2H/1C Heat Pumps Only		
		TH2110DH1002/U				1H/1C Heat Pumps + 1H/1C Conventional Systems		
		TH2110DV1008/U				1H/1C Heat Pumps + 1H/1C Conventional Systems		
	PRO 1000	TH1210DH1001/U	Non-Programmable	Battery or C-wire	1.32 sq. in.	2H/1C Heat Pumps Only		
		TH1210DV1007/U						
		TH1110DH1003/U				1H/1C Heat Pumps + 1H/1C Conventional Systems		
		TH1110DV1009/U						
		TH1100DH1004/U				1 Heat Only		
		TH1100DV1000/U						
	E1 PRO	TH1110E1000/U	Non-Programmable	Battery or C-wire	2.4 sq. in.	1 Heat/1 Cool		
	"The Digital Round™"	T8775A1009/U	Non-Programmable	Power-stealing	0.75 sq. in.	1 Heat Only		
		T8775C1005/U				1 Heat/1 Cool		

	Description	Model	Fahrenheit/Celsius	Stages	Distributor Part Number	Price
Non-Connected	The Round™	T87K1007/U	Fahrenheit	1 Heat		
		T87N1000/U		1 Heat/1 Cool		
		T87K1015/U	Celsius	1 Heat		
		T87N1018/U		1 Heat/1 Cool		
	The Round™ (Easy-to-See)	T87N1026/U	Fahrenheit	1 Heat/1 Cool		
	Econostat Vertical	T834N1002/U	Fahrenheit	1 Heat/1 Cool		
	Econostat	T834L1004/U	Both	1 Cool		
		T834N1010/U	Celsius	1 Heat/1 Cool		
	Econostat Horizontal	T8034N1007/U	Fahrenheit	1 Heat/1 Cool		
	Econostat	T822K1000/U	Fahrenheit	1 Heat		
		T822K1018/U	Fahrenheit			
		T822K1034/U	Celsius (7–32 Degrees)			
		T822K1042/U	Fahrenheit (35–85 Degrees)			
		T822L1000/U	Fahrenheit (45–95 Degrees)	1 Cool		
	Econostat	T827K1009/U	Fahrenheit	1 Heat		
		T827K1017/U	Celsius (10–32 Degrees)			
	T812	T812A1002/U	Both	1 Heat		
		T812A1010/U		1 Heat with positive off		
		T812C1000/U		1 Heat/1 Cool		
		TS812A1007/U		1 Heat		