

I want to create a basic C++ console program that generates funny excuses for missing homework or assignments using the student's name. The program should first ask the user to enter their name, and then it should store at least 10 different excuse messages in an array or vector. Each excuse will have a placeholder like {name}, which will later be replaced with the actual name entered by the user. After that, the program should randomly select one excuse from the list, replace the placeholder with the student's name, and display the final excuse on the screen. The code should be simple, easy to understand, and use basic C++ concepts with clear variable names and comments where needed. The program should give a different random excuse each time it is run

Here's a simple and clean C++ console program that does exactly what you described. It uses basic concepts like arrays (vector), random selection, and string replacement — with clear comments.

✅ C++ Program: Funny Excuse Generator

✅ C++ Program: Funny Excuse Generator

```
// C++  
  
#include <iostream>  
#include <vector>  
#include <string>  
#include <cstdlib> // for rand() and srand()  
#include <ctime>   // for time()  
  
// Function to replace {name} with actual student name  
std::string replaceName(std::string excuse, std::string name) {  
    size_t pos = excuse.find("{name}"); // find placeholder  
  
    if (pos != std::string::npos) {  
        excuse.replace(pos, 6, name); // replace "{name}" with actual name  
    }  
  
    return excuse;  
}  
  
int main() {  
    std::string studentName;  
  
    // Ask user for name  
    std::cout << "Enter student name: ";  
    std::getline(std::cin, studentName);  
  
    // ...  
}
```

+ Ask anything

C++

```
// List of excuse templates
std::vector<std::string> excuses = {
    "{name} could not finish homework because the laptop suddenly stopped working.",
    "{name} forgot the assignment at home due to a rush in the morning.",
    "{name} was helping a friend and forgot to complete the homework.",
    "{name}'s internet was not working last night.",
    "{name} had a power cut while working on the assignment.",
    "{name} accidentally deleted the homework file.",
    "{name} was not feeling well and could not complete the work.",
    "{name} thought the deadline was tomorrow.",
    "{name}'s pet messed up the homework.",
    "{name} was busy attending a family function."
};

// Seed random number generator
srand(time(0));

// Generate random index
int randomIndex = rand() % excuses.size();

// Pick random excuse
std::string selectedExcuse = excuses[randomIndex];

// Replace placeholder with actual name
std::string finalExcuse = replaceName(selectedExcuse, studentName);

// Display result
```

C++

```
// Generate random index
int randomIndex = rand() % excuses.size();

// Pick random excuse
std::string selectedExcuse = excuses[randomIndex];

// Replace placeholder with actual name
std::string finalExcuse = replaceName(selectedExcuse, studentName);

// Display result
std::cout << "\nExcuse:\n" << finalExcuse << std::endl;

return 0;
}
```

💡 How it works (simple explanation)

- Takes input name using `getline`
- Stores excuses in a `vector`
- Uses `rand()` to pick a random excuse
- Replaces `{name}` with actual name using a func.
- Prints a different excuse each run

