

# TRODDEN

TRACK SYSTEM



**Model No: LM-010-TLR7\*\*-15W**

## TECHNICAL DESCRIPTION

Single head square design, Its solid appearance can provide more luminous flux. It can be rotated 355° horizontally and 90° vertically. Tunable White allows the colour temperature to be continuously adjusted from warm light to cool light.


## INSTALLATION

Track Mounted

## AREAS OF APPLICATION

• Hotel • Restaurant • Shopping Mall • Stores • Household

## DIAGRAM




## MODEL NUMBER SELECTION

LM-010-TLR7  - 15W

S- Non Dimmable  
D - Dali  
A - 0-10, 1-10  
P - Phase  
B - Bluetooth

CW - 6000K  
NW - 4000K  
WW - 3000K

## LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



## PHYSICAL CHARACTERISTICS

Installation	Track Mounted	IP-Rating	IP20
Driver	Built In Driver	IK-Rating	IK03
Dimension	L86 x W84 x H219 (D84 / A120) (mm)	Standard Finish	White, Black
Adjustability	90° Adjustable Vertical	Optional Accessories	Honeycomb
Rotation	355° on Adapter	Track Adapter	Adaptive to 2 wires, 3 wires, 4 wires tracks
Fixture Material	Die Cast Aluminium		

## ELECTRICAL CHARACTERISTICS

LED Power	15W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Luminous Flux	1275lm	Power Factor	0.9
Chromaticity Tolerance	SDCM≤3	UGR	<22
Color Rendering Index	>80/90	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Color Temperature	3000K, 4000K, 6000K	Extended Configuration	2700K, 5000K
Beam Angle	15°/24°/38°	Options On Request	Bluetooth

## PRODUCT SPECIFICATION

Mains Volatge	220-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	III	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.