


TROPFEN

PENDANT SERIES



Model No: LM-007-SRP-30W**

TECHNICAL DESCRIPTION

TROPFEN provides innovative and gilt-edge lighting solution to match the premium interiors of a commercial place. This suspended luminaire provides shadowless lighting and the uniform lighting distribution. Tropfen can be customized and manufactured in different sizes to match the requirements.


INSTALLATION

Suspended from a concrete or Gypsum ceiling.


AREAS OF APPLICATION

• Offices • Villas • Apartments • Stores • Malls


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Suspended, Diffuser	IP-Rating	IP20
Driver	Remote	IK-Rating	IK03
Dimension	D1000 x W60 (mm)	Fixture Material	Extruded Aluminium
Adjustability	Fixed	Standard Finish	White, Black, Silver
Diffuser	PMMA/Polycarbonate	Optional Accessories	Suspension cable
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Temperature	3000K, 4000K, 6000K
LED Current	700 mA	Beam Angle	120°
LED Voltage	42V	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Power	30W	Power Factor	0.9
System Power	29.4W	UGR	<22
LED Luminous Flux	3300lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Extended Configuration	2700K, 5000K
Color Rendering Index	>80/90	Options On Request	Bluetooth

PRODUCT SPECIFICATION

Mains Volatge	100-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	I	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.