


AURA

SPOT DOWN SERIES



Model No: LM-011-DLPS4-20W**

TECHNICAL DESCRIPTION

Round luminaire for recessed mounted installation with tapered frame. The optical assembly consists of an die - cast painted aluminium frame and heat sink, a satin finish methacrylate diffuser screen for general light emission. The product is fixed with remote driver.


INSTALLATION

Recessed using steel springs in false ceilings with thicknesses starting at 5 mm.


AREAS OF APPLICATION

• Hotel • Restaurant • Shopping Mall • Stores • Household


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Recessed	Rotation	Non Adjustable
Driver	Remote	IP-Rating	IP20, IP44
Cut-Out Size	160 (mm)	IK-Rating	IK03
Dimension	D188 x H36 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	White, Black, White+Black
Reflector	N/A	Optional Accessories	N/A

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Temperature	3000K, 4000K, 6000K
LED Current	550 mA	Beam Angle	110°
LED Voltage	36V	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Power	20W	Power Factor	0.9W
System Power	19.8W	UGR	<13
LED Luminous Flux	1600lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤4	Extended Configuration	2700K, 5000K
Color Rendering Index	>80/90	Options On Request	Bluetooth

PRODUCT SPECIFICATION

Mains Volatge	220-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.