


WASSER LI 1

UNDERWATER SERIES



Model No: LM-202-WSUL1-6W**

TECHNICAL DESCRIPTION

Extruded aluminium alloy body, surface with anodizing treatment, high strength toughened glass, DMX512 interface adopts high reliable bus connect.


INSTALLATION

Recessed

AREAS OF APPLICATION

• Swimming Pools • Water Feature

DIAGRAM



MODEL NUMBER SELECTION

LM-202-WSUL1 -6W

S- Non Dimmable
D - DALI
A - 0-10, 1-10
P - Phase
DMX-DMX512

Beam Angle
15 - 15°
30 - 30°
45 - 45°
60 - 60°

CW - 6000K
NW - 4000K
WW- 3000
RGB-RGBW

PHYSICAL CHARACTERISTICS

Installation	Recessed	IP-Rating	IP68
Driver	Integrated	IK-Rating	IK09
Dimension	D195 x H65 (mm)	Fixture Material	316 Chrome Plated Stainless Steel
Adjustability	Fixed	Standard Finish	Stainless Steel
Diffuser	Tempered Glass	Optional Accessories	N/A
Rotation	180° On Clamp		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Beam Angle	15°/30°/45°/60°
LED Power	6W	Dimming Options	NON-DIM, 1-10V, DALI, DMX512
LED Luminous Flux	450lm	Power Factor	0.9
Chromaticity Tolerance	SDCM≤3	Driver Options	LYTEMASTER / MEANWELL / TRIDONIC
Color Rendering Index	≥75	Options On Request	N/A
UGR	<22		
Color Temperature	2700K-6000K, R/G/B		

PRODUCT SPECIFICATION

Mains Volatge	DC12V/24V	Environmental Temp	-25°C ~ +50°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.