



VEGA

PROFILE SERIES



Model No: LM-011-RLL5-50W**

TECHNICAL DESCRIPTION

Compatible in creating and customizing multiple geometric designs, Being capable of offering seamless connectivity of the diffuser and Micro Prismatic PMMA diffuser as optional, this luminaire meets all design requirements.


INSTALLATION

Recessed

AREAS OF APPLICATION

• Villas • Office • Reception

DIAGRAM




MODEL NUMBER SELECTION

LM-011-RLL5 -50W

S- Non Dimmable
D - DALI
A - 0-10, 1-10
P - Phase
B - Bluetooth

CW - 6000K
NW - 4000K
WW- 3000K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

| | | | |
|---------------|----------------------------------|----------------------|---|
| Installation | Recessed | Rotation | Non Adjustable |
| Driver | Integrated | IP-Rating | IP40 |
| Cut-Out Size | 1490 x 50 (mm) | IK-Rating | IK03 |
| Dimension | L1500 x W65 x H35 (mm) | Fixture Material | Extruded Anodized Aluminium with PC end cap cover |
| Adjustability | Fixed | Standard Finish | White, Black, White+Black |
| Reflector | PMMA / Polycarbonate Shock Proof | Optional Accessories | N/A |

ELECTRICAL CHARACTERISTICS

| | | | |
|------------------------|---------------------|------------------------|------------------------------|
| LED Current | 1050mA | Beam Angle | 120° |
| LED Voltage | 44V | Dimming Options | NON-DIM, PHASE, 1-10V, DALI |
| LED Power | 50W | Power Factor | 0.9 |
| System Power | 50.4W | UGR | <22 |
| LED Luminous Flux | 4000lm | Driver Options | LYTEMASTER, TRIDONIC, HELVAR |
| Chromaticity Tolerance | SDCM≤3 | Extended Configuration | 2700K, 5000K |
| Color Rendering Index | >85 | Options On Request | Bluetooth |
| Color Temperature | 3000K, 4000K, 6000K | | |

PRODUCT SPECIFICATION

| | | | |
|---------------|---------------------|------------------------|---------------|
| Mains Volatge | AC 85- 265V, DC 24V | Environmental Temp | -20°C ~ +40°C |
| Frequency | 50/60 Hz | Rated Service Life (h) | 55,000 |
| Safety Class | II | Certification | TUV, CE, RoHS |

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.