

# GEOX C

BULKHEAD & WALL LIGHT



**Model No: LM-B15-GOXC\*\*-0.5W**

## TECHNICAL DESCRIPTION

Wall recessed Geox C with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08. All integral in a compact body for easy integration with pre-ordered recessed housing.


## INSTALLATION

Install the recessed housing inside the wall. Connect the light source to the mains supply. fix the body to the recessed housing. Attach the Geox C luminaire to the chosen frame with two torx screws.


## AREAS OF APPLICATION

• Ramp Light • Wall Recessed • Walkway Light

## DIAGRAM



## MODEL NUMBER SELECTION



## PHYSICAL CHARACTERISTICS

Installation	Recessed	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	D53 x H43 (mm)	Fixture Material	Extruded Aluminium
Adjustability	Fixed	Standard Finish	Silver, Matt
Diffuser	Tempered Glass	Optional Accessories	N/A
Rotation	Non Adjustable		

## ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80/90
LED Current	100 mA	Color Temperature	3000K, 4000K, 5000K, R/G/B
LED Voltage	25V	Beam Angle	21°, 36°, 40°
LED Power	0.5W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, PWM/DMX512
System Power	0.5W	Power Factor	0.9
LED Luminous Flux	75lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

## PRODUCT SPECIFICATION

Mains Voltage	12V/24V AC/DC	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.