

# STYLE E6

SPOT DOWN SERIES



**Model No: LM-C05-STZE6\*\*-20W**


## DESCRIPTION

High power circular deep cylinder light outlet, adjustable angle design, can provide more luminous flux, and project light to further objects.


## AREAS OF APPLICATION

• Star-Rated Hotels • Villas • Residential Buildings

## DIAGRAM



## MODEL NUMBER SELECTION



## LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

7W 15° 3000K Ra90			7W 20° 3000K Ra90			7W 25° 3000K Ra90			7W 30° 3000K Ra90			7W 15°x40° 3000K Ra90		
H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)	H(m)	E(lx)	D(m)
1	3499	0.23	1	2679	0.35	1	1951	0.44	1	1469	0.57	1	1348	0.28
2	875	0.45	2	670	0.69	2	488	0.87	2	367	1.14	2	337	0.56
3	389	0.68	3	298	1.04	3	217	1.31	3	163	1.70	3	150	0.85
4	219	0.90	4	168	1.39	4	122	1.74	4	92	2.27	4	84	1.13
5	140	1.13	5	107	1.73	5	78	2.18	5	59	2.84	5	54	1.41
HEIGHT	ILLUMINANCE	DIAMETER	HEIGHT	ILLUMINANCE	DIAMETER	HEIGHT	ILLUMINANCE	DIAMETER	HEIGHT	ILLUMINANCE	DIAMETER	HEIGHT	ILLUMINANCE	DIAMETER

## PHYSICAL CHARACTERISTICS

Installation	Recessed	Rotation	Rotatable
Driver	Remote	IP-Rating	IP20/IP54
Cut-Out Size	104 (mm)	IK-Rating	IK03
Dimension	D116 x H133 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Tilt +/-20°	Standard Finish	White / Black
Reflector	/	Optional Accessories	Honeycomb/Glass/ Trim with spring

## ELECTRICAL CHARACTERISTICS

Light Source	Citizen	Color Temperature	3000K, 4000K
LED Current	500mA	Beam Angle	15°/24°/38°/15x30°
LED Voltage	36V	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Power	18W	Power Factor	0.9W
System Power	20W	UGR	<13
LED Luminous Flux	905~1358 lm, 911~1421 lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Extended Configuration	2700K, 5000K
Color Rendering Index	>80/90	Options On Request	Bluetooth

## PRODUCT SPECIFICATION

Mains Voltage	220-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.