

GEOX A

BULKHEAD & WALL LIGHT



Model No: LM-B15-GOXA-2W**

TECHNICAL DESCRIPTION

Wall recessed Geox A with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08. All integral in a compact body for easy integration with pre-ordered recessed housing.


INSTALLATION

Install the recessed housing inside the wall. Connect the light source to the mains supply. fix the body to the recessed housing. Attach the Geox B luminaire to the chosen frame with two torx screws.


AREAS OF APPLICATION

• Ramp Light • Wall Recessed • Walkway Light

DIAGRAM



MODEL NUMBER SELECTION



PHYSICAL CHARACTERISTICS

Installation	Recessed	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	D65 x H59 (mm)	Fixture Material	Extruded Aluminium
Adjustability	Fixed	Standard Finish	Silver, Matt
Diffuser	Tempered Glass	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80/90
LED Current	100 mA	Color Temperature	2700K, 3000K, 4000K, R/G/B
LED Voltage	25V	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, PWM/DMX512
LED Power	2W	Power Factor	0.9
System Power	2W	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
LED Luminous Flux	200lm	Options On Request	N/A
Chromaticity Tolerance	SDCM≤3		

PRODUCT SPECIFICATION

Input Volatge	12V/24V DC	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.