



ELITE

SURFACE & FACADE LUMINAIRES



Model No: LM-002-IGWW1-18W**

TECHNICAL DESCRIPTION

Surface mounted with accessory brackets, Extruded aluminium alloy body, surface with anodizing treatment, high strength toughened glass, DMX512 interface adopts high reliable bus connect.


INSTALLATION

Surface mounted with available brackets.


AREAS OF APPLICATION

- Wall Washer • Uplight


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Surface	IP-Rating	IP66
Driver	Integrated	IK-Rating	IK08
Dimension	L1000 x W65 x H57 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	Grey, Black
Diffuser	Tempered Glass		
Rotation	180° On Clamp		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux, LUXEON	Beam Angle	20°/30°/45°/60°/25°x45°
LED Power	18W	Dimming Options	NON-DIM, 1-10V, DALI, DMX512
LED Luminous Flux	1530lm	Power Factor	0.9
Chromaticity Tolerance	SDCM≤3	Driver Options	LYTEMASTER / MEANWELL / TRIDONIC
Color Rendering Index	≥70/80	Extended Configuration	2700K, 5000K
UGR	<22	Options On Request	Honey comb Louver, Anti Glare Shield
Color Temperature	3000K, 4000K, 6000K, RGB		

PRODUCT SPECIFICATION

Mains Volatge	DC24V	Environmental Temp	-25°C ~ +50°C
Frequency	50/60 Hz	Ambient Humidity	10% ~ 90%
Safety Class	II	Rated Service Life (h)	55,000
		Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.