

ZION

TRACK SYSTEM



Model No: LM-010-TLCW1**-15W

TECHNICAL DESCRIPTION

Single head square design, Its solid appearance can provide more luminous flux. It can be rotated 355° horizontally and 90° vertically. Tunable White allows the colour temperature to be continuously adjusted from warm light to cool light.


INSTALLATION

Track Mounted

AREAS OF APPLICATION

• Hotel • Club • Supermarket • Store • Office • Residential

DIAGRAM



MODEL NUMBER SELECTION


LM-010-TLCW1 - 15W

S - Non Dimmable
D - Dali
A - 0-10, 1-10
P - Phase
B - Bluetooth

CW - 6000K
NW - 4000K
WW - 3000K



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Track Mounted	IP-Rating	IP20
Driver	Built In Driver	IK-Rating	IK03
Dimension	L179 x W105 x H200 (D95 / A49) (mm)	Standard Finish	White, Black, White + Black
Adjustability	Tilttable	Optional Accessories	Honeycomb
Rotation	Non Adjustable		
Fixture Material	Extruded Aluminium		

ELECTRICAL CHARACTERISTICS

LED Power	15W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Luminous Flux	1200lm	Power Factor	0.9
Chromaticity Tolerance	SDCM≤3	UGR	<22
Color Rendering Index	>80/90	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Color Temperature	3000K, 4000K, 6000K	Extended Configuration	2700K, 5000K
Beam Angle	10°/20°/30°	Options On Request	Bluetooth

PRODUCT SPECIFICATION

Mains Volatge	220-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	III	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.