


WESTO IV

BULKHEAD & WALL LIGHT



Model No: LM-B13-WST4-4W**

TECHNICAL DESCRIPTION

Wall recessed Westo IV with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08. All integral in a compact body for easy integration with pre-ordered recessed housing.


INSTALLATION

Install the recessed housing inside the wall. Connect the light source to the mains supply. fix the body to the recessed housing. Attach the Westo III luminaire to the chosen frame with two torx screws.

AREAS OF APPLICATION

• Ramp Light • Wall Recessed • Walkway Light

DIAGRAM



MODEL NUMBER SELECTION

LM-B13-WST4 - 4W

S- Non Dimmable
D - DALI
A - 0-10, 1-10
P - Phase
DMX - DMX512

CW - 6000K
NW - 4000K
WW - 3000K

PHYSICAL CHARACTERISTICS

Installation	Wall Mounted	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	D80 x H60 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	Silver, Black
Diffuser	Polycarbonate	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80/90
LED Current	150 mA	Color Temperature	3000K, 4000K, 6000K, R/G/B
LED Voltage	33V	Beam Angle	80°
LED Power	1 x 4W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, PWM/DMX512
System Power	4W	Power Factor	0.9
LED Luminous Flux	160lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

PRODUCT SPECIFICATION

Mains Volatge	24V/12V DC 240V/120 AC	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.