


FLEX II

FLOOD & SPORTS LIGHTS



Model No: LM-100-NFLX2-50W**

TECHNICAL DESCRIPTION

Flex II Flood Lights are high quality flood light fittings designed for long life and low maintenance. Combined with the subtle closed design, this results in a much calmer ceiling appearance with increased efficiency.


INSTALLATION

Suitable for installation directly to walls or ceilings, indoors or outdoors.

AREAS OF APPLICATION

- Sports Lighting • Area Lighting • Factories,
- Warehouses • Street & High-Mast.

DIAGRAM




MODEL NUMBER SELECTION

LM-100-NFLX2 - 50W

S- Non Dimmable
D - Dali
A - 0-10, 1-10
P - Phase
B - Bluetooth

CW - 6000K
NW - 4000K
WW - 3000K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Surface/Wall	IP-Rating	IP66
Driver	Integrated	IK-Rating	IK08
Dimension	L307.62 x W247 x H58.9 (mm)	Fixture Material	Aluminium Alloy
Adjustability	Fixed	Standard Finish	Black
Diffuser	Tempered Glass	Net weight	2.4kg
Rotation	270°	Gross Weight	2.8kg

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Beam Angle	30° /60° /90° / 120°/ Type II / Type III
LED Power	50W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Luminous Flux	6500lm	Power Factor	0.95
Chromaticity Tolerance	SDCM≤6	Driver Options	LYTEMASTER / MEANWELL / TRIDONIC
Color Rendering Index	≥70/80	Extended Configuration	2700K, 5000K
Color Temperature	3000K, 4000K, 6000K	THD	<15%

PRODUCT SPECIFICATION

Mains Volatge	AC200-240V AC110-277V	Environmental Temp	-20°C ~ +50°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.