



ACCENT

PANEL & GENERAL LIGHTING



Model No: LM-001-PL5-35W**

TECHNICAL DESCRIPTION

Ultra Slim LED Panel Light adopts qualified super bright LED as light source, which is stable, long life and no UV & IR emission.


INSTALLATION

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 5 mm to 12 mm.


AREAS OF APPLICATION

• Hotel • Kitchen • Offices • Factories • Villas • Supermarkets


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Recessed	IP-Rating	IP40
Driver	Remote	IK-Rating	IK05
Dimension	L595 x B595 x H10 (mm)	Fixture Material	Extruded Aluminium/Sheet Steel
Adjustability	Fixed	Standard Finish	White
Diffuser	PC OPAL	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

LED Current	750mA	Beam Angle	120°
LED Voltage	44V	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Power	35W	Power Factor	0.9
System Power	33W	UGR	<22/<19
LED Luminous Flux	3500lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Extended Configuration	5000K
Color Rendering Index	>90	Options On Request	Bluetooth
Color Temperature	3000K, 4000K, 5700K		

PRODUCT SPECIFICATION

Mains Volatge	220-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	TUV, CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.