

# TAURUS

BULKHEAD & WALL LIGHT



**Model No: LM-005-UDB6L\*\*-10W**

## TECHNICAL DESCRIPTION

Wall mounted Taurus bulkhead with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08 double wall design that will conceal cable from view. Round large/small.


## INSTALLATION

Suitable for wall or ceiling mounting with central BESA provision and four fixing points, horizontal holes to aid adjustments. Additional holes for security or uneven surfaces.


## AREAS OF APPLICATION

• Supplementary lighting • Indoor • Outdoor


## DIAGRAM



## MODEL NUMBER SELECTION



## LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



## PHYSICAL CHARACTERISTICS

Installation	Surface	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	L95 x W71 x H225 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	White, Black
Diffuser	Lens	Optional Accessories	N/A
Rotation	Non Adjustable		

## ELECTRICAL CHARACTERISTICS

Light Source	Vossloh-Schwabe	Color Rendering Index	>80/90
LED Current	250 mA	Color Temperature	3000K, 4000K, 6000K
LED Voltage	36V	Beam Angle	90°
LED Power	2x 5W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
System Power	10W	Power Factor	0.9
LED Luminous Flux	700lm	Driver Options	In-built
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

## PRODUCT SPECIFICATION

Mains Volatge	230-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.