

# ZESTA I

FOCUS & SPIKE



**Model No: LM-B03-ZSA4\*\*-12W**

## TECHNICAL DESCRIPTION

Special housing design and high-quality optical components specifically for demanding visual tasks to provide enhanced visual comfort. Discreet and compact aesthetically designed architectural outdoor spotlight, Ideal for Glare-Free Accent Lighting, Flood lighting and Wall washing in Outdoor Area.


## INSTALLATION

Floor/ Wall mounted, Spike mounted, Tree or Pole mounted

## AREAS OF APPLICATION

• Facade • Garden • Focus Light

## DIAGRAM



## MODEL NUMBER SELECTION

LM-B03-ZSA4    - 12W

S- Non Dimmable  
D - DALI  
A - 0-10, 1-10  
P - Phase  
DMX - DMX512

Beam Angle  
10-10° 55-55°  
15-15° 28\*38-28\*38°  
25-25° 15\*50-15\*50°  
30-30° 20\*45-20\*45°

CW - 6000K  
NW - 4000K  
WW- 3000K  
RGBW-RGBW

## PHYSICAL CHARACTERISTICS

Installation	Surface, Pole, Spike	IP-Rating	IP66
Driver	Integrated	IK-Rating	IK04
Dimension	D: 67, L: 137, H: 175 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Vertical Tilttable	Standard Finish	Silver, Black
Diffuser	Tempered Glass	Optional Accessories	Mounting Brackets, Spike, Honey Comb, Hood
Rotation	Mounting Plate rotatable 355°		

## ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Temperature	RGBW
LED Power	12W	Beam Angle	40°/50°/60°/65°/75°
LED Luminous Flux	900lm-960lm	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, DMX512
Chromaticity Tolerance	SDCM≤3	Driver Options	LYTEMASTER, TRIDONIC, MEANWELL
Color Rendering Index	>80/90	Options On Request	Filters, Diffusers, Honeycomb louvers, Refractor for elliptical distribution.

## PRODUCT SPECIFICATION

Mains Voltage	AC220V DC24V	Environmental Temp	-20°C ~ +50°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.