

GEOX D

BULKHEAD & WALL LIGHT



Model No: LM-B15-GOXD-5W**

TECHNICAL DESCRIPTION

Wall recessed Geox D with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08. All integral in a compact body for easy integration with pre-ordered recessed housing.


INSTALLATION

Install the recessed housing inside the wall. Connect the light source to the mains supply. fix the body to the recessed housing. Attach the Geox D luminaire to the chosen frame with two torx screws.

AREAS OF APPLICATION

• Ramp Light • Wall Recessed • Walkway Light

DIAGRAM



MODEL NUMBER SELECTION

LM-B15-GOXD - 5W

S- Non Dimmable
D - DALI
A - 0-10, 1-10
P - Phase
DMX - DMX512

CW - 6000K
NW - 4000K
WW- 3000K

PHYSICAL CHARACTERISTICS

Installation	Recessed	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	L64x B64 x H102 (mm)	Fixture Material	Extruded Aluminium
Adjustability	Fixed	Standard Finish	Silver, Matt
Diffuser	Tempered Glass	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80/90
LED Current	150 mA	Color Temperature	3000K, 4000K, 6000K, R/G/B
LED Voltage	33V	Beam Angle	40°
LED Power	5W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, PWM/DMX512
System Power	4.95W	Power Factor	0.9
LED Luminous Flux	550lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

PRODUCT SPECIFICATION

Mains Volatge	12V/24V AC/DC	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.