

ANGELA II

BULKHEAD & WALL LIGHT



Model No: LM-B14-AGN2-6W**

TECHNICAL DESCRIPTION

Surface mounted Angela II with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK08. All integral in a compact body for easy integration with pre-ordered recessed housing.


INSTALLATION

Surface Mounted


AREAS OF APPLICATION

• Ramp Light • Wall Recessed • Walkway Light

DIAGRAM



MODEL NUMBER SELECTION



PHYSICAL CHARACTERISTICS

Installation	Surface Mounted	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK08
Dimension	L150 x B36 x H150 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	Silver, Black
Diffuser	Polycarbonate	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80/90
LED Current	150 mA	Color Temperature	3000K, 4000K, 6000K, R/G/B
LED Voltage	40V	Beam Angle	120°
LED Power	6W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI, PWM/DMX512
System Power	6W	Power Factor	0.9
LED Luminous Flux	350lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

PRODUCT SPECIFICATION

Mains Volatge	24VDC 240V/120 AC	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.