


LINEA

HIGH BAY SERIES



Model No: LM-010-HBLP1-150W**

TECHNICAL DESCRIPTION

Linea Lights are high quality light fittings designed for long life and low maintenance. Combined with the subtle closed design, this results in a much calmer ceiling appearance with increased efficiency.


INSTALLATION

Suspended

AREAS OF APPLICATION

- Factories • Warehouses • Supermarkets
- Other Large Areas

DIAGRAM




MODEL NUMBER SELECTION

LM-010-HBLP1 - 150W

S- Non Dimmable
D - DALI
A - 0-10, 1-10
P - Phase

CW - 6000K
NW - 4000K
WW - 3000K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Suspended	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK10
Dimension	L890 x B130 x H130 (mm)	Fixture Material	Die Cast Aluminium
Adjustability	Non Adjustable	Standard Finish	White, Black, White + Black
Diffuser	PMMA Lens		
Rotation	Fixed		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Beam Angle	30°/60°/90°/120°
LED Power	150W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
LED Luminous Flux	19500lm	Power Factor	0.9
Chromaticity Tolerance	SDCM≤6	Driver Options	LYTEMASTER / MEANWELL / TRIDONIC
Color Rendering Index	≥80	Options On Request	Micro Wave Sensor Daylight Sensor, 80°/120° Aluminium Reflector
Color Temperature	3000K, 4000K, 6000K		

PRODUCT SPECIFICATION

Mains Volatge	AC100-277V	Environmental Temp	-30°C ~ +45°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	I	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.