

FULL MOON

BULKHEAD & WALL LIGHT



Model No: LM-010-RCM7-35W**

TECHNICAL DESCRIPTION

Surface mounted Round Full Moon bulkhead with die-cast black/silver grey aluminium body and opal polycarbonate diffuser. IP65, IK10 double wall design that will conceal cable from view. Round large/small.


INSTALLATION

Suitable for wall or ceiling mounting with central BESA provision and four fixing points, horizontal holes to aid adjustments. Additional holes for security or uneven surfaces.


AREAS OF APPLICATION

• Boundary Walls • Accomodations • Villas • Outdoor


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

Installation	Surface	IP-Rating	IP65
Driver	Integrated	IK-Rating	IK10
Dimension	L275 x H75 mm)	Fixture Material	Die Cast Aluminium
Adjustability	Fixed	Standard Finish	White, Black, Grey
Diffuser	Polycarbonate	Optional Accessories	N/A
Rotation	Non Adjustable		

ELECTRICAL CHARACTERISTICS

Light Source	Bridgelux	Color Rendering Index	>80
LED Current	750 mA	Color Temperature	3000K, 4000K, 6000K
LED Voltage	44V	Beam Angle	120°
LED Power	35W	Dimming Options	NON-DIM, PHASE, 1-10V, DALI
System Power	33W	Power Factor	0.9
LED Luminous Flux	3500lm	Driver Options	LYTEMASTER, TRIDONIC, HELVAR
Chromaticity Tolerance	SDCM≤3	Options On Request	N/A

PRODUCT SPECIFICATION

Mains Volatge	230-240V	Environmental Temp	-20°C ~ +40°C
Frequency	50/60 Hz	Rated Service Life (h)	55,000
Safety Class	II	Certification	CE, RoHS

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.