

AMBER RD

SPOT DOWN SERIES



Model No: LM-011-DLMA9-40W**

TECHNICAL DESCRIPTION

Fixed round luminaire designed to use LED lamps with C.o.B. technology. Clear/frosted diffuser, with aluminium reflector complete with flux enhancer. Body made of painted white die-cast aluminium. Product complete with LED lamp in different CCT. General lighting beam.


INSTALLATION

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 5 mm.


AREAS OF APPLICATION

• Hotel • Club • Museum • Shopping Mall


DIAGRAM



MODEL NUMBER SELECTION



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PHYSICAL CHARACTERISTICS

| | | | |
|---------------|------------------|----------------------|--------------------|
| Installation | Recessed | Rotation | Non Adjustable |
| Driver | Remote | IP-Rating | IP20, IP44 |
| Cut-Out Size | 150 (mm) | IK-Rating | IK03 |
| Dimension | D165 x H175 (mm) | Fixture Material | Die Cast Aluminium |
| Adjustability | Fixed | Standard Finish | White, Black, Grey |
| Reflector | Aluminium | Optional Accessories | N/A |

ELECTRICAL CHARACTERISTICS

| | | | |
|------------------------|-----------|------------------------|------------------------------|
| Light Source | Bridgelux | Color Temperature | 3000K, 4000K, 6000K |
| LED Current | 900mA | Beam Angle | 15°/24°/38° |
| LED Voltage | 44V | Dimming Options | NON-DIM, PHASE, 1-10V, DALI |
| LED Power | 40W | Power Factor | 0.9W |
| System Power | 39.6W | UGR | <10 |
| LED Luminous Flux | 3200lm | Driver Options | LYTEMASTER, TRIDONIC, HELVAR |
| Chromaticity Tolerance | SDCM≤3 | Extended Configuration | 2700K, 5000K |
| Color Rendering Index | >80/90 | Options On Request | Bluetooth |

PRODUCT SPECIFICATION

| | | | |
|---------------|----------|------------------------|---------------|
| Mains Volatge | 220-240V | Environmental Temp | -20°C ~ +40°C |
| Frequency | 50/60 Hz | Rated Service Life (h) | 55,000 |
| Safety Class | II | Certification | TUV, CE, RoHS |

Notice: We reserve the right to make the technical changes without notice. Please contact our sales office for further information.