Lab Report – 8

Generative Adversarial Networks (GAN)


Goutham Krishnan

21BAI1007

Aim

- 1. Implement Vanilla GAN to generate images of the MNIST Handwritten digits dataset.
- 2. Implement Vanilla GAN to generate images of the CIFAR-10 image dataset.

Code and Output for Aim (i)







```
| Comment | A Description | A
```

```
### STEAM TOTAL | Mark | American | American
```

```
| Comment | A |
```










Code and Output for Aim (ii)


```
## 2 Pabel 1007 - offert O gan legypte 0: ## 2 Feet Case Verw Sears Reserve Tools 18th Lestement ## 12 Feet Case Verw Sears Reserve Tools 18th Lestement ## 12 Feet Case Verw Sears Reserve Tools 18th Lestement ## 12 Feet Case Verw Sears Reserve Tools 18th Lestement ## 12 Feet Case Verw Sears Reserve Tools 18th Lestement ## 12 Feet Case Verw Sears Reserve Tools 18th Lestement ## 18th Lest
```











Results

Successfully generated images of MNIST Handwritten digits dataset with a generator loss of 1.49 and discriminator loss of 0.96. The generated image is clear and distinguishable as digits.

For the CIFAR-10 image dataset, Vanilla GAN did not turn out to be effective since only dense layers are being used to generate and discriminate images. The generated image after 30 epochs is pixelated and cannot be recognized as specific images. A DCGAN using convolution layers will be more effective for three dimensional and complex image datasets like CIFAR.