The Adaptation–Embodied Carbon Paradox: A Lifetime-Aware Theory of Continual Learning on Wear-Limited Edge Hardware

Gadi Govardhan Satya
School of Computing
Amrita Vishwa Vidyapeetham
Kollam, India
am.sc.u4aid24015@am.students.amrita.edu

Joshitha Nambakam
School of Computing
Amrita Vishwa Vidyapeetham
Kollam, India
am.sc.u4cse24338@am.students.amrita.edu

Hrudya P
School of Computing
Amrita Vishwa Vidyapeetham
Kollam, India
hrudyap@am.amrita.edu

Abstract

Green-AI work usually minimizes *operational* edge-inference energy, yet tiny AIoT devices often incur most life-cycle emissions as *embodied* carbon amortized over physical lifetime. Continual Learning (CL) is needed under concept drift, but every on-device update spends finite non-volatile-memory (NVM) endurance. We identify the *Adaptation–Embodied Carbon Paradox*: adaptation preserves accuracy while accelerating wear-out, replacement, and embodied-carbon emissions. We therefore treat learning algorithms as physical agents constrained by carbon and endurance, not merely software objectives, and recast stability–plasticity as a *stability–plasticity–endurance trilemma*. We derive an embodied-carbon amortization lemma, a no-free-lifetime bound, a Lyapunov near-optimality theorem for *Stability-Controlled Lifetime-Aware Continual Learning* (SC-LACL), a deterministic (non-asymptotic) greedy wear-leveling peak bound, and a lifetime-and-carbon bound. We also propose the Total Carbon-Lifetime-Delay Product (tCLDP). Results are grounded simulations using counted per-cell P/E wear and datasheet endurance/energy parameters, not yet hardware lifetime tests. Across three drift streams and seven baselines, wear-agnostic CL exhausts memory on two streams and is throttled by harvested energy on the third, whereas SC-LACL nearly matches accuracy with 13–30× fewer NVM writes, survives on one device, and attains the best tCLDP; a 19× sparsity sweep suggests most plasticity is redundant wear, and a static shadow-price baseline matches SC-LACL until endurance turns severely scarce, where adaptivity cuts device count 4.6×.

CCS Concepts

• **Computing methodologies** → **Lifelong machine learning**; • **Hardware** → *Non-volatile memory*; • **Social and professional topics** → *Sustainability*; • **Theory of computation** → Stochastic control and optimization.



This work is licensed under a Creative Commons Attribution 4.0 International License.
AI Summit '26, Atlanta, GA, USA
© 2026 Copyright held by the owner/author(s).
ACM ISBN 979-8-4007-2638-5/2026/08
https://doi.org/10.1145/3806096.3844884

Keywords

sustainable computing, embodied carbon, continual learning, NVM endurance, Lyapunov optimization, energy harvesting, edge AI

ACM Reference Format:
Gadi Govardhan Satya, Joshitha Nambakam, and Hrudya P. 2026. The Adaptation–Embodied Carbon Paradox: A Lifetime-Aware Theory of Continual Learning on Wear-Limited Edge Hardware. In *ACM AI Summit 2026 (AI Summit '26), August 31-September 02, 2026, Atlanta, GA, USA.* ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/3806096.3844884

1 Introduction

The Information and Communication Technology sector emits an estimated 2.1–3.9% of global greenhouse gases [14]. In consumer electronics, IoT sensors, and edge-AI devices, embodied carbon from manufacturing, packaging, and transport often dominates life-cycle emissions at 70–90% [10, 16]. Since this fixed cost is amortized over lifetime, device longevity directly lowers annualized emissions; reported cradle-to-gate footprints range from ≈0.52 kg CO_2e (Raspberry Pi Pico) to ≈2.59 kg CO_2e (Coral Dev Board Micro), while IoT deployments already exceed 16.6 billion devices [8, 10].

Edge data is non-stationary, so static models degrade under concept drift [15]; CL restores accuracy by updating weights in place [21, 24, 25, 32]. But microcontrollers have only 128–512 KB SRAM, so training state spills to Flash or emerging NVM, where finite P/E endurance (10^4–10^5 for commodity Flash; $\sim 10^6$ for flash-replacement embedded STT-MRAM) and write energy (e.g., 16.82 pJ/bit for PCM) matter [7, 19, 23]. This exposes the **Adaptation–Embodied Carbon Paradox** (Fig. 1): writes sustain accuracy but shorten physical life, and replacement embodied carbon can outweigh operational savings. We use *paradox* in the self-defeating-optimization sense: the writes that sustain accuracy are exactly what can raise *net* life-cycle carbon above a static baseline (Lemma 1, Table 1).

Contributions. (1) We formalize the paradox and make device lifetime endogenous to the learning algorithm, adding a physical endurance axis to stability–plasticity (Sec. 3). (2) We derive carbon amortization, no-free-lifetime, Lyapunov near-optimality, a deterministic greedy wear-leveling peak bound, and lifetime/carbon bounds (Secs. 3–4). (3) We propose tCLDP and validate against seven baselines on three drift streams, including PRICE, a new




Figure 1: The Adaptation–Embodied Carbon Paradox: plasticity drives NVM wear, premature replacement, and embodied carbon that can offset operational savings.

static shadow-price baseline that isolates when adaptive control matters (Secs. 5–6).

2 Related Work

Carbon-aware computing. ACT, CORDOBA, CarbonClarity, and spatio-temporal accounting show that embodied carbon dominates and motivate CDP/tCDP metrics [11–13, 17, 38], but treat lifetime as a fixed *input*; we make it an output of learning. FlexiFlow [28] and COFFEE [35] are concurrent and complementary: they fix hardware/lifetime at *design time*, whereas SC-LACL fixes hardware and controls learning *at runtime*. **Continual learning.** EWC, LwF, Experience Replay, and ADWIN-like drift detectors optimize accuracy or forgetting, not write endurance or embodied carbon [3, 15, 21, 24, 32]. Edge and fog learning frameworks [4, 22, 29, 33] likewise target accuracy, latency, energy, or privacy rather than device wear. **Energy harvesting and intermittent computing.** Checkpointing and Lyapunov-stabilized harvesting CL manage *joules*, not write cycles [27, 31]. **Endurance-aware hardware/training.** NVM training, bit-flip-robust methods, approximate flash, memory-light on-device training, and HDC reduce update cost [1, 5, 7, 20, 25, 36, 37]; SC-LACL adds near-optimality/lifetime bounds.

3 The Paradox and the Trilemma

A renewable-powered node's operational carbon $\to$ 0, so total carbon is dominated by embodied carbon C_{emb} amortized over its mean time to failure. For a deployment horizon T, define

$$N_T(M) = \left\lceil \frac{T}{M} \right\rceil, \qquad C_{\text{total}}(M) \approx C_{\text{emb}} N_T(M), \tag{1}$$
$$M = \text{MTTF}(\rho) = \frac{E_{\text{cyc}}}{\beta\rho}.$$

Here M is mean time to failure, N_T is the number of required devices, E_{cyc} is per-cell endurance, ρ is the plasticity (P/E) rate, and β is write amplification. Thus MTTF is inversely proportional to plasticity: the learner controls its own lifetime.

Lemma 1 (Embodied-carbon amortization). *Let*

$$g(M) = \frac{C_{emb}}{T}\left\lceil \frac{T}{M} \right\rceil \tag{2}$$

be annualized embodied carbon for a device with MTTF = M. Then: (i) $g(M)$ is non-increasing in M; (ii) $g(M) = C_{emb}/T$ for every $M \geq T$; and (iii) among one-device, carbon-optimal policies, the most plastic sustainable target is $M = T$, equivalently $\bar{w} = E_{cyc}/T$.

The trilemma. Classical CL trades *stability* (retaining knowledge) against *plasticity* (acquiring it). On wear-limited NVM a third, physical axis is unavoidable: every act of plasticity spends finite endurance. We pose adaptation as constrained control—maximize time-average accuracy subject to (i) an energy buffer that never browns out and (ii) a wear rate $\leq \bar{w}$.

Proposition 1 (No-free-lifetime bound). *Suppose any learner that tracks drift rate δ at time-average accuracy $\geq \alpha$ must issue writes at rate at least $\rho_{\min} = \rho_{\min}(\delta, \alpha)$. Then*

$$MTTF \leq \frac{E_{cyc}}{\beta\rho_{\min}}. \tag{3}$$

A one-device target horizon T is feasible only if

$$\beta\rho_{\min} \leq \frac{E_{cyc}}{T}, \tag{4}$$

and the corresponding update energy is covered by harvested power.

4 SC-LACL: A Controller for the Trilemma

We build on Lyapunov-stabilized energy-harvesting CL [27], which throttles training from the residual energy state but accounts only for joules. We introduce the missing axis via an **Endurance-Aware Carbon Virtual Queue**

$$Q_Z(t{+}1) = \max\left\{ Q_Z(t) + \frac{w(t)}{\bar{w}} - 1, 0 \right\}, \tag{5}$$

which tracks normalized wear above the ideal linear trajectory of Lemma 1, alongside data (Q_D) and energy-deficit (Q_E) queues. With $L(t) = \frac{1}{2}\sum_j Q_j(t)^2$, SC-LACL minimizes, each slot, the drift-plus-penalty bound

$$V\, p(t) + \sum_j Q_j(t)\Delta_j(t), \tag{6}$$

where $p(t) = \text{loss}(t) + \text{operational carbon}(t)$ and $\Delta_j(t)$ is the increment of queue j. The parameter V trades accuracy against queue stability (Fig. 2).

Theorem 1 (Near-optimality; adapts [26]). *Assume i.i.d. random events, a penalty depending only on the current event and action, every queue increment bounded by σ, and data, energy, and wear constraints Slater-feasible with slack $\epsilon > 0$. Let $p^\star$ be the optimal time-average penalty, $p_{\max}$ an upper bound on $p(t) \geq 0$, and $B = \frac{3}{2}\sigma^2$. For every horizon T,*

$$\frac{1}{T}\sum_{t<T}\mathbb{E}[p(t)] \leq p^\star + \frac{B}{V}, \tag{7}$$

$$\frac{1}{T}\sum_{t<T}\sum_j \mathbb{E}[Q_j(t)] \leq \frac{B + V p_{\max}}{\epsilon}. \tag{8}$$

Thus the optimality gap is $O(1/V)$ and the average backlog is $O(V)$.




Figure 2: SC-LACL: three virtual queues feed a Lyapunov controller that gates updates (carbon break-even) and applies endurance-aware, wear-leveled sparse updates, closing the loop with measured P/E and energy.

Proof. The queue update and $\max[x,0]^2 \le x^2$ give the one-step drift bound

$$\Delta(t) \le B + \sum_j Q_j(t)\mathbb{E}[a_j(t) - b_j(t) \mid \mathbf{Q}(t)]. \tag{9}$$

SC-LACL minimizes the bound on $\Delta(t) + V\mathbb{E}[p(t) \mid \mathbf{Q}(t)]$ over feasible actions, so this quantity is no larger than under any stationary randomized policy. The optimal one (penalty $p^\star$, no expected queue growth) gives $\Delta(t) + V\mathbb{E}[p(t) \mid \mathbf{Q}(t)] \le B + Vp^\star$; an ϵ-slack one gives

$$\Delta(t) + V\mathbb{E}[p(t) \mid \mathbf{Q}(t)] \le B + Vp_{\max} - \epsilon \sum_j Q_j(t). \tag{10}$$

Taking expectations, summing over $t < T$, and telescoping $L(t)$ with $L(0) = 0$ and $L(T) \ge 0$, the first bound divided by VT yields (7); the second, with $p(t) \ge 0$, divided by ϵT yields (8). □

Proposition 2 (Greedy wear-leveling bound). *Consider a pool of n physically interchangeable cells with equal initial wear. If every write, of size at most $\delta_{\max}$, is routed to a cell currently attaining $\min_i w_i(t)$ (ties broken arbitrarily), then for all t,*

$$\max_i w_i(t) \;\le\; \frac{1}{n}\sum_i w_i(t) \;+\; \delta_{\max}. \tag{11}$$

Theorem 2 (Lifetime and carbon bound). *Under Theorem 1, the wear queue Q_Z is mean-rate stable, and*

$$\overline{w}_T = \frac{1}{T}\sum_{t<T}\mathbb{E}[w(t)] \le \bar{w}\Big(1 + \frac{\mathbb{E}[Q_Z(T)]}{T}\Big). \tag{12}$$

Under greedy wear-leveling (Prop. 2), peak per-cell wear exceeds the pool mean by at most $\delta_{\max}$ (a single write's worth), so the expected peak cell wear at T is at most E_{cyc} whenever $E_{cyc} \ge \overline{w}_T \cdot T + \delta_{\max}$. If $\max_i w_i(T) \le E_{cyc}$ almost surely, its embodied carbon is the one-device optimum of Lemma 1.

Proof. Summing the queue update over $t < T$ gives the displayed bound, whose excess term $\mathbb{E}[Q_Z(T)]/T$ vanishes by mean-rate stability. With zero initial wear, $\mathbb{E}[\text{mean}_i w_i(T)] = \overline{w}_T T \le E_{\text{cyc}} - \delta_{\max}$ by hypothesis. By Prop. 2, the peak cell satisfies $\mathbb{E}[\max_i w_i(T)] \le E_{\text{cyc}}$, so the hottest cell remains within the endurance limit in expectation. The carbon claim follows from Lemma 1. □

Remark. Prop. 2 assumes physically interchangeable cells and greedy routing within a wear-leveling pool; SC-LACL's allocation only biases writes toward less-worn cells, so the bound describes an idealized router rather than our simulation, and it does not hold across arbitrary hardware layouts (e.g., cells split across independent dies or planes are not interchangeable in this sense, and a physical flash-translation layer may not honor the greedy assignment exactly).

Proposition 3 (Carbon break-even rule). *A candidate update that reduces loss by $\Delta\ell$, consumes energy Δe, and spends normalized wear $\Delta w/\bar{w}$ is accepted, ignoring Q_D and operational carbon, exactly when*

$$V\Delta\ell \ge Q_E\Delta e + Q_Z\frac{\Delta w}{\bar{w}}. \tag{13}$$

Endurance-aware gradient allocation. Each update applies only the top-k highest-magnitude gradients, biased toward the least-worn cells via per-cell counters: algorithmic wear-leveling independent of the flash-translation layer.

5 The tCLDP Metric

Energy-Delay Product and carbon-delay variants (CDP, tCDP) amortize embodied carbon over a *fixed* lifetime [12, 13]. We propose the **Total Carbon-Lifetime-Delay Product (tCLDP)**, making MTTF $= f(\rho)$ from (1) explicit:

$$\text{tCLDP} = \frac{g(M)}{\bar{\alpha}} = \frac{N_T(M)\,C_{\text{emb}}/T}{\bar{\alpha}}, \tag{14}$$

in kg CO_2e·yr^{-1} per unit accuracy, with $g(M)$ from Lemma 1 and $\bar{\alpha}$ the time-average accuracy (inference delay is identical across policies here and omitted); dividing by $\bar{\alpha}$ prevents winning by writes alone (Static: 1.53 vs. SC-LACL's 1.26, Table 1). Validating tCLDP itself against ground truth — correlating it with measured MTTF and audited cradle-to-gate carbon rather than the datasheet/simulation inputs used here — is open; CarbonClarity's [11] and COFFEE's [35] uncertainty-aware carbon models are the natural first step.

6 Experiments

Setup and scope. A small MLP learns online on ELEC2 [18], a 40k Covertype block [6], and SEA [34]. Accuracy is prequential; NVM wear is counted from actual per-cell P/E operations (E_{cyc}=10^4, seasonal solar trace, supercapacitor). Endurance exhaustion triggers replacement and one 2.59 kg embodied-carbon unit; the horizon T is each stream's length at one sample per 30 min (2.6 yr ELEC2, 2.3 yr Covertype and SEA). We compare Static, Naive, Periodic, EWC [21], Experience Replay [32], LwF [24], and PRICE (a static shadow-price baseline, detailed below) with SC-LACL (V=12, top-k=0.18, $\bar{w}$=$0.85E_{\text{cyc}}/T$), over 5 seeds; baselines train 6 epochs/day, SC-LACL 1–4 scaled by drift. The simulated controller applies the break-even test of Prop. 3 with Q_E and Q_Z, estimating $\Delta\ell$ from

Table 1: Six of seven baselines vs. SC-LACL on three drift streams (mean, 5 seeds); PRICE, the seventh, ties SC-LACL exactly here. Accuracy is per dataset; Dev (devices over the horizon), Writes (lifetime P/E, M) and tCLDP (lower is better) are for ELEC2.

	Accuracy					
Method	ELEC2	Cover	SEA	Dev	Writes	tCLDP
Static	0.66	0.75	0.82	**1**	**0.0**	1.53
Naive CL	0.80	0.86	0.86	2	17.1	2.50
Periodic	0.73	0.78	0.84	**1**	**0.8**	1.37
EWC	0.79	0.80	0.86	2	17.1	2.53
Exp. Replay	0.79	0.85	0.86	2	17.1	2.54
LwF	**0.81**	0.86	**0.87**	2	17.1	2.48
SC-LACL	0.80	**0.87**	0.87	**1**	**0.8**	**1.26**

recent accuracy in place of Q_D; Theorems 1–2 describe the idealized controller. Every policy trains only as many epochs as its energy buffer and harvest can pay for. These are grounded simulations using datasheet endurance/energy constants, not hardware lifetime tests: real P/E endurance is temperature- and pattern-sensitive, write amplification varies with the flash-translation layer, and wear-leveling here is algorithmic (Sec. 4), not validated against a physical FTL.

Main results. Accuracy-oriented CL is wear-agnostic: on ELEC2 and SEA, dense writes exhaust memory at 1.6 yr, require two devices, and give the worst tCLDP (≈2.5–2.6; Table 1); on Covertype, the larger model's dense updates are instead throttled by harvested energy (one device, 30M writes). SC-LACL stays within 1.5 accuracy points of the best baseline while issuing 13–30× fewer writes (Fig. 3; SEA: 5.65 vs. 0.19M), surviving on one device and attaining the best tCLDP on all three streams, narrowly on Covertype (1.310±0.004 vs. 1.319±0.005; Fig. 4).

Why it works. The sparsity sweep (Fig. 5) shows accuracy is nearly invariant (0.792 → 0.799) across a 19× write range (0.24 → 4.59M P/E), suggesting that most plasticity is redundant wear. Table 2 isolates the controller: in this ample-endurance regime the break-even gate and wear-leveling are inactive, consistent with the Remark.

Decomposing the gain. In this ample-endurance regime, static sparsity alone recovers much of the write reduction (k=0.05 vs. dense: 0.007 accuracy at 19× fewer writes; of ELEC2's 20× reduction, top-k gives 5.5× and drift-scaled epochs 3.7×, 17.1 → 4.59M); the controller's distinct contribution is *binding* once endurance is severely scarce.

PRICE: a static shadow-price baseline. We test this directly with **PRICE**, a new baseline identical to SC-LACL's top-k wear-leveled update except that the adaptive queues Q_E, Q_Z in the gate (Prop. 3) are replaced by constants — calibrated once from SC-LACL's own long-run average on ELEC2, then frozen — in the spirit of treating flash endurance as a fixed-price depreciating asset [9]. Because SC-LACL's wear queue stays empty in that regime, the calibrated wear price is zero, so PRICE never penalizes wear. In Table 1's regime and under moderately tight endurance (E_{cyc}=2.5×10^3), PRICE is numerically identical to SC-LACL on all three streams: the frozen price never needs to move, so adaptivity adds nothing there. The

Table 2: Ablations on ELEC2 (mean, 5 seeds); on/off columns compare the named mechanism enabled vs. disabled.

Ablation	Acc	Writes (M)	tCLDP
sparsity k=0.05	0.792	0.24	1.265
sparsity k=0.18	0.795	0.84	1.260
sparsity k=1.0 (dense)	0.799	4.59	1.254
wear-level. on/off	0.795/0.796	0.84/0.83	1.260/1.258
break-even on/off	0.795/0.795	0.84/0.84	1.260/1.260

two diverge only far outside PRICE's calibration point: under severe scarcity (E_{cyc}=200, V=2 for both, ELEC2, 5 seeds), PRICE keeps higher accuracy (0.795 vs. 0.756) but needs 4.6× more devices (23 vs. 5) and a 4.4× worse tCLDP (28.97 vs. 6.62), because without a wear price it never throttles writes.

Regime analysis. On ELEC2 (5 seeds), under *tight endurance* (E_{cyc}=2.5×10^3), all SC-LACL variants need two devices (the densely updated output-bias cells wear out first, while Q_Z tracks mean wear) but use 5.5× fewer writes than dense updating; under *scarce harvest* (mean daily harvest 0.45 vs. 0.95 nominal), low write volume gives 12.6× fewer brownout days than naive CL (126 → 10.0) and higher serviceable accuracy (0.787 vs. 0.695).

7 Research Agenda

A roadmap toward community practice: (near-term) benchmarks should log endurance traces, per-cell P/E counters, energy traces, and replacement-carbon factors alongside accuracy, calibrated by accelerated wear tests; (mid-term) lifetime-aware NAS should score candidates by accuracy, latency, write footprint, survival probability, and tCLDP, rejecting architectures that merely shift cost into NVM wear; (long-term) MLPerf Tiny [2] and related suites could add tCLDP leaderboards and uncertainty-aware embodied-carbon models [11, 38], making lifetime and carbon accounting first-class review artifacts.

8 Conclusion

Sustainable edge AI cannot be achieved by optimizing operational energy alone; embodied carbon dominates, is amortized over lifetime, and unmanaged on-device learning spends that lifetime [30]. By making lifetime endogenous, SC-LACL turns the stability–plasticity–endurance trilemma into a tractable control problem. The evidence is simulation-based, so hardware lifetime validation remains next; the broader agenda is an edge-AI design discipline that optimizes accuracy, energy, endurance, and embodied carbon together.

References

[1] Jebacyril Arockiaraj, Dhruv Parikh, and Viktor Prasanna. 2026. ImageHD: Energy-Efficient On-Device Continual Learning of Visual Representations via Hyperdimensional Computing. In *Proc. IEEE FCCM*. IEEE, 231–240. doi:10.1109/FCCM68464.2026.00041

[2] Colby Banbury et al. 2021. MLPerf Tiny Benchmark. In *Proc. NeurIPS Datasets and Benchmarks*, Vol. 1.

[3] Albert Bifet and Ricard Gavaldà. 2007. Learning from Time-Changing Data with Adaptive Windowing. In *Proc. SIAM SDM*. SIAM, 443–448. doi:10.1137/1.9781611972771.42

[4] Narendra Singh Bisht and Subhasri Duttagupta. 2022. Deploying a Federated Learning Based AI Solution in a Hierarchical Edge Architecture. In *Proc. IEEE R10-HTC*. IEEE, 247–252. doi:10.1109/R10-HTC54060.2022.9929526




Figure 3: Accuracy vs. lifetime writes (log axis): SC-LACL reaches near-top accuracy at 13–30× fewer writes than wear-agnostic CL. Static (0 writes) is shown at the axis floor.




Figure 4: SC-LACL attains the best tCLDP on all three streams.




Figure 5: Accuracy is nearly flat across a 19× write range, suggesting most plasticity is redundant wear.

[5] Anmol Biswas et al. 2025. Regularization-based Framework for Quantization-, Fault- and Variability-Aware Training. arXiv:2503.01297 [cs.LG]

[6] Jock A. Blackard and Denis J. Dean. 1999. Comparative Accuracies of Artificial Neural Networks and Discriminant Analysis in Predicting Forest Cover Types from Cartographic Variables. *Comput. Electron. Agric.* 24, 3 (1999), 131–151. doi:10.1016/S0168-1699(99)00046-0

[7] Alexander Buck, Karthik Ganesan, and Natalie Enright Jerger. 2024. FlipBit: Approximate Flash Memory for IoT Devices. In *Proc. IEEE HPCA*. IEEE, 876–890. doi:10.1109/HPCA57654.2024.00072

[8] Fan Chen, Shahzeen Attari, Gayle Buck, and Lei Jiang. 2024. IoTCO2: End-to-End Carbon Footprint Assessment of Internet-of-Things-Enabled Deep Learning. arXiv:2403.10984

[9] Josef Chen. 2026. Memory as a Wasting Asset: Pricing Flash Endurance for Embodied Agents, and the Limits of Doing So. arXiv:2606.18144 [cs.AI]

[10] Xuesi Chen et al. 2025. From Component to System: Rethinking Edge Computing Design through a Carbon-Aware Lens. *ACM SIGEnergy Energy Inform. Rev.* 5, 2 (2025), 125–131. doi:10.1145/3757892.3757910

[11] Xuesi Chen, Leo Han, Anvita Bhagavathula, and Udit Gupta. 2025. CarbonClarity: Understanding and Addressing Uncertainty in Embodied Carbon for Sustainable Computing. In *Proc. IEEE/ACM ICCAD*. IEEE, 1–9. doi:10.1109/ICCAD66269.2025.11240799

[12] Mariam Elgamal et al. 2023. Carbon-Efficient Design Optimization for Computing Systems. In *Proc. HotCarbon*. ACM, 7 pages. doi:10.1145/3604930.3605712

[13] Mariam Elgamal et al. 2025. CORDOBA: Carbon-Efficient Optimization Framework for Computing Systems. In *Proc. IEEE HPCA*. IEEE, 1289–1300. doi:10.1109/HPCA61900.2025.00098

[14] Charlotte Freitag et al. 2021. The real climate and transformative impact of ICT: A critique of estimates, trends, and regulations. *Patterns* 2, 9 (2021), 100340. doi:10.1016/j.patter.2021.100340

[15] João Gama et al. 2014. A Survey on Concept Drift Adaptation. *Comput. Surveys* 46, 4 (2014), 1–37. doi:10.1145/2523813

[16] Udit Gupta et al. 2021. Chasing Carbon: The Elusive Environmental Footprint of Computing. In *Proc. IEEE HPCA*. IEEE, 854–867. doi:10.1109/HPCA51647.2021.00076

[17] Udit Gupta et al. 2022. ACT: Designing Sustainable Computer Systems with an Architectural Carbon Modeling Tool. In *Proc. ACM/IEEE ISCA*. ACM, 784–799. doi:10.1145/3470496.3527408

[18] Michael Harries. 1999. *SPLICE-2 Comparative Evaluation: Electricity Pricing*. Technical Report. University of New South Wales.

[19] Markus Hellenbrand, Isabella Teck, and Judith L. MacManus-Driscoll. 2024. Progress of Emerging Non-Volatile Memory Technologies in Industry. *MRS Communications* 14, 6 (2024), 1099–1112. doi:10.1557/s43579-024-00660-2

[20] Chien-Chung Ho et al. 2021. Approximate Programming Design for Enhancing Energy, Endurance and Performance of Neural Network Training on NVM-based Systems. In *Proc. IEEE NVMSA*. IEEE, 1–6. doi:10.1109/NVMSA53655.2021.9628582

[21] James Kirkpatrick et al. 2017. Overcoming Catastrophic Forgetting in Neural Networks. *Proc. Natl. Acad. Sci.* 114, 13 (2017), 3521–3526. doi:10.1073/pnas.1611835114

[22] Varsha S. Lalapura, J. Amudha, and Hariramn Selvamuruga Satheesh. 2021. Recurrent Neural Networks for Edge Intelligence: A Survey. *Comput. Surveys* 54, 4, Article 91 (2021), 38 pages. doi:10.1145/3448974

[23] Benjamin C. Lee, Engin Ipek, Onur Mutlu, and Doug Burger. 2009. Architecting Phase Change Memory as a Scalable DRAM Alternative. In *Proc. ACM/IEEE ISCA*. ACM, 2–13. doi:10.1145/1555754.1555758

[24] Zhizhong Li and Derek Hoiem. 2016. Learning without Forgetting. In *Computer Vision – ECCV 2016 (Lecture Notes in Computer Science, Vol. 9908)*. Springer, 614–629. doi:10.1007/978-3-319-46493-0_37

[25] Ji Lin et al. 2022. On-Device Training Under 256KB Memory. In *Proc. NeurIPS*. 22941–22954.

[26] Michael J. Neely. 2010. *Stochastic Network Optimization with Application to Communication and Queueing Systems*. Morgan & Claypool. doi:10.2200/S00271ED1V01Y201006CNT007

[27] Junsoo Park, Ikjune Yoon, and Dong Kun Noh. 2026. Stability-Controlled Continual Federated Learning for Energy-Harvesting AIoT Systems. *Sensors* 26, 11 (2026), 3325. doi:10.3390/s26113325

[28] Shvetank Prakash et al. 2026. Lifetime-Aware Design for Item-Level Intelligence at the Extreme Edge. In *Proc. ACM ASPLOS, Vol. 2*. ACM, 1089–1112. doi:10.1145/3779212.3790182

[29] Shinu M. Rajagopal, Supriya M., and Rajkumar Buyya. 2025. Leveraging Blockchain and Federated Learning in Edge-Fog-Cloud Computing Environments for Intelligent Decision-Making with ECG Data in IoT. *Journal of Network and Computer Applications* 233 (2025), 104037. doi:10.1016/j.jnca.2024.104037

[30] Rajkumar Ramasamy, Rahul Sanmugam Gopi, and Rohini Palanisamy. 2024. E-Waste Management in the Digital Era: A Sustainable Computing Approach. *IEEE Potentials* 43, 2 (2024), 30–36. doi:10.1109/MPOT.2024.3473292

[31] Benjamin Ransford, Jacob Sorber, and Kevin Fu. 2011. Mementos: System Support for Long-Running Computation on RFID-Scale Devices. In *Proc. ACM ASPLOS*. ACM, 159–170. doi:10.1145/1950365.1950386

[32] David Rolnick et al. 2019. Experience Replay for Continual Learning. In *Proc. NeurIPS*.

[33] V. Sindhu, Pradeep Sudhakaran, G. Anitha, and P. D. Mahendiran. 2022. Fog based Edge Learning using IoT: Concepts, Challenges and Applications. In *Proc. IEEE ICSSIT*. IEEE, 18–21. doi:10.1109/ICSSIT53264.2022.9716489

[34] W. Nick Street and YongSeog Kim. 2001. A Streaming Ensemble Algorithm (SEA) for Large-Scale Classification. In *Proc. ACM SIGKDD*. ACM, 377–382. doi:10.1145/502512.502568

[35] Hongbang Wu et al. 2026. COFFEE: A Carbon-Modeling and Optimization Framework for HZO-based FeFET eNVMs. In *Proc. DATE*. IEEE, 1–7. doi:10.23919/DATE69613.2026.11539619

[36] Xiaofan Yu et al. 2024. Lifelong Intelligence Beyond the Edge using Hyperdimensional Computing. In *Proc. ACM/IEEE IPSN*. IEEE, 1–13. doi:10.1109/IPSN61024.2024.00005

[37] Fan Zhang, Li Yang, and Deliang Fan. 2024. Hyb-Learn: A Framework for On-Device Self-Supervised Continual Learning with Hybrid RRAM/SRAM Memory. In *Proc. ACM/IEEE DAC*. ACM, Article 180, 6 pages. doi:10.1145/3649329.3657389

[38] Xiaoyang Zhang, Yijie Yang, and Dan Wang. 2025. Spatial-Temporal Embodied Carbon Models With Dual Carbon Attribution for Embodied Carbon Accounting of Computer Systems. *IEEE Trans. Comput.* 74, 12 (2025), 4037–4049. doi:10.1109/TC.2025.3605743