

**SUBSTITUTE FOR
HOUSE BILL NO. 5571**

A bill to amend 1972 PA 230, entitled
"Stille-DeRossett-Hale single state construction code act,"
(MCL 125.1501 to 125.1531) by adding section 4k.

THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

1 **Sec. 4k. (1) A multiple-family dwelling that has more than 4,**
2 **but not more than 6, levels above grade plane may have a single**
3 **interior exit stairway if all of the following conditions are met:**

4 **(a) The dwelling has not more than 4 units on each level.**

5 **(b) The net floor area of each level of the dwelling is not**
6 **more than 4,000 square feet.**

7 **(c) The exit access travel distance is not more than 125 feet**
8 **measured from the most remote point within a level of the dwelling**
9 **along the natural and unobstructed path of egress travel.**



(d) Openings to the interior exit stairway enclosure are limited to all of the following openings:

(i) Openings required for exit access into the enclosure from normally occupied spaces.

(ii) Openings required for egress from the enclosure.

(iii) Openings to the exterior.

(e) An elevator does not open into the interior exit stairway enclosure.

(f) The dwelling has a manual fire alarm system and an automatic smoke detection system that activates an occupant notification system. The manual fire alarm system, automatic smoke detection system, and occupant notification system all must be installed in accordance with the building code.

(g) Smoke detectors are located in common spaces outside of the dwelling units, including, but not limited to, all of the following areas:

(i) Gathering areas.

(ii) Laundry rooms.

(iii) Mechanical equipment rooms.

(iv) Storage rooms.

(v) Interior corridors.

(vi) Interior exit stairways.

(vii) Exit passageways.

(h) Regardless of the stairway construction type in the dwelling, automatic sprinkler locations in the interior exit stairway comply with the requirements for combustibile stairways under the "Standard for the Installation of Sprinkler Systems", 2025 edition, developed by the National Fire Protection Association. If a standard described in this subdivision is revised

1 after the effective date of the amendatory act that added this
2 section, the department shall take notice of the revision and the
3 department shall promulgate rules to incorporate the revision by
4 reference.

5 (i) An electrical receptacle is not located in an interior
6 exit stairway.

7 (j) The interior exit stairway is not less than 48 inches
8 wide.

9 (k) The multiple-family dwelling is located within a city or
10 township that is served by a fire department, fire district, or
11 fire authority that meets all of the following requirements:

12 (i) Is accredited by the Commission on Fire Accreditation
13 International. This subparagraph is satisfied if the fire
14 department, fire district, or fire authority that serves the city
15 was accredited by the Commission on Fire Accreditation
16 International but does not maintain an active accreditation.

17 (ii) Has a class 1 or 2 rating from the public protection
18 classification program developed by the Insurance Services Office.

19 (iii) Meets the aerial apparatus requirements of the applicable
20 class rating described in subparagraph (ii).

21 (2) This section does not apply if the department incorporates
22 by reference the International Code Council's publication of single
23 interior exit stairway for a multiple family dwelling that is 6 or
24 more levels above grade plane into the code.

25 Enacting section 1. This amendatory act does not take effect
26 unless Senate Bill No. ____ (request no. S00659'25) or House Bill
27 No. 5570 of the 103rd Legislature is enacted into law.

