	tell?
T	
+	Quick Quiz - Create a string using " " and print its content using a loop.
1	beint its content using a loop.
+	Disting Chimas
-	a chaine can be beinted character by character
1	11 Story vand de provinces missiones og
	2 t there is another Convenient way to brint
P.	Printing Strings A string can be printed character by character using printf and % c But there is another convenient way to print Strings in c
1	SAUTUS
	Char St[] = "HARRY";
	print f ("%s", st); => prints the entire string.
	Drint + (1/03 , 50)
	Thing along inbut Geom the 1160%
	Taking string input from the user We can use %5 with scanf to take string
	in the wan we is sufficient to some story
	input from the user:
	Class C+[ra]: Lever were a company of march 1911
	Char St [50] is his push prish prish prish the
1	Sanf ("7.5", & St); 200000 1000000000000000000000000000000
9	Scanf automatically adds the null character when the the enter key is pressed.
	Scant wiromaniany was the null whater when
	the the there key is presold.
	N. J.
_	Note: worth foreign hard livened on
7	The string should be short enough to fit into the array
-	(1 (1
12	Stanf Cannot be used to input multi-word strings
	with spaces and will being a support
_	Lympt the withough it and hery order
_	the strange of first withing pointers are at the second
_	like 2 Korda
	·

•	
	gets() and puts() gets() is a function which can be used to roceive a multi-word string.
	gest with passing which can be used to
	adrive a multi- word string.
	Maria Character Company
4	Chart St 30 Tinto Stand on the land
11/1	Char st [30]; => The entered string is stored in st!
1	The there was red man we shall take
	Multiple gets () calls will be needed for multiple Strings
	Stringe
	Likewise, puts can be used to output a string.
	String.
	Tokung start who the list of the list of
	puts (5t); => prints the string places the cursor on the next line
	blaces the wesor on the next line
	Declaring a string using pointers
	Declaring a string using pointers We can declare strings using pointers
No Nill	Char + ptr = "Harry"; World Moule
,	This fells the compiler to store the string
	in memory and assigned address is stored
1, place	This fells the compiler to store the string in memory and assigned address is stored in a char pointer
	A1
10	Note: Blace Trader of him of towns towns
17	Once a String is defined using char st [] = "Harry", it
	Once a String is defined using char st [1 = "Harry", it Cannot be reinitialized to something else. A string defined using pointers can be reinitialized ptr = "Rohan";
27	A string defined using pointers can be reinitialized
	ptr'="Rohan";"
l	<u> </u>

_	
	Standard library functions for Strings
	Standard library functions for Strings C provides a set of Standard library functions for String manipulation.
	for string manipulation.
	Some of the most commonly used string functions
	are:
1	Strong Daniel World Contact Contact
Copies "	This function is used to count the number of
100	characters in the string excluding the null ('10')
	This function is used to count the number of characters in the string excluding the null ('\0') character.
	Shore and Elmin ? I (: Missing 1)
Frie	int length = Strlen (st);
10 A 2 4	ACEIL indus is not stronger - had society - read
3000	These functions are declared under < string h >
	header file
	" Set up [" fox" " loke"] = [[10kg]] = [10kg] 10kg]
-	Steepy () 1- ("rot" "adol" " dand
	This function is used to copy the conkent of
41	second string into first string passed to it.
	Char Source [] = "Harry";
	char target [30];
	Stropy (target, source); => target now
	Contains "Harry"
	Tough the shall be a control of the
	Target string should have enough capacity to store the Source String.
	the source strung.
-	<u> </u>

Streat 1) This function is used to concatenate Strings	two
Char S, [5] = "Hello"; Char S2[] = "Harry"; Streat (S,, S2); => S, now contains "He	Mar Harri
This Guaction is used to Compare two	No space in between
It returns: O if Strings are equal Negative value if first String's mismatching AS EII Value is not greater than Second Str mismatching character. It returns positive va	character's ring's corresponding
Stremb ("For", "Joke"); Positive va Stremb ("Joke", "For"); Negative	Value
I string into first strang passed to it.	
	reto
Sounce should want though informly to store	tornot

· · ·	EDGE
8	Write a program to count the occurence of a given character in a string. Write a program to check whether a given character is present in a string or not.
	Li densità de la constitución de
1	a fairte as brossons de take stand as and
	That the straight and straight
	File Charles and American Control of the Control of
20.	whit a succion succion will align to the strains are to tot the strains to tot and a succion to tot and a succion to the succession for succe
- Asi	The stand our resource of stella function for
	the pet yours a state of the sharp to the state of the st
	the property of marriage of the string out