

## MACHINE LEARNING

Q1 to Q11 have only one correct answer. Choose the correct option to answer your question.

1. Movie Recommendation systems are an example of:

- i) Classification
- ii) Clustering
- iii) Regression

Options:

- a) 2 Only
- b) 1 and 2
- c) 1 and 3
- d) 2 and 3

**ANS = (b) 1 and 2**

2. Sentiment Analysis is an example of:

- i) Regression
- ii) Classification
- iii) Clustering
- iv) Reinforcement

Options:

- a) 1 Only
- b) 1 and 2
- c) 1 and 3
- d) 1, 2 and 3

**Answer - a) Only**

3. Can decision trees be used for performing clustering?

- a) True
- b) False

**Answer - b) False**

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points:

- i) Capping and flooring of variables
- ii) Removal of outliers

Options:

- a) 1 only
- b) 2 only
- c) 1 and 2
- d) None of the above

**Answer – a) 1 only**

5. What is the minimum no. of variables/ features required to perform clustering?

- a) 0
- b) 1
- c) 2
- d) 3

**Answer – b) 1**

6. For two runs of K-Mean clustering is it expected to get same clustering results?

- a) Yes
- b) No

**Answer – b) No**

7. Is it possible that Assignment of observations to clusters does not change between successive

---

**MACHINE LEARNING**

iterations in K-Means?

- a) Yes
- b) No
- c) Can't say
- d) None of these

**Answer – a) Yes**

---

## MACHINE LEARNING

8. Which of the following can act as possible termination conditions in K-Means?
- i) For a fixed number of iterations.
  - ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
  - iii) Centroids do not change between successive iterations.
  - iv) Terminate when RSS falls below a threshold.

Options:

- a) 1, 3 and 4
- b) 1, 2 and 3
- c) 1, 2 and 4
- d) All of the above

**Answer - d) All of the above**

9. Which of the following algorithms is most sensitive to outliers?
- a) K-means clustering algorithm
  - b) K-medians clustering algorithm
  - c) K-modes clustering algorithm
  - d) K-medoids clustering algorithm

**Answer – a) K-means clustering algorithm**

10. How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):
- i) Creating different models for different cluster groups.
  - ii) Creating an input feature for cluster ids as an ordinal variable.
  - iii) Creating an input feature for cluster centroids as a continuous variable.
  - iv) Creating an input feature for cluster size as a continuous variable.

Options:

- a) 1 only
- b) 2 only
- c) 3 and 4
- d) All of the above

**Answer – d) K- All of the above**

11. What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?
- a) Proximity function used
  - b) of data points used
  - c) of variables used
  - d) All of the above

**Answer – D) All of the above**

Q12 to Q14 are subjective answers type questions, Answers them in their own words briefly

12. Why is K sensitive to outliers?

**Answer- The K-sensitive to outlier easily influence by extreme values.**

13. Why is K means better?

**Answer – The K- means better clustering Easily adapts to new examples and clusters of different Shapes and size.**

14. Is K means a deterministic algorithm?

**Answer – The k-means a deterministic algorithm its random selection of data points as initial centroids .An improved, density based version and involves a novel and systematic.**

---