

Q1.

select rider-type, Count(*) as total_rides,
 Sum(Fare) AS total_fare from
 rides.

group by rider-type, Having (count(*) > 7
 order by total_fare DESC;

Q2.

select station-id, (count(*) AS ride_count
 round (Avg (duration-min), 2) as avg-duration
 from rides

group by station-id

Having Avg (duration-min) > 30

order by avg-duration DESC;

Q3.

select rider-type, Max (duration-min) AS
 longest-ride,

Min (duration-min) AS shortest-ride,

Round (Avg (duration-min), 2) AS Avg-ride

from rides

group by rider-type

having Max (duration-min) > 50

order by longest-ride Desc;

03
 //

select month (ride-date) as ride-month
 count (*) as total-rides, round(sum(distance-km), 1)
 as total-distance from rides
 group by month(ride-date)
 having sum(distance-km) > 30
 order by ride-month;

③

select station-id, rides-type, count (*)
 as ride-count, round(sum(distance-km), 1)
 as total-distance from rides
 group by rides,

④

select station-id, count(~~rides-type~~ rides-
 type) as rides-type-count,
 count (*) as total-rides,
 round(avg(score, 2) as avg-score, from rides
 group by station-id
 Having count(rides-type) = 3
 order by station-id;

Date: ___/___/___

MON TUE WED THR FRI SAT SUN
□ □ □ □ □ □ □

(7)

~~8~~ ~~Set~~

Select Stations. ~~id~~. Stations,
Stations. Station_name,
rides. rideid from Stations
~~&~~ Left join rides
on Stations: Station_id = rides.Station_id

(9)

Five type →

①

DDL

→ Data Definition

②

DML

③

DQL

④

TCL

⑤

DCL

(10)

SQL join is used to two tables
related on a column column.

... May use join.

①

inner join

②

Left join

Right join

Full join

cross join

Self join